


CS 417 – DISTRIBUTED SYSTEMS

Week 9: Distributed Lookup Part 4: Domain Name System (DNS)




Paul Krzyzanowski

© 2021 Paul Krzyzanowski. No part of this content, may be reproduced or reposted in whole or in part in any manner without the permission of the copyright owner.

How are IP addresses assigned?

IP addresses are distributed hierarchically

- Internet Assigned Numbers Authority (IANA) at the top
 - IANA is currently run by ICANN
 - Internet Corporation for Assigned Names and Numbers



How are machine names assigned?


- Early ARPANET
 - Globally unique names per machine (e.g., UCBVAX)
 - Kept track at the Network Information Center (NIC) at the Stanford Research Institute (SRI)
- That doesn't scale!
- A **domain hierarchy** was created in 1984 (RFC 920)
 - Domains are administrative entities: divide name management
 - Tree-structured global name space
 - Textual representation of domain names

`www.cs.rutgers.edu`



Jon Postel
kept approved
and tracked
computer
names &
addresses on
the Internet

Domain Name Hierarchy



Top Level Domains (TLDs)

ccTLD

Country-code domains
ISO 3166 codes
e.g., .us, .de, .ca, .es

IDN ccTLD

Internationalized
country-code domains
e.g., .السعودية, .中國, .pф

gTLD

Generic top-level domains
e.g., .biz, .com, .edu,
.gov, .info, .net, .org,
.audio, .catering, .网络

There are currently 1,589 top-level domains (as of March 30, 2021)

Each top-level domain has an administrator assigned to it

Assignment is delegated to various organizations by the Internet Assigned Numbers Authority (IANA)

IANA keeps track of the **root servers**

See <http://www.iana.org/domains/root/db> for the latest count

Shared registration

- Domain name registry: *this is the database*
 - Keeps track of all domain names registered under a top-level domain
- Domain name registry operator: *this is the company that runs the DB*
 - NIC = Network Information Center – organization that keeps track of the registration of domain names under a top-level domain
 - Keeps the database of domain names
 - See <https://www.icann.org/resources/pages/listing-2012-02-25-en>
- Domain name registrar: *this is the company you use to register*
 - Company that lets you register a domain name
 - Registrars update the registry database at the NIC

Shared registration

- Multiple domain **registrars** provide domain **registration services**
 - 2,437 registrars as of March 2021, including 1202 unique DropCatch.com registrars
- The registrar you choose becomes the **designated registrar** for your domain
 - Maximum period of registration for a domain name = 10 years
- The **registry operator** keeps the **central registry database** for the top-level domain
- Only the designated registrar can change information about domain names
 - A domain name owner may invoke a domain transfer process

Example

- *Namecheap* is the designated registrar for `poopybrain.com`
- *VeriSign*, Inc. is the registry operator for the `.com` gTLD

See <https://www.icann.org/registrar-reports/accredited-list.html> for the latest list of registrars

The problem

Every device connected to the internet has a unique Internet Protocol (IP) address

How do you **resolve** user-friendly machine names to IP addresses?

`www.cs.rutgers.edu` \longrightarrow `128.6.4.24`

Original solution

Through the 1980s

- Search `/etc/hosts` file for machine name (see RFC 606)
- File periodically downloaded from Network Information Center (NIC) at the Stanford Research Institute (SRI)
- This was not sustainable with millions of hosts on the Internet
 - A lot of data
 - A lot of churn in the data
 - new hosts added, deleted, addresses changed
 - Maintenance
 - Traffic volume

Solution doesn't scale!

DNS: Domain Name System


- Distributed database: a hierarchy of **name servers**
- **DNS** is an application-layer protocol
 - Name-address resolution is handled at the edge
 - The network core is unaware of host names ... and does not care
 - There is no special relationship between names and addresses
 - Example: `cs.poopybrain.com` can resolve to `cs.rutgers.edu`

`cs.poopybrain.com` → `cs.rutgers.edu`

DNS servers provide...

- Name to IP address translation
- Aliasing of names (called **canonical** names)
- Identification of name servers
- Names of mail servers
- Load distribution:
 - Multiple name servers may handle a query for a domain
 - Caching – store past look-ups
 - Ability to provide a set of IP addresses for a name

DNS is a distributed, hierarchical database



A collection of DNS servers

Authoritative DNS server

- An **authoritative name server** is responsible for answering queries about its zone
 - Provides *real* answers vs. *cached* answers
 - Configured by the administrator
- **Zone** = group of machines under a node in the tree
E.g., rutgers.edu

A DNS server returns answers to queries

Key data that a DNS server maintains (partial list)

Information	Abbreviation	Description
Host	A	Host address (name to address) Includes name, IP address, time-to-live (TTL)
Canonical name	CNAME	Name for an alias
Mail exchanger	MX	Host that handles email for the domain
Name server	NS	Identifies the name server for the zone: tell other servers that yours is the authority for info within the domain
Start of Zone Authority	SOA	Specifies authoritative server for the zone. Identifies the zone, time-to-live, and primary name server for the zone

Finding your way

- How do you find the DNS Server for rutgers.edu?
 - That's what the **domain registry** keeps track of
 - When you register a domain,
 - You supply the addresses of at least two DNS servers that can answer queries for your zone
 - You give this to the **domain registrar**, who updates the database at the **domain registry**
- So how do you find the right DNS server?
 - Start at the root

Root name servers

- The **root name server** answers can return a list of authoritative name servers for top-level domains
- 13 root name servers
 - A.ROOT-SERVERS.NET, B.ROOT-SERVERS.NET, ...
 - Each has redundancy (via *anycast* routing or load balancing)
 - Each server is really a set of machines



Download the latest list at <http://www.internic.net/domain/named.root>

DNS Queries

- **Iterative** (non-recursive) name resolution

- DNS server will return a definitive answer or a **referral** to another DNS server
 - **referral** = reference to a DNS server for a lower level of the queried namespace
 - Server returns intermediate results to the client
- 1. Send query to a **root** name server
- 2. Send query to an **edu** name server
- 3. Send query to a **rutgers** name server
- **Advantage: stateless**

Quiz answer:

With iterative resolution in DNS...

... a DNS server returns a referral or the requested information

- **Recursive** DNS name resolution


- Name server will take on the responsibility of fully resolving the name
 - May query multiple other DNS servers on your behalf
- **DNS server cannot refer the client to a different server**
- **Disadvantage: name server has more work; has to keep track of state**
- **Advantages: Caching opportunities, less work for the client!**

Most top-level DNS servers only support iterative queries

DNS Resolvers: local name server

- **DNS Resolver** = client side of DNS
 - Not really a part of the DNS hierarchy
 - Acts as an intermediary between programs that need to resolve names and the name servers
 - A resolver is responsible for performing the full resolution of the query
- Where are the resolvers?
 - Each local system has one: that's what applications contact
 - Local cache; may be a process or a library
 - On Linux & Windows, these are limited DNS servers (called **stub resolvers**)
 - Usually not capable of handling referrals and expect to talk with a name server that can handle recursion (full resolution)
 - ISPs (and organizations) run them on behalf of their customers
 - Including a bunch of free ones (OpenDNS, Google Public DNS)
- Resolvers cache past lookups – they are not responsible for zones

DNS Resolvers in action



Local stub resolver:


- check local cache
- check local hosts file
- send request to external resolver

External resolver

- DNS server that accepts recursion
- Running at ISP, Cloudflare, Google Public DNS, OpenDNS, etc.

E.g., on Linux: resolver is configured via the `/etc/resolv.conf` file

Sample query

- Rutgers registered rutgers.edu with the .edu domain
 - educause.net is the domain registry for the .edu gTLD
 - Registration includes defining the name servers for .rutgers.edu
 - ns124.a2.incapsecuredns.net: 192.230.123.124
 - ns8.a1.incapsecuredns.net: 192.230.122.8
 - ns87.a0.incapsecuredns.net: 192.230.121.87
- EDUCAUSE registered its name servers with root name servers
 - ns1.twtelecom.net
 - ns1.educause.edu
 - ns1.twtelecom.net

Name servers for .edu
- We know how to get to root name servers
 - Download <http://www.internic.net/domain/named.root>

Sample Query

Submit query to a local *DNS resolver*:

1. *query(cs.rutgers.edu)* → any root name server
send query to f.root-servers.net: 192.5.5.241
2. Receive *referral* to a list of DNS servers for *edu*
a.edu-servers.net: 192.5.6.30 ... d.edu-servers.net: 192.31.80.30 ...
3. *query(cs.rutgers.edu)* → edu name server
send query to d.edu-servers.net: 192.31.80.30
4. Receive *referral* to *rutgers.edu* name servers:
 - dns2.rutgers.edu. 192.230.121.86
 - ns1.rutgers.edu. 192.230.122.7
 - ru-ufl.rutgers.edu. 192.230.123.123
 - ns6.dnsmadeeasy.com. 208.80.124.13
5. *query(cs.rutgers.edu)* → rutgers name server
send query to 208.80.124.13
6. The rutgers name server returns
 - A: 128.6.48.178 *address*
 - MX: cs-rutgers-edu.mail.protection.outlook.com. *domain name for email*

Caching

- Starting every query at the root would place a huge load on root name servers
- A name server can cache results of previous queries
 - Save query results for a *time-to-live* amount of time
 - The time-to-live value is specified in the domain name record by an authoritative name server

The End