
OpenPGP Card Application

Add-on

Ledger SAS



https://github.com/LedgerHQ/app-openpgp

October 9, 2026

Contents

1 License **1**

2 Introduction **1**
2.1 OpenPGP Card Application add-ons summary . . . 1
2.1.1 Key management: . . . 1
2.1.2 Keys Slots . . . 2
2.1.3 Random number generation . . . 2
2.1.4 Key Backup . . . 3

3 Ledger OpenPGP Application **3**
3.1 How . . . 3
3.1.1 Deterministic key derivation . . . 3
3.1.2 Deterministic random number . . . 4
3.1.3 Key Backup & Restore . . . 5
3.2 APDU Modification . . . 5
3.2.1 Key Slot management . . . 5
3.2.2 Deterministic key derivation . . . 6
3.2.3 Deterministic random number . . . 6
3.3 Other minor add-on . . . 6

1 License

Ledger App OpenPGP.
(c) 2024 Ledger SAS.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

2 Introduction

2.1 OpenPGP Card Application add-ons summary

2.1.1 Key management:

OpenPGP Application manage 4 keys to Perform Security Operation (PSO) plus 2 for secure channel.

The 4 keys are defined as follow:

- One asymmetric signature private key (RSA or EC), named 'sig'
- One asymmetric decryption private key (RSA or EC), named 'dec'
- One asymmetric authentication private key (RSA or EC), named 'aut'
- One symmetric decryption private key (AES), named 'sym0'

The 3 first asymmetric keys can be either randomly generated on-card or explicitly imported from outside.

The 4th is imported from outside.

It's never possible to retrieve private key from the card.

This add-on specification propose a solution to derive those keys from the master seed managed by the Ledger Token. This allows owner to restore a broken token without the needs to keep track of keys outside the card.

Moreover this add-on specification propose to manage multiple set of the 4 previously described keys.

2.1.2 Keys Slots

To modify the keys slot, just select the corresponding menu from the screen.

Nano



Wallet (Stax, Flex)



2.1.3 Random number generation

OpenPGP Application provides, as optional feature, to generate random bytes.

This add-on specification propose new type of random generation:

- random prime number generation
- seeded random number
- seeded prime number generation

2.1.4 Key Backup

A full key backup mechanism is provided.

DANGER

On-device data is wiped on every App or OS update.
The OpenPGP App stores all keys and metadata in its own non-volatile memory. Anything generated or imported on the device is erased whenever the App is reinstalled, which happens during any App update and during any OS update.
The backup/restore mechanism described here (and the companion `pytools` script) is, today, the only available mitigation. It is **not trivial to operate and not guaranteed to work in every scenario** — private-key restore in particular only works when **SEED mode** was enabled when the backup was taken. It remains a procedure reserved to advanced users.

3 Ledger OpenPGP Application

3.1 How

3.1.1 Deterministic key derivation

The deterministic key derivation process relies on the **BIP32** scheme. The master install path of the App is set to `/0x80'GPG'`, aka `/80475047`.

Deterministic key derivation maybe activated in:

```
Settings -> Seed Mode -> Set on
```

This activation remains effective until *set off* is selected.

The key management remains the same if seed mode is *on* or *off*. So there is no performance impact when using seeded keys.

Seeded keys are generated as follow:

Step 1:

For a given keys slot n, starting from 1, a seed is first derived with the following path

```
Sn = BIP32_derive (/0x80475047'/n')
```

The last index is hardened, so that the seed of one slot gives no information on the other slots.

Step 2:

Then specific seeds are derived with the *SHAKE256* function for each key:

```
Sk[i] = SHAKE256(SHA256("kdf2" \| Sn \| <key_name> \| int16(i) \| int8(len(ctx))
\| ctx), length)
```

Where:

- Sn is the dedicated slot seed from step 1.
- key_name is one of 'sig ','dec ', 'aut ', each 4 characters.
- i is the index, starting from 1, of the desired seed (see below)
- ctx is the algorithm with the key size: the first 3 bytes of the key attributes for RSA (algorithm and modulus size), the whole key attributes for ECC (algorithm and curve OID).
- length is the output length, in bytes.

Step 3:

RSA key generation

Generate two seed Sp, Sq in step2 with:

- i € {1,2}
- length equals to half key size

Generate two prime numbers p, q:

- set the two most significant bits of Sp and Sq
- p = next_prime(Sp)
- q = next_prime(Sq)

Generate RSA key pair as usual:

- choose e
- n = p*q
- d = inv(e) mod (p-1)(q-1)

ECC key generation

Generate one seed Sd in step2 with:

- i = 1
- length equals to twice the curve size

Generate ECC key pair:

- d = Sd mod curve order, on the curve size
- for Curve25519, d is clamped as in RFC 7748
- W = d.G

Legacy derivation

App versions up to 2.x derived the seeded keys differently, and this derivation is only kept to restore their keys (see P2 of GENERATE ASYMMETRIC KEY PAIR):

- step 1 uses a non-hardened last index: `Sn = BIP32_derive (/0x80475047'/n)`
- step 2 hashes neither "kdf2" nor ctx: `SHA256(Sn | <key_name> | int16(i))`
- only the first length/8 bytes of the key buffer are derived:
  - for RSA, the rest of Sp and Sq is zero, and only their most significant bit is set
  - for ECC, the derivation is done over Sn, so d is these bytes followed by the rest of Sn, without reduction nor clamping

WARNING

A legacy RSA key can be factored from its public key alone, and the legacy ECC keys of a slot share most of their bytes. Keys restored with the legacy derivation should be replaced by newly generated ones.

AES key generation

Generate one seed Sd in step2 with:

- i = 1
- length equals to 16

Generate AES key:

- k = Sk

3.1.2 Deterministic random number

The deterministic random number generation relies on the **BIP32** scheme. The master install path of the App is set to `/0x80'GPG'`, aka `/80475047`.

Random prime number generation:

For a given length L:

- generate random number r of L bytes.
- generate rp = next_prime(r)

- return rp

Seeded random number:

For a given length L and seed S:

- generate Sr = BIP32_derive(/0x80475047/0x0F0F0F0F)
- generate r = SHA3-XOF(SHA256(Sr | 'rnd' | S), L)
- return r

Seeded prime number generation:

For a given length L and seed S:

- generate r as for "Seeded random number"
- generate rp = next_prime(r)
- return rp

3.1.3 Key Backup & Restore

In order to backup/restore private key the commands put_data and get_data accept the tags:

- B6 (signature key)
- B8 (encryption key)
- A4 (authentication).

put_data command accept the exact output of get_data. The get_data command return both the public and private key.

For security and confidentiality, private key is returned encrypted in AES. The key used is derived according to previously described AES key derivation with name 'key'.

The data payload is formatted as follow:

size	Description
4	OS Target ID
4	API Level
4	public key size
var	public key
4	private key size
var	encrypted private key

3.2 APDU Modification

3.2.1 Key Slot management

Key slots are managed by data object *01F1* and *01F2* witch are manageable by PUT/GET DATA command as for others DO and organized as follow.

On application reset, the *01F2* content is set to *Default Slot* value of *01F1*.

01F1:

bytes	Description	R/W
1	Number of slot	R
2	Default slot	R/W
3	Allowed slot selection method	R/W

Byte 3 is encoded as follow:

b8	b7	b6	b5	b4	b3	b2	b1	Meaning
-	-	-	-	-	-	-	x	selection by APDU
-	-	-	-	-	-	x	-	selection by screen

01F2:

bytes	Description	R/W
1	Current slot	R/W

01F0:

bytes	Description	R/W
1-3	01F1 content	R
4	01F2 content	R

Access Conditions:

DO	Read	Write
01F0	Always	Never
01F1	Always	Verify PW3
01F2	Always	Verify PW2

3.2.2 Deterministic key derivation

P2 parameter of GENERATE ASYMMETRIC KEY PAIR is set to (hex value):

- 00 for the default generation: a seeded key when the Seed mode is *on*, a random key otherwise
- 01 for a seeded key with the legacy derivation, to restore the keys of app versions up to 2.x
- 02 for a seeded key, whatever the Seed mode

A restore regenerates each key with 02 first, then with 01 when the key does not match the fingerprint of the backup; once a key matches, its value of P2 is tried first for the next keys.

3.2.3 Deterministic random number

P1 parameter of GET CHALLENGE is a bit-field encoded as follow:

b8	b7	b6	b5	b4	b3	b2	b1	Meaning
-	-	-	-	-	-	-	x	seeded random
-	-	-	-	-	-	x	-	prime random

When *seeded mode* is set, data field contains the seed and P2 contains the length of random bytes to generate.

3.3 Other minor add-on

GnuPG use both fingerprints and serial number to identify key on card. So, the put_data command is able to modify the AID file with '4F' tag. In that case the data field shall be 4 bytes length and shall contain the new serial number. '4F' is protected by PW3 (admin) PIN.