📖 yayinternet / **module-examples**

No description, website, or topics provided.

ⓘ **8** commits	⑂ **1** branch	◇ **0** releases	👥 **1** contributor

Branch: master ▾   New pull request   Create new file   Upload files   Find File   Clone or download ▾

👤 **vrk** Update README.md   Latest commit `bba7cbd` on 31 May 2017

📁 dictionary-with-routes	add files	2 years ago
📁 simple-middleware	clean	2 years ago
📁 simple-modules	add modules	2 years ago
📄 README.md	Update README.md	2 years ago

📖 **README.md**

NodeJS Module examples

simple-modules

- Directory with several simple modules
- The main script is `scripts.js` and only requires `print-util.js`
- Examples explained in Lecture 25
- To run:
    - In your terminal, navigate to the `module-examples/simple-modules/` directory
    - Run `$ node scripts.js`
- Try loading the other modules (e.g. `function-module.js`) by changing the `require` statement in `scripts.js`. See Lecture 25 for more details.

simple-middleware

- Simple server with middleware function that runs on each request
- Example explained in Lecture 25
- To run:
    - In your terminal, navigate to the `module-examples/simple-middle/` directory
    - Run `$ node scripts.js`
    - Navigate to http://localhost:3000
    - See that the "request to server!" message prints on the terminal every time you make a request
        - Try loading http://localhost:3000/hello/hello/hello for instance

dictionary-with-routes

- Dictionary lookup example with server-side rendering using Handlebars, organized in different files via NodeJS modules and Express routes
- Each word in the dictionary has its own page, like http://localhost:3000/dog
- Example explained in Lecture 25
- To run:
    - In your terminal, run `$ mongod`. Keep that process running and don't close the terminal.
    - Create a second terminal window. In this terminal window, navigate to the `dictionary-server-side/` directory
    - Run `$ npm install`
    - Run `$ npm start`

- View the running app at http://localhost:3000