

# 파이썬 라이브러리를 활용한 데이터 분석

## 3장: 판다스 시작하기

# 파이썬 라이브러리를 활용한 데이터 분석

## 5장 2절 핵심기능

2020.06.25(목) 2h

# 재색인

## • obj.reindex()

- 새로운 색인에 맞도록 새로 생성
- 존재하지 않는 색인의 값에는 NaN 추가

```
In [70]: obj = pd.Series([4.5, 7.2, -5.3, 3.6], index=['d', 'b', 'a', 'c'])
obj
```

```
Out[70]: d    4.5
         b    7.2
         a   -5.3
         c    3.6
         dtype: float64
```

```
In [71]: obj2 = obj.reindex(['a', 'b', 'c', 'd', 'e'])
obj2
```

```
Out[71]: a   -5.3
         b    7.2
         c    3.6
         d    4.5
         e    NaN
         dtype: float64
```

```
In [72]: obj3 = pd.Series(['blue', 'purple', 'yellow'], index=[0, 2, 4])
obj3
```

```
Out[72]: 0    blue
         2   purple
         4   yellow
         dtype: object
```

```
In [75]: obj3.reindex(range(6))
```

```
Out[75]: 0    blue
         1    NaN
         2   purple
         3    NaN
         4   yellow
         5    NaN
         dtype: object
```

```
In [74]: obj3.reindex(range(6), method='ffill')
```

```
Out[74]: 0    blue
         1    blue
         2   purple
         3   purple
         4   yellow
         5   yellow
         dtype: object
```

누락된 값을 이전  
값으로 저장

# loc[행명, 열명]

- 이름을 여러 개
  - 리스트 형태로
- 슬라이싱도 가능
  - `frame.loc['a':'c', 'Texas':'California']`
- Columns 재색인

```
In [135]: frame = pd.DataFrame(np.arange(9).reshape((3, 3)),
                                index=['a', 'c', 'd'],
                                columns=['Ohio', 'Texas', 'California'])
frame
```

Out[135]:

	Ohio	Texas	California
a	0	1	2
c	3	4	5
d	6	7	8

```
In [136]: frame2 = frame.reindex(['a', 'b', 'c', 'd'])
frame2
```

Out[136]:

	Ohio	Texas	California
a	0.0	1.0	2.0
b	NaN	NaN	NaN
c	3.0	4.0	5.0
d	6.0	7.0	8.0

```
In [137]: states = ['Texas', 'Utah', 'California']
frame.reindex(columns = states)
```

Out[137]:

	Texas	Utah	California
a	1	NaN	2
c	4	NaN	5
d	7	NaN	8

```
In [126]: frame.loc[['a', 'c'], ['Texas', 'California']]
```

Out[126]:

	Texas	California
a	1	2
c	4	5

# 하나의 행이나 열 삭제

- 선택한 값들이 삭제된 객체를 반환
  - 옵션 inplace=True
    - 원본 객체에 반영
- 행 삭제
  - drop('행명')
    - ['행명1', '행명2', ...]
- 열 삭제
  - Drop('열명', axis=1)
    - ['열명1', '열명2', ...]

```
In [156]: obj = pd.Series(np.arange(5.), index=['a', 'b', 'c', 'd', 'e'])
obj.drop('c', inplace=True)
obj
```

```
Out[156]: a    0.0
b    1.0
d    3.0
e    4.0
dtype: float64
```

```
In [144]: data = pd.DataFrame(np.arange(16).reshape((4, 4)),
                             index=['Ohio', 'Colorado', 'Utah', 'New York'],
                             columns=['one', 'two', 'three', 'four'])
data
```

```
Out[144]:
```

	one	two	three	four
Ohio	0	1	2	3
Colorado	4	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

```
In [145]: data.drop(['Colorado', 'Ohio'])
```

```
Out[145]:
```

	one	two	three	four
Utah	8	9	10	11
New York	12	13	14	15

```
In [146]: data.drop('two', axis=1)
```

```
Out[146]:
```

	one	three	four
Ohio	0	2	3
Colorado	4	6	7
Utah	8	10	11
New York	12	14	15

```
In [147]: data.drop(['two', 'four'], axis='columns')
```

```
Out[147]:
```

	one	three
Ohio	0	2
Colorado	4	6
Utah	8	10
New York	12	14

## 시리즈 색인

p203

- 정수와 인덱스 라벨 모두 가능
  - 라벨 슬라이싱은 끝점도 포함

```
In [157]: obj = pd.Series(np.arange(4.), index=['a', 'b', 'c', 'd'])
           obj
```

```
Out[157]: a    0.0
           b    1.0
           c    2.0
           d    3.0
           dtype: float64
```

```
In [158]: obj['b']
```

```
Out[158]: 1.0
```

```
In [159]: obj[1]
```

```
Out[159]: 1.0
```

```
In [160]: obj[2:4]
```

```
Out[160]: c    2.0
           d    3.0
           dtype: float64
```

```
In [161]: obj[['b', 'a', 'd']]
```

```
Out[161]: b    1.0
           a    0.0
           d    3.0
           dtype: float64
```

```
In [162]: obj[[1, 3]]
```

```
Out[162]: b    1.0
           d    3.0
           dtype: float64
```

```
In [163]: obj[obj < 2]
```

```
Out[163]: a    0.0
           b    1.0
           dtype: float64
```

```
In [164]: obj['b':'c']
```

```
Out[164]: b    1.0
           c    2.0
           dtype: float64
```

```
In [165]: obj['b':'c'] = 5
           obj
```

```
Out[165]: a    0.0
           b    5.0
           c    5.0
           d    3.0
           dtype: float64
```

# 데이터프레임의 열과 행 참조

p206

- `df['열명'], df[['열명1', '열명2', ...]]`

- `df[m:n]`

- 슬라이싱으로 로우를 선택
- `df[정수]`

- 정수의 열이 없으면 오류

- `df[조건]`

- 조건이 참인 로우를 선택

```
In [170]: data[data['three'] > 5]
```

```
Out[170]:
```

	one	two	three	four
Colorado	4	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

```
In [171]: data < 5
```

```
Out[171]:
```

	one	two	three	four
Ohio	True	True	True	True
Colorado	True	False	False	False
Utah	False	False	False	False
New York	False	False	False	False

```
In [166]: data = pd.DataFrame(np.arange(16).reshape((4, 4)),
                                index=['Ohio', 'Colorado', 'Utah', 'New York'],
                                columns=['one', 'two', 'three', 'four'])
data
```

```
Out[166]:
```

	one	two	three	four
Ohio	0	1	2	3
Colorado	4	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

```
In [167]: data['two']
```

```
Out[167]: Ohio      1
Colorado    5
Utah        9
New York   13
Name: two, dtype: int32
```

```
In [168]: data[['three', 'one']]
```

```
Out[168]:
```

	three	one
Ohio	2	0
Colorado	6	4
Utah	10	8
New York	14	12

# loc과 iloc으로 선택하기

- 이름 선택: **df.loc(행명, 열명)**
  - 슬라이싱도 가능: 끝도 포함
- 정수 색인 선택: **df.iloc(행번호, 열번호)**
  - 슬라이싱도 가능

## Selection with loc and iloc

```
In [173]: data
```

```
Out[173]:
```

	one	two	three	four
Ohio	0	0	0	0
Colorado	0	5	6	7
Utah	8	9	10	11
New York	12	13	14	15

```
In [174]: data.loc['Colorado', ['two', 'three']]
```

```
Out[174]: two      5
          three    6
          Name: Colorado, dtype: int32
```

```
In [175]: data.iloc[2, [3, 0, 1]]
```

```
Out[175]: four     11
          one       8
          two       9
          Name: Utah, dtype: int32
```

```
In [176]: data.iloc[2]
```

```
Out[176]: one      8
          two      9
          three    10
          four     11
          Name: Utah, dtype: int32
```

```
In [177]: data.iloc[[1, 2], [3, 0, 1]]
```

```
Out[177]:
```

	four	one	two
Colorado	7	0	5
Utah	11	8	9

```
In [178]: data.loc[:, 'Utah', 'two']
```

```
Out[178]: Ohio      0
          Colorado   5
          Utah       9
          Name: two, dtype: int32
```

```
In [179]: data.iloc[:, :3]
```

```
Out[179]:
```

	one	two	three
Ohio	0	0	0
Colorado	0	5	6
Utah	8	9	10
New York	12	13	14

```
In [180]: data.iloc[:, :3][data.three > 5]
```

```
Out[180]:
```

	one	two	three
Colorado	0	5	6
Utah	8	9	10
New York	12	13	14



# 데이터프레임 색인

Table 5-4. Indexing options with DataFrame

Type	Notes
<code>df[val]</code>	Select single column or sequence of columns from the DataFrame; special case conveniences: <code>boolean array (filter rows)</code> , <code>slice (slice rows)</code> , or <code>boolean DataFrame</code> (set values based on some criterion)
<code>df.loc[val]</code>	Selects single row or subset of rows from the DataFrame by label
<code>df.loc[:, val]</code>	Selects single column or subset of columns by label
<code>df.loc[val1, val2]</code>	Select both rows and columns by label
<code>df.iloc[where]</code>	Selects single row or subset of rows from the DataFrame by integer position
<code>df.iloc[:, where]</code>	Selects single column or subset of columns by integer position
<code>df.iloc[where_i, where_j]</code>	Select both rows and columns by integer position
<code>df.at[label_i, label_j]</code>	Select a single scalar value by row and column label
<code>df.iat[i, j]</code>	Select a single scalar value by row and column position (integers)
<code>reindex method</code>	Select either rows or columns by labels
<code>get_value, set_value methods</code>	Select single value by row and column label

# 정수 색인

- 정수 색인
  - `iloc()` 사용 권장
- 라벨 색인
  - `ser.loc[:1]`

```
In [182]: ser = pd.Series(np.arange(3.))
          ser
```

```
Out[182]: 0    0.0
          1    1.0
          2    2.0
          dtype: float64
```

```
In [190]: ser[0]
```

*#ser[-1] # 색인 자체가 정수, -1을 라벨로 인지하고 검색, 오류 발생*

```
Out[190]: 0.0
```

```
In [191]: ser2 = pd.Series(np.arange(3.), index=['a', 'b', 'c'])
          ser2[-1]
```

```
Out[191]: 2.0
```

```
In [192]: ser[:1]
```

```
Out[192]: 0    0.0
          dtype: float64
```

```
In [193]: ser.loc[:1]
```

```
Out[193]: 0    0.0
          1    1.0
          dtype: float64
```

```
In [194]: ser.iloc[:1]
```

```
Out[194]: 0    0.0
          dtype: float64
```

라벨이므로  
1까지이다.

# 시리즈 산술 연산과 데이터 정렬

## • + 연산

– 연산에 참여하는 값이 하나라도 na라면 결과는

• NaN

```
In [195]: s1 = pd.Series([7.3, -2.5, 3.4, 1.5], index=['a', 'c', 'd', 'e'])
          s2 = pd.Series([-2.1, 3.6, -1.5, 4, 3.1],
                        index=['a', 'c', 'e', 'f', 'g'])
          s1
```

```
Out[195]: a    7.3
          c   -2.5
          d    3.4
          e    1.5
          dtype: float64
```

```
In [196]: s2
```

```
Out[196]: a   -2.1
          c    3.6
          e   -1.5
          f    4.0
          g    3.1
          dtype: float64
```

```
In [197]: s1 + s2
```

```
Out[197]: a    5.2
          c    1.1
          d   NaN
          e    0.0
          f   NaN
          g   NaN
          dtype: float64
```

# 데이터프레임 산술 연산과 데이터 정렬

- 양쪽에 겹치지 않은 부분은 NaN

```
In [198]: df1 = pd.DataFrame(np.arange(9.).reshape((3, 3)), columns=list('bcd'),
                             index=['Ohio', 'Texas', 'Colorado'])
df2 = pd.DataFrame(np.arange(12.).reshape((4, 3)), columns=list('bde'),
                   index=['Utah', 'Ohio', 'Texas', 'Oregon'])
df1
```

Out[198]:

	b	c	d
Ohio	0.0	1.0	2.0
Texas	3.0	4.0	5.0
Colorado	6.0	7.0	8.0

In [199]: df2

Out[199]:

	b	d	e
Utah	0.0	1.0	2.0
Ohio	3.0	4.0	5.0
Texas	6.0	7.0	8.0
Oregon	9.0	10.0	11.0

In [200]: df1 + df2

Out[200]:

	b	c	d	e
Colorado	NaN	NaN	NaN	NaN
Ohio	3.0	NaN	6.0	NaN
Oregon	NaN	NaN	NaN	NaN
Texas	9.0	NaN	12.0	NaN
Utah	NaN	NaN	NaN	NaN

# 산술 연산 메소드에 채워 넣을 값 지정하기

## • 옵션 fill\_value=0

```
In [205]: df1 = pd.DataFrame(np.arange(12.).reshape((3, 4)),
                             columns=list('abcd'))
df1
```

Out[205]:

	a	b	c	d
0	0.0	1.0	2.0	3.0
1	4.0	5.0	6.0	7.0
2	8.0	9.0	10.0	11.0

```
In [206]: df2 = pd.DataFrame(np.arange(20.).reshape((4, 5)),
                             columns=list('abcde'))
df2.loc[1, 'b'] = np.nan
df2
```

Out[206]:

	a	b	c	d	e
0	0.0	1.0	2.0	3.0	4.0
1	5.0	NaN	7.0	8.0	9.0
2	10.0	11.0	12.0	13.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [208]: df1.add(df2, fill_value=0)
```

Out[208]:

	a	b	c	d	e
0	0.0	2.0	4.0	6.0	4.0
1	9.0	5.0	13.0	15.0	9.0
2	18.0	20.0	22.0	24.0	14.0
3	15.0	16.0	17.0	18.0	19.0

```
In [207]: df1 + df2
```

Out[207]:

	a	b	c	d	e
0	0.0	2.0	4.0	6.0	NaN
1	9.0	NaN	13.0	15.0	NaN
2	18.0	20.0	22.0	24.0	NaN
3	NaN	NaN	NaN	NaN	NaN

# 데이터프레임과 시리즈 간의 연산(1)

## • 브로드캐스팅과 동일

- 칼럼에 맞추고 로우로 전파

```
In [215]: frame = pd.DataFrame(np.arange(12.).reshape((4, 3)),
                                columns=list('bde'),
                                index=['Utah', 'Ohio', 'Texas', 'Oregon'])
frame
```

Out[215]:

	b	d	e
Utah	0.0	1.0	2.0
Ohio	3.0	4.0	5.0
Texas	6.0	7.0	8.0
Oregon	9.0	10.0	11.0

```
In [216]: series = frame.iloc[0]
series
```

Out[216]:

b	0.0
d	1.0
e	2.0

Name: Utah, dtype: float64

```
In [217]: frame - series
```

Out[217]:

	b	d	e
Utah	0.0	0.0	0.0
Ohio	3.0	3.0	3.0
Texas	6.0	6.0	6.0
Oregon	9.0	9.0	9.0

# 데이터프레임과 시리즈 간의 연산(2)

- 색인 값을 DataFrame의 열이나 Series의 색인에서 찾을 수 없다면
  - 그 개체는 형식을 맞추기 위해 재색인
  - 중복되지 않는 부분은 NaN

In [218]: frame

Out[218]:

	b	d	e
Utah	0.0	1.0	2.0
Ohio	3.0	4.0	5.0
Texas	6.0	7.0	8.0
Oregon	9.0	10.0	11.0

In [221]: series2 = pd.Series(range(3), index=['b', 'e', 'f'])  
series2

Out[221]:

b	0
e	1
f	2

dtype: int64

In [222]: frame + series2

Out[222]:

	b	d	e	f
Utah	0.0	NaN	3.0	NaN
Ohio	3.0	NaN	6.0	NaN
Texas	6.0	NaN	9.0	NaN
Oregon	9.0	NaN	12.0	NaN

# 시리즈 값을 열로 전파

## • 행 연산: axis='index' 또는 0

- 원래는 칼럼에 맞추고 로우로 전파하나 축이 0이므로 그대로 열로 전파

```
In [224]: series3 = frame['d']
          series3
```

```
Out[224]:
```

Utah	1.0	1	1
Ohio	4.0	4	4
Texas	7.0	7	7
Oregon	10.0	10	10

Name: d, dtype: float64

```
In [225]: frame
```

```
Out[225]:
```

	b	d	e
Utah	0.0	1.0	2.0
Ohio	3.0	4.0	5.0
Texas	6.0	7.0	8.0
Oregon	9.0	10.0	11.0

```
In [233]: frame.sub(series3)
```

```
Out[233]:
```

	Ohio	Oregon	Texas	Utah	b	d	e
Utah	NaN	NaN	NaN	NaN	NaN	NaN	NaN
Ohio	NaN	NaN	NaN	NaN	NaN	NaN	NaN
Texas	NaN	NaN	NaN	NaN	NaN	NaN	NaN
Oregon	NaN	NaN	NaN	NaN	NaN	NaN	NaN

```
In [226]: frame.sub(series3, axis='index')
```

```
Out[226]:
```

	b	d	e
Utah	-1.0	0.0	1.0
Ohio	-1.0	0.0	1.0
Texas	-1.0	0.0	1.0
Oregon	-1.0	0.0	1.0



# 함수 적용과 매핑

p217

- **Numpy 유니버설 함수 적용 가능**

- 각 원소에 적용되는 메소드

- **df.apply(함수, axis=0)**

- 축 행에 따른 연산이 기본
  - axis=1

- **축 열에 따라 계산**

```
In [236]: f = lambda x: x.max() - x.min()
          frame.apply(f)
```

```
Out[236]: b    1.802165
          d    1.684034
          e    2.689627
          dtype: float64
```

```
In [237]: frame.apply(f, axis='columns')
```

```
Out[237]: Utah    0.998382
          Ohio    2.521511
          Texas    0.676115
          Oregon  2.542656
          dtype: float64
```

```
In [234]: frame = pd.DataFrame(np.random.randn(4, 3), columns=list('bde'),
                               index=['Utah', 'Ohio', 'Texas', 'Oregon'])
          frame
```

```
Out[234]:
```

	b	d	e
Utah	-0.204708	0.478943	-0.519439
Ohio	-0.555730	1.965781	1.393406
Texas	0.092908	0.281746	0.769023
Oregon	1.246435	1.007189	-1.296221

```
In [235]: np.abs(frame)
```

```
Out[235]:
```

	b	d	e
Utah	0.204708	0.478943	0.519439
Ohio	0.555730	1.965781	1.393406
Texas	0.092908	0.281746	0.769023
Oregon	1.246435	1.007189	1.296221

열에서 최대-최소

행에서 최대-최소

# 함수 반환 값이 시리즈

- 여러 값을 가진 시리즈 반환도 가능

```
In [238]: def f(x):
           return pd.Series([x.min(), x.max()], index=['min', 'max'])
           frame
```

Out[238]:

	b	d	e
Utah	-0.204708	0.478943	-0.519439
Ohio	-0.555730	1.965781	1.393406
Texas	0.092908	0.281746	0.769023
Oregon	1.246435	1.007189	-1.296221

```
In [240]: frame.apply(f)
```

Out[240]:

	b	d	e
min	-0.555730	0.281746	-1.296221
max	1.246435	1.965781	1.393406

```
In [241]: frame.apply(f, axis=1)
```

Out[241]:

	min	max
Utah	-0.519439	0.478943
Ohio	-0.555730	1.965781
Texas	0.092908	0.769023
Oregon	-1.296221	1.246435

# 배열의 원소에 적용되는 함수 사용

- **df.applymap(함수명)**
  - Series.map(함수명)

```
In [243]: format = lambda x: '%.2f' % x
          frame
```

```
Out[243]:
```

	b	d	e
Utah	-0.204708	0.478943	-0.519439
Ohio	-0.555730	1.965781	1.393406
Texas	0.092908	0.281746	0.769023
Oregon	1.246435	1.007189	-1.296221

```
In [244]: frame.applymap(format)
```

```
Out[244]:
```

	b	d	e
Utah	-0.20	0.48	-0.52
Ohio	-0.56	1.97	1.39
Texas	0.09	0.28	0.77
Oregon	1.25	1.01	-1.30

```
In [246]: frame['e'].map(format)
```

```
Out[246]: Utah      -0.52
Ohio        1.39
Texas       0.77
Oregon     -1.30
Name: e, dtype: object
```

# 정렬과 순위

## • 행, 열의 색인을 정렬: `sort_index`

– 옵션 `axis=`

```
In [249]: frame = pd.DataFrame(np.arange(8).reshape((2, 4)),
                                index=['three', 'one'],
                                columns=['d', 'a', 'b', 'c'])
frame
```

Out[249]:

	d	a	b	c
three	0	1	2	3
one	4	5	6	7

```
In [251]: frame.sort_index(axis=1)
```

Out[251]:

	a	b	c	d
three	1	2	3	0
one	5	6	7	4

```
In [250]: frame.sort_index()
```

Out[250]:

	d	a	b	c
one	4	5	6	7
three	0	1	2	3

```
In [252]: frame.sort_index(axis=1, ascending=False)
```

Out[252]:

	d	c	b	a
three	0	3	2	1
one	4	7	6	5

# 값에 따른 정렬

## • 메소드 df.sort\_values()

- 시리즈에서 NaN는 마지막에 배치
- 데이터프레임에서 반드시 필요한 인자 by='열명'
  - 정렬할 열명, 없으면 오류
  - by=['열명1', '열명2' ...]

```
In [254]: obj = pd.Series([4, np.nan, 7, np.nan, -3, 2])
          obj.sort_values()
```

```
Out[254]: 4    -3.0
          5     2.0
          0     4.0
          2     7.0
          1     NaN
          3     NaN
          dtype: float64
```

```
In [255]: frame = pd.DataFrame({'b': [4, 7, -3, 2], 'a': [0, 1, 0, 1]})
          frame
```

```
Out[255]:
```

	b	a
0	4	0
1	7	1
2	-3	0
3	2	1

```
In [260]: frame.sort_values(by='b')
```

```
Out[260]:
```

	b	a
2	-3	0
3	2	1
0	4	0
1	7	1

```
In [257]: frame.sort_values(by=['a', 'b'])
```

```
Out[257]:
```

	b	a
2	-3	0
0	4	0
3	2	1
1	7	1

# 값에 따른 정렬 **axis=1**

- 지정된 행의 값에 따라 정렬

In [387]: df

Out[387]:

	col1	col2	col3
0	A	2	0
1	A	1	1
2	B	9	9
3	NaN	8	4
4	D	7	2
5	C	4	3

In [388]: df.sort\_values(by=3, axis=1)

Out[388]:

	col3	col2	col1
0	0	2	A
1	1	1	A
2	9	9	B
3	4	8	NaN
4	2	7	D
5	3	4	C

# 시리즈 항목의 순위

- 메소드 `series.rank()`, `df.rank()`
  - 동점인 항목은 평균 순위가 기본
  - 옵션 `method='first'`, `method='max'`
    - 먼저 나타난 순서 대로 순위
    - 동등이면 큰 값으로
      - 1등이 3개이면 모두 3
  - 옵션 `ascending=False`
    - 내림차순으로

```
In [274]: obj = pd.Series([7, -5, 7, 4, 2, 0, 4])
          obj.rank()
```

```
Out[274]: 0    6.5
          1    1.0
          2    6.5
          3    4.5
          4    3.0
          5    2.0
          6    4.5
          dtype: float64
```

```
In [275]: obj.rank(method='first')
```

```
Out[275]: 0    6.0
          1    1.0
          2    7.0
          3    4.0
          4    3.0
          5    2.0
          6    5.0
          dtype: float64
```

```
In [276]: # Assign tie values the maximum rank in the group
          obj.rank(ascending=False, method='max')
```

```
Out[276]: 0    2.0
          1    7.0
          2    2.0
          3    4.0
          4    5.0
          5    6.0
          6    4.0
          dtype: float64
```

# 데이터프레임 항목의 순위

## • 메소드 df.rank()

- 동점인 항목은 평균 순위가 기본
- 옵션 method='first', method='max'
  - 먼저 나타나 순서 대로 순위
  - 동등이면 큰 값으로
    - 1등이 3개이면 모두 3
- 옵션 ascending=False
  - 내리차순으로

## • 데이터프레임에서

- 모든 열에 대해 순위를 매김
- axis=1
  - 모든 행에 대해 각 값의 순위를 매김
    - 3등, 2등, 1등

```
In [277]: frame = pd.DataFrame({'b': [4.3, 7, -3, 2], 'a': [0, 1, 0, 1],
                                'c': [-2, 5, 8, -2.5]})
frame
```

Out[277]:

	b	a	c
0	4.3	0	-2.0
1	7.0	1	5.0
2	-3.0	0	8.0
3	2.0	1	-2.5

```
In [278]: frame.rank(axis='columns')
```

Out[278]:

	b	a	c
0	3.0	2.0	1.0
1	3.0	1.0	2.0
2	1.0	2.0	3.0
3	3.0	2.0	1.0



# 각 열에서 등수 표시

- 옵션 **axis=0**
  - 이것이 기본
    - 각 열에서의 값의 등수 표시

In [61]: frame

Out[61]:

	b	a	c
0	4.3	0	-2.0
1	7.0	1	5.0
2	-3.0	0	8.0
3	2.0	1	-2.5

In [60]: frame.rank(axis=0)

Out[60]:

	b	a	c
0	3.0	1.5	2.0
1	4.0	3.5	3.0
2	1.0	1.5	4.0
3	2.0	3.5	1.0

# 중복 색인

## • 색인 값은 중복 가능

- 시리즈에서 참조 시 결과가 여러 개면 시리즈 반환

```
In [283]: obj = pd.Series(range(5), index=['a', 'a', 'b', 'b', 'c'])
obj
```

```
Out[283]: a    0
          a    1
          b    2
          b    3
          c    4
          dtype: int64
```

```
In [284]: obj.index.is_unique
```

```
Out[284]: False
```

```
In [285]: obj['a']
```

```
Out[285]: a    0
          a    1
          dtype: int64
```

```
In [286]: obj['c']
```

```
Out[286]: 4
```

```
In [287]: df = pd.DataFrame(np.random.randn(4, 3), index=['a', 'a', 'b', 'b'])
df
```

```
Out[287]:
```

	0	1	2
a	0.274992	0.228913	1.352917
a	0.886429	-2.001637	-0.371843
b	1.669025	-0.438570	-0.539741
b	0.476985	3.248944	-1.021228

```
In [289]: df.loc['b']
```

```
Out[289]:
```

	0	1	2
b	1.669025	-0.438570	-0.539741
b	0.476985	3.248944	-1.021228

```
In [292]: df[1] #열 자체의 레이블이 1
```

```
Out[292]:
```

```
a    0.228913
a   -2.001637
b   -0.438570
b    3.248944
Name: 1, dtype: float64
```