Probe-Gated Critic Transfer: Latent Team Discovery from Individual Reward Responses

Anonymous Submission

Abstract

Agents that share a workspace need not share a goal. We study online latent team discovery in fully decentralized multi-team reinforcement learning, where each agent observes only its own observations and individual reward, team labels are never given, and agents communicate only on physical contact. We propose Probe-Gated Critic Transfer (PGCT). Each agent learns a predictor of its own reward. When two agents meet, both predictors answer a common set of public reward-event probes, and a normalized response distance, smoothed over rounds, approves persistent agreement; agents without enough reward experience abstain. To test whether the discovered relation is useful, an approved teammate's Critic evaluates the receiver's own history, and its positive uplift enters a masked, scale-limited Max-GAE advantage for the Actor only, while every Critic keeps learning its own return. In a six-agent, two-team warehouse task, discovery separates teammates from about 0.25M steps (response distance 0.25 versus 0.99) and directs 93.7% of approved peer access to true teammates over 5M steps. Learning comparisons of the integrated method are in progress.

1 Introduction

Cooperation in multi-agent reinforcement learning (MARL) usually assumes that the cooperating group is known. A shared team reward, a centralized Critic, or parameter sharing all presuppose which agents belong together [Yu *et al.*, 2022; Christianos *et al.*, 2021]. In many deployments this assumption is not available. Several teams of robots may work in the same warehouse, each team serving its own request queue and delivering to its own goal. An agent sees its neighbors, but proximity does not reveal whether a neighbor pursues the same task. If the agent shares value information indiscriminately, estimates learned for different goals are mixed. If it never shares, it cannot benefit from a teammate that has already learned the task.

We therefore ask two questions. **Q1 (discovery):** can an agent identify its latent teammates online, using only its own experience and local communication? **Q2 (use):** once teammates are identified, does their value information help the agent learn? Q1 is the main subject of this paper; Q2 serves to test whether the discovered relation is useful for learning.

A natural signal for Q1 is policy similarity. However, policies of agents with the same task can differ while they learn, and agents with different tasks can behave alike when both act almost randomly. We instead use the quantity that defines a task: the reward. Agents of the same team receive reward under the same rule, so the same event should be rewarding for both. Agents of different teams are rewarded for different events. Each agent can learn this rule from its own reward without sharing any reward value. Two agents then compare what their reward predictors say about a common set of public events. This comparison raises three difficulties. Reward events are sparse. Observations contain task-private channels that must not be exchanged. And an agent without reward experience has no reward rule to compare.

Contributions. (i) We formulate online latent team discovery in fully decentralized multi-team MARL with individual rewards, no team labels and contact-limited communication. (ii) We propose a reward-response probe test for discovery: each agent learns a predictor of its own reward from public transitions; agents that meet compare predictions on common reward-event probes with a scale-free distance; persistent agreement approves the pair, agents without enough own reward evidence abstain, and only information that existed at the time of contact enters the comparison. (iii) We use the discovered relation through selective peer-Critic access: an approved teammate's Critic evaluates the receiver's own history, and its positive uplift shapes the Actor advantage through a masked, scale-limited Max-GAE term, while each Critic keeps its own-return target and the method reduces exactly to independent PPO when no teammate is approved. (iv) We report discovery logs, an offline replay of the discovery rule and a counterfactual check of why the team relation matters for peer values in a warehouse task, together with a branch protocol for the pending learning comparison.

2 Related Work

Independent and shared learning. Independent learners optimize their own objective and remain strong baselines in cooperative MARL [Tan, 1993; de Witt *et al.*, 2020;

Papoudakis *et al.*, 2021]. PPO and generalized advantage estimation (GAE) are standard components of such learners [Schulman *et al.*, 2017; Schulman *et al.*, 2016; Yu *et al.*, 2022]. Shared Experience Actor-Critic shares experience among cooperating agents [Christianos *et al.*, 2020]. Selective parameter sharing groups agents before sharing parameters [Christianos *et al.*, 2021]. Fully decentralized actor-critic methods let networked agents reach consensus on a common Critic [Zhang *et al.*, 2018]. These methods assume that the group with a common objective is given, or that all agents share one objective. PGCT instead infers the group from individual rewards and keeps separate Actors and Critics.

Modelling other agents. Agent modelling infers properties of other agents, such as goals, types or policies [Albrecht and Stone, 2018]. Ad hoc teamwork asks an agent to cooperate with unknown teammates without prior coordination [Stone *et al.*, 2010]. Our inferred object is narrower: whether another agent is rewarded by the same rule. The inference uses the agent's own reward predictor and a peer's predictions on public events. It requires no model of the peer's policy.

Combining several value functions. Generalized policy improvement combines value functions of several policies through a maximum [Barreto *et al.*, 2017]. MAMBA uses the statewise maximum of several oracle values inside a GAE-style estimator and gives improvement guarantees when these oracle values are estimated in the learner's state distribution [Cheng *et al.*, 2020]. Our Max-GAE term follows this aggregation idea. Its premises are not met, however. A peer Critic is trained on the peer's own histories and is evaluated on the receiver's history; it is not an oracle value re-estimated by rollouts. We therefore claim no performance guarantee and treat the peer value as an auxiliary Actor signal whose effect must be measured.

3 Problem Setting

Consider N agents in a partially observable environment. Agent i receives an observation $o_{i,t}$, takes an action $a_{i,t}$ and receives its own scalar reward $r_{i,t}$. Each agent has a hidden team label z_i, and agents of one team are rewarded by the same rule. Two agents are *latent teammates* if $z_i = z_j$. Labels are used only for evaluation and for oracle baselines.

Information model. Each agent keeps its own recurrent Actor and Critic. Agents i and j can communicate during rollout u only if they come within Chebyshev distance r_c at some step:

$$C^u_{ij} = \mathbf{1}[\exists t \text{ in rollout } u : \|p_{i,t} - p_{j,t}\|_\infty \le r_c], \qquad (1)$$
$$\mathcal{G}^u_i = \{j \neq i : C^u_{ij} B_{ij} = 1\}.$$

We take the communication radius equal to the observation radius ($r_c = 5$ in our task), so an agent can talk to the agents it can see; the radius of the reported runs is stated in Section 6.1. On contact, agents may exchange public event views, their predicted rewards on those views and Critic weights. They never exchange reward values, team labels, Actor weights or private trajectories. A public projection P removes task-private observation channels (requested shelves and the agent's own goal) and absolute coordinates. In the implementation, $P(o)$ keeps six ego features and eleven physical grid channels within radius two, a 281-dimensional view. Actor and Critic use the full semantic observation with the two coordinate entries set to zero.

Goal. Each agent should estimate the relation $\mathbf{1}[z_i = z_j]$ for agents it meets, abstain when it lacks evidence, and use the estimate to improve its own learning without changing its own reward or its Critic's target.

4 Probe-Gated Critic Transfer

Figure 1 and Algorithm 1 summarize one PGCT update. Steps 1–4 answer Q1; steps 5–7 answer Q2.

4.1 Individual Reward Prediction

Each agent fits a multilayer perceptron to its own reward on public transitions $q = (u_t, a_t, u_{t+1})$:

$$\widehat{r}_i(q; \psi_i) = \mathrm{MLP}_{\psi_i}[u_t, \mathrm{onehot}(a_t), u_{t+1}], \quad u_t = P(o_{i,t}). \qquad (2)$$

The input has $281+5+281 = 567$ dimensions, and the hidden layers have 128 and 64 ReLU units. Each agent stores its last 20,000 transitions and, separately, its last 512 reward events. An event is a transition with own reward $r_i \ge 0.5$; in our task these are deliveries and shelf returns. Events make up less than 0.5% of transitions, so a quarter of every training batch is drawn from the event buffer. The loss is

$$\mathcal{L}^r_i = \mathbb{E}_{(q,r_i)\sim\mathcal{B}^{\mathrm{mix}}_i}[(\widehat{r}_i(q;\psi_i) - r_i)^2]. \qquad (3)$$

Every five PPO updates, the predictor takes 50 Adam steps (batch 256, learning rate 10^{-3}). Because public views hide task-private information, the same public transition can be rewarding or not. The regression then learns the conditional mean of the reward, which is the quantity we compare.

4.2 Reward Probes

When i and j have met during rollout u, they build a common probe set

$$\mathcal{Q}^u_{ij} = \mathcal{E}^u_i \cup \mathcal{E}^u_j. \qquad (4)$$

Here $\mathcal{E}^u_i$ is the public view of the 32 most recent own events of agent i recorded before rollout u starts. Probes are concatenated with repetitions. Reward values are never part of a probe. The two event sets already contain the question that separates teams when both agents have rewarded events: a delivery at one goal is rewarding for one team and not for the other. When the map has a known left–right symmetry, the probe set can optionally be augmented with mirrored copies $M(\mathcal{E}^u_i \cup \mathcal{E}^u_j)$, where M mirrors views and turning actions; this adds an assumption about the map and is not part of the core method. Our runs use this augmentation (Section 6.1).

Causal snapshot. Comparisons happen at the end of a rollout, but a pair may have met early in it. To use only information that existed at contact time, each agent freezes its event probes, its maturity flag and its predictor version at the start of rollout u. Predictors are refitted only after a rollout, so the frozen version is exactly the predictor used during the rollout. The comparison for rollout u uses this frozen state and is performed before the predictors are refitted.




Figure 1: Overall PGCT procedure for one agent. Steps 2–4 discover latent teammates from the agent's own reward; steps 5–7 use approved teammates only through the Actor advantage. All computation is local; peers exchange public event views, predicted responses and Critic weights only on contact.




Figure 2: Reward-based team discovery for a pair of agents that met. Both predictors answer the same public probes. Teammates assign reward to the same probes (distance near 0). Agents of different teams assign reward to complementary probes (distance near 1). Bars are an illustration, not data. Agents without enough own reward events abstain.

4.3 Response Distance and Team Discovery

Both predictors evaluate the same probes (Figure 2). Their discrepancy is

$$D_{ij}^u = \frac{\sum_{q \in \mathcal{Q}_{ij}^u} |\hat{r}_i^u(q) - \hat{r}_j^u(q)|}{\sum_{q \in \mathcal{Q}_{ij}^u} \left(|\hat{r}_i^u(q)| + |\hat{r}_j^u(q)|\right)}. \tag{5}$$

Probes on which both predictors answer zero add nothing to the numerator or the denominator. Many uninformative probes therefore do not dilute the distance. If the denominator is below 10^{-8} the comparison abstains. An agent is *mature* ($m_i^u = 1$) if it has observed at least 20 own events, its predictor has been fitted, and its mean prediction on its own recent events is at least 0.3. Pairs are compared every five updates and only if both agents are mature. The distance is smoothed across comparison rounds and the pair is approved by

$$\bar{D}_{ij} \leftarrow (1-\beta)\bar{D}_{ij} + \beta D_{ij}^u, \tag{6}$$
$$B_{ij} = \mathbf{1}[i \neq j,\ n_{ij} \geq n_{\min},\ \bar{D}_{ij} < \tau,\ m_i^u = m_j^u = 1].$$

Here n_{ij} counts rounds in which both predictors were refitted on new experience; we use $\beta = 0.35$, $n_{\min} = 3$ and $\tau = 0.5$. The approval is symmetric and persists when the agents lose contact; a stale approval is used only if the pair meets again. The threshold $\tau = 0.5$ means that most of the response mass is shared; it is fixed in advance and not tuned on our runs. No team label enters this decision.

4.4 Selective Peer Critic Access

The donor set of agent i for rollout u is

$$\mathcal{G}_i^u = \{j \neq i : C_{ij}^u = 1,\ B_{ij} = 1\}. \tag{7}$$

Donor Critic weights are those used during rollout u and are received on contact; they are frozen during the update. Agent

Algorithm 1 One PGCT update of agent i

1: At rollout start, freeze event probes, maturity flag and predictor version.
2: Collect the rollout; store own public transitions and own events; record contacts C^u_{ij}.
3: **if** the update index is a multiple of five **then**
4: Compare contacted mature pairs on frozen probes; update $\bar{D}_{ij}$ and n_{ij} (Eqs. 5–6).
5: Refit the reward predictor on own experience (Eq. 3).
6: **end if**
7: Donors: approved peers met in this rollout (Eq. 7).
8: Replay own history through donor Critics; compute b, f and A^{PGCT} (Eqs. 8–10).
9: Update the Actor by PPO with A^{PGCT} and the Critic toward its own return (Eq. 11).

i replays its own observation sequence through each donor Critic and obtains a donor-specific recurrent state $\tilde{h}^j_{i,t}$. The donor's hidden state is never sent. The replay starts from a zero state at the rollout boundary and resets at episode ends. Until eight observations have passed or the first reset occurs, the replayed value is not yet reliable, and a mask $w_t = 0$ removes it.

4.5 Max-GAE Advantage Estimation

For a nonempty donor set, the positive uplift and the combined value are

$$b_{i,t} = \Big[\max_{j \in \mathcal{G}^u_i} V_j(\tilde{h}^j_{i,t}) - V_i(h_{i,t}) \Big]_+, \qquad (8)$$
$$f_{i,t} = V_i(h_{i,t}) + w_t b_{i,t}.$$

The GAE recursion uses the trainer's termination and time-limit handling:

$$\delta^f_{i,t} = r_{i,t} + \gamma(1-d_t) f_{i,t+1} + \gamma z^f_{i,t} - f_{i,t}, \qquad (9)$$
$$A^f_{i,t} = \delta^f_{i,t} + \gamma\lambda_f (1-d_t) A^f_{i,t+1}.$$

where d_t marks episode ends and $z^f_{i,t}$ is the value of a captured time-limit observation (zero otherwise). The self advantage A^{self} uses the same recursion with V_i in place of f. With $\gamma = 0.99$ and $\lambda_f = \lambda = 0.95$, the Actor advantage is

$$A^{\text{PGCT}}_{i,t} = A^{\text{self}}_{i,t} + \eta\, s_i\, w_t \big(A^f_{i,t} - A^{\text{self}}_{i,t}\big), \qquad \eta = 0.5, \quad (10)$$
$$s_i = \min\left(1, \frac{\text{std}_t\, A^{\text{self}}_{i,t}}{\max\big(\text{std}_t\; w_t(A^f_{i,t} - A^{\text{self}}_{i,t}),\, 10^{-8}\big)}\right).$$

Figure 3 shows the computation. Two details matter. First, the mask w_t multiplies the advantage difference $A^f - A^{\text{self}}$, not only b. Masking only b would let future uplift leak into the cold-start steps through the GAE recursion. Second, the factor $s_i \le 1$ shrinks a large auxiliary term to the scale of the agent's own advantage but never inflates a small one. In our task the raw difference was 2.6–12 times std A^{self} for lagging agents. Without s_i, PPO's advantage normalization would make the result almost independent of η.

4.6 Actor and Critic Updates

After per-agent normalization, write the Actor advantage as $\widetilde{A}_{i,t}$. PPO uses

$$\rho_{i,t}(\theta_i) = \pi_{\theta_i}(a_{i,t} \mid h_{i,t}) / \pi_{\theta_i^{\text{old}}}(a_{i,t} \mid h_{i,t}), \qquad (11)$$
$$L^\pi_i = \mathbb{E}_t[\min\{\rho_{i,t}\widetilde{A}_{i,t}, \text{clip}(\rho_{i,t}, 1-\epsilon, 1+\epsilon)\widetilde{A}_{i,t}\}],$$
$$R^{\text{self}}_{i,t} = A^{\text{self}}_{i,t} + V^{\text{old}}_i(h_{i,t}).$$

The Actor maximizes the clipped objective plus an entropy bonus. The Critic minimizes the trainer's clipped value loss toward its own return R^{self}; there is no peer distillation loss. Actor and Critic have separate encoders and recurrent layers. They share one gradient-norm clip, so a different Actor advantage can change the effective Critic step size but not its target.

5 Properties

Bounded, scale-free distance. By the triangle inequality, $D^u_{ij} \in [0,1]$ whenever its denominator is positive. The distance does not depend on the reward scale shared by both predictors.

A necessary condition for discovery. If two reward rules induce the same predictor responses on every public probe available to the agents, no rule that sees only these responses can tell them apart. Discovery therefore requires task-discriminating public reward events. An agent that has never received a qualifying reward has no response to compare, and PGCT abstains for it by design.

Reduction to independent PPO. If $\mathcal{G}^u_i = \emptyset$ or $b_{i,t} = 0$ for all t, then $A^f = A^{\text{self}}$ and therefore $A^{\text{PGCT}} = A^{\text{self}}$. Because $s_i \le 1$, the change $|A^{\text{PGCT}} - A^{\text{self}}|$ goes to zero as the uplift does. For a fixed donor set, unmasked steps and fixed s_i, GAE is linear in its value input, and the Actor advantage equals GAE computed with $V_i + \eta s_i w_t b_i$.

Sensitivity to value errors. For bounded value perturbations Δf on continuing trajectories,

$$\|\Delta A\|_\infty \le \left(1 + \frac{\gamma(1-\lambda)}{1-\gamma\lambda}\right) \|\Delta f\|_\infty. \qquad (12)$$

This bounds how a peer-value error can move the advantage. It is not a performance guarantee: the peer value is extrapolated to another agent's histories, other agents keep learning, and contacts change between rollouts.

6 Experiments

6.1 Setup

Environment. We use a multi-team variant of the robotic warehouse [Papoudakis *et al.*, 2021]: an 11×10 grid with six agents in two teams of three. The team goals are at the two bottom corners, $(0, 10)$ and $(9, 10)$. Each team has three requested shelves. Observations are semantic grids with sensor radius five. Every agent receives its own reward: 1 for a delivery, 1 for a shelf return, 0.15 for picking up a requested shelf, small progress terms (0.02, 0.005, 0.002) and small penalties (0.002–0.05) for unproductive actions. No team reward




Figure 3: Selective peer Critic use by receiver i. Approved donor Critics evaluate i's own history. Their positive uplift changes only the Actor advantage, while the Critic keeps learning its own return. Without a donor or an uplift, PGCT is independent PPO.

Setting	Value
Rollout / recurrent sequence	1024 / 64 steps
PPO epochs / minibatches	4 / 8
Learning rate / entropy	2×10^{-4} / 0.05
PPO clip / value clip	0.2 / 0.2
Discount / GAE parameter	0.99 / 0.95
Encoder / GRU width	128 / 128
Reward fit: interval / steps	5 updates / 50
Event threshold / maturity	$r \geq 0.5$ / 20 events
EMA β / threshold τ / rounds $n_{\min}$	0.35 / 0.5 / 3
Contact radius r_c (Chebyshev), runs	3
Mirrored probes, runs	yes
Max-GAE η / scale	0.5 / shrink

Table 1: Environment interaction and PGCT settings.

is used. Table 1 lists the learning settings. The reported runs differ from the default method in two settings: they use a contact radius $r_c = 3$, smaller than the observation radius, and they augment probes with mirrored copies. A contact within radius 3 is also a contact within radius 5, so the default only adds contacts; without mirrors, an offline replay gave the same decisions (Section 6.2). Runs with $r_c = 5$ and without mirrors are pending.

Compared methods. All methods use the same observations, rewards, network sizes and PPO settings. (i) Independent PPO. (ii) True-team Max-GAE: donors are true teammates met in the rollout, an upper bound on discovery. (iii) True-team Max-GAE restricted to agents with mature reward predictors; this separates the cost of abstention from the cost of discovery errors. (iv) PGCT. (v) Count-matched random donors, which receive as many donors as (ii). Labels are used only by (ii), (iii) and evaluation.

Protocol and metrics. Evaluation uses 20 deterministic episodes of 500 steps with fixed reset seeds. The learning comparison branches all methods from a common independent-PPO checkpoint at 1.024M steps (seed 1) and trains each for 0.5M further steps with seeds 1, 3 and 5, which keep the checkpoint's goal layout. At this checkpoint three agents (a_0, a_1, a_4) deliver little or nothing. The primary outcome is their evaluation deliveries; the deliveries of a_2, a_3, a_5 are a safety measure. Branch seeds continue one training run and are not independent training seeds; independent runs from scratch will follow if the branch shows an effect.

6.2 Team Discovery

Figure 4 shows a 5M-step run (seed 1) in which the discovery rule of PGCT was active. Same-team and different-team pairs separate as soon as agents mature. In the 0.1–0.25M bin, the mean response distance is 0.25 for teammates and 0.99 for others, and five of six agents are mature by 0.25M. The same-team distance keeps falling (0.08 after 4M). The different-team distance stays near 0.99 until about 1M and then slowly declines. Over the run, 5,252 directed peer-access arcs went to true teammates and 352 to agents of the other team, a same-team share of 93.7%. The first different-team approval appears at 4.28M steps, so all access before that point was correct. This share is weighted by access frequency and is not a pair-level accuracy. The run used update-end positions as contacts and an earlier peer-usage rule, so it evaluates the discovery component only.

As an offline check, we replayed a subsample of the experience of a completed independent-PPO run (0.26–5M steps, about 1/180 of its transitions) through the same rule, assuming every pair is in contact at every round. Of the 15 pairs, the 10 that reached a decision were all classified correctly: four same-team approvals and no different-team approval (same-team distances 0.14–0.18, different-team 0.58–0.70). The other five pairs all involved the one agent that never learned to deliver, and they abstained. Removing the mirrored probes from this replay left every decision unchanged.




Figure 4: Discovery in the warehouse task (corner goals, individual rewards, seed 1, 5M steps). (a) Mean response-distance EMA of compared pairs, 100k-step bins; the dashed line is the approval threshold. (b) Number of agents with a mature reward predictor. (c) Cumulative directed peer-access arcs by true relation.

6.3 Why the Team Relation Matters for Peer Values

Is a teammate's Critic useful only for teammates? We ran a counterfactual check on saved checkpoints of independent PPO. From the same environment state, we let a lagging agent act either with its own policy or with a peer's policy, while all other agents kept their own policies, and compared the lagging agent's own return over 100 steps (common random numbers, 8 repetitions). Across four checkpoint datasets (two time points of one run and two runs of an earlier configuration with visible coordinates), when a same-team peer Critic predicted an uplift above 0.2 for the lagging agent, the peer's policy actually increased the agent's return in 67–100% of cases, with mean gains of 0.28–0.58. Different-team uplifts of similar size corresponded to mean gains of only -0.01 to 0.14. For leading agents, different-team Critics often predicted uplifts that came with significant losses. The predicted uplift also overestimated the real gain by up to a factor of 1.6. These observations motivate both the discovery step and the conservative scaling of the uplift.

6.4 Learning Performance

Figure 5 shows the independent PPO baseline from scratch (two seeds). After 5M steps it reaches 25.7 and 24.1 deliveries per evaluation episode, and the learning progress is uneven across agents. The integrated PGCT comparison (Table 2) is running and is reported as pending. We do not report partial curves.




Figure 5: Independent PPO from scratch: evaluation deliveries per 500-step episode (corner goals, individual rewards).

7 Limitations

Discovery depends on reward experience. Agents that never receive a qualifying reward cannot be matched, and they may be exactly the agents that need help most. In our checkpoint, two of the three lagging agents had no delivery or return events, so PGCT abstains for them while a true-team method does not. Probes cover only experienced events, and mirrors assume that predictions generalize to mirrored scenes. Late in the 5M run, the different-team distance declines and a few cross-team approvals appear; the cause is not yet analyzed. A peer Critic estimates returns under the peer's own policy and history distribution, so its value on another agent's history can be biased, and the maximum can amplify this bias. Scale shrinkage limits the Actor perturbation but does not prove that it helps. With 1,024-step rollouts nearly all pairs meet at least once, so the contact rule mainly limits how fast approvals accumulate. Finally, current evidence comes from one environment family and few seeds.

8 Conclusion

PGCT discovers latent teammates online from individual reward responses. Each agent predicts its own reward, compares predictions on public reward-event probes with peers it meets, and approves only persistent agreement backed by enough own experience. The discovered relation is used conservatively: approved teammates' Critics shape the Actor advantage through a masked, scale-limited Max-GAE term, and each Critic keeps its own return. In a two-team warehouse, discovery separates teammates early and directs most peer ac-

Method (branch, +0.5M)	Lagging agents	Leading agents
Independent PPO	*pending*	*pending*
True-team Max-GAE	*pending*	*pending*
True-team, mature only	*pending*	*pending*
PGCT	*pending*	*pending*
Count-matched random	*pending*	*pending*

Table 2: Evaluation deliveries after branching from the common 1.024M-step checkpoint (seeds 1, 3, 5). Results will be inserted when the runs finish.

cess to true teammates. Whether this access speeds up learning is being tested in the pending branch comparison.

References

[Albrecht and Stone, 2018] Stefano V. Albrecht and Peter Stone. Autonomous agents modelling other agents: A comprehensive survey and open problems. *Artificial Intelligence*, 258:66–95, 2018.

[Barreto *et al.*, 2017] André Barreto, Will Dabney, Rémi Munos, Jonathan J. Hunt, Tom Schaul, Hado van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

[Cheng *et al.*, 2020] Ching-An Cheng, Andrey Kolobov, and Alekh Agarwal. Policy improvement via imitation of multiple oracles. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[Christianos *et al.*, 2020] Filippos Christianos, Lukas Schäfer, and Stefano V. Albrecht. Shared experience actor-critic for multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[Christianos *et al.*, 2021] Filippos Christianos, Georgios Papoudakis, Arrasy Rahman, and Stefano V. Albrecht. Scaling multi-agent reinforcement learning with selective parameter sharing. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, 2021.

[de Witt *et al.*, 2020] Christian Schroeder de Witt, Tarun Gupta, Denys Makoviichuk, Viktor Makoviychuk, Philip H. S. Torr, Mingfei Sun, and Shimon Whiteson. Is independent learning all you need in the StarCraft multi-agent challenge? *arXiv preprint arXiv:2011.09533*, 2020.

[Papoudakis *et al.*, 2021] Georgios Papoudakis, Filippos Christianos, Lukas Schäfer, and Stefano V. Albrecht. Benchmarking multi-agent deep reinforcement learning algorithms in cooperative tasks. In *NeurIPS Datasets and Benchmarks*, 2021.

[Schulman *et al.*, 2016] John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

[Schulman *et al.*, 2017] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[Stone *et al.*, 2010] Peter Stone, Gal A. Kaminka, Sarit Kraus, and Jeffrey S. Rosenschein. Ad hoc autonomous agent teams: Collaboration without pre-coordination. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 24, 2010.

[Tan, 1993] Ming Tan. Multi-agent reinforcement learning: Independent vs. cooperative agents. In *Proceedings of the Tenth International Conference on Machine Learning*, pages 330–337, 1993.

[Yu *et al.*, 2022] Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of PPO in cooperative multi-agent games. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, volume 35, 2022.

[Zhang *et al.*, 2018] Kaiqing Zhang, Zhuoran Yang, Han Liu, Tong Zhang, and Tamer Başar. Fully decentralized multi-agent reinforcement learning with networked agents. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 5872–5881, 2018.