

2025년 상반기 K-디지털 트레이닝

# AOP

---

## [KB] IT's Your Life


✓ 다음 프로젝트를 생성하세요.

- 템플릿: SpringLegacy
- name: aopex

 다음과 같이 SampleService를 추가하세요.

```
package org.scoula.sample.service;
```

```
public interface SampleService {  
    public Integer doAdd(String str1, String str2) throws Exception;  
}
```




 다음과 같이 SampleServiceImpl.java를 추가하세요.

```
package org.scoula.sample.service;

import org.springframework.stereotype.Service;

@Service
public class SampleServiceImpl implements SampleService {

    @Override
    public Integer doAdd(String str1, String str2) throws Exception {
        return Integer.parseInt(str1) + Integer.parseInt(str2);
    }
}
```



✓ RootConfig 설정을 다음과 같이 수정하세요.

- AOP 기능 활성화
- 컴포넌트 스캔
  - org.scoula.advice
  - org.scoula.sample.service


## Rootconfig

```
@Configuration
@ComponentScan(basePackages = {
    "org.scoula.advice",
    "org.scoula.sample.service"
})
@EnableAspectJAutoProxy
public class RootConfig {

}
```

- ✓ LogAdvice를 추가하고, SampleService의 모든 메서드에 대해 Before Advice 설정하고, 해당 메서드가 호출됐을 때, 로그를 출력하세요.

○ 로그 내용: "====="



## LogAdvice

```
package org.scoula.advice;
```

```
import lombok.extern.log4j.Log4j2;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Before;
import org.springframework.stereotype.Component;
```

**@Aspect**

@Log4j2

@Component

```
public class LogAdvice {
```


```
    @Before("execution(* org.scoula.sample.service.SampleService*.*(..))")
```

```
    public void logBefore() {
```

```
        log.info("=====");
```

```
    }
```

```
}
```







- ✓ 테스트 클래스 `SampleServiceTest`를 추가하고, Before Advice 동작을 확인하세요.

## test::SampleServiceTest.java

```
package org.scoula.sample.service;
...
@ExtendWith(SpringExtension.class)
@ContextConfiguration(classes = { RootConfig.class })
@Log4j2
class SampleServiceTest {
    @Autowired
    private SampleService service;

    @Test
    public void doAdd() throws Exception {
        log.info(service.doAdd("123", "456"));
    }
}
```



**INFO : org.scoula.advice.LogAdvice - =====**

INFO : org.scoula.sample.service.SampleServiceTest - 579

> Task :test

- ✓ SampleService의 doAdd 메서드에 대해 매개변수를 체크하는 Before Advice 추가하고, 단위 테스트로 확인하세요.
  - 로그 내용:
    - 매개변수명: 실제값

...

```
public class LogAdvice {
```

```
    @Before("execution(* org.scoula.sample.service.SampleService*.doAdd(String, String)) && args(str1, str2)")
```

```
    public void logBeforeWithParam(String str1, String str2) {
```

```
        log.info("str1:" + str1);
```

```
        log.info("str2:" + str2);
```

```
    }
```

```
}
```

INFO : org.scoula.advice.LogAdvice - =====

**INFO : org.scoula.advice.LogAdvice - str1:123**

**INFO : org.scoula.advice.LogAdvice - str2:456**

INFO : org.scoula.sample.service.SampleServiceTest - 579

