

“

Suricata 是一个免费和开源，成熟，快速且强大的网络威胁检测引擎。

Suricata引擎能够进行实时入侵检测（IDS），内联入侵防御（IPS），网络安全监控（NSM）和离线pcap处理。Suricata使用强大而广泛的规则和签名语言检查网络流量，并具有强大的Lua脚本支持来检测复杂的威胁。通过YAML和JSON之类的标准输入和输出格式，与现有SIEM，Splunk，Logstash / Elasticsearch，Kibana和其他数据库之类的工具的集成变得毫不费力。

安装

```
1  # Recommended dependency
2  apt-get install libpcap3 libpcap3-dbg libpcap3-dev build-essential libpcap-dev \
3                      libnet1-dev libyaml-0-2 libyaml-dev pkg-config zlib1g zlib1g-dev \
4                      libcap-ng-dev libcap-ng0 make libmagic-dev \
5                      libgeoip-dev liblua5.1-dev libhiredis-dev libevent-dev \
6                      python-yaml rustc cargo
7
8  # Binary packages - Ubuntu
9  sudo add-apt-repository ppa:oisf/suricata-stable
10 sudo apt-get update
11 # `jq` help with displaying information from Suricata's EVE JSON output
12 sudo apt-get install suricata jq
13
14 # Verify Installation
15 sudo suricata --build-info
16 sudo systemctl status suricata
17 # Outputs:
18 ● suricata.service - LSB: Next Generation IDS/IPS
19    Loaded: loaded (/etc/init.d/suricata; bad; vendor preset: enabled)
20    Active: active (exited) since 2021-05-25 15:29:42 CST; 2min 27s ago
21    Docs: man:systemd-sysv-generator(8)
22
23 5月 25 15:29:42 ubuntu systemd[1]: Starting LSB: Next Generation IDS/IPS...
24 5月 25 15:29:42 ubuntu suricata[39360]: Starting suricata in IDS (af-packet)
25 5月 25 15:29:42 ubuntu systemd[1]: Starte™d LSB: Next Generation IDS/IPS.
26
27 # update rules: merge the lastet rules to /etc/suricata/rules/*
28 suricate-update
```

网卡配置

```
vim /etc/suricata/suricata.yaml
```

本例中，网卡为 `ens33`

```
1  # Linux high speed capture support
2  af-packet:
3    - interface: ens33
4      # Number of receive threads. "auto" uses the number of cores
5    ...
6    ...
7  # default rules
8  default-rule-path: /var/lib/suricata/rules
9
10 rule-files:
11   - suricata.rules
```

修改完成后重启服务 `systemctl restart suricata`

测试

使用 `2100498` 规则进行测试。规则可在 `/var/lib/suricata/rules/suricata.rules` 查看：

```
1  alert ip any any -> any any (msg:"GPL ATTACK_RESPONSE id check returned root";
  content:"uid=0|28|root|29|"; classtype:bad-unknown; sid:2100498; rev:7;
  metadata:created_at 2010_09_23, updated_at 2010_09_23;)
```

`tail` 查看 `fast.log` 文件，运行 `curl http://testmyids.org/uid/index.html`。可看到log文件中，增加到了监测内容。

```
1 # path of log files
2 fastlog_file:"/var/log/suricata/fast.log"
3 log_file:"/var/log/suricata/suricata.log"
4 statistics_file:"/var/log/suricata/stats.log"
5
6 suricata tail -f fast.log
7 # Outputs:
8 05/25/2021-17:10:53.943090  [**] [1:2013028:5] ET POLICY curl User-Agent Outbound
  [**] [Classification: Attempted Information Leak] [Priority: 2] {TCP}
  192.168.205.6:50856 -> 13.225.103.101:80
9 05/25/2021-17:10:54.040108  [**] [1:2100498:7] GPL ATTACK_RESPONSE id check returned
  root [**] [Classification: Potentially Bad Traffic] [Priority: 2] {TCP}
  13.225.103.101:80 -> 192.168.205.6:50856
```

```
1 curl http://testmynids.org/uid/index.html
2 # Outputs:
3 uid=0(root) gid=0(root) groups=0(root)
```

“

参考:

<https://suricata.readthedocs.io/en/latest/>