

My Project

Generated by Doxygen 1.8.15

1 Hierarchical Index	1
1.1 Class Hierarchy	1
2 Class Index	3
2.1 Class List	3
3 Class Documentation	5
3.1 optimazation.pkg1.Algorithm Class Reference	5
3.1.1 Constructor & Destructor Documentation	5
3.1.1.1 Algorithm()	5
3.1.2 Member Function Documentation	6
3.1.2.1 calc()	6
3.1.2.2 crossover()	6
3.1.2.3 expbin()	7
3.1.2.4 getFitness()	7
3.1.2.5 mutate()	8
3.1.2.6 mutateandRecombine()	8
3.1.2.7 reduce()	8
3.1.2.8 select() [1/2]	9
3.1.2.9 select() [2/2]	9
3.1.2.10 selectParent()	10
3.1.2.11 tournament()	10
3.2 optimazation.pkg1.CreateCSV Class Reference	10
3.2.1 Detailed Description	11
3.2.2 Member Function Documentation	11
3.2.2.1 CreateCsv()	11
3.2.2.2 CreateCsv0()	11
3.2.2.3 CreateCsv1()	12
3.3 optimazation.pkg1.CreateMatrix Class Reference	12
3.3.1 Detailed Description	12
3.3.2 Constructor & Destructor Documentation	13
3.3.2.1 CreateMatrix()	13
3.3.3 Member Function Documentation	13
3.3.3.1 add()	13
3.3.3.2 create()	13
3.4 optimazation.pkg1.Functioning Class Reference	14
3.4.1 Detailed Description	14
3.4.2 Member Function Documentation	14
3.4.2.1 funct()	14
3.5 optimazation.pkg1.Functions Class Reference	15
3.5.1 Detailed Description	15
3.5.2 Member Function Documentation	15
3.5.2.1 Ackely2()	15

3.5.2.2 Ackley1()	16
3.5.2.3 Alpine()	16
3.5.2.4 DeJong()	16
3.5.2.5 EggHolder()	16
3.5.2.6 Griewangk()	17
3.5.2.7 Levy()	17
3.5.2.8 Masters()	17
3.5.2.9 Michalewicz()	18
3.5.2.10 Pathological()	18
3.5.2.11 Quartic()	18
3.5.2.12 Rana()	18
3.5.2.13 Rastrigin()	19
3.5.2.14 Rosenbrock()	19
3.5.2.15 Schwefel()	19
3.5.2.16 SineEnvelope()	20
3.5.2.17 Step()	20
3.5.2.18 StretchedV()	20
3.6 optimazation.pkg1.IterativeLocalSearch Class Reference	20
3.6.1 Detailed Description	21
3.6.2 Constructor & Destructor Documentation	21
3.6.2.1 IterativeLocalSearch()	21
3.7 optimazation.pkg1.LocalSearch Class Reference	21
3.7.1 Detailed Description	22
3.7.2 Constructor & Destructor Documentation	22
3.7.2.1 LocalSearch()	22
3.8 optimazation.pkg1.Main Class Reference	23
3.8.1 Detailed Description	23
3.8.2 Member Function Documentation	23
3.8.2.1 main()	23
3.9 optimazation.pkg1.MTRandom Class Reference	23
3.9.1 Detailed Description	24
3.9.2 Constructor & Destructor Documentation	25
3.9.2.1 MTRandom() [1/5]	25
3.9.2.2 MTRandom() [2/5]	25
3.9.2.3 MTRandom() [3/5]	25
3.9.2.4 MTRandom() [4/5]	26
3.9.2.5 MTRandom() [5/5]	26
3.9.3 Member Function Documentation	26
3.9.3.1 next()	26
3.9.3.2 pack()	27
3.9.3.3 setSeed() [1/3]	28
3.9.3.4 setSeed() [2/3]	28

3.9.3.5 setSeed() [3/3]	29
3.10 optimazation.pkg1.RandomWalk Class Reference	29
3.10.1 Detailed Description	29
3.10.2 Member Function Documentation	29
3.10.2.1 randomWalk()	29
Index	31

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

optimazation.pkg1.Algorithm	5
optimazation.pkg1.CreateCSV	10
optimazation.pkg1.CreateMatrix	12
optimazation.pkg1.Functioning	14
optimazation.pkg1.Functions	15
optimazation.pkg1.IterativeLocalSearch	20
optimazation.pkg1.LocalSearch	21
optimazation.pkg1.Main	23
optimazation.pkg1.RandomWalk	29
Random	
optimazation.pkg1.MTRandom	23

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

optimazation.pkg1.Algorithm	5
optimazation.pkg1.CreateCSV	
CreateCSV class	10
optimazation.pkg1.CreateMatrix	
CreateMatrix class	12
optimazation.pkg1.Functioning	
Functioning class	14
optimazation.pkg1.Functions	15
optimazation.pkg1.IterativeLocalSearch	20
optimazation.pkg1.LocalSearch	21
optimazation.pkg1.Main	
Optimization1 class	23
optimazation.pkg1.MTRandom	23
optimazation.pkg1.RandomWalk	29

Chapter 3

Class Documentation

3.1 optimazation.pkg1.Algorithm Class Reference

Public Member Functions

- [Algorithm](#) (int rows, int columns, int functNum) throws FileNotFoundException, UnsupportedEncodingException↵
Exception
- void [getFitness](#) (double[] result)
- int [selectParent](#) ()
- double [][] [select](#) (double [][] input)
- double [][] [tournament](#) (double [][] input)
- void [crossover](#) (double[] p1, double[] p2, int n)
- void [mutate](#) (double[] cr, double Upper, double Lower)
- void [reduce](#) (double[] popu, double[][] newpopu, int Elitism, int functionNum) throws FileNotFoundException
- double [][] [mutateandRecombine](#) (double[][] init, double F, int functionNum, int num)
- double [] [select](#) (double[][] a, int functionNum)
- double [calc](#) (double[][] a, int functionNum)
- double [expbin](#) (int num, int best, int i, double F, double Lam, int j, int r1, int r2, int r3, int r4, int r5)

3.1.1 Constructor & Destructor Documentation

3.1.1.1 Algorithm()

```
optimazation.pkg1.Algorithm.Algorithm (
    int rows,
    int columns,
    int functNum ) throws FileNotFoundException, UnsupportedEncodingException
```

The constructor for Genetic [Algorithm](#) and Differential [Algorithm](#). Create initialize populations.

Parameters

<i>populations</i>	
<i>chromazones</i>	
<i>functNum</i>	

Exceptions

<i>FileNotFoundException</i>	
<i>UnsupportedEncodingException</i>	

3.1.2 Member Function Documentation

3.1.2.1 calc()

```
double optimazation.pkg1.Algorithm.calc (
    double a[][],
    int functionNum )
```

calc method to get best solution after differential algorithm.

Parameters

<i>newpopulation</i>	
<i>functionNum</i>	

Returns

solution

3.1.2.2 crossover()

```
void optimazation.pkg1.Algorithm.crossover (
    double [] p1,
    double [] p2,
    int n )
```

Crossover method(CR probability(0.8~0.95).

Parameters

<i>First</i>	parent
<i>Second</i>	parent
<i>number</i>	of crossover point.

3.1.2.3 expbin()

```
double optimazation.pkg1.Algorithm.expbin (
    int num,
    int best,
    int i,
    double F,
    double Lam,
    int j,
    int r1,
    int r2,
    int r3,
    int r4,
    int r5 )
```

method for 10 strategies for differential evolution.

Parameters

<i>num</i>	
<i>best</i>	
<i>i</i>	
<i>F[1,2]</i>	
<i>Lamda[1,2]</i>	
<i>j</i>	
<i>r1</i>	
<i>r2</i>	
<i>r3</i>	
<i>r4</i>	
<i>r5</i>	

Returns

mutate individual after crossover.

3.1.2.4 getFitness()

```
void optimazation.pkg1.Algorithm.getFitness (
    double [] result )
```

This method to get fitness value for each populations. Array for fitness value for each population will be provided.

Parameters

<i>result</i>	
---------------	--

3.1.2.5 mutate()

```
void optimazation.pkg1.Algorithm.mutate (
    double cr [][],
    double Upper,
    double Lower )
```

This method for mutation after crossover. mutation probability 0.005 Mutation Range 0.1 Mutation Precision (1~5)

Parameters

<i>cr</i>	
<i>Upper</i>	
<i>Lower</i>	

3.1.2.6 mutateandRecombine()

```
double [][] optimazation.pkg1.Algorithm.mutateandRecombine (
    double init [][],
    double F,
    int functionNum,
    int num )
```

Mutate and recombine method is first step of differential evolution.

Parameters

<i>init</i>	
<i>F</i>	
<i>functionNum</i>	
<i>num</i>	

Returns

3.1.2.7 reduce()

```
void optimazation.pkg1.Algorithm.reduce (
    double popu [][],
    double newpopu [][],
    int Elitism,
    int functionNum ) throws FileNotFoundException
```

Reduce method.(

Parameters

<i>initialpopulation</i>	
<i>newpopulation</i>	
<i>Elitism(Elitism</i>	Rate * number of population)
<i>functionNum</i>	

Exceptions

<i>FileNotFoundException</i>	
------------------------------	--

3.1.2.8 select() [1/2]

```
double [][] optimazation.pkg1.Algorithm.select (
    doubleinput [][] )
```

This method provide 2 parents.

Parameters

<i>initial</i>	<i>matrix.</i>
----------------	----------------

Returns

2d array which has 2 parents vector.

3.1.2.9 select() [2/2]

```
double [] optimazation.pkg1.Algorithm.select (
    double a[][],
    int functionNum )
```

select method is method to check mutate vector's cost is more optimized than original vector's cost

Parameters

<i>a</i>	
<i>functionNum</i>	

Returns

3.1.2.10 selectParent()

```
int optimazation.pkg1.Algorithm.selectParent ( )
```

This method is method to choose parents.

Returns

int value $0 < x < \text{population}$.

3.1.2.11 tournament()

```
double [][] optimazation.pkg1.Algorithm.tournament (
    doubleinput [][] )
```

Tournament Selection, parents are chosen at random from population.

Parameters

<i>initial</i>	matrix.
----------------	---------

Returns

two parents.

The documentation for this class was generated from the following file:

- Algorithm.java

3.2 optimazation.pkg1.CreateCSV Class Reference

[CreateCSV](#) class.

Public Member Functions

- void [CreateCsv](#) (double[] [] a, int rows, String b)
- void [CreateCsv0](#) (double[] [] a, int columns, String C) throws IOException
- void [CreateCsv1](#) (double[] []a, String C) throws IOException

3.2.1 Detailed Description

CreateCSV class.

Author

JuneYeob Lee(2462 9603)

•

This class is for creating CSV file about results

Date

4/5/2019 !\Contact:Leej @cwu.edu !\Created on: 3/28/2019

3.2.2 Member Function Documentation

3.2.2.1 CreateCsv()

```
void optimazation.pkg1.CreateCSV.CreateCsv (
    double a[][],
    int rows,
    String b )
```

CreateCsv method ! this method will create csv file and calculate datas for csv file /**

Parameters

<i>a</i>	2d array
<i>rows</i>	
<i>b</i>	for the file name

message if cannot find file

3.2.2.2 CreateCsv0()

```
void optimazation.pkg1.CreateCSV.CreateCsv0 (
    double a[][],
    int columns,
    String C ) throws IOException
```

CreateCsv0 method for creating the csv file of the best Vectors

Parameters

<i>a</i>	(a for the best solution);
<i>columns</i>	(the number of columns)
<i>C</i>	

Exceptions

<i>IOException</i>	
--------------------	--

3.2.2.3 CreateCsv1()

```
void optimazation.pkg1.CreateCSV.CreateCsv1 (
    doublea [][],
    String C ) throws IOException
```

CreateCsv method to create the csv file for best solutions

Parameters

<i>a(the</i>	best solutions 2d array length should be 18 size should be the number of iteration)
<i>C</i>	(File name)

Exceptions

<i>IOException</i>	
--------------------	--

The documentation for this class was generated from the following file:

- CreateCSV.java

3.3 optimazation.pkg1.CreateMatrix Class Reference

[CreateMatrix](#) class.

Public Member Functions

- [CreateMatrix](#) (int a, int b)
A constructor.
- void [create](#) (int length, int size)
- void [add](#) (double min, double max, String a) throws FileNotFoundException, UnsupportedEncodingException

3.3.1 Detailed Description

[CreateMatrix](#) class.

Author

JuneYeob Lee(24629603)

•

Date

4/5/2019 \Contact:Leej @cwu.edu \Created on: 3/28/2019

3.3.2 Constructor & Destructor Documentation

3.3.2.1 CreateMatrix()

```
optimazation.pkg1.CreateMatrix.CreateMatrix (
    int a,
    int b )
```

A constructor.

Parameters

<i>int</i>	a the first argument(rows)
<i>int</i>	b the second argument(columns)

3.3.3 Member Function Documentation

3.3.3.1 add()

```
void optimazation.pkg1.CreateMatrix.add (
    double min,
    double max,
    String a ) throws FileNotFoundException, UnsupportedEncodingException
```

A add method !this method will fill out input with random numbers(this method will create 7 files which

```
@param double min for first parameter( minimum range for random number)
!@param double max for second parameter(Maximum range for random number)
```

3.3.3.2 create()

```
void optimazation.pkg1.CreateMatrix.create (
    int length,
    int size )
```

A create method /*! this method will create input 2d arrays with all 0.0

Parameters

<i>int</i>	length for first parameter(length)
<i>int</i>	size for second parameter(size)

The documentation for this class was generated from the following file:

- CreateMatrix.java

3.4 optimazation.pkg1.Functioning Class Reference

[Functioning](#) class.

Public Member Functions

- `double [][] funct (int length, int size) throws FileNotFoundException, UnsupportedEncodingException`

3.4.1 Detailed Description

[Functioning](#) class.

Author

JuneYeob Lee(24629603) \This [Functioning](#) class has made to implemente all 18 functions by ranges.

•

Date

4/5/2019 Contact:Leej @cwu.edu Created on: 3/28/2019

3.4.2 Member Function Documentation

3.4.2.1 `funct()`

```
double [][] optimazation.pkg1.Functioning.funct (
    int length,
    int size ) throws FileNotFoundException, UnsupportedEncodingException
```

[CreateMatrix](#) object has created

[Functions](#) object has created

result 2d arrays

The documentation for this class was generated from the following file:

- Functioning.java

3.5 optimazation.pkg1.Functions Class Reference

Public Member Functions

- **Functions** (int populations)
- double [] [Schwefel](#) (double[][] a)
- double [] [DeJong](#) (double[][] a)
- double [] [Rosenbrock](#) (double[][] a)
- double [] [Rastrigin](#) (double[][] a)
- double [] [Griewangk](#) (double[][] a)
- double [] [SineEnvelope](#) (double[][] a)
- double [] [StretchedV](#) (double[][] a)
- double [] [Ackley1](#) (double[][] a)
- double [] [Ackely2](#) (double[][] a)
- double [] [EggHolder](#) (double[][] a)
- double [] [Rana](#) (double[][] a)
- double [] [Pathological](#) (double[][] a)
- double [] [Michalewicz](#) (double[][] a)
- double [] [Masters](#) (double[][] a)
- double [] [Quartic](#) (double[][] a)
- double [] [Levy](#) (double[][] a)
- double [] [Step](#) (double[][] a)
- double [] [Alpine](#) (double[][] a)

3.5.1 Detailed Description

Author

JuneYeob Lee(24629603) [Functions](#) class is composed with 18 functions

•

Date

4/5/2019 Contact:Leej @cwu.edu Created on: 3/28/2019

3.5.2 Member Function Documentation

3.5.2.1 Ackely2()

```
double [] optimazation.pkg1.Functions.Ackely2 (
    double a[][] )
```

Ackley Two function Range[-32,32] expected global minimum = 0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.2 Ackley1()

```
double [] optimazation.pkg1.Functions.Ackley1 (
    double a[][] )
```

Ackley One Function

- Range[-32,32] expected global minimum = -7.54276-2.91867(n-3)

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.3 Alpine()

```
double [] optimazation.pkg1.Functions.Alpine (
    double a[][] )
```

Alpine function Range[-100,100] expected global minimum = 0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.4 DeJong()

```
double [] optimazation.pkg1.Functions.DeJong (
    double a[][] )
```

DeJong 1 function Range [-100,100] expected minimum =0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.5 EggHolder()

```
double [] optimazation.pkg1.Functions.EggHolder (
    double a[][] )
```

EggHolder Range[-500,500] expected global minimum none

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.6 Griewangk()

```
double [] optimazation.pkg1.Functions.Griewangk (
    double a[][] )
```

Griewangk function Range[-500,500] expected global minimum =0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.7 Levy()

```
double [] optimazation.pkg1.Functions.Levy (
    double a[][] )
```

Levy function Range[-10,10] expected global minimum = 0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.8 Masters()

```
double [] optimazation.pkg1.Functions.Masters (
    double a[][] )
```

Masters'Cosine Wave function Range[-30,30] expected global minimum = 1-n when n is size of input matrix

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.9 Michalewicz()

```
double [] optimazation.pkg1.Functions.Michalewicz (
    double a[][] )
```

Michalewicz function Range[0,Pi] expected global minimum = 0.996n when n is size of input matrix

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.10 Pathological()

```
double [] optimazation.pkg1.Functions.Pathological (
    double a[][] )
```

Pathological function Range[-100,100] expected global minimum = none

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.11 Quartic()

```
double [] optimazation.pkg1.Functions.Quartic (
    double a[][] )
```

Quartic function Range[-100,100] expected global minimum = 0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.12 Rana()

```
double [] optimazation.pkg1.Functions.Rana (
    double a[][] )
```

Rana function Range[-500,500] expected global minimum =none

Parameters

a	(input matrix)
-----	----------------

3.5.2.13 Rastrigin()

```
double [] optimazation.pkg1.Functions.Rastrigin (
    double a[][] )
```

Rastrigin function Range[-30,30] expected global minimum =0

Parameters

a	(input matrix)
-----	----------------

3.5.2.14 Rosenbrock()

```
double [] optimazation.pkg1.Functions.Rosenbrock (
    double a[][] )
```

Rosenbrock's Saddle function Range[-100,100] expected global minimum =0

Parameters

a	(input matrix)
-----	----------------

3.5.2.15 Schwefel()

```
double [] optimazation.pkg1.Functions.Schwefel (
    double a[][] )
```

Schwefel method input range[-512,512] expect global minimum = 0

Parameters

a	(input matrix)
-----	----------------

3.5.2.16 SineEnvelope()

```
double [] optimazation.pkg1.Functions.SineEnvelope (
    double a[][] )
```

Sine Envelope Sine Wave Range[-30,30] expected global minimum = -1.4915(n-1) when n is size of input matrix

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.17 Step()

```
double [] optimazation.pkg1.Functions.Step (
    double a[][] )
```

Step function Range[-100,100] expected global minimum = 0

Parameters

<i>a</i>	(input matrix)
----------	----------------

3.5.2.18 StretchedV()

```
double [] optimazation.pkg1.Functions.StretchedV (
    double a[][] )
```

StretchedV Range[-30,30] expected global minimum = 0

Parameters

<i>a</i>	(input matrix)
----------	----------------

The documentation for this class was generated from the following file:

- Functions.java

3.6 optimazation.pkg1.IterativeLocalSearch Class Reference

Public Member Functions

- double [][] [IterativeLocalSearch](#) ([LocalSearch](#) l, int itr, int length, int size, [Functioning](#) f) throws [FileNotFoundException](#), [UnsupportedEncodingException](#), [IOException](#)

3.6.1 Detailed Description

Author

JuneYeob Lee(24629603) IterativLocalSearch is that find best solution of local search with iteration. This class should deal with FileNotFoundException, IOException and Unsupported Encoding Exception

3.6.2 Constructor & Destructor Documentation

3.6.2.1 IterativeLocalSearch()

```
double [][] optimazation.pkg1.IterativeLocalSearch.IterativeLocalSearch (
    LocalSearch l,
    int itr,
    int length,
    int size,
    Functioning f ) throws FileNotFoundException, UnsupportedEncodingException, IO←
Exception
```

IterativeLocal search method to find best solution of the x times iterated local search

Parameters

<i>l</i>	(Local search object)
<i>itr</i>	(number of iteration)
<i>length</i>	(number of input rows)
<i>size</i>	(number of input columns)
<i>f</i>	(functioning object)

Returns

Best solution for Local Search

Exceptions

<i>FileNotFoundException</i>	
<i>UnsupportedEncodingException</i>	
<i>IOException</i>	

The documentation for this class was generated from the following file:

- IterativeLocalSearch.java

3.7 optimazation.pkg1.LocalSearch Class Reference

Public Member Functions

- `double [][] LocalSearch (int length, int size, Functioning f)` throws FileNotFoundException, UnsupportedEncodingException, IOException

3.7.1 Detailed Description

Author

JuneYeob Lee Local Search [Algorithm](#) class This class should deal with FileNot FoundException, IOException and Unsupported Encoding Exception

3.7.2 Constructor & Destructor Documentation

3.7.2.1 LocalSearch()

```
double [][] optimazation.pkg1.LocalSearch.LocalSearch (
    int length,
    int size,
    Functioning f ) throws FileNotFoundException, UnsupportedEncodingException, IO←
Exception
```

This method is made for local search algorithm. First set the initial solutions for 18 functions but it's not best because it's picked randomly this method will find the local minimum solution or global minimum.(in the neighbor area.) it will iterate until the standing point is smaller that left or right.

Parameters

<i>length</i>	(number of input rows)
<i>size</i>	(number of input columns)
<i>f</i>	(functioning object)

Returns

Best solution for Local Search

Exceptions

<i>FileNotFoundException</i>	
<i>UnsupportedEncodingException</i>	
<i>IOException</i>	

The documentation for this class was generated from the following file:

- LocalSearch.java

3.8 optimazation.pkg1.Main Class Reference

Optimization1 class.

Static Public Member Functions

- static void [main](#) (String[] args) throws FileNotFoundException, IOException
- static void **Algorithms** () throws UnsupportedEncodingException, IOException
- static void **GeneticAlgorithms** () throws FileNotFoundException, FileNotFoundException, UnsupportedEncodingException, IOException
- static void **DifferentialEvolution** () throws FileNotFoundException, UnsupportedEncodingException, IOException

3.8.1 Detailed Description

Optimization1 class.

3.8.2 Member Function Documentation

3.8.2.1 main()

```
static void optimazation.pkg1.Main.main (  
    String [] args ) throws FileNotFoundException, IOException [static]
```

[Main](#) function will

Parameters

<i>args</i>	the command line arguments
-------------	----------------------------

Exceptions


<i>java.io.FileNotFoundException</i>	
<i>java.io.UnsupportedEncodingException</i>	

The documentation for this class was generated from the following file:

- Main.java

3.9 optimazation.pkg1.MTRandom Class Reference

Inheritance diagram for optimazation.pkg1.MTRandom:



Public Member Functions

- [MTRandom](#) ()
- [MTRandom](#) (boolean compatible)
- [MTRandom](#) (long seed)
- [MTRandom](#) (byte[] buf)
- [MTRandom](#) (int[] buf)
- final synchronized void [setSeed](#) (long seed)
- final void [setSeed](#) (byte[] buf)
- final synchronized void [setSeed](#) (int[] buf)

Static Public Member Functions

- static int [] [pack](#) (byte[] buf)

Protected Member Functions

- final synchronized int [next](#) (int bits)

3.9.1 Detailed Description

Version

1.0

Author

David Beaumont, Copyright 2005

A Java implementation of the MT19937 (Mersenne Twister) pseudo random number generator algorithm based upon the original C code by Makoto Matsumoto and Takuji Nishimura (see <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html> for more information).

As a subclass of java.util.Random this class provides a single canonical method [next\(\)](#) for generating bits in the pseudo random number sequence. Anyone using this class should invoke the public inherited methods ([next\(\)](#), [nextInt\(\)](#), [nextFloat\(\)](#) etc.) to obtain values as normal. This class should provide a drop-in replacement for the standard implementation of java.util.Random with the additional advantage of having a far longer period and the ability to use a far larger seed value.

This is **not** a cryptographically strong source of randomness and should **not** be used for cryptographic systems or in any other situation where true random numbers are required.

This software is licensed under the [CC-GNU LGPL](#).

3.9.2 Constructor & Destructor Documentation

3.9.2.1 MTRandom() [1/5]

```
optimazation.pkg1.MTRandom.MTRandom ( )
```

The default constructor for an instance of [MTRandom](#). This invokes the no-argument constructor for `java.util.Random` which will result in the class being initialised with a seed value obtained by calling `System.currentTimeMillis()`.

3.9.2.2 MTRandom() [2/5]

```
optimazation.pkg1.MTRandom.MTRandom (
    boolean compatible )
```

This version of the constructor can be used to implement identical behaviour to the original C code version of this algorithm including exactly replicating the case where the seed value had not been set prior to calling `genrand_int32`.

If the compatibility flag is set to true, then the algorithm will be seeded with the same default value as was used in the original C code. Furthermore the `setSeed()` method, which must take a 64 bit long value, will be limited to using only the lower 32 bits of the seed to facilitate seamless migration of existing C code into Java where identical behaviour is required.

Whilst useful for ensuring backwards compatibility, it is advised that this feature not be used unless specifically required, due to the reduction in strength of the seed value.

Parameters

<i>compatible</i>	Compatibility flag for replicating original behaviour.
-------------------	--

3.9.2.3 MTRandom() [3/5]

```
optimazation.pkg1.MTRandom.MTRandom (
    long seed )
```

This version of the constructor simply initialises the class with the given 64 bit seed value. For a better random number sequence this seed value should contain as much entropy as possible.

Parameters

<i>seed</i>	The seed value with which to initialise this class.
-------------	---

3.9.2.4 MTRandom() [4/5]

```
optimazation.pkg1.MTRandom.MTRandom (
    byte [] buf )
```

This version of the constructor initialises the class with the given byte array. All the data will be used to initialise this instance.

Parameters

<i>buf</i>	The non-empty byte array of seed information.
------------	---

Exceptions

<i>NullPointerException</i>	if the buffer is null.
<i>IllegalArgumentException</i>	if the buffer has zero length.

3.9.2.5 MTRandom() [5/5]

```
optimazation.pkg1.MTRandom.MTRandom (
    int [] buf )
```

This version of the constructor initialises the class with the given integer array. All the data will be used to initialise this instance.

Parameters

<i>buf</i>	The non-empty integer array of seed information.
------------	--

Exceptions

<i>NullPointerException</i>	if the buffer is null.
<i>IllegalArgumentException</i>	if the buffer has zero length.

3.9.3 Member Function Documentation**3.9.3.1 next()**

```
final synchronized int optimazation.pkg1.MTRandom.next (
    int bits ) [protected]
```

This method forms the basis for generating a pseudo random number sequence from this class. If given a value of 32, this method behaves identically to the `genrand_int32` function in the original C code and ensures that using the standard `nextInt()` function (inherited from `Random`) we are able to replicate behaviour exactly.

Note that where the number of bits requested is not equal to 32 then bits will simply be masked out from the top of the returned integer value. That is to say that:

```
mt.setSeed(12345);  
int foo = mt.nextInt(16) + (mt.nextInt(16) << 16);
```

will not give the same result as

```
mt.setSeed(12345);  
int foo = mt.nextInt(32);
```

Parameters

<i>bits</i>	The number of significant bits desired in the output.
-------------	---

Returns

The next value in the pseudo random sequence with the specified number of bits in the lower part of the integer.

3.9.3.2 pack()

```
static int [] optimazation.pkg1.MTRandom.pack (  
    byte [] buf ) [static]
```

This simply utility method can be used in cases where a byte array of seed data is to be used to repeatedly re-seed the random number sequence. By packing the byte array into an integer array first, using this method, and then invoking `setSeed()` with that; it removes the need to re-pack the byte array each time `setSeed()` is called.

If the length of the byte array is not a multiple of 4 then it is implicitly padded with zeros as necessary. For example:

```
byte[] { 0x01, 0x02, 0x03, 0x04, 0x05, 0x06 }
```

becomes

```
int[] { 0x04030201, 0x00000605 }
```

Note that this method will not complain if the given byte array is empty and will produce an empty integer array, but the `setSeed()` method will throw an exception if the empty integer array is passed to it.

Parameters

<i>buf</i>	The non-null byte array to be packed.
------------	---------------------------------------

Returns

A non-null integer array of the packed bytes.

Exceptions

<i>NullPointerException</i>	if the given byte array is null.
-----------------------------	----------------------------------

3.9.3.3 setSeed() [1/3]

```
final synchronized void optimazation.pkg1.MTRandom.setSeed (
    long seed )
```

This method resets the state of this instance using the 64 bits of seed data provided. Note that if the same seed data is passed to two different instances of [MTRandom](#) (both of which share the same compatibility state) then the sequence of numbers generated by both instances will be identical.

If this instance was initialised in 'compatibility' mode then this method will only use the lower 32 bits of any seed value passed in and will match the behaviour of the original C code exactly with respect to state initialisation.

Parameters

<i>seed</i>	The 64 bit value used to initialise the random number generator state.
-------------	--

3.9.3.4 setSeed() [2/3]

```
final void optimazation.pkg1.MTRandom.setSeed (
    byte [] buf )
```

This method resets the state of this instance using the byte array of seed data provided. Note that calling this method is equivalent to calling "setSeed(pack(buf))" and in particular will result in a new integer array being generated during the call. If you wish to retain this seed data to allow the pseudo random sequence to be restarted then it would be more efficient to use the "pack()" method to convert it into an integer array first and then use that to re-seed the instance. The behaviour of the class will be the same in both cases but it will be more efficient.

Parameters

<i>buf</i>	The non-empty byte array of seed information.
------------	---

Exceptions

<i>NullPointerException</i>	if the buffer is null.
<i>IllegalArgumentException</i>	if the buffer has zero length.

3.9.3.5 `setSeed()` [3/3]

```
final synchronized void optimazation.pkg1.MTRandom.setSeed (
    int [] buf )
```

This method resets the state of this instance using the integer array of seed data provided. This is the canonical way of resetting the pseudo random number sequence.

Parameters

<i>buf</i>	The non-empty integer array of seed information.
------------	--

Exceptions

<i>NullPointerException</i>	if the buffer is null.
<i>IllegalArgumentException</i>	if the buffer has zero length.

The documentation for this class was generated from the following file:

- MTRandom.java

3.10 optimazation.pkg1.RandomWalk Class Reference

Public Member Functions

- double [][] [randomWalk](#) (int itr, int length, int size, [Functioning](#) f) throws FileNotFoundException, UnsupportedEncodingException, IOException

3.10.1 Detailed Description

Author

JuneYeob Lee [RandomWalk](#) calss which generated the best fitness for 18 solutions. randomly pick the solution, iterate 30 times for 18 functions.

3.10.2 Member Function Documentation

3.10.2.1 `randomWalk()`

```
double [][] optimazation.pkg1.RandomWalk.randomWalk (
    int itr,
    int length,
    int size,
    Functioning f ) throws FileNotFoundException, UnsupportedEncodingException, IO←
Exception
```

This method is used for blind search. minumum iterate 30 times each time it generate random integer from Mersenne Twister.

Parameters

<i>itr</i>	iteration time.
<i>length</i>	numbers of input vectors(at least 30).
<i>size</i>	size of input it should be 10 or 20 or 30.
<i>f</i>	functioning object which has funct method to get the result of 18 functions.

Returns

This method return the bestfitness for 18 functions at least 30 times iterations.

Exceptions

<i>FileNotFoundException</i>	
<i>UnsupportedEncodingException</i>	
<i>IOException</i>	

The documentation for this class was generated from the following file:

- RandomWalk.java

Index

- Ackely2
 - [optimazation.pkg1.Functions, 15](#)
- Ackley1
 - [optimazation.pkg1.Functions, 16](#)
- add
 - [optimazation.pkg1.CreateMatrix, 13](#)
- Algorithm
 - [optimazation.pkg1.Algorithm, 5](#)
- Alpine
 - [optimazation.pkg1.Functions, 16](#)
- calc
 - [optimazation.pkg1.Algorithm, 6](#)
- create
 - [optimazation.pkg1.CreateMatrix, 13](#)
- CreateCsv
 - [optimazation.pkg1.CreateCSV, 11](#)
- CreateCsv0
 - [optimazation.pkg1.CreateCSV, 11](#)
- CreateCsv1
 - [optimazation.pkg1.CreateCSV, 12](#)
- CreateMatrix
 - [optimazation.pkg1.CreateMatrix, 13](#)
- crossover
 - [optimazation.pkg1.Algorithm, 6](#)
- DeJong
 - [optimazation.pkg1.Functions, 16](#)
- EggHolder
 - [optimazation.pkg1.Functions, 16](#)
- expbin
 - [optimazation.pkg1.Algorithm, 6](#)
- funct
 - [optimazation.pkg1.Functioning, 14](#)
- getFitness
 - [optimazation.pkg1.Algorithm, 7](#)
- Griewangk
 - [optimazation.pkg1.Functions, 17](#)
- IterativeLocalSearch
 - [optimazation.pkg1.IterativeLocalSearch, 21](#)
- Levy
 - [optimazation.pkg1.Functions, 17](#)
- LocalSearch
 - [optimazation.pkg1.LocalSearch, 22](#)
- main
 - [optimazation.pkg1.Main, 23](#)
- Masters
 - [optimazation.pkg1.Functions, 17](#)
- Michalewicz
 - [optimazation.pkg1.Functions, 17](#)
- MTRandom
 - [optimazation.pkg1.MTRandom, 25, 26](#)
- mutate
 - [optimazation.pkg1.Algorithm, 7](#)
- mutateandRecombine
 - [optimazation.pkg1.Algorithm, 8](#)
- next
 - [optimazation.pkg1.MTRandom, 26](#)
- optimazation.pkg1.Algorithm, 5
 - [Algorithm, 5](#)
 - [calc, 6](#)
 - [crossover, 6](#)
 - [expbin, 6](#)
 - [getFitness, 7](#)
 - [mutate, 7](#)
 - [mutateandRecombine, 8](#)
 - [reduce, 8](#)
 - [select, 9](#)
 - [selectParent, 9](#)
 - [tournament, 10](#)
- optimazation.pkg1.CreateCSV, 10
 - [CreateCsv, 11](#)
 - [CreateCsv0, 11](#)
 - [CreateCsv1, 12](#)
- optimazation.pkg1.CreateMatrix, 12
 - [add, 13](#)
 - [create, 13](#)
 - [CreateMatrix, 13](#)
- optimazation.pkg1.Functioning, 14
 - [funct, 14](#)
- optimazation.pkg1.Functions, 15
 - [Ackely2, 15](#)
 - [Ackley1, 16](#)
 - [Alpine, 16](#)
 - [DeJong, 16](#)
 - [EggHolder, 16](#)
 - [Griewangk, 17](#)
 - [Levy, 17](#)
 - [Masters, 17](#)
 - [Michalewicz, 17](#)
 - [Pathological, 18](#)
 - [Quartic, 18](#)
 - [Rana, 18](#)

- Rastrigin, [19](#)
- Rosenbrock, [19](#)
- Schwefel, [19](#)
- SineEnvelope, [19](#)
- Step, [20](#)
- StretchedV, [20](#)
- optimazation.pkg1.IterativeLocalSearch, [20](#)
 - IterativeLocalSearch, [21](#)
- optimazation.pkg1.LocalSearch, [21](#)
 - LocalSearch, [22](#)
- optimazation.pkg1.Main, [23](#)
 - main, [23](#)
- optimazation.pkg1.MTRandom, [23](#)
 - MTRandom, [25](#), [26](#)
 - next, [26](#)
 - pack, [27](#)
 - setSeed, [28](#)
- optimazation.pkg1.RandomWalk, [29](#)
 - randomWalk, [29](#)
- pack
 - optimazation.pkg1.MTRandom, [27](#)
- Pathological
 - optimazation.pkg1.Functions, [18](#)
- Quartic
 - optimazation.pkg1.Functions, [18](#)
- Rana
 - optimazation.pkg1.Functions, [18](#)
- randomWalk
 - optimazation.pkg1.RandomWalk, [29](#)
- Rastrigin
 - optimazation.pkg1.Functions, [19](#)
- reduce
 - optimazation.pkg1.Algorithm, [8](#)
- Rosenbrock
 - optimazation.pkg1.Functions, [19](#)
- Schwefel
 - optimazation.pkg1.Functions, [19](#)
- select
 - optimazation.pkg1.Algorithm, [9](#)
- selectParent
 - optimazation.pkg1.Algorithm, [9](#)
- setSeed
 - optimazation.pkg1.MTRandom, [28](#)
- SineEnvelope
 - optimazation.pkg1.Functions, [19](#)
- Step
 - optimazation.pkg1.Functions, [20](#)
- StretchedV
 - optimazation.pkg1.Functions, [20](#)
- tournament
 - optimazation.pkg1.Algorithm, [10](#)