

DICTIONARY DATA STRUCTURE

- >We can use List, Tuple and Set to represent a group of individual objects as a single entity.
- If we want to represent a group of objects as key-value pairs then we should go for Dictionary.

Eg:

- rollno ---- name
- phone number -- address
- ipaddress --- domain name

- Duplicate keys are not allowed but values can be duplicated.
- Heterogeneous objects are allowed for both key and values.
- Insertion order is not preserved
- Dictionaries are mutable
- Dictionaries are dynamic
- indexing and slicing concepts are not applicable

Note: In C++ and Java Dictionaries are known as "Map" where as in Perl and Ruby it is known as "Hash"

How to Create Dictionary?

- d = {} OR d = dict()
- We are creating empty dictionary. We can add entries as follows

```
1) d[100]="latha"
2) d[200]="ravi"
3) d[300]="shiva"
4) print(d) {100: 'latha', 200: 'ravi', 300: 'shiva'}
```

- If we know data in advance then we can create dictionary as follows
- d = {100:'latha', 200:'ravi', 300:'shiva'}
- d = {key:value, key:value}

How to Access Data from the Dictionary?

We can access data by using keys.

```
1) d = {100:'latha',200:'ravi', 300:'shiva'}
2) print(d[100]) #latha
3) print(d[300]) #shiva
```

If the specified key is not available then we will get KeyError

```
print(d[400]) → KeyError: 400
```

We can prevent this by checking whether key is already available or not by using `has_key()` function or by using `in` operator.

```
d.has_key(400) → Returns 1 if key is available otherwise returns 0
```

But `has_key()` function is available only in Python 2 but not in Python 3. Hence compulsory we have to use `in` operator.

```
if 400 in d:  
    print(d[400])
```

Q) Write a Program to Enter Name and Percentage Marks in a Dictionary and Display Information on the Screen

```
1) rec={}
2) n=int(input("Enter number of students: "))
3) i=1
4) while i <=n:
5)     name=input("Enter Student Name: ")
6)     marks=input("Enter % of Marks of Student: ")
7)     rec[name]=marks
8)     i=i+1
9) print("Name of Student","\t","% of marks")
10) for x in rec:
11)     print("\t",x,"\t\t",rec[x])
```

```
D:\Python_classes>py test.py
Enter number of students: 3
Enter Student Name: latha
Enter % of Marks of Student: 60%
Enter Student Name: ravi
Enter % of Marks of Student: 70%
Enter Student Name: shiva
Enter % of Marks of Student: 80%
```

Name of Student	% of marks
latha	60%
ravi	70 %
shiva	80%

How to Update Dictionaries?

- 🌀 `d[key] = value`
- 🌀 If the key is not available then a new entry will be added to the dictionary with the specified key-value pair
- 🌀 If the key is already available then old value will be replaced with new value.

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) print(d)  
3) d[400]="pavan"  
4) print(d)  
5) d[100]="sunny"  
6) print(d)
```

Output

```
{100: 'latha', 200: 'ravi', 300: 'shiva'}  
{100: 'latha', 200: 'ravi', 300: 'shiva', 400: 'pavan'}  
{100: 'sunny', 200: 'ravi', 300: 'shiva', 400: 'pavan'}
```

How to Delete Elements from Dictionary?

1) del d[key]

- It deletes entry associated with the specified key.
- If the key is not available then we will get KeyError.

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) print(d)  
3) del d[100]  
4) print(d)  
5) del d[400]
```

Output

```
{100: 'latha', 200: 'ravi', 300: 'shiva'}  
{200: 'ravi', 300: 'shiva'}  
KeyError: 400
```

2) d.clear()

To remove all entries from the dictionary.

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) print(d)  
3) d.clear()  
4) print(d)
```

Output

```
{100: 'latha', 200: 'ravi', 300: 'shiva'}  
{}
```

3) del d

To delete total dictionary. Now we cannot access d.

- 1) d={100:"latha",200:"ravi",300:"shiva"}
- 2) `print(d)`
- 3) `del d`
- 4) `print(d)`

Output

```
{100: 'latha', 200: 'ravi', 300: 'shiva'}  
NameError: name 'd' is not defined
```

Important Functions of Dictionary:

1) dict():

To create a dictionary

- `d = dict()` → It creates empty dictionary
- `d = dict({100:"latha",200:"ravi"})` -> It creates dictionary with specified elements
- `d = dict([(100,"latha"),(200,"shiva"),(300,"ravi")])`
→ It creates dictionary with the given list of tuple elements

2) len()

Returns the number of items in the dictionary.

3) clear():

To remove all elements from the dictionary.

4) get():

To get the value associated with the key

d.get(key)

If the key is available then returns the corresponding value otherwise returns None. It wont raise any error.

d.get(key,defaultvalue)

If the key is available then returns the corresponding value otherwise returns default value.

- 1) d={100:"latha",200:"ravi",300:"shiva"}
- 2) `print(d[100])` latha
- 3) `print(d[400])` → KeyError:400
- 4) `print(d.get(100))` latha
- 5) `print(d.get(400))` → None
- 6) `print(d.get(100,"Guest"))` latha
- 7) `print(d.get(400,"Guest"))` → Guest

5) pop():

d.pop(key)

- It removes the entry associated with the specified key and returns the corresponding value.
- If the specified key is not available then we will get KeyError.

- 1) d={100:"latha",200:"ravi",300:"shiva"}
- 2) `print(d.pop(100))`
- 3) `print(d)`
- 4) `print(d.pop(400))`

Output

```
latha
{200: 'ravi', 300: 'shiva'}
KeyError: 400
```

6) popitem():

It removes an arbitrary item(key-value) from the dictionary and returns it.

- 1) d={100:"latha",200:"ravi",300:"shiva"}
- 2) `print(d)`
- 3) `print(d.popitem())`
- 4) `print(d)`

Output

```
{100: 'latha', 200: 'ravi', 300: 'shiva'}
(300, 'shiva')
{100: 'latha', 200: 'ravi'}
If the dictionary is empty then we will get KeyError
d={}
print(d.popitem()) ==>KeyError: 'popitem(): dictionary is empty'
```

7) keys():

It returns all keys associated with dictionary.

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) print(d.keys())  
3) for k in d.keys():  
4)     print(k)
```

Output

```
dict_keys([100, 200, 300])  
100  
200  
300
```

8) values():

It returns all values associated with the dictionary.

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) print(d.values())  
3) for v in d.values():  
4)     print(v)
```

Output

```
dict_values(['latha', 'ravi', 'shiva'])  
latha  
ravi  
shiva
```

9) items():

It returns list of tuples representing key-value pairs.

`[(k,v),(k,v),(k,v)]`

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) for k,v in d.items():  
3)     print(k,"--",v)
```

Output

```
100 -- latha  
200 -- ravi  
300 -- shiva
```

10) copy():

To create exactly duplicate dictionary (cloned copy)

```
d1 = d.copy();
```

11) setdefault():

```
d.setdefault(k,v)
```

- If the key is already available then this function returns the corresponding value.
- If the key is not available then the specified key-value will be added as new item to the dictionary.

```
1) d={100:"latha",200:"ravi",300:"shiva"}  
2) print(d.setdefault(400,"pavan"))  
3) print(d)  
4) print(d.setdefault(100,"sachin"))  
5) print(d)
```

Output

```
pavan  
{100: 'latha', 200: 'ravi', 300: 'shiva', 400: 'pavan'}  
durga  
{100: 'latha', 200: 'ravi', 300: 'shiva', 400: 'pavan'}
```

12) update():

```
d.update(x)
```

All items present in the dictionary x will be added to dictionary d

Q) Write a Program to take Dictionary from the Keyboard and print the Sum of Values?

```
1) d=eval(input("Enter dictionary:"))  
2) s=sum(d.values())  
3) print("Sum= ",s)
```

Output

```
D:\Python_classes>py test.py  
Enter dictionary:{'A':100,'B':200,'C':300}  
Sum= 600
```

Q) Write a Program to find Number of Occurrences of each Letter present in the given String?

```
1) word=input("Enter any word: ")  
2) d={}  
3) for x in word:  
4)     d[x]=d.get(x,0)+1  
5) for k,v in d.items():  
6)     print(k,"occurred ",v," times")
```

Output

```
D:\Python_classes>py test.py  
Enter any word: mississippi  
m occurred 1 times  
i occurred 4 times  
s occurred 4 times  
p occurred 2 times
```

Q) Write a Program to find Number of Occurrences of each Vowel present in the given String?

```
1) word=input("Enter any word: ")  
2) vowels={'a','e','i','o','u'}  
3) d={}  
4) for x in word:  
5)     if x in vowels:  
6)         d[x]=d.get(x,0)+1  
7) for k,v in sorted(d.items()):  
8)     print(k,"occurred ",v," times")
```

Output

```
D:\Python_classes>py test.py  
Enter any word: doganimaldoganimal  
a occurred 4 times  
i occurred 2 times  
o occurred 2 times
```

Q) Write a Program to accept Student Name and Marks from the Keyboard and creates a Dictionary. Also display Student Marks by taking Student Name as Input?

```
1) n=int(input("Enter the number of students: "))
2) d={}
3) for i in range(n):
4)     name=input("Enter Student Name: ")
5)     marks=input("Enter Student Marks: ")
6)     d[name]=marks
7) while True:
8)     name=input("Enter Student Name to get Marks: ")
9)     marks=d.get(name,-1)
10)    if marks== -1:
11)        print("Student Not Found")
12)    else:
13)        print("The Marks of",name,"are",marks)
14)    option=input("Do you want to find another student marks[Yes|No]")
15)    if option=="No":
16)        break
17) print("Thanks for using our application")
```

Output

D:\Python_classes>py test.py
Enter the number of students: 5

Enter Student Name: sunny
Enter Student Marks: 90

Enter Student Name: banny
Enter Student Marks: 80

Enter Student Name: chinny
Enter Student Marks: 70

Enter Student Name: pinny
Enter Student Marks: 60

Enter Student Name: vinny
Enter Student Marks: 50

Enter Student Name to get Marks: sunny
The Marks of sunny are 90

Do you want to find another student marks[Yes|No]Yes

Enter Student Name to get Marks: latha

Student Not Found

Do you want to find another student marks[Yes|No]No

Thanks for using our application

Dictionary Comprehension:

Comprehension concept applicable for dictionaries also.

- 1) squares={x:x*x for x in range(1,6)}
- 2) print(squares)
- 3) doubles={x:2*x for x in range(1,6)}
- 4) print(doubles)

Output

{1: 1, 2: 4, 3: 9, 4: 16, 5: 25}

{1: 2, 2: 4, 3: 6, 4: 8, 5: 10}