



Message Implementation Guideline

Calls

Model: D_TX_EX_FIUNIVATRPD96APTYV1xxISO
Version: 1-DEV
Variant: EDIT0008412
Issue date: 02-09-2025
Author: EXT.Priyanka.Palli

Structure

Occurrence	Element/Attribute
Calls	
1 .. unbounded	xs:sequence
1 .. 1	tns:Call
1 .. unbounded	xs:choice
0 .. 1	tns:CustomerOrders
1 .. unbounded	xs:sequence
1 .. 1	tns:CustomerOrder
1 .. 1	xs:sequence
0 .. 1	ChannelId
0 .. 1	ChannelRef
0 .. 1	TransactionId
0 .. 1	aCustomerOrderHeadDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderType
1 .. 1	CustomerOrderClass
1 .. 1	CustomerOrderReference
1 .. 1	BillToCustomerIdentity
1 .. 1	SellToCustomerIdentity
1 .. 1	ShipToCustomerIdentity
1 .. 1	PickPriority
1 .. 1	DispatchFee
1 .. 1	CODFee
1 .. 1	FreightCost
1 .. 1	FreightPartyQualifier
1 .. 1	FreightPartyIdentity
1 .. 1	Division
1 .. 1	TermsOfDelivery
1 .. 1	TermsOfDeliveryLocation
1 .. 1	CODReference
1 .. 1	WwsDepartureIdentity
1 .. 1	TermsOfDeliveryCountry
1 .. 1	ShipToCustomerReference
1 .. 1	SenderPartyIdentity
1 .. 1	SenderPartyQualifier
1 .. 1	ReturnPartyIdentity
1 .. 1	ReturnPartyQualifier
1 .. 1	DeliveryPointPartyIdentity
1 .. 1	DeliveryPointPartyQualifier
1 .. 1	ExporterPartyIdentity
1 .. 1	ExporterPartyQualifier
1 .. 1	ImporterPartyIdentity
1 .. 1	ImporterPartyQualifier
1 .. 1	PickUpPartyIdentity
1 .. 1	PickUpPartyQualifier
1 .. 1	Export
0 .. 1	aCustomerOrderTextDocs
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. unbounded	CustomerOrderTextDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. 1	aCustomerOrderLineDocs
1 .. 1	xs:sequence
0 .. unbounded	CustomerOrderLineDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderLinePosition
1 .. 1	CustomerOrderLineKitPosition
1 .. 1	CustomerOrderLineSequence
1 .. 1	CustomerOrderLineType
1 .. 1	Kitproduct
1 .. 1	ShipToPartyQualifier
1 .. 1	ShipToPartyIdentity
1 .. 1	ShipToCustomerSubAddress
1 .. 1	RequestedShipDate
1 .. 1	AcknowledgedShipdate
1 .. 1	RequestedDeliveryDate
1 .. 1	AcknowledgedDeliveryDate
1 .. 1	Warehouselidentity
1 .. 1	ProductNumber
1 .. 1	OwnerIdentity
1 .. 1	ProductionLotRequireMent
1 .. 1	MarketingLotIdentity
1 .. 1	StorageLotIdentity
1 .. 1	Packagelidentity
1 .. 1	OrderedQuantity
1 .. 1	OrderedQuantityTolerancePlus
1 .. 1	OrderedQuantityToleranceMinus
1 .. 1	KitDetailQuantity
1 .. 1	RequestedShelfLife
1 .. 1	ForcePackage
1 .. 1	SerialNumberHandling
1 .. 1	SerialNumber
1 .. 1	VATPercent
1 .. 1	DeliveryMethod
1 .. 1	Measure
1 .. 1	MeasureQualifier
1 .. 1	SalesPrice
1 .. 1	LineTotal
1 .. 1	ShipToCustomerProductNumber
1 .. 1	PurchaseOrderNumber
1 .. 1	PurchaseOrderSequence
1 .. 1	PurchaseOrderLinePosition
1 .. 1	PurchaseOrderLineSequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	OriginalOrderIdentity
1 .. 1	OriginalOrderLinePosition
1 .. 1	DepartureLoadIdentity
1 .. 1	PlanLoad
1 .. 1	DateSelectionType
1 .. 1	FirstPlannedDeliveryDtm
1 .. 1	LastPlannedDeliveryDtm
1 .. 1	FirstPlannedShipDtm
1 .. 1	LastPlannedShipDtm
1 .. 1	OwnerIdentityAtShipToCustomer
1 .. 1	InventoryStatusCode
1 .. 1	OrderedQuantityLowerTolerance
1 .. 1	OrderedQuantityUpperTolerance
1 .. 1	CatchMeasureLowerTolerance
1 .. 1	CatchMeasureUpperTolerance
1 .. 1	ProductionLotIdentity
1 .. 1	ProductionSubLotIdentity
1 .. 1	AssembleToStock
1 .. 1	ReserveForAssembly
1 .. 1	AllowTransit
1 .. 1	AllowPartDelivery
1 .. 1	AdditionalInfo
1 .. 1	CustomsRequirement
1 .. 1	ItemLoadIdentity
1 .. 1	LegalLOT
1 .. 1	LegalReq
1 .. 1	SalesInvoiceNumber
1 .. 1	SalesInvoiceLine
1 .. 1	SalesInvoiceDate
1 .. 1	UseSalesPrice
1 .. 1	SalesCurrency
1 .. 1	CustomerProductGroup
1 .. 1	ReturnsDeliveryMethod
1 .. 1	ReturnsForwarder
0 .. 1	aCustomerOrderLineTextDocs
1 .. 1	xs:sequence
0 .. unbounded	CustomerOrderLineTextDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderLinePosition
1 .. 1	CustomerOrderLineKitPosition
1 .. 1	CustomerOrderLineSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. 1	tns:Partys
1 .. unbounded	xs:sequence
1 .. 1	tns:Party
1 .. 1	xs:sequence
0 .. 1	ChannelId
0 .. 1	ChannelRef

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	TransactionId
0 .. 1	aPartyDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
0 .. 1	aCustomerDocs
1 .. 1	xs:sequence
0 .. unbounded	CustomerDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerNumber
1 .. 1	CustomerName1
1 .. 1	CustomerName2
1 .. 1	CustomerTypeIdentity
1 .. 1	LoadCarrierGroupIdentity
0 .. 1	aPartyAddressDocs
1 .. 1	xs:sequence
0 .. unbounded	PartyAddressDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	PartyQualifier
1 .. 1	PartyIdentity
1 .. 1	PartyProfile
1 .. 1	PartyStatus
1 .. 1	PartyName1
1 .. 1	PartyName2
1 .. 1	PartyName3
1 .. 1	PartyName4
1 .. 1	PartyName5
1 .. 1	PartyAddress1
1 .. 1	PartyAddress2
1 .. 1	PartyAddress3
1 .. 1	PartyAddress4
1 .. 1	ZipCode
1 .. 1	City
1 .. 1	Region
1 .. 1	CountryCode
1 .. 1	Country
1 .. 1	GeographicalCode
1 .. 1	Phone
1 .. 1	Fax
1 .. 1	Telex
1 .. 1	Email
1 .. 1	PostalGiroAccount
1 .. 1	BankGiroAccount
1 .. 1	VATNumber
1 .. 1	OrganizationNumber
1 .. 1	Language
1 .. 1	Division
1 .. 1	SendASN
1 .. 1	RcvCheckType
1 .. 1	FreCustomerId
1 .. 1	FreCustomerIdEUR

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	— CustomsDeclarant
1 .. 1	— CustomsDeclType
1 .. 1	— CustomsClearanceType
1 .. 1	— ExecuteCustomsDecl
1 .. 1	— PayCustomsDecl
1 .. 1	— EORINumber
1 .. 1	— DeliveryPointCode
1 .. 1	— DoorCode

Guideline

Element/Attribute	Annotation
Calls	Map Instructions Instruction Nr 1 <i>Instruction</i> Use BGMe02/1004 as LW Reference, for alt ref it si not mandatory to keep in LW. more over these values may change, though we have set unique value, It's business responsibility to suggest us the correct values at the time of testing.
xs:sequence	Occurence 1 .. unbounded
tns:Call	Occurence 1 .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> To the fields, for which we don't have mappings, we need to populate below name spaces to those fields: xsi:nil="true" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xs:choice	Occurence 1 .. unbounded
tns:CustomerOrders	Occurence 0 .. 1
xs:sequence	Occurence 1 .. unbounded
tns:CustomerOrder	Occurence 1 .. 1
xs:sequence	Occurence 1 .. 1
ChannelId	Occurence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI-UNIVAR"
ChannelRef	Occurence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI-UNIVAR"
TransactionId	Occurence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> map the original file name which was sent by customer
aCustomerOrderHeadDoc	Occurence 0 .. 1 Type tns:CustomerOrderHeadDoc Map Instructions Instruction Nr 1 <i>Instruction</i> This segment will populate only once
xs:sequence	Occurence 1 .. 1
OPCODE	Occurence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> hardcode "1"
CustomerOrderNumber	Occurence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If BGMe01/C002e01/1001 = "340" then

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions <i>Instruction</i> Map BGMe02/1004
	CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
	CustomerOrderType	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "N"
	CustomerOrderClass	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "N"
	CustomerOrderReference	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If FTXe01/4451 = "ZZ2" then <i>Instruction</i> Map FTXe04/C108e01/4440
	BillToCustomerIdentity	Occurrence 1 .. 1 Type xs:string
	SellToCustomerIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If BGMe01/C002e01/1001 = "340" then <i>Instruction</i> Concatenate "BY" with BGMe02/1004 <i>Additional Info</i> eg: 1234567 ----> BY1234567
	ShipToCustomerIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If BGMe01/C002e01/1001 = "340" then <i>Instruction</i> Concatenate "DP" with BGMe02/1004 <i>Additional Info</i> eg: 123445678 ----> DP12345678
	PickPriority	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "9"
	DispatchFee	Occurrence 1 .. 1 Type xs:double
	CODFee	Occurrence 1 .. 1 Type xs:double
	FreightCost	Occurrence 1 .. 1 Type xs:double

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	FreightPartyQualifier	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CL"
	FreightPartyIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI-UNIVAR"
	Division	Occurrence 1 .. 1 Type xs:string
	TermsOfDelivery	Occurrence 1 .. 1 Type xs:string
	TermsOfDeliveryLocation	Occurrence 1 .. 1 Type xs:string
	CODReference	Occurrence 1 .. 1 Type xs:string
	WwsDepartureIdentity	Occurrence 1 .. 1 Type xs:string
	TermsOfDeliveryCountry	Occurrence 1 .. 1 Type xs:string
	ShipToCustomerReference	Occurrence 1 .. 1 Type xs:string
	SenderPartyIdentity	Occurrence 1 .. 1 Type xs:string
	SenderPartyQualifier	Occurrence 1 .. 1 Type xs:string
	ReturnPartyIdentity	Occurrence 1 .. 1 Type xs:string
	ReturnPartyQualifier	Occurrence 1 .. 1 Type xs:string
	DeliveryPointPartyIdentity	Occurrence 1 .. 1 Type xs:string
	DeliveryPointPartyQualifier	Occurrence 1 .. 1 Type xs:string
	ExporterPartyIdentity	Occurrence 1 .. 1 Type xs:string
	ExporterPartyQualifier	Occurrence 1 .. 1 Type xs:string
	ImporterPartyIdentity	Occurrence 1 .. 1 Type xs:string
	ImporterPartyQualifier	Occurrence 1 .. 1 Type xs:string
	PickUpPartyIdentity	Occurrence 1 .. 1 Type xs:string
	PickUpPartyQualifier	Occurrence 1 .. 1 Type xs:string
	Export	Occurrence 1 .. 1 Type xs:string
	aCustomerOrderTextDocs	Occurrence 0 .. 1 Type tns:ArrayOfCustomerOrderTextDoc
	xs:sequence	Occurrence 1 .. 1
	CustomerOrderTextDoc	Occurrence 0 .. unbounded Type tns:CustomerOrderTextDoc

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Loop based on the value of FTXe01/4451 as SenderCode exists in the DSV_CL_FIUNIVAR_FTX_CODES_SL_cl
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Hardcode "1"
	CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string
		Map Instructions
		Instruction Nr 1
		<i>Condition</i> If BGMe01/C002e01/1001 = "340" then
		<i>Instruction</i> Map BGMe02/1004
	CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Hardcode "1"
	TextFunction	Occurrence 1 .. 1 Type xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Create new Codelist DSV_CL_FIUNIVAR_FTX_CODES_SL_cl, use FTXe01/4451 as SenderCode to get the ReceiverCode from the codelist
	Text	Occurrence 1 .. 1 Type xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Map FTXe04/C108e01/4440
	aCustomerOrderLineDocs	Occurrence 0 .. 1 Type tns:ArrayOfCustomerOrderLineDoc
	xs:sequence	Occurrence 1 .. 1
	CustomerOrderLineDoc	Occurrence 0 .. unbounded Type tns:CustomerOrderLineDoc
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Loop based on count of SG15/SG37/GID
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Hardcode "1"
	CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	ShipToPartyQualifier	Occurence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CU"
	ShipToPartyIdentity	Occurence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If BGMe01/C002e01/1001 = "340" then <i>Instruction</i> Concatenate "DP" with BGMe02/1004 <i>Additional Info</i> eg: 1234567 ----> DP1234567
	ShipToCustomerSubAddress	Occurence 1 .. 1 Type xs:string
	RequestedShipDate	Occurence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and map the data in the format YYYY-MM-DD & concatenate with "T00:00:00" <i>Additional Info</i> eg: 20250716 ----> 2025-07-16T00:00:00
	AcknowledgedShipdate	Occurence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and map the data in the format YYYY-MM-DD & concatenate with "T00:00:00" <i>Additional Info</i> eg: 20250716 ----> 2025-07-16T00:00:00
	RequestedDeliveryDate	Occurence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and map the data in the format YYYY-MM-DD & concatenate with "T00:00:00" <i>Additional Info</i> eg: 20250716 ----> 2025-07-16T00:00:00
	AcknowledgedDeliveryDate	Occurence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and map the data in the format YYYY-MM-DD & concatenate with "T00:00:00" <i>Additional Info</i> eg: 20250716 ----> 2025-07-16T00:00:00
	WarehouseIdentity	Occurence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI00"
	ProductNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map SG15/SG37/PIA202/C212e01/7140, remove 0's of the reslt value start with <i>Additional Info</i> eg: 0000000000001005887 ----> 1005887
	OwnerIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI-UNIVAR"
	ProductionLotRequireMent	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG37/FTXe01/4451 = "BX" exists then <i>Instruction</i> Hardcode "3"
	MarketingLotIdentity	Occurrence 1 .. 1 Type xs:string
	StorageLotIdentity	Occurrence 1 .. 1 Type xs:string
	PackagelIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Create Codelist DSV_CL_FIUNIVAR_PACKAGING_SL_cl, use Sg15/SG37/GlDe02/C213e02/7065 as SenderCode to get the Receivercode from the above codelist.
	OrderedQuantity	Occurrence 1 .. 1 Type xs:double Map Instructions Instruction Nr 1 <i>Instruction</i> Map Sg15/SG37/GlDe02/C213e01/7224
	OrderedQuantityTolerancePlus	Occurrence 1 .. 1 Type xs:double
	OrderedQuantityToleranceMinus	Occurrence 1 .. 1 Type xs:double
	KitDetailQuantity	Occurrence 1 .. 1 Type xs:double
	RequestedShelfLife	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	ForcePackage	Occurrence 1 .. 1 Type xs:string
	SerialNumberHandling	Occurrence 1 .. 1 Type xs:string
	SerialNumber	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	VATPercent	Occurrence 1 .. 1 Type xs:double
	DeliveryMethod	Occurrence 1 .. 1 Type xs:string
	Measure	Occurrence 1 .. 1 Type xs:string
	MeasureQualifier	Occurrence 1 .. 1 Type xs:string
	SalesPrice	Occurrence 1 .. 1 Type xs:double
	LineTotal	Occurrence 1 .. 1 Type xs:double
	ShipToCustomerProductNumber	Occurrence 1 .. 1 Type xs:string
	PurchaseOrderNumber	Occurrence 1 .. 1 Type xs:string
	PurchaseOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	PurchaseOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive - .. 922337203685477 922337203685477 5807
	PurchaseOrderLineSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	OriginalOrderIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG37/FTXe01/4451 = "LIN" then <i>Instruction</i> Map SG15/SG37/FTXe04/C108e01/4440
	OriginalOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive - .. 922337203685477 922337203685477 5807
	DepartureLoadIdentity	Occurrence 1 .. 1 Type xs:string
	PlanLoad	Occurrence 1 .. 1 Type xs:string
	DateSelectionType	Occurrence 1 .. 1 Type xs:string
	FirstPlannedDeliveryDtm	Occurrence 1 .. 1 Type xs:dateTime General Notes It still a question if the additional day falls under weekend/holiday, checking with Schenker contact Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and covert the mapped date format to be YYYY-MM-

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions DDT00:00:00 and Add one day with 15 minutes to the resulted date <i>Additional Info</i> eg: 20250716 -----> 2025-07-17T00:15:00
	LastPlannedDeliveryDtm	Occurrence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and covert the mapped date format to be YYYY-MM-DDT00:00:00 and Add two day to the resulted date <i>Additional Info</i> eg: 20250716 -----> 2025-07-18T00:00:00
	FirstPlannedShipDtm	Occurrence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and covert the mapped date format to be YYYY-MM-DDT00:00:00 <i>Additional Info</i> eg: 20250716 -----> 2025-07-16T00:00:00
	LastPlannedShipDtm	Occurrence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Condition</i> If DTMe01/C507e01/2005 = "2" then <i>Instruction</i> Map the first 8 characters from DTMe01/C507e02/2380 and covert the mapped date format to be YYYY-MM-DDT00:00:00 and Add two day to the resulted date <i>Additional Info</i> eg: 20250716 -----> 2025-07-18T00:00:00
	OwnerIdentityAtShipToCustomer	Occurrence 1 .. 1 Type xs:string
	InventoryStatusCode	Occurrence 1 .. 1 Type xs:string
	OrderedQuantityLowerTolerance	Occurrence 1 .. 1 Type xs:double
	OrderedQuantityUpperTolerance	Occurrence 1 .. 1 Type xs:double
	CatchMeasureLowerTolerance	Occurrence 1 .. 1 Type xs:double
	CatchMeasureUpperTolerance	Occurrence 1 .. 1 Type xs:double
	ProductionLotIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG37/FTXe01/4451 = "BX" then <i>Instruction</i> Map SG15/SG37/FTXe04/C108e01/4440
	ProductionSubLotIdentity	Occurrence 1 .. 1 Type xs:string
	AssembleToStock	Occurrence 1 .. 1 Type xs:string
	ReserveForAssembly	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation	
	AllowTransit	Occurrence	1 .. 1
		Type	xs:string
	AllowPartDelivery	Occurrence	1 .. 1
		Type	xs:string
	AdditionalInfo	Occurrence	1 .. 1
		Type	xs:string
	CustomsRequirement	Occurrence	1 .. 1
		Type	xs:string
	ItemLoadIdentity	Occurrence	1 .. 1
		Type	xs:string
	LegalLOT	Occurrence	1 .. 1
		Type	xs:string
	LegalReq	Occurrence	1 .. 1
		Type	xs:string
	SalesInvoiceNumber	Occurrence	1 .. 1
		Type	xs:string
	SalesInvoiceLine	Occurrence	1 .. 1
		Type	xs:string
	SalesInvoiceDate	Occurrence	1 .. 1
		Type	xs:dateTime
	UseSalesPrice	Occurrence	1 .. 1
		Type	xs:string
	SalesCurrency	Occurrence	1 .. 1
		Type	xs:string
	CustomerProductGroup	Occurrence	1 .. 1
		Type	xs:string
	ReturnsDeliveryMethod	Occurrence	1 .. 1
		Type	xs:string
	ReturnsForwarder	Occurrence	1 .. 1
		Type	xs:string
	aCustomerOrderLineTextDocs	Occurrence	0 .. 1
		Type	tns:ArrayOfCustomerOrderLineTextDoc
	xs:sequence	Occurrence	1 .. 1
	CustomerOrderLineTextDoc	Occurrence	0 .. unbounded
		Type	tns:CustomerOrderLineTextDoc
		Map Instructions Instruction Nr 1 <i>Instruction</i> for each /CustomerOrderLineDoc we will have one / CustomerOrderLineTextDoc(both are from target side only)	
	xs:sequence	Occurrence	1 .. 1
	OPCODE	Occurrence	0 .. 1
		Type	xs:string
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"	
	CustomerOrderNumber	Occurrence	1 .. 1
		Type	xs:string
		Map Instructions Instruction Nr 1 <i>Condition</i> If BGMe01/C002e01/1001 = "340" then <i>Instruction</i> Map BGMe02/1004	
	CustomerOrderSequence	Occurrence	1 .. 1
		Type	xs:int
		FractionDigits	0
		Inclusive	-2147483648 .. 2147483647

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
ChannelId		Occurrence 0 .. 1 Type xs:string
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI-UNIVAR"
ChannelRef		Occurrence 0 .. 1 Type xs:string
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "FI-UNIVAR"
TransactionId		Occurrence 0 .. 1 Type xs:string
		Map Instructions Instruction Nr 1 <i>Instruction</i> map the original file name which was sent by customer
aPartyDoc		Occurrence 0 .. 1 Type tns:PartyDoc
	xs:sequence	Occurrence 1 .. 1
OPCODE		Occurrence 0 .. 1 Type xs:string
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
aCustomerDocs		Occurrence 0 .. 1 Type tns:ArrayOfCustomerDoc
	xs:sequence	Occurrence 1 .. 1
CustomerDoc		Occurrence 0 .. unbounded Type tns:CustomerDoc
		Map Instructions Instruction Nr 1 <i>Instruction</i> we should have two duplicate copies of /CustomerDoc first loop based on if SG15/SG30/NADe01/3035 = "BY" Second loop based on if SG15/SG30/NADe01/3035 = "DP"
	xs:sequence	Occurrence 1 .. 1
OPCODE		Occurrence 0 .. 1 Type xs:string
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
CustomerNumber		Occurrence 1 .. 1 Type xs:string
		Map Instructions Instruction Nr 1 <i>Condition</i> If If BGMe01/C002e01/1001 = "340" AND SG15/SG30/NADe01/3035 = "BY" then <i>Instruction</i> Concatenate "BY" with BGMe02/1004 resulting value should appear as : 1234567 ----> BY1234567 <i>Additional Info</i> for the first loop Instruction Nr 2 <i>Condition</i> If If BGMe01/C002e01/1001 = "340" AND SG15/SG30/NADe01/3035 = "DP" then <i>Instruction</i> Concatenate "DP" with BGMe02/1004 resulting value should appear as : 1234567 ---->

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions DP1234567 <i>Additional Info</i> for the second loop
	CustomerName1	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG30/NADe01/3035 = "BY" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e01/3036(First Index value) <i>Additional Info</i> for the first loop Instruction Nr 2 <i>Condition</i> If SG15/SG30/NADe01/3035 = "DP" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e01/3036(First index value) <i>Additional Info</i> for the second loop
	CustomerName2	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG30/NADe01/3035 = "BY" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e02/3036 (second index value) <i>Additional Info</i> for the first loop Instruction Nr 2 <i>Condition</i> If SG15/SG30/NADe01/3035 = "DP" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e02/3036 (second index value) <i>Additional Info</i> for the second loop
	CustomerTypeIdentity	Occurrence 1 .. 1 Type xs:string
	LoadCarrierGroupIdentity	Occurrence 1 .. 1 Type xs:string
	aPartyAddressDocs	Occurrence 0 .. 1 Type tns:ArrayOfPartyAddressDoc
	xs:sequence	Occurrence 1 .. 1
	PartyAddressDoc	Occurrence 0 .. unbounded Type tns:PartyAddressDoc Map Instructions Instruction Nr 1 <i>Instruction</i> we should have two duplicate copies of /CustomerDoc first loop based on if SG15/SG30/NADe01/3035 = "BY" Second loop based on if SG15/SG30/NADe01/3035 = "DP"
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
	PartyQualifier	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CU"

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
PartyIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If If BGMe01/C002e01/1001 = "340" AND SG15/SG30/NADe01/3035 = "BY" then <i>Instruction</i> Concatenate "BY" with BGMe02/1004 resulting value should appear as : 1234567 ----> BY1234567 <i>Additional Info</i> for the first loop Instruction Nr 2 <i>Condition</i> If If BGMe01/C002e01/1001 = "340" AND SG15/SG30/NADe01/3035 = "DP" then <i>Instruction</i> Concatenate "DP" with BGMe02/1004 resulting value should appear as : 1234567 ----> DP1234567 <i>Additional Info</i> for the second loop
PartyProfile	Occurrence 1 .. 1 Type xs:string
PartyStatus	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "T"
PartyName1	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG30/NADe01/3035 = "BY" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e01/3036(First Index value) <i>Additional Info</i> for the First loop Instruction Nr 1 <i>Condition</i> If SG15/SG30/NADe01/3035 = "DP" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e01/3036(First Index value) <i>Additional Info</i> for the second loop
PartyName2	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> If SG15/SG30/NADe01/3035 = "BY" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e02/3036(second index value) <i>Additional Info</i> for the first loop Instruction Nr 2 <i>Condition</i> If SG15/SG30/NADe01/3035 = "DP" then <i>Instruction</i> Map SG15/SG30/NADe04/C080e02/3036(second index value) <i>Additional Info</i> for the second loop
PartyName3	Occurrence 1 .. 1 Type xs:string
PartyName4	Occurrence 1 .. 1 Type xs:string
PartyName5	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
PartyAddress1	Occurrence	1 .. 1
	Type	xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Map SG15/SG30/NADe05/C059e01/3042
PartyAddress2	Occurrence	1 .. 1
	Type	xs:string
PartyAddress3	Occurrence	1 .. 1
	Type	xs:string
PartyAddress4	Occurrence	1 .. 1
	Type	xs:string
ZipCode	Occurrence	1 .. 1
	Type	xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Map SG15/SG30/NADe08/3251
City	Occurrence	1 .. 1
	Type	xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Map SG15/SG30/NADe06/3164
Region	Occurrence	1 .. 1
	Type	xs:string
CountryCode	Occurrence	1 .. 1
	Type	xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Map SG15/SG30/NADe09/3207
Country	Occurrence	1 .. 1
	Type	xs:string
GeographicalCode	Occurrence	1 .. 1
	Type	xs:string
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Hardcode "F00"
Phone	Occurrence	1 .. 1
	Type	xs:string
Fax	Occurrence	1 .. 1
	Type	xs:string
Telex	Occurrence	1 .. 1
	Type	xs:string
Email	Occurrence	1 .. 1
	Type	xs:string
		Map Instructions
		Instruction Nr 1
		<i>Condition</i> If SG15/SG30/NADe01/3035 = "DP" AND (SG15/SG30/SG31/COMe01/C076e01/3148 exists when SG15/SG30/SG31/COMe01/C076e02/3155 = "EM") then
		<i>Instruction</i> Map SG15/SG30/SG31/COMe01/C076e01/3148
		<i>Additional Info</i> this mapping should be applied to second loop.
PostalGiroAccount	Occurrence	1 .. 1
	Type	xs:string
BankGiroAccount	Occurrence	1 .. 1
	Type	xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation	
	VATNumber	Occurrence	1 .. 1
		Type	xs:string
	OrganizationNumber	Occurrence	1 .. 1
		Type	xs:string
	Language	Occurrence	1 .. 1
		Type	xs:string
	Division	Occurrence	1 .. 1
		Type	xs:string
	SendASN	Occurrence	1 .. 1
		Type	xs:string
	RcvCheckType	Occurrence	1 .. 1
		Type	xs:string
	FreCustomerId	Occurrence	1 .. 1
		Type	xs:string
	FreCustomerIdEUR	Occurrence	1 .. 1
		Type	xs:string
	CustomsDeclarant	Occurrence	1 .. 1
		Type	xs:string
	CustomsDeclType	Occurrence	1 .. 1
		Type	xs:string
	CustomsClearanceType	Occurrence	1 .. 1
		Type	xs:string
	ExecuteCustomsDecl	Occurrence	1 .. 1
		Type	xs:string
	PayCustomsDecl	Occurrence	1 .. 1
		Type	xs:string
	EORINumber	Occurrence	1 .. 1
		Type	xs:string
	DeliveryPointCode	Occurrence	1 .. 1
		Type	xs:string
	DoorCode	Occurrence	1 .. 1
		Type	xs:string

Bold = Element, Italic = Attribute, Grey = Group