



Message Implementation Guideline

MBGMCR03

Post Goods Movements with MB_CREATE_GOODS_MOVEMENT

Model: D_TX_XX_ITMANNHODVV1xxREAV1xxOSW
Version: 1-DEV
Variant: EDIT0011223
Issue date: 04-01-2026
Author: ext.kavitha.murugan

Structure

Occurrence	Element/Attribute
------------	-------------------

	MBGMCR03
1 .. 1	xs:sequence
1 .. 1	IDOC
required	<i>BEGIN</i>
1 .. 1	xs:sequence
1 .. 1	EDI_DC40
required	<i>SEGMENT</i>
1 .. 1	xs:sequence
1 .. 1	TABNAM
0 .. 1	DOCNUM
1 .. 1	DIRECT
1 .. 1	IDOCTYP
0 .. 1	MESTYP
0 .. 1	MESCOD
1 .. 1	SNDPOR
1 .. 1	SNDPRT
0 .. 1	SNDPFC
1 .. 1	SNDPRN
1 .. 1	RCVPOR
0 .. 1	RCVPRT
0 .. 1	RCVPFC
1 .. 1	RCVPRN
0 .. 1	CREDAT
0 .. 1	CRETIM
0 .. 1	E1MBGMCR
required	<i>SEGMENT</i>
1 .. 1	xs:sequence
0 .. 1	E1BP2017_GM_HEAD_01
required	<i>SEGMENT</i>
1 .. 1	xs:sequence
0 .. 1	PSTNG_DATE
0 .. 1	DOC_DATE
0 .. 1	REF_DOC_NO
0 .. 1	E1BP2017_GM_CODE
required	<i>SEGMENT</i>
1 .. 1	xs:sequence
0 .. 1	GM_CODE
0 .. 999999	E1BP2017_GM_ITEM_CREATE
required	<i>SEGMENT</i>
1 .. 1	xs:sequence
0 .. 1	MATERIAL
0 .. 1	MOVE_TYPE
0 .. 1	VENDOR
0 .. 1	ENTRY_QNT
0 .. 1	MVT_IND
0 .. 1	DELIV_NUMB_TO_SEARCH
0 .. 1	DELIV_ITEM_TO_SEARCH

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
MBGMCR03	Map Instructions Instruction Nr 1 <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/TransactionId to LW Primary reference and after split map /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX3" for corresponding file and CDM filename without extension to Alt Reference. Instruction Nr 2 <i>Instruction</i> Create separate output file for each unique /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX3" Instruction Nr 3 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ChannelId = "IT-MH" <i>Instruction</i> route this to 2 flows DELIVERYRECEIPT_MH122 & DELIVERYRECEIPT_MH101 with 30 seconds delay.
xs:sequence	Occurrence 1 .. 1
IDOC	Occurrence 1 .. 1
<i>BEGIN</i>	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurrence 1 .. 1
EDI_DC40	Occurrence 1 .. 1
<i>SEGMENT</i>	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurrence 1 .. 1
TABNAM	Occurrence 1 .. 1 Type xs:string Fixed EDI_DC40 Map Instructions Instruction Nr 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions <i>Instruction</i> hardcode "EDI_DC40"
— DOCNUM	Occurence 0 .. 1 Type restriction (xs:string) Length .. 16 Map Instructions Instruction Nr 1 <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/TransactionId
— DIRECT	Occurence 1 .. 1 Type restriction (xs:string) Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "2"
— IDOCTYP	Occurence 1 .. 1 Type xs:string Fixed MBGMCR03 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "MBGMCR03"
— MESTYP	Occurence 0 .. 1 Type restriction (xs:string) Length .. 30 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "ZMBGMCR"
— MESCOD	Occurence 0 .. 1 Type restriction (xs:string) Length .. 3 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "101"
— SNDPOR	Occurence 1 .. 1 Type restriction (xs:string) Length .. 10 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "SAPE16" for test Instruction Nr 2 <i>Instruction</i> hardcode "SAPP16" for prod
— SNDPRT	Occurence 1 .. 1 Type restriction (xs:string) Length .. 2 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "LI"
— SNDPFC	Occurence 0 .. 1 Type restriction (xs:string) Length .. 2 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "TU"

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
— SNDPRN		Occurrence 1 .. 1 Type restriction (xs:string) Length .. 10 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "0000621101"
	— RCVPOR	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 10 Map Instructions Instruction Nr 1 <i>Instruction</i> map SenderCode from Codelist DSV_CL_ITMANNH_RCVPOR_RCVPRN_SL when Description = "DEFAULT"
— RCVPRT		Occurrence 0 .. 1 Type restriction (xs:string) Length .. 2 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "LS"
	— RCVPFC	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 2 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "LS"
— RCVPRN		Occurrence 1 .. 1 Type restriction (xs:string) Length .. 10 Map Instructions Instruction Nr 1 <i>Instruction</i> map ReceiverCode from Codelist DSV_CL_ITMANNH_RCVPOR_RCVPRN_SL when Description = "DEFAULT"
	— CREDAT	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 8 Map Instructions Instruction Nr 1 <i>Instruction</i> map current system date in format yyymmdd <i>Additional Info</i> <CREDAT>20251015</CREDAT>
— CRETIM		Occurrence 0 .. 1 Type restriction (xs:string) Length .. 6 Map Instructions Instruction Nr 1 <i>Instruction</i> map current system time in format hhmmss <i>Additional Info</i> <CRETIM>160259</CRETIM>
	E1MBGMCR	Occurrence 0 .. 1
— SEGMENT		Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
E1BP2017_GM_HEAD_01	Occurrence 0 .. 1
SEGMENT	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurrence 1 .. 1
PSTNG_DATE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 8 Map Instructions Instruction Nr 1 <i>Instruction</i> map current system date in format yyyyymmdd <i>Additional Info</i> <PSTNG_DATE>20251015</PSTNG_DATE>
DOC_DATE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 8 Map Instructions Instruction Nr 1 <i>Instruction</i> map current system date in format yyyyymmdd <i>Additional Info</i> <DOC_DATE>20251015</DOC_DATE>
REF_DOC_NO	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 16 Map Instructions Instruction Nr 1 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX3" then <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text
E1BP2017_GM_CODE	Occurrence 0 .. 1
SEGMENT	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurrence 1 .. 1
GM_CODE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 2 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "01"
E1BP2017_GM_ITEM_CREATE	Occurrence 0 .. 999999 Map Instructions Instruction Nr 1 <i>Instruction</i> Generate for each unique group by grouping same/ Calls/Call/DeliveryReceipts/DeliveryReceipt/

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ProductIdentity and value after + in /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text when /Calls/Call/ DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX1" & / Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX3" input --> <TextFunction>TX1</TextFunction> <Text>4502612481+000150</ Text> output : <DELIV_ITEM_TO_SEARCH>000150</ DELIV_ITEM_TO_SEARCH>
SEGMENT	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 Instruction hardcode "1"
xs:sequence	Occurrence 1 .. 1
MATERIAL	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 18 Map Instructions Instruction Nr 1 Instruction map /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ProductIdentity
MOVE_TYPE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 3 Map Instructions Instruction Nr 1 Instruction hardcode "101" for first ouput file
VENDOR	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 10 Map Instructions Instruction Nr 1 Condition if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX2" Instruction map /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
ENTRY_QNT	Map Instructions DeliveryReceiptLineTextDoc/Text
	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 15 Map Instructions Instruction Nr 1 <i>Condition</i> when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "ORD" then <i>Instruction</i> map first occurrence of /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text
MVT_IND	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 1
	Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "B"
DELIV_NUMB_TO_SEARCH	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 10
	Map Instructions Instruction Nr 1 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX3" then <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text
DELIV_ITEM_TO_SEARCH	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 6
	Map Instructions Instruction Nr 1 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX1" <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text after + symbol

Bold = Element, Italic = Attribute, Grey = Group