



Message Implementation Guideline

MBGMCR03

Post Goods Movements with MB_CREATE_GOODS_MOVEMENT

Model: D_TX_XX_ITMANNHODVV1xxSTSV1xxOSW
Version: 1-DEV
Variant: EDIT0011223
Issue date: 30-12-2025
Author: ext.l.k.pasupuleti

Structure

Occurrence	Element/Attribute
	MBGMCR03
1 .. 1	xs:sequence
1 .. 1	IDOC
required	BEGIN
1 .. 1	xs:sequence
1 .. 1	EDI_DC40
required	SEGMENT
1 .. 1	xs:sequence
1 .. 1	TABNAM
0 .. 1	DOCNUM
1 .. 1	DIRECT
1 .. 1	IDOCTYP
0 .. 1	MESTYP
0 .. 1	MESCOD
1 .. 1	SNDPOR
1 .. 1	SNDPRT
0 .. 1	SNDPFC
1 .. 1	SNDPRN
1 .. 1	RCVPOR
0 .. 1	RCVPRT
0 .. 1	RCVPFC
1 .. 1	RCVPRN
0 .. 1	CREDAT
0 .. 1	CRETIM
0 .. 1	E1MBGMCR
required	SEGMENT
1 .. 1	xs:sequence
0 .. 1	E1BP2017_GM_HEAD_01
required	SEGMENT
1 .. 1	xs:sequence
0 .. 1	PSTNG_DATE
0 .. 1	DOC_DATE
0 .. 1	REF_DOC_NO
0 .. 1	E1BP2017_GM_CODE
required	SEGMENT
1 .. 1	xs:sequence
0 .. 1	GM_CODE
0 .. 999999	E1BP2017_GM_ITEM_CREATE
required	SEGMENT
1 .. 1	xs:sequence
0 .. 1	MATERIAL
0 .. 1	MOVE_TYPE
0 .. 1	VENDOR
0 .. 1	ENTRY_QNT
0 .. 1	MVT_IND
0 .. 1	MOVE_REAS
0 .. 1	DELIV_NUMB_TO_SEARCH
0 .. 1	DELIV_ITEM_TO_SEARCH

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
MBGMCR03	Map Instructions Instruction Nr 1 <i>Instruction</i> generate separate output file for each unique /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX3". Instruction Nr 2 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ChannelId = "IT-MH" <i>Instruction</i> route to both DELIVERYRECEIPT_MH122 & DELIVERYRECEIPT_MH101 flows and DELIVERYRECEIPT_MH122 should be sent with delay of 30 seconds after DELIVERYRECEIPT_MH101 is sent. Instruction Nr 3 <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/TransactionId to LW Primary reference to original flow and after split map /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX3" for corresponding file and CDM filename without extension to Alt Reference. Instruction Nr 4 <i>Instruction</i> Customer filemask: SCHENKER.GRMOV.MHIT.AA
xs:sequence	Occurence 1 .. 1
IDOC	Occurence 1 .. 1
<i>BEGIN</i>	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurence 1 .. 1
EDI_DC40	Occurence 1 .. 1
<i>SEGMENT</i>	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
—	TABNAM	Occurrence 1 .. 1 Type xs:string Fixed EDI_DC40 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "EDI_DC40"
—	DOCNUM	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 16 Map Instructions Instruction Nr 1 <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/TransactionId
—	DIRECT	Occurrence 1 .. 1 Type restriction (xs:string) Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "2"
—	IDOCTYP	Occurrence 1 .. 1 Type xs:string Fixed MBGMCR03 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "MBGMCR03"
—	MESTYP	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 30 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "ZMBGMCR"
—	MESCOD	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 3 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "122" for second output file
—	SNDPOR	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 10 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "SAPE16" for test Instruction Nr 2 <i>Instruction</i> hardcode "SAPP16" for prod
—	SNDPRT	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 2 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "LI"
—	SNDPFC	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 2

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> hardcode "TU"
— SNDPRN		Occurence 1 .. 1
		Type restriction (xs:string)
		Length .. 10
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> hardcode "0000621101"
— RCVPOR		Occurence 1 .. 1
		Type restriction (xs:string)
		Length .. 10
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> map SenderCode from Codelist DSV_CL_ITMANNH_RCVPOR_RCVPRN_SL when Description = "DEFAULT"
— RCVPRT		Occurence 0 .. 1
		Type restriction (xs:string)
		Length .. 2
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> hardcode "LS"
— RCVPFC		Occurence 0 .. 1
		Type restriction (xs:string)
		Length .. 2
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> hardcode "LS"
— RCVPRN		Occurence 1 .. 1
		Type restriction (xs:string)
		Length .. 10
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> map ReceiverCode from Codelist DSV_CL_ITMANNH_RCVPOR_RCVPRN_SL when Description = "DEFAULT"
— CREDAT		Occurence 0 .. 1
		Type restriction (xs:string)
		Length .. 8
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> map current System Date in YYYYMMDD format
— CRETIM		Occurence 0 .. 1
		Type restriction (xs:string)
		Length .. 6
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> map current System Time in HHMMSS format
— E1MBGMCR		Occurence 0 .. 1
		Type restriction (xs:string)
		Use required
		Map Instructions
		Instruction Nr 1
— SEGMENT		Type restriction (xs:string)
		Use required
		Map Instructions
		Instruction Nr 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions
	<i>Instruction</i> hardcoded "1"
xs:sequence	Occurrence 1 .. 1
E1BP2017_GM_HEAD_01	Occurrence 0 .. 1
SEGMENT	Type restriction (xs:string) Use required
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> hardcoded "1"
xs:sequence	Occurrence 1 .. 1
PSTNG_DATE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 8
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> map current system date in YYYYMMDD format
DOC_DATE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 8
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> map current system date in YYYYMMDD format
REF_DOC_NO	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 16
	Map Instructions
	Instruction Nr 1
	<i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX3"
	<i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text
E1BP2017_GM_CODE	Occurrence 0 .. 1
SEGMENT	Type restriction (xs:string) Use required
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> hardcoded "1"
xs:sequence	Occurrence 1 .. 1
GM_CODE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 2
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> hardcoded "01"
E1BP2017_GM_ITEM_CREATE	Occurrence 0 .. 999999
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> 1. /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions DeliveryReceiptLineDoc are grouped by same /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/ProductIdentity and value after + in /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "TX1". sum up all /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/DeliveredQuantity in grouped DeliveryReceiptLineDocs. 2. Subtract resultant DeliveredQuantity from step# 1 from first occurrence of /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/Text when /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/aDeliveryReceiptLineTextDocs/DeliveryReceiptLineTextDoc/TextFunction = "ORD" 3. Check if subtraction result from step 2 is not equal to zero then only generate this segment.
SEGMENT	Type restriction (xs:string) Use required Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "1"
xs:sequence	Occurrence 1 .. 1
MATERIAL	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 18 Map Instructions Instruction Nr 1 <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/ProductIdentity
MOVE_TYPE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 3 Map Instructions Instruction Nr 1 <i>Instruction</i> hardcode "122"
VENDOR	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 10

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions Instruction Nr 1 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX2" <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text
ENTRY_QNT	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 15 Map Instructions Instruction Nr 1 <i>Instruction</i> 1. /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc are grouped by same /Calls/ Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ProductIdentity and value after + in /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text when /Calls/Call/ DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX1". sum up all /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/DeliveredQuantity in grouped DeliveryReceiptLineDocs. 2. Subtract resultant DeliveredQuantity from first occurrence of /Calls/Call/DeliveryReceipts/ DeliveryReceipt/aDeliveryReceiptHeadDoc/ aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text when /Calls/Call/ DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "ORD" and map the resultant value. Instruction Nr 2 <i>Condition</i> if resultant value from instruction#1 is equal to 0 <i>Instruction</i> then halt the file in LW with error message "ENTRY_QNT is zero"
MVT_IND	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 1 Map Instructions Instruction Nr 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
MOVE_REAS	Map Instructions
	<i>Instruction</i> hardcode "B"
	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 4
DELIV_NUMB_TO_SEARCH	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> hardcode "0004"
DELIV_ITEM_TO_SEARCH	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 10
	Map Instructions
	Instruction Nr 1 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX3" <i>Instruction</i> map /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text
DELIV_ITEM_TO_SEARCH	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 6
	Map Instructions
	Instruction Nr 1 <i>Condition</i> if /Calls/Call/DeliveryReceipts/DeliveryReceipt/ aDeliveryReceiptHeadDoc/aDeliveryReceiptLineDocs/ DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/TextFunction = "TX1" <i>Instruction</i> map the value of /Calls/Call/DeliveryReceipts/ DeliveryReceipt/aDeliveryReceiptHeadDoc/ aDeliveryReceiptLineDocs/DeliveryReceiptLineDoc/ aDeliveryReceiptLineTextDocs/ DeliveryReceiptLineTextDoc/Text which is after character "+"