



Message Implementation Guideline

Calls

Model: D_TX_XX_SEACORV1xxPTYV1xxISO
Version: 1-DEV
Variant: EDIT0008913
Issue date: 08-08-2025
Author: ext.usha.penke

Structure

Occurrence	Element/Attribute
Calls	
1 .. unbounded	xs:sequence
1 .. 1	tns:Call
1 .. unbounded	xs:choice
0 .. 1	tns:CustomerOrders
1 .. unbounded	xs:sequence
1 .. 1	tns:CustomerOrder
1 .. 1	xs:sequence
0 .. 1	ChannelId
0 .. 1	ChannelRef
0 .. 1	TransactionId
0 .. 1	aCustomerOrderHeadDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderType
1 .. 1	CustomerOrderClass
1 .. 1	CustomerOrderReference
1 .. 1	BillToCustomerIdentity
1 .. 1	SellToCustomerIdentity
1 .. 1	ShipToCustomerIdentity
1 .. 1	PickPriority
1 .. 1	DispatchFee
1 .. 1	CODFee
1 .. 1	FreightCost
1 .. 1	FreightPartyQualifier
1 .. 1	FreightPartyIdentity
1 .. 1	Division
1 .. 1	TermsOfDelivery
1 .. 1	TermsOfDeliveryLocation
1 .. 1	CODReference
1 .. 1	WwsDepartureIdentity
1 .. 1	TermsOfDeliveryCountry
1 .. 1	ShipToCustomerReference
1 .. 1	SenderPartyIdentity
1 .. 1	SenderPartyQualifier
1 .. 1	ReturnPartyIdentity
1 .. 1	ReturnPartyQualifier
1 .. 1	DeliveryPointPartyIdentity
1 .. 1	DeliveryPointPartyQualifier
1 .. 1	ExporterPartyIdentity
1 .. 1	ExporterPartyQualifier
1 .. 1	ImporterPartyIdentity
1 .. 1	ImporterPartyQualifier
1 .. 1	PickUpPartyIdentity
1 .. 1	PickUpPartyQualifier
1 .. 1	Export
0 .. 1	aCustomerOrderTextDocs
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. unbounded	CustomerOrderTextDoc1
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. unbounded	CustomerOrderTextDoc2
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. 1	aCustomerOrderLineDocs
1 .. 1	xs:sequence
0 .. unbounded	CustomerOrderLineDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderLinePosition
1 .. 1	CustomerOrderLineKitPosition
1 .. 1	CustomerOrderLineSequence
1 .. 1	CustomerOrderLineType
1 .. 1	Kitproduct
1 .. 1	ShipToPartyQualifier
1 .. 1	ShipToPartyIdentity
1 .. 1	ShipToCustomerSubAddress
1 .. 1	RequestedShipDate
1 .. 1	AcknowledgedShipdate
1 .. 1	RequestedDeliveryDate
1 .. 1	AcknowledgedDeliveryDate
1 .. 1	Warehouselidentity
1 .. 1	ProductNumber
1 .. 1	OwnerIdentity
1 .. 1	ProductionLotRequireMent
1 .. 1	MarketingLotIdentity
1 .. 1	StorageLotIdentity
1 .. 1	Packagelidentity
1 .. 1	OrderedQuantity
1 .. 1	OrderedQuantityTolerancePlus
1 .. 1	OrderedQuantityToleranceMinus
1 .. 1	KitDetailQuantity
1 .. 1	RequestedShelfLife
1 .. 1	ForcePackage
1 .. 1	SerialNumberHandling
1 .. 1	SerialNumber
1 .. 1	VATPercent
1 .. 1	DeliveryMethod
1 .. 1	Measure
1 .. 1	MeasureQualifier

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	— SalesPrice
1 .. 1	— LineTotal
1 .. 1	— ShipToCustomerProductNumber
1 .. 1	— PurchaseOrderNumber
1 .. 1	— PurchaseOrderSequence
1 .. 1	— PurchaseOrderLinePosition
1 .. 1	— PurchaseOrderLineSequence
1 .. 1	— OriginalOrderIdentity
1 .. 1	— OriginalOrderLinePosition
1 .. 1	— DepartureLoadIdentity
1 .. 1	— PlanLoad
1 .. 1	— DateSelectionType
1 .. 1	— FirstPlannedDeliveryDtm
1 .. 1	— LastPlannedDeliveryDtm
1 .. 1	— FirstPlannedShipDtm
1 .. 1	— LastPlannedShipDtm
1 .. 1	— OwnerIdentityAtShipToCustomer
1 .. 1	— InventoryStatusCode
1 .. 1	— OrderedQuantityLowerTolerance
1 .. 1	— OrderedQuantityUpperTolerance
1 .. 1	— CatchMeasureLowerTolerance
1 .. 1	— CatchMeasureUpperTolerance
1 .. 1	— ProductionLotIdentity
1 .. 1	— ProductionSubLotIdentity
1 .. 1	— AssembleToStock
1 .. 1	— ReserveForAssembly
1 .. 1	— AllowTransit
1 .. 1	— AllowPartDelivery
1 .. 1	— AdditionalInfo
1 .. 1	— CustomsRequirement
1 .. 1	— ItemLoadIdentity
1 .. 1	— LegalLOT
1 .. 1	— LegalReq
1 .. 1	— SalesInvoiceNumber
1 .. 1	— SalesInvoiceLine
1 .. 1	— SalesInvoiceDate
1 .. 1	— UseSalesPrice
1 .. 1	— SalesCurrency
1 .. 1	— CustomerProductGroup
1 .. 1	— ReturnsDeliveryMethod
1 .. 1	— ReturnsForwarder
0 .. 1	aCustomerOrderLineTextDocs
1 .. 1	— xs:sequence
0 .. unbounded	CustomerOrderLineTextDoc1
1 .. 1	— xs:sequence
0 .. 1	— OPCODE
1 .. 1	— CustomerOrderNumber
1 .. 1	— CustomerOrderSequence
1 .. 1	— CustomerOrderLinePosition
1 .. 1	— CustomerOrderLineKitPosition
1 .. 1	— CustomerOrderLineSequence
1 .. 1	— TextFunction
1 .. 1	— Text

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. unbounded	CustomerOrderLineTextDoc2
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderLinePosition
1 .. 1	CustomerOrderLineKitPosition
1 .. 1	CustomerOrderLineSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. unbounded	CustomerOrderLineTextDoc3
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderLinePosition
1 .. 1	CustomerOrderLineKitPosition
1 .. 1	CustomerOrderLineSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. unbounded	CustomerOrderLineTextDoc4
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	CustomerOrderNumber
1 .. 1	CustomerOrderSequence
1 .. 1	CustomerOrderLinePosition
1 .. 1	CustomerOrderLineKitPosition
1 .. 1	CustomerOrderLineSequence
1 .. 1	TextFunction
1 .. 1	Text
0 .. 1	tns:Partys
1 .. unbounded	xs:sequence
1 .. 1	tns:Party
1 .. 1	xs:sequence
0 .. 1	ChannelId
0 .. 1	ChannelRef
0 .. 1	TransactionId
0 .. 1	aPartyDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
0 .. 1	aPartyAddressDocs
1 .. 1	xs:sequence
0 .. unbounded	PartyAddressDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	PartyQualifier
1 .. 1	PartyIdentity
1 .. 1	PartyProfile
1 .. 1	PartyStatus
1 .. 1	PartyName1
1 .. 1	PartyName2
1 .. 1	PartyName3

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	PartyName4
1 .. 1	PartyName5
1 .. 1	PartyAddress1
1 .. 1	PartyAddress2
1 .. 1	PartyAddress3
1 .. 1	PartyAddress4
1 .. 1	ZipCode
1 .. 1	City
1 .. 1	Region
1 .. 1	CountryCode
1 .. 1	Country
1 .. 1	GeographicalCode
1 .. 1	Phone
1 .. 1	Fax
1 .. 1	Telex
1 .. 1	Email
1 .. 1	PostalGiroAccount
1 .. 1	BankGiroAccount
1 .. 1	VATNumber
1 .. 1	OrganizationNumber
1 .. 1	Language
1 .. 1	Division
1 .. 1	SendASN
1 .. 1	RcvCheckType
1 .. 1	FreCustomerId
1 .. 1	FreCustomerIdEUR
1 .. 1	CustomsDeclarant
1 .. 1	CustomsDeclType
1 .. 1	CustomsClearanceType
1 .. 1	ExecuteCustomsDecl
1 .. 1	PayCustomsDecl
1 .. 1	EORINumber
1 .. 1	DeliveryPointCode
1 .. 1	DoorCode
1 .. 1	tns:Party
1 .. 1	xs:sequence
0 .. 1	ChannelId
0 .. 1	ChannelRef
0 .. 1	TransactionId
0 .. 1	aPartyDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
0 .. 1	aPartyAddressDocs
1 .. 1	xs:sequence
0 .. unbounded	PartyAddressDoc
1 .. 1	xs:sequence
0 .. 1	OPCODE
1 .. 1	PartyQualifier
1 .. 1	PartyIdentity
1 .. 1	PartyProfile
1 .. 1	PartyStatus
1 .. 1	PartyName1

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	PartyName2
1 .. 1	PartyName3
1 .. 1	PartyName4
1 .. 1	PartyName5
1 .. 1	PartyAddress1
1 .. 1	PartyAddress2
1 .. 1	PartyAddress3
1 .. 1	PartyAddress4
1 .. 1	ZipCode
1 .. 1	City
1 .. 1	Region
1 .. 1	CountryCode
1 .. 1	Country
1 .. 1	GeographicalCode
1 .. 1	Phone
1 .. 1	Fax
1 .. 1	Telex
1 .. 1	Email
1 .. 1	PostalGiroAccount
1 .. 1	BankGiroAccount
1 .. 1	VATNumber
1 .. 1	OrganizationNumber
1 .. 1	Language
1 .. 1	Division
1 .. 1	SendASN
1 .. 1	RcvCheckType
1 .. 1	FreCustomerId
1 .. 1	FreCustomerIdEUR
1 .. 1	CustomsDeclarant
1 .. 1	CustomsDeclType
1 .. 1	CustomsClearanceType
1 .. 1	ExecuteCustomsDecl
1 .. 1	PayCustomsDecl
1 .. 1	EORINumber
1 .. 1	DeliveryPointCode
1 .. 1	DoorCode

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
Calls	
xs:sequence	Occurrence 1 .. unbounded
tns:Call	Occurrence 1 .. 1
xs:choice	Occurrence 1 .. unbounded
tns:CustomerOrders	Occurrence 0 .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> Use /message/content/CUSORD/COID as LW reference, for alt ref it is not mandatory to keep in LW. more over these values may change though. We have set unique value, It's business responsibility to suggest us the correct values at the time of testing.
xs:sequence	Occurrence 1 .. unbounded
tns:CustomerOrder	Occurrence 1 .. 1
xs:sequence	Occurrence 1 .. 1
ChannelId	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "SE-ACO"
ChannelRef	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "SE-ACO"
TransactionId	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map "ACO"+counter
aCustomerOrderHeadDoc	Occurrence 0 .. 1 Type tns:CustomerOrderHeadDoc Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by /message/content/CUSORD
xs:sequence	Occurrence 1 .. 1
OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/COID
CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
CustomerOrderType	Map Instructions <i>Instruction</i> Hardcode "0" Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/COTYPID = empty or / message/content/CUSORD/COTYPID = "0" or / message/content/CUSORD/COTYPID = "O" then <i>Instruction</i> Map "N" Instruction Nr 2 <i>Condition</i> if /message/content/CUSORD/COTYPID = others then <i>Instruction</i> Map /message/content/CUSORD/COTYPID
CustomerOrderClass	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/COTYPID = empty or / message/content/CUSORD/COTYPID = "0" or / message/content/CUSORD/COTYPID = "O" then <i>Instruction</i> Map "N" Instruction Nr 2 <i>Condition</i> if /message/content/CUSORD/COTYPID = others then <i>Instruction</i> Map /message/content/CUSORD/COTYPID
CustomerOrderReference	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/CO_REF+";"+/ message/content/CUSORD/COID
BillToCustomerIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/ADDRESS/ADR2 exists then <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/ PARTY_ID+"_" +/message/content/CUSORD/COID+"B" Instruction Nr 2 <i>Condition</i> if /message/content/CUSORD/ADDRESS/ADR2 doesnt exists then <i>Instruction</i> empty
SellToCustomerIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> 1. concat (/message/content/CUSORD/ADDRESS/ ADR/PARTY_ID+"_" +/message/content/CUSORD/ COID) <i>Additional Info</i> 2. Remove the last two characters and Map the value Ex: value - C06560_117656-001 Output - C06560_117656-0 value - 10002_15547-1 Output - 10002_15547

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	ShipToCustomerIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> 1. concat (/message/content/CUSORD/ADDRESS/ADR/PARTY_ID+"_"+/message/content/CUSORD/COID) <i>Additional Info</i> 2. Remove the last two characters and Map the value Ex: value - C06560_117656-001 Output - C06560_117656-0 value - 10002_15547-1 Output - 10002_15547
	PickPriority	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "5"
	DispatchFee	Occurrence 1 .. 1 Type xs:double
	CODFee	Occurrence 1 .. 1 Type xs:double
	FreightCost	Occurrence 1 .. 1 Type xs:double
	FreightPartyQualifier	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CU"
	FreightPartyIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "SE-ACO"
	Division	Occurrence 1 .. 1 Type xs:string
	TermsOfDelivery	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/ADDRESS/ADR/COUNTRYCODE = "NO" then <i>Instruction</i> Map "0001"
	TermsOfDeliveryLocation	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/TERMS_OF_DELIVERY_LOCATION exists then <i>Instruction</i> Map /message/content/CUSORD/TERMS_OF_DELIVERY_LOCATION
	CODReference	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation	
	WwsDepartureIdentity	Occurrence	1 .. 1
		Type	xs:string
	TermsOfDeliveryCountry	Occurrence	1 .. 1
		Type	xs:string
	ShipToCustomerReference	Occurrence	1 .. 1
		Type	xs:string
	SenderPartyIdentity	Occurrence	1 .. 1
		Type	xs:string
	SenderPartyQualifier	Occurrence	1 .. 1
		Type	xs:string
	ReturnPartyIdentity	Occurrence	1 .. 1
		Type	xs:string
	ReturnPartyQualifier	Occurrence	1 .. 1
		Type	xs:string
	DeliveryPointPartyIdentity	Occurrence	1 .. 1
		Type	xs:string
	DeliveryPointPartyQualifier	Occurrence	1 .. 1
		Type	xs:string
	ExporterPartyIdentity	Occurrence	1 .. 1
		Type	xs:string
	ExporterPartyQualifier	Occurrence	1 .. 1
		Type	xs:string
	ImporterPartyIdentity	Occurrence	1 .. 1
		Type	xs:string
	ImporterPartyQualifier	Occurrence	1 .. 1
		Type	xs:string
	PickUpPartyIdentity	Occurrence	1 .. 1
		Type	xs:string
	PickUpPartyQualifier	Occurrence	1 .. 1
		Type	xs:string
	Export	Occurrence	1 .. 1
		Type	xs:string
	aCustomerOrderTextDocs	Occurrence	0 .. 1
		Type	tns:ArrayOfCustomerOrderTextDoc
	xs:sequence	Occurrence	1 .. 1
	CustomerOrderTextDoc1	Occurrence	0 .. unbounded
		Type	tns:CustomerOrderTextDoc
		Map Instructions	
		Instruction Nr 1	
		<i>Instruction</i> Triggered by each /message/content/CUSORD/TEXT_HEAD/FTX_H when /message/content/CUSORD/TEXT_HEAD/FTX_H/FTX_QUALIFIER = "DOD"	
	xs:sequence	Occurrence	1 .. 1
	OPCODE	Occurrence	0 .. 1
		Type	xs:string
		Map Instructions	
		Instruction Nr 1	
		<i>Instruction</i> Hardcode "1"	
	CustomerOrderNumber	Occurrence	1 .. 1
		Type	xs:string
		Map Instructions	
		Instruction Nr 1	
		<i>Instruction</i> Map /message/content/CUSORD/COID	

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	TextFunction	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "DOD"
	Text	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/TEXT_HEAD/FTX_H/FTX_1
	CustomerOrderTextDoc2	Occurrence 0 .. unbounded Type tns:CustomerOrderTextDoc Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by each /message/content/CUSORD/TEXT_HEAD/FTX_H when /message/content/CUSORD/TEXT_HEAD/FTX_H/FTX_QUALIFIER = "DEL"
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
	CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/COID
	CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	TextFunction	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "DEL"
	Text	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/TEXT_HEAD/FTX_H/

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions
	FTX_1
aCustomerOrderLineDocs	Occurrence 0 .. 1 Type tns:ArrayOfCustomerOrderLineDoc
xs:sequence	Occurrence 1 .. 1
CustomerOrderLineDoc	Occurrence 0 .. unbounded Type tns:CustomerOrderLineDoc
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Triggered by each /message/content/CUSORD/ORDER_LINE/COR
xs:sequence	Occurrence 1 .. 1
OPCODE	Occurrence 0 .. 1 Type xs:string
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Hardcode "1"
CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Map /message/content/CUSORD/COID
CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Hardcode "0"
CustomerOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive - 922337203685477 5807 .. 922337203685477 5807
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/COPOS
CustomerOrderLineKitPosition	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Hardcode "0"
CustomerOrderLineSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	Map Instructions
	Instruction Nr 1
	<i>Instruction</i> Hardcode "0"
CustomerOrderLineType	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "N"
	Kitproduct	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	ShipToPartyQualifier	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CU"
	ShipToPartyIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> 1. concat (/message/content/CUSORD/ADDRESS/ ADR/PARTY_ID+"_"+/message/content/CUSORD/ COID) 2. Remove the last two characters and Map the value Ex: value - C06560_117656-001 Output - C06560_117656-0 value - 10002_15547-1 Output - 10002_15547
	ShipToCustomerSubAddress	Occurrence 1 .. 1 Type xs:string
	RequestedShipDate	Occurrence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/SHIPDATE + "T00: 00:00"
	AcknowledgedShipdate	Occurrence 1 .. 1 Type xs:dateTime
	RequestedDeliveryDate	Occurrence 1 .. 1 Type xs:dateTime
	AcknowledgedDeliveryDate	Occurrence 1 .. 1 Type xs:dateTime
	WarehouseIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "NSJ"
	ProductNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/ ARTID
	OwnerIdentity	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Hardcode "ACO"
	ProductionLotRequireMent	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/PRODLOTREQ
	MarketingLotIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/ORDER_LINE/COR/PRODLOT is not null then <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/PROMOTN +" "+/message/content/CUSORD/ORDER_LINE/COR/PRODLOT Instruction Nr 2 <i>Condition</i> if /message/content/CUSORD/ORDER_LINE/COR/PRODLOT is null then <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/PROMOTN
	StorageLotIdentity	Occurrence 1 .. 1 Type xs:string
	PackagelIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "ST"
	OrderedQuantity	Occurrence 1 .. 1 Type xs:double Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/ORDQTY
	OrderedQuantityTolerancePlus	Occurrence 1 .. 1 Type xs:double
	OrderedQuantityToleranceMinus	Occurrence 1 .. 1 Type xs:double
	KitDetailQuantity	Occurrence 1 .. 1 Type xs:double
	RequestedShelfLife	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647
	ForcePackage	Occurrence 1 .. 1 Type xs:string
	SerialNumberHandling	Occurrence 1 .. 1 Type xs:string
	SerialNumber	Occurrence 1 .. 1 Type xs:string
	VATPercent	Occurrence 1 .. 1 Type xs:double
	DeliveryMethod	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation	
		Map Instructions Instruction Nr 1 <i>Condition</i> if /message/content/CUSORD/TEXT_HEAD/FTX_H/FTX_QUALIFIER = "COR" and /message/content/CUSORD/TEXT_HEAD/FTX_H/FTX_1 = "DBS" <i>Instruction</i> Map empty Instruction Nr 2 <i>Condition</i> if /message/content/CUSORD/DLVRYMETH_ID exists then <i>Instruction</i> Map /message/content/CUSORD/DLVRYMETH_ID	
	Measure	Occurrence 1 .. 1 Type xs:string	
	MeasureQualifier	Occurrence 1 .. 1 Type xs:string	
	SalesPrice	Occurrence 1 .. 1 Type xs:double Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/PRICE1	
	LineTotal	Occurrence 1 .. 1 Type xs:double Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/PRICE2	
	ShipToCustomerProductNumber	Occurrence 1 .. 1 Type xs:string	
	PurchaseOrderNumber	Occurrence 1 .. 1 Type xs:string	
	PurchaseOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647	
	PurchaseOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive -9223372036854775808 .. 9223372036854775807	
	PurchaseOrderLineSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647	
	OriginalOrderIdentity	Occurrence 1 .. 1 Type xs:string	
	OriginalOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive -9223372036854775808 .. 9223372036854775807	
	DepartureLoadIdentity	Occurrence 1 .. 1 Type xs:string	
	PlanLoad	Occurrence 1 .. 1 Type xs:string	

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions
		Instruction Nr 1
		<i>Instruction</i> Hardcode "1"
	DateSelectionType	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "S"
	FirstPlannedDeliveryDtm	Occurrence 1 .. 1 Type xs:dateTime
	LastPlannedDeliveryDtm	Occurrence 1 .. 1 Type xs:dateTime
	FirstPlannedShipDtm	Occurrence 1 .. 1 Type xs:dateTime Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/SHIPDATE + "T00:00:00"
	LastPlannedShipDtm	Occurrence 1 .. 1 Type xs:dateTime
	OwnerIdentityAtShipToCustomer	Occurrence 1 .. 1 Type xs:string
	InventoryStatusCode	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/BLOCKCOD
	OrderedQuantityLowerTolerance	Occurrence 1 .. 1 Type xs:double
	OrderedQuantityUpperTolerance	Occurrence 1 .. 1 Type xs:double
	CatchMeasureLowerTolerance	Occurrence 1 .. 1 Type xs:double
	CatchMeasureUpperTolerance	Occurrence 1 .. 1 Type xs:double
	ProductionLotIdentity	Occurrence 1 .. 1 Type xs:string
	ProductionSubLotIdentity	Occurrence 1 .. 1 Type xs:string
	AssembleToStock	Occurrence 1 .. 1 Type xs:string
	ReserveForAssembly	Occurrence 1 .. 1 Type xs:string
	AllowTransit	Occurrence 1 .. 1 Type xs:string
	AllowPartDelivery	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	AdditionalInfo	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/ADDITIONAL_INFO
	CustomsRequirement	Occurrence 1 .. 1 Type xs:string
	ItemLoadIdentity	Occurrence 1 .. 1 Type xs:string
	LegalLOT	Occurrence 1 .. 1 Type xs:string
	LegalReq	Occurrence 1 .. 1 Type xs:string
	SalesInvoiceNumber	Occurrence 1 .. 1 Type xs:string
	SalesInvoiceLine	Occurrence 1 .. 1 Type xs:string
	SalesInvoiceDate	Occurrence 1 .. 1 Type xs:dateTime
	UseSalesPrice	Occurrence 1 .. 1 Type xs:string
	SalesCurrency	Occurrence 1 .. 1 Type xs:string
	CustomerProductGroup	Occurrence 1 .. 1 Type xs:string
	ReturnsDeliveryMethod	Occurrence 1 .. 1 Type xs:string
	ReturnsForwarder	Occurrence 1 .. 1 Type xs:string
	aCustomerOrderLineTextDocs	Occurrence 0 .. 1 Type tns:ArrayOfCustomerOrderLineTextDoc
	xs:sequence	Occurrence 1 .. 1
	CustomerOrderLineTextDoc1	Occurrence 0 .. unbounded Type tns:CustomerOrderLineTextDoc Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by each /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE when /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_QUALIFIER = "DI1"
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
	CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/COID
	CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
	CustomerOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive - .. 922337203685477 922337203685477 5807 5808 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/COPOS
	CustomerOrderLineKitPosition	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	CustomerOrderLineSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	TextFunction	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "DI1"
	Text	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_1
	CustomerOrderLineTextDoc2	Occurrence 0 .. unbounded Type tns:CustomerOrderLineTextDoc Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by each /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE when /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_QUALIFIER = "DO"
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
	CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/COID

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
	CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	CustomerOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive - 922337203685477 5807 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/COPOS
	CustomerOrderLineKitPosition	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	CustomerOrderLineSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
	TextFunction	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "DO"
	Text	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_1
	CustomerOrderLineTextDoc3	Occurrence 0 .. unbounded Type tns:CustomerOrderLineTextDoc Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by each /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE when /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_QUALIFIER = "TSR"
	xs:sequence	Occurrence 1 .. 1
	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_2 <i>Additional Info</i> <FTX_1>TID <FTX_2>2021-01-21 10:00 Output: TID 2021-01-21 10:00 Instruction Nr 3 <i>Condition</i> else <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/FTX_LINES/FTX_LINE/FTX_1
CustomerOrderLineTextDoc4	Occurrence 0 .. unbounded Type tns:CustomerOrderLineTextDoc General Notes Ex: Message includes two <COR>, <COPOS>2001 and <COPOS>2002 <ORDQTY> for <COPOS>2001 is 0. Add CustomerOrderLineText4 to the CustomerOrderLine created for <COPOS>2002 and fetch the values from <COR> where <COPOS>2001 Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by each /message/content/CUSORD/ORDER_LINE/COR where /message/content/CUSORD/ORDER_LINE/COR/ORDQTY = "0" <i>Additional Info</i> Map values from <COR> where <ORDQTY>=0 to the next CustomerOrderLine/CustomerOrderLineText4
xs:sequence	Occurrence 1 .. 1
OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
CustomerOrderNumber	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/COID
CustomerOrderSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "0"
CustomerOrderLinePosition	Occurrence 1 .. 1 Type xs:long FractionDigits 0 Inclusive -922337203685477 5808 .. 922337203685477 5807 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ORDER_LINE/COR/COPOS

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
	CustomerOrderLineKitPosition	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 Instruction Hardcode "0"
	CustomerOrderLineSequence	Occurrence 1 .. 1 Type xs:int FractionDigits 0 Inclusive -2147483648 .. 2147483647 Map Instructions Instruction Nr 1 Instruction Hardcode "0"
	TextFunction	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 Instruction Hardcode "TXT"
	Text	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 Instruction Map /message/content/CUSORD/ORDER_LINE/COR/COPOS+"#"+/message/content/CUSORD/ORDER_LINE/COR/ARTID Additional Info map from previous CustomerOrderLine where /message/content/CUSORD/ORDER_LINE/COR/ORDQTY = "0"
tns:Partys		Occurrence 0 .. 1
xs:sequence		Occurrence 1 .. unbounded
	tns:Party	Occurrence 1 .. 1 Map Instructions Instruction Nr 1 Instruction Triggered by /message/content/CUSORD/ADDRESS/ADR
	xs:sequence	Occurrence 1 .. 1
	ChannelId	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 Instruction Hardcode "SE-ACO"
	ChannelRef	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 Instruction Hardcode "SE-ACO"
	TransactionId	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 Instruction Map "ACO"+counter+"_1"
	aPartyDoc	Occurrence 0 .. 1 Type tns:PartyDoc
xs:sequence		Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation
-	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
-	aPartyAddressDocs	Occurrence 0 .. 1 Type tns:ArrayOfPartyAddressDoc
		xs:sequence
		Occurrence 1 .. 1
-	PartyAddressDoc	Occurrence 0 .. unbounded Type tns:PartyAddressDoc
		xs:sequence
		Occurrence 1 .. 1
-	OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1"
-	PartyQualifier	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CU"
-	PartyIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> 1. concat (/message/content/CUSORD/ADDRESS/ADR/PARTY_ID+"_"+/message/content/CUSORD/COID) 2. Remove the last two characters and Map the value <i>Additional Info</i> Ex: value - C06560_117656-001 Output - C06560_117656-0 value - 10002_15547-1 Output - 10002_15547
-	PartyProfile	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "SE-ACO"
-	PartyStatus	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "N"
-	PartyName1	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/NAME1
-	PartyName2	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/NAME2
	PartyName3	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/NAME3
	PartyName4	Occurrence 1 .. 1 Type xs:string
	PartyName5	Occurrence 1 .. 1 Type xs:string
	PartyAddress1	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/ADR1
	PartyAddress2	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/ADR2
	PartyAddress3	Occurrence 1 .. 1 Type xs:string
	PartyAddress4	Occurrence 1 .. 1 Type xs:string
	ZipCode	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/POSTCODE
	City	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/CITY
	Region	Occurrence 1 .. 1 Type xs:string
	CountryCode	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/COUNTRYCODE
	Country	Occurrence 1 .. 1 Type xs:string
	GeographicalCode	Occurrence 1 .. 1 Type xs:string
	Phone	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
		Map Instructions
		PHONE
	Fax	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/CONTACT1
	Telex	Occurrence 1 .. 1 Type xs:string
	Email	Occurrence 1 .. 1 Type xs:string
	PostalGiroAccount	Occurrence 1 .. 1 Type xs:string
	BankGiroAccount	Occurrence 1 .. 1 Type xs:string
	VATNumber	Occurrence 1 .. 1 Type xs:string
	OrganizationNumber	Occurrence 1 .. 1 Type xs:string
	Language	Occurrence 1 .. 1 Type xs:string
	Division	Occurrence 1 .. 1 Type xs:string
	SendASN	Occurrence 1 .. 1 Type xs:string
	RcvCheckType	Occurrence 1 .. 1 Type xs:string
	FreCustomerId	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR/FRE_CUSTOMER_ID
	FreCustomerIdEUR	Occurrence 1 .. 1 Type xs:string
	CustomsDeclarant	Occurrence 1 .. 1 Type xs:string
	CustomsDeclType	Occurrence 1 .. 1 Type xs:string
	CustomsClearanceType	Occurrence 1 .. 1 Type xs:string
	ExecuteCustomsDecl	Occurrence 1 .. 1 Type xs:string
	PayCustomsDecl	Occurrence 1 .. 1 Type xs:string
	EORINumber	Occurrence 1 .. 1 Type xs:string
	DeliveryPointCode	Occurrence 1 .. 1 Type xs:string
	DoorCode	Occurrence 1 .. 1 Type xs:string
	tns:Party	Occurrence 1 .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> Triggered by /message/content/CUSORD/ADDRESS/

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions
	ADR2
xs:sequence	Occurrence 1 .. 1
ChannelId	Occurrence 0 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Hardcode "SE-ACO"
ChannelRef	Occurrence 0 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Hardcode "SE-ACO"
TransactionId	Occurrence 0 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Map "ACO"+counter+"_2"
aPartyDoc	Occurrence 0 .. 1 Type tns:PartyDoc
xs:sequence	Occurrence 1 .. 1
OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Hardcode "1"
aPartyAddressDocs	Occurrence 0 .. 1 Type tns:ArrayOfPartyAddressDoc
xs:sequence	Occurrence 1 .. 1
PartyAddressDoc	Occurrence 0 .. unbounded Type tns:PartyAddressDoc
xs:sequence	Occurrence 1 .. 1
OPCODE	Occurrence 0 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Hardcode "1"
PartyQualifier	Occurrence 1 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Hardcode "CU"
PartyIdentity	Occurrence 1 .. 1 Type xs:string Map Instructions
	Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/ PARTY_ID+"_"/+/message/content/CUSORD/COID+"B"
PartyProfile	Occurrence 1 .. 1 Type xs:string
PartyStatus	Occurrence 1 .. 1 Type xs:string Map Instructions
	Instruction Nr 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions <i>Instruction</i> Hardcode "N"
PartyName1	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/NAME1
PartyName2	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/NAME2
PartyName3	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/NAME3
PartyName4	Occurrence 1 .. 1 Type xs:string
PartyName5	Occurrence 1 .. 1 Type xs:string
PartyAddress1	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/ADR1
PartyAddress2	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/ADR2
PartyAddress3	Occurrence 1 .. 1 Type xs:string
PartyAddress4	Occurrence 1 .. 1 Type xs:string
ZipCode	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/POSTCODE
City	Occurrence 1 .. 1 Type xs:string Map Instructions Instruction Nr 1 <i>Instruction</i> Map /message/content/CUSORD/ADDRESS/ADR2/CITY
Region	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
CountryCode	Occurrence	1 .. 1
	Type	xs:string
Map Instructions		
Instruction Nr 1		
Instruction		Map /message/content/CUSORD/ADDRESS/ADR2/COUNTRYCODE
Country	Occurrence	1 .. 1
	Type	xs:string
GeographicalCode	Occurrence	1 .. 1
	Type	xs:string
Phone	Occurrence	1 .. 1
	Type	xs:string
Map Instructions		
Instruction Nr 1		
Instruction		Map /message/content/CUSORD/ADDRESS/ADR2/PHONE
Fax	Occurrence	1 .. 1
	Type	xs:string
Map Instructions		
Instruction Nr 1		
Instruction		Map /message/content/CUSORD/ADDRESS/ADR2/CONTACT1
Telex	Occurrence	1 .. 1
	Type	xs:string
Email	Occurrence	1 .. 1
	Type	xs:string
PostalGiroAccount	Occurrence	1 .. 1
	Type	xs:string
BankGiroAccount	Occurrence	1 .. 1
	Type	xs:string
VATNumber	Occurrence	1 .. 1
	Type	xs:string
OrganizationNumber	Occurrence	1 .. 1
	Type	xs:string
Language	Occurrence	1 .. 1
	Type	xs:string
Division	Occurrence	1 .. 1
	Type	xs:string
SendASN	Occurrence	1 .. 1
	Type	xs:string
RcvCheckType	Occurrence	1 .. 1
	Type	xs:string
FreCustomerId	Occurrence	1 .. 1
	Type	xs:string
FreCustomerIdEUR	Occurrence	1 .. 1
	Type	xs:string
CustomsDeclarant	Occurrence	1 .. 1
	Type	xs:string
CustomsDeclType	Occurrence	1 .. 1
	Type	xs:string
CustomsClearanceType	Occurrence	1 .. 1
	Type	xs:string
ExecuteCustomsDecl	Occurrence	1 .. 1
	Type	xs:string
PayCustomsDecl	Occurrence	1 .. 1
	Type	xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation	
	EORINumber	Occurrence	1 .. 1
		Type	xs:string
	DeliveryPointCode	Occurrence	1 .. 1
		Type	xs:string
	DoorCode	Occurrence	1 .. 1
		Type	xs:string