



Message Implementation Guideline

message

Model: D_TX_XX_SEACOxxPKCV1xxDEAV1xxOS
Version: 1-DEV
Variant: EDIT0008913
Issue date: 14-08-2025
Author: ext.lalli.k

Structure

Occurrence	Element/Attribute
	message
required	<i>revision</i>
required	<i>src</i>
optional	<i>srcSub</i>
required	<i>dst</i>
optional	<i>type</i>
required	<i>date</i>
1 .. 1	xs:sequence
1 .. unbounded	content
1 .. 9999	xs:sequence
1 .. 1	CORRES
1 .. 1	xs:all
1 .. 1	COID
0 .. 1	COSEQ
0 .. 1	COSUBSEQ
1 .. 1	WHID
0 .. 1	ASSEMBLE_TO_STOCK
1 .. 1	PACK_HEAD
0 .. 9999	xs:sequence
0 .. 1	PMH
1 .. 1	xs:all
0 .. 1	PMTYPID
0 .. 1	PMQTY
1 .. 1	CORRES_LINE
0 .. 9999	xs:sequence
1 .. 1	CSR
1 .. 1	xs:all
1 .. 1	COPOS
0 .. 1	COROWKITPOS
0 .. 1	COSUBPOS
1 .. 1	OWNID
1 .. 1	ARTID
1 .. 1	PAKID
1 .. 1	PICKQTY
0 .. 1	PROMOTN
0 .. 1	STORBAT
0 .. 1	SHIPDTM
0 .. 1	CONSNOTE
0 .. 1	DELVRYNOTE
0 .. 1	ORDQTY
0 .. 1	BLOCKCOD
0 .. 1	ASSEMBLE_TO_STOCK
1 .. 1	SERIAL
0 .. 9999	xs:sequence
0 .. 1	SNO
1 .. 1	xs:all
0 .. 1	SERNUMB

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
message	Map Instructions Instruction Nr 1 <i>Instruction</i> Use /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/CustomerOrderNumber (or suggested by business at the time of SIT etc.) as LW reference, for alt reference /DocumentMessage/Document/FileName (from CDM Wrapper parameter) to keep in LW, more over these values may change though we have set unique values, it is business responsibility to suggest us the correct values at the time of testing
revision	Type xs:string Use required Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "1.1"
src	Type xs:string Use required Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "SCHENKER"
srcSub	Type xs:string Use optional Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "OW"
dst	Type xs:string Use required Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "7300009054275"
type	Type xs:string Use optional Map Instructions Instruction Nr 1 <i>Instruction</i> Hardcode "CORRES"
date	Type xs:dateTime Use required Map Instructions Instruction Nr 1 <i>Instruction</i> Map current date time <i>Additional Info</i> Format: 'yyyy-MM-ddTHH:mm:ssZ'
xs:sequence	Occurence 1 .. 1
content	Occurence 1 .. unbounded
xs:sequence	Occurence 1 .. 9999
CORRES	Occurence 1 .. 1
xs:all	Occurence 1 .. 1
C0ID	Occurence 1 .. 1 Type restriction (xs:string) Length .. 35 Map Instructions Instruction Nr 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/CustomerOrderNumber
COSEQ	Occurrence 0 .. 1 Type restriction (xs:decimal) FractionDigits 0 TotalDigits 3 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/CustomerOrderSequence
COSUBSEQ	Occurrence 0 .. 1 Type restriction (xs:decimal) FractionDigits 0 TotalDigits 2 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/CustomerOrderSubSequence
WHID	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 4 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/WarehouseIdentity
ASSEMBLE_TO_STOCK	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/AssembleToStock
PACK_HEAD	Occurrence 1 .. 1
xs:sequence	Occurrence 0 .. 9999
PMH	Occurrence 0 .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> Trigger each time based on /Calls/Call/PickReceipts/ PickReceipt/aPickReceiptHeadDoc/ aPickReceiptHeadPackingMaterialDocs/ PickReceiptHeadPackingMaterialDoc
xs:all	Occurrence 1 .. 1
PMTYPID	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 35 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/ aPickReceiptHeadPackingMaterialDocs/ PickReceiptHeadPackingMaterialDoc/ PackingMaterialType

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
└ PMQTY	Occurrence 0 .. 1 Type restriction (xs:byte) Length .. 26 FractionDigits 0 Inclusive -128 .. 127 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/ aPickReceiptHeadPackingMaterialDocs/ PickReceiptHeadPackingMaterialDoc/Quantity
└ CORRES_LINE	Occurrence 1 .. 1
└ xs:sequence	Occurrence 0 .. 9999
└ CSR	Occurrence 1 .. 1 Map Instructions Instruction Nr 1 <i>Condition</i> When /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/aPickReceiptLineTextDocs/ PickReceiptLineTextDoc/TextFunction = "TXT" and / Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/aPickReceiptLineTextDocs/ PickReceiptLineTextDoc/Text value separated by # <i>Instruction</i> Trigger this segment and set <PICKQTY> and <ORDQTY> to 0 Instruction Nr 2 <i>Instruction</i> Trigger this segment for the unique combination of / Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/ProductIdentity and /Calls/Call/ PickReceipts/PickReceipt/aPickReceiptHeadDoc/ aPickReceiptLineDocs/PickReceiptLineDoc/ aPickReceiptLineTextDocs/PickReceiptLineTextDoc/ CustomerOrderLinePosition Instruction Nr 3 <i>Instruction</i> Sort the looping in ascending order based on the / message/content/CORRES/CORRES_LINE/CSR/ COPOS (target side)
└ xs:all	Occurrence 1 .. 1
└ COPOS	Occurrence 1 .. 1 Type restriction (xs:decimal) FractionDigits 0 TotalDigits 5 Map Instructions Instruction Nr 1 <i>Condition</i> If /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/aPickReceiptLineTextDocs/ PickReceiptLineTextDoc/TextFunction = "TXT" and / Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/aPickReceiptLineTextDocs/ PickReceiptLineTextDoc/Text value separated by # <i>Instruction</i> Map the value which comes before # Instruction Nr 2 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/CustomerOrderLinePosition
COROWKITPOS	Occurrence 0 .. 1 Type restriction (xs:decimal) FractionDigits 0 TotalDigits 2 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/CustomerOrderLineKitPosition
COSUBPOS	Occurrence 0 .. 1 Type restriction (xs:decimal) FractionDigits 0 TotalDigits 3 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/CustomerOrderLineSequence
OWNID	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 17 Map Instructions Instruction Nr 1 <i>Instruction</i> Map /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/OwnerIdentity
ARTID	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 35 Map Instructions Instruction Nr 1 <i>Condition</i> If /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/aPickReceiptLineTextDocs/ PickReceiptLineTextDoc/TextFunction = "TXT" and / Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/aPickReceiptLineTextDocs/ PickReceiptLineTextDoc/Text value separated by # <i>Instruction</i> Map the value after # Instruction Nr 2 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/ProductIdentity
PAKID	Occurrence 1 .. 1 Type restriction (xs:string) Length .. 17 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/ aPickReceiptHeadDoc/aPickReceiptLineDocs/ PickReceiptLineDoc/PackageIdentity

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
PICKQTY	Occurrence 1 .. 1 Type restriction (xs:decimal) FractionDigits 0 TotalDigits 10 Map Instructions Instruction Nr 1 <i>Instruction</i> Map SUM (/Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/PickQuantity) groupby /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/CustomerOrderLinePosition
PROMOTN	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 20 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/MarketingLotIdentity
STORBAT	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 3 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/QualityLotIdentity
SHIPDTM	Occurrence 0 .. 1 Type xs:date Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/ShipDate
CONSNOTE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 35 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/ConsignmentNote
DELVRYNOTE	Occurrence 0 .. 1 Type restriction (xs:string) Length .. 20 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/PackingSlipIdentity
ORDQTY	Occurrence 0 .. 1 Type restriction (xs:decimal) FractionDigits 3 TotalDigits 13

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	Map Instructions Instruction Nr 1 <i>Instruction</i> Map SUM (/Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/OrderedQuantity) groupby /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/CustomerOrderLinePosition
BLOCKCOD	Occurence 0 .. 1 Type restriction (xs:string) Length .. 5 Map Instructions Instruction Nr 1 <i>Instruction</i> Map this field only if /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/InventoryStatusCode <> 00 Instruction Nr 2 <i>Condition</i> else omit this field
ASSEMBLE_TO_STOCK	Occurence 0 .. 1 Type restriction (xs:string) Length .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/AssembleToStock
SERIAL	Occurence 1 .. 1
xs:sequence	Occurence 0 .. 9999
SNO	Occurence 0 .. 1 Map Instructions Instruction Nr 1 <i>Instruction</i> Trigger each time based on the /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs
xs:all	Occurence 1 .. 1
SERNUMB	Occurence 0 .. 1 Type restriction (xs:string) Length .. 21 Map Instructions Instruction Nr 1 <i>Instruction</i> Map from /Calls/Call/PickReceipts/PickReceipt/aPickReceiptHeadDoc/aPickReceiptLineDocs/PickReceiptLineDoc/aPickReceiptLineSerialNumberDocs/PickReceiptLineSerialNumberDoc/SerialNumber

Bold = Element, Italic = Attribute, Grey = Group