

Chat : <https://chatgpt.com/share/cf37777d-9dff-42e8-8e2f-e10eb87933e7>

I want to refactor this verilog module ``include "preemphasis_filter.v"

`include "framing_windowing.v"

`include "goertzel_dft.v"

`include "mel_filterbank.v"

`include "logarithm_comp.v"

`include "dct_comp.v"

`include "mfcc_accelerator.v"

`include "conv2d.v"

`include "maxpool2d.v"

`include "fully_connected.v"

`include "softmax.v"

module cnn_kws_accel #(
 parameter NUM_KEYWORDS = 10,
 parameter MFCC_FEATURES = 40,
 parameter ACTIV_BITS = 8,
 parameter FC1_INPUT_SIZE = (MFCC_FEATURES/2)*(CONV2_NUM_FILTERS),
 parameter FC1_OUTPUT_SIZE = 64,
 parameter FC2_INPUT_SIZE = 64,
 parameter FC2_OUTPUT_SIZE = NUM_KEYWORDS,
 parameter CONV1_KERNEL_SIZE = 3,
 parameter CONV1_NUM_FILTERS = 8,
 parameter CONV2_KERNEL_SIZE = 3,
 parameter CONV2_NUM_FILTERS = 8
)(
 input wire clk,
 input wire rst_n,
 input wire [15:0] audio_in,

```

input wire audio_valid,
output reg [NUM_KEYWORDS-1:0] kws_result,
output reg kws_valid,
input wire [7:0] frame_size,
input wire [7:0] frame_overlap,
input wire [7:0] num_mfcc_coefs,
input wire [7:0] goertzel_coefs,
output wire goertzel_coefs_start,
output wire goertzel_coefs_valid,
output wire goertzel_coefs_done,

input wire [CONV1_NUM_FILTERS*CONV1_KERNEL_SIZE*CONV1_KERNEL_SIZE*ACTIV_BITS-1:0]
conv1_weights,

input wire [CONV1_NUM_FILTERS*ACTIV_BITS-1:0] conv1_biases,
input wire conv1_load_weights,
input wire conv1_load_biases,

input wire
[CONV2_NUM_FILTERS*CONV1_NUM_FILTERS*CONV2_KERNEL_SIZE*CONV2_KERNEL_SIZE*ACTIV_
BITS-1:0] conv2_weights,

input wire [CONV2_NUM_FILTERS*ACTIV_BITS-1:0] conv2_biases,
input wire conv2_load_weights,
input wire conv2_load_biases,

input wire [FC1_OUTPUT_SIZE*FC1_INPUT_SIZE*ACTIV_BITS-1:0] fc1_weights,
input wire [FC1_OUTPUT_SIZE*ACTIV_BITS-1:0] fc1_biases,
input wire fc1_load_weights,
input wire fc1_load_biases,

input wire [FC2_OUTPUT_SIZE*FC2_INPUT_SIZE*ACTIV_BITS-1:0] fc2_weights,
input wire [FC2_OUTPUT_SIZE*ACTIV_BITS-1:0] fc2_biases,
input wire fc2_load_weights,
input wire fc2_load_biases
);

// MFCC module signals

```

```

wire [MFCC_FEATURES*ACTIV_BITS-1:0] mfcc_out;

wire mfcc_valid;


// CNN-KWS layers

wire [MFCC_FEATURES*CONV1_NUM_FILTERS*ACTIV_BITS-1:0] conv1_out;

wire conv1_valid;

wire [MFCC_FEATURES*CONV2_NUM_FILTERS*ACTIV_BITS-1:0] conv2_out;

wire conv2_valid;

wire [(MFCC_FEATURES/2)*CONV2_NUM_FILTERS*ACTIV_BITS-1:0] maxpool_out;

wire maxpool_valid;

wire [FC1_OUTPUT_SIZE*ACTIV_BITS-1:0] fc1_out;

wire fc1_valid;

wire [FC2_OUTPUT_SIZE*ACTIV_BITS-1:0] fc2_out;

wire fc2_valid;

wire [FC2_OUTPUT_SIZE*ACTIV_BITS-1:0] softmax_out;

wire softmax_valid;


// MFCC module instantiation

mfcc_accelerator #(
    .MFCC_FEATURES(MFCC_FEATURES),
    .ACTIV_BITS(ACTIV_BITS)
) mfcc (
    .clk(clk),
    .rst_n(rst_n),
    .audio_in(audio_in),
    .audio_valid(audio_valid),
    .mfcc_out(mfcc_out),
    .mfcc_valid(mfcc_valid),
    .frame_size(frame_size),
    .frame_overlap(frame_overlap),
    .num_mfcc_coeffs(num_mfcc_coeffs),

```

```
.goertzel_coefs(goertzel_coefs),  
.goertzel_coefs_start(goertzel_coefs_start),  
.goertzel_coefs_valid(goertzel_coefs_valid),  
.goertzel_coefs_done(goertzel_coefs_done)  
);
```

```
// Convolutional layer 1
```

```
conv2d #(  
    .INPUT_WIDTH(MFCC_FEATURES),  
    .INPUT_HEIGHT(1),  
    .INPUT_CHANNELS(1),  
    .KERNEL_SIZE(CONV1_KERNEL_SIZE),  
    .NUM_FILTERS(CONV1_NUM_FILTERS),  
    .PADDING(1),  
    .ACTIV_BITS(ACTIV_BITS)  
) conv1 (  
    .clk(clk),  
    .rst_n(rst_n),  
    .data_in(mfcc_out),  
    .data_valid(mfcc_valid),  
    .data_out(conv1_out),  
    .data_out_valid(conv1_valid),  
    .weights_in(conv1_weights),  
    .biases_in(conv1_biases),  
    .load_weights(conv1_load_weights),  
    .load_biases(conv1_load_biases)  
);
```

```
// Convolutional layer 2
```

```
conv2d #(  
    .INPUT_WIDTH(MFCC_FEATURES),  
    .INPUT_HEIGHT(1),  
    .INPUT_CHANNELS(1),  
    .KERNEL_SIZE(CONV1_KERNEL_SIZE),  
    .NUM_FILTERS(CONV1_NUM_FILTERS),  
    .PADDING(1),  
    .ACTIV_BITS(ACTIV_BITS)  
) conv2 (  
    .clk(clk),  
    .rst_n(rst_n),  
    .data_in(conv1_out),  
    .data_valid(conv1_valid),  
    .data_out(conv2_out),  
    .data_out_valid(conv2_valid),  
    .weights_in(conv2_weights),  
    .biases_in(conv2_biases),  
    .load_weights(conv2_load_weights),  
    .load_biases(conv2_load_biases)  
);
```

```

.INPUT_WIDTH(MFCC_FEATURES),
.INPUT_HEIGHT(1),
.INPUT_CHANNELS(CONV1_NUM_FILTERS),
.KERNEL_SIZE(CONV2_KERNEL_SIZE),
.NUM_FILTERS(CONV2_NUM_FILTERS),
.PADDING(1),
.ACTIV_BITS(ACTIV_BITS)
) conv2 (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(conv1_out),
    .data_valid(conv1_valid),
    .data_out(conv2_out),
    .data_out_valid(conv2_valid),
    .weights_in(conv2_weights),
    .biases_in(conv2_biases),
    .load_weights(conv2_load_weights),
    .load_biases(conv2_load_biases)
);

```

```

maxpool2d #(
    .INPUT_WIDTH(MFCC_FEATURES),
    .INPUT_HEIGHT(1),
    .INPUT_CHANNELS(CONV2_NUM_FILTERS),
    .KERNEL_SIZE(2),
    .STRIDE(2),
    .ACTIV_BITS(ACTIV_BITS)
) maxpool (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(conv2_out),

```

```

        .data_valid(conv2_valid),
        .data_out(maxpool_out),
        .data_out_valid(maxpool_valid)
    );

```

```

fully_connected #(
    .INPUT_SIZE(FC1_INPUT_SIZE),
    .OUTPUT_SIZE(FC1_OUTPUT_SIZE),
    .ACTIV_BITS(ACTIV_BITS)
) fc1 (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(maxpool_out),
    .data_valid(maxpool_valid),
    .data_out(fc1_out),
    .data_out_valid(fc1_valid),
    .weights_in(fc1_weights[FC1_OUTPUT_SIZE*FC1_INPUT_SIZE*ACTIV_BITS-1:0]),
    .biases_in(fc1_biases),
    .load_weights(fc1_load_weights),
    .load_biases(fc1_load_biases)
);

```

// Fully connected layer 2 (output layer)

```

fully_connected #(
    .INPUT_SIZE(FC2_INPUT_SIZE),
    .OUTPUT_SIZE(FC2_OUTPUT_SIZE),
    .ACTIV_BITS(ACTIV_BITS)
) fc2 (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(fc1_out),

```

```

        .data_valid(fc1_valid),
        .data_out(fc2_out),
        .data_out_valid(fc2_valid),
        .weights_in(fc2_weights),
        .biases_in(fc2_biases),
        .load_weights(fc2_load_weights),
        .load_biases(fc2_load_biases)
    );

```

```

// Softmax layer

```

```

softmax #(
    .INPUT_SIZE(NUM_KEYWORDS),
    .ACTIV_BITS(ACTIV_BITS)
) softmax (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(fc2_out),
    .data_valid(fc2_valid),
    .data_out(softmax_out),
    .data_out_valid(softmax_valid)
);

```

```

// Output assignment

```

```

always @(posedge clk or negedge rst_n) begin
    if (!rst_n) begin
        kws_result <= 'b0;
        kws_valid <= 1'b0;
    end else begin
        kws_result <= softmax_out[NUM_KEYWORDS-1:0];
        kws_valid <= softmax_valid;
    end
end

```

end

endmodule" so as not to instantiate the mfcc_accelerator module but instead the mfcc_accel module that has this code "module mfcc_accel (

```
    input wire clk,  
    input wire rst,  
    input wire [15:0] audio_sample,  
    input wire sample_valid,  
    output wire [15:0] mfcc_feature,  
    output wire mfcc_valid  
);
```

// Instantiate the Hanning window real module

```
wire [15:0] hanning_real_out;  
wire hanning_real_valid;
```

```
hanning_window_real hanning_real (  
    .clk(clk),  
    .rst(rst),  
    .sample_in(audio_sample),  
    .sample_valid(sample_valid),  
    .sample_out(hanning_real_out),  
    .sample_out_valid(hanning_real_valid)  
);
```

// Instantiate the Hanning window imaginary module

```
wire [15:0] hanning_imag_out;  
wire hanning_imag_valid;
```

```
hanning_window_imag hanning_imag (  
    .clk(clk),
```



```
.rst(rst),  
.sample_in(audio_sample),  
.sample_valid(sample_valid),  
.sample_out(hanning_imag_out),  
.sample_out_valid(hanning_imag_valid)  
);
```

```
// Instantiate the periodogram module
```

```
wire [31:0] periodogram_out;
```

```
wire periodogram_valid;
```

```
periodogram_squared periodogram (
```

```
    .clk(clk),
```

```
    .rst(rst),
```

```
    .sample_in_real(hanning_real_out),
```

```
    .sample_in_imag(hanning_imag_out),
```

```
    .sample_valid(hanning_real_valid), // Use the valid signal from the real Hanning window
```

```
    .periodogram_out(periodogram_out),
```

```
    .periodogram_valid(periodogram_valid)
```

```
);
```

```
// Instantiate the pow_module
```

```
wire [31:0] pow_out;
```

```
wire pow_valid;
```

```
pow_module pow (
```

```
    .clk(clk),
```

```
    .rst(rst),
```

```
    .data_in(periodogram_out),
```

```
    .data_valid(periodogram_valid),
```

```
    .data_out(pow_out),
```

```

        .data_out_valid(pow_valid)
    );

// Instantiate the mel_filterbank module
wire [31:0] mel_out;
wire mel_valid;

mel_filterbank mel (
    .clk(clk),
    .rst(rst),
    .data_in(pow_out),
    .data_valid(pow_valid),
    .mel_out(mel_out),
    .mel_valid(mel_valid)
);

// Instantiate the log_module
wire [15:0] log_out;
wire log_valid;

log_module log (
    .clk(clk),
    .rst(rst),
    .data_in(mel_out),
    .data_valid(mel_valid),
    .log_out(log_out),
    .log_valid(log_valid)
);

// Instantiate the dct_module
dct_module dct (

```

```

.clk(clk),
.rst(rst),
.data_in(log_out),
.data_valid(log_valid),
.dct_out(mfcc_feature),
.dct_valid(mfcc_valid)
);

```

endmodule"

ChatGPT

To refactor the `cnn_kws_accel` Verilog module to use the `mfcc_accel` module instead of `mfcc_accelerator`, you need to update the instantiation of the MFCC module in `cnn_kws_accel` accordingly. Here's how the refactored `cnn_kws_accel` module would look:

verilog

Copy code

```

`include "preemphasis_filter.v"
`include "framing_windowing.v"
`include "goertzel_dft.v"
`include "mel_filterbank.v"
`include "logarithm_comp.v"
`include "dct_comp.v"
`include "conv2d.v"
`include "maxpool2d.v"
`include "fully_connected.v"
`include "softmax.v"

module cnn_kws_accel #(
    parameter NUM_KEYWORDS = 10,
    parameter MFCC_FEATURES = 40,
    parameter ACTIV_BITS = 8,
    parameter FC1_INPUT_SIZE = (MFCC_FEATURES/2)*(CONV2_NUM_FILTERS),

```

```

parameter FC1_OUTPUT_SIZE = 64,
parameter FC2_INPUT_SIZE = 64,
parameter FC2_OUTPUT_SIZE = NUM_KEYWORDS,
parameter CONV1_KERNEL_SIZE = 3,
parameter CONV1_NUM_FILTERS = 8,
parameter CONV2_KERNEL_SIZE = 3,
parameter CONV2_NUM_FILTERS = 8
)(
    input wire clk,
    input wire rst_n,
    input wire [15:0] audio_in,
    input wire audio_valid,
    output reg [NUM_KEYWORDS-1:0] kws_result,
    output reg kws_valid,
    input wire [7:0] frame_size,
    input wire [7:0] frame_overlap,
    input wire [7:0] num_mfcc_coefs,
    input wire [7:0] goertzel_coefs,
    output wire goertzel_coefs_start,
    output wire goertzel_coefs_valid,
    output wire goertzel_coefs_done,

    input wire [CONV1_NUM_FILTERS*CONV1_KERNEL_SIZE*CONV1_KERNEL_SIZE*ACTIV_BITS-1:0]
conv1_weights,

    input wire [CONV1_NUM_FILTERS*ACTIV_BITS-1:0] conv1_biases,
    input wire conv1_load_weights,
    input wire conv1_load_biases,

    input wire
[CONV2_NUM_FILTERS*CONV1_NUM_FILTERS*CONV2_KERNEL_SIZE*CONV2_KERNEL_SIZE*ACTIV_
BITS-1:0] conv2_weights,

    input wire [CONV2_NUM_FILTERS*ACTIV_BITS-1:0] conv2_biases,
    input wire conv2_load_weights,
    input wire conv2_load_biases,

```

```

input wire [FC1_OUTPUT_SIZE*FC1_INPUT_SIZE*ACTIV_BITS-1:0] fc1_weights,
input wire [FC1_OUTPUT_SIZE*ACTIV_BITS-1:0] fc1_biases,
input wire fc1_load_weights,
input wire fc1_load_biases,
input wire [FC2_OUTPUT_SIZE*FC2_INPUT_SIZE*ACTIV_BITS-1:0] fc2_weights,
input wire [FC2_OUTPUT_SIZE*ACTIV_BITS-1:0] fc2_biases,
input wire fc2_load_weights,
input wire fc2_load_biases
);

// MFCC module signals
wire [15:0] mfcc_out;
wire mfcc_valid;

// CNN-KWS layers
wire [MFCC_FEATURES*CONV1_NUM_FILTERS*ACTIV_BITS-1:0] conv1_out;
wire conv1_valid;
wire [MFCC_FEATURES*CONV2_NUM_FILTERS*ACTIV_BITS-1:0] conv2_out;
wire conv2_valid;
wire [(MFCC_FEATURES/2)*CONV2_NUM_FILTERS*ACTIV_BITS-1:0] maxpool_out;
wire maxpool_valid;
wire [FC1_OUTPUT_SIZE*ACTIV_BITS-1:0] fc1_out;
wire fc1_valid;
wire [FC2_OUTPUT_SIZE*ACTIV_BITS-1:0] fc2_out;
wire fc2_valid;
wire [FC2_OUTPUT_SIZE*ACTIV_BITS-1:0] softmax_out;
wire softmax_valid;

// MFCC module instantiation
mfcc_accel mfcc (
    .clk(clk),

```

```

.rst(rst_n), // Adjusted to rst_n

.audio_sample(audio_in), // Adjusted to audio_sample

.sample_valid(audio_valid), // Adjusted to sample_valid

.mfcc_feature(mfcc_out), // Adjusted to mfcc_feature

.mfcc_valid(mfcc_valid) // Adjusted to mfcc_valid

);

```

// Convolutional layer 1

```

conv2d #(

.INPUT_WIDTH(MFCC_FEATURES),

.INPUT_HEIGHT(1),

.INPUT_CHANNELS(1),

.KERNEL_SIZE(CONV1_KERNEL_SIZE),

.NUM_FILTERS(CONV1_NUM_FILTERS),

.PADDING(1),

.ACTIV_BITS(ACTIV_BITS)

) conv1 (

.clk(clk),

.rst_n(rst_n),

.data_in(mfcc_out),

.data_valid(mfcc_valid),

.data_out(conv1_out),

.data_out_valid(conv1_valid),

.weights_in(conv1_weights),

.biases_in(conv1_biases),

.load_weights(conv1_load_weights),

.load_biases(conv1_load_biases)

);

```

// Convolutional layer 2

```

conv2d #(

```

```

.INPUT_WIDTH(MFCC_FEATURES),
.INPUT_HEIGHT(1),
.INPUT_CHANNELS(CONV1_NUM_FILTERS),
.KERNEL_SIZE(CONV2_KERNEL_SIZE),
.NUM_FILTERS(CONV2_NUM_FILTERS),
.PADDING(1),
.ACTIV_BITS(ACTIV_BITS)
) conv2 (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(conv1_out),
    .data_valid(conv1_valid),
    .data_out(conv2_out),
    .data_out_valid(conv2_valid),
    .weights_in(conv2_weights),
    .biases_in(conv2_biases),
    .load_weights(conv2_load_weights),
    .load_biases(conv2_load_biases)
);

```

```

maxpool2d #(
    .INPUT_WIDTH(MFCC_FEATURES),
    .INPUT_HEIGHT(1),
    .INPUT_CHANNELS(CONV2_NUM_FILTERS),
    .KERNEL_SIZE(2),
    .STRIDE(2),
    .ACTIV_BITS(ACTIV_BITS)
) maxpool (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(conv2_out),

```

```

        .data_valid(conv2_valid),
        .data_out(maxpool_out),
        .data_out_valid(maxpool_valid)
    );

```

```

fully_connected #(
    .INPUT_SIZE(FC1_INPUT_SIZE),
    .OUTPUT_SIZE(FC1_OUTPUT_SIZE),
    .ACTIV_BITS(ACTIV_BITS)
) fc1 (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(maxpool_out),
    .data_valid(maxpool_valid),
    .data_out(fc1_out),
    .data_out_valid(fc1_valid),
    .weights_in(fc1_weights[FC1_OUTPUT_SIZE*FC1_INPUT_SIZE*ACTIV_BITS-1:0]),
    .biases_in(fc1_biases),
    .load_weights(fc1_load_weights),
    .load_biases(fc1_load_biases)
);

```

```

// Fully connected layer 2 (output layer)

```

```

fully_connected #(
    .INPUT_SIZE(FC2_INPUT_SIZE),
    .OUTPUT_SIZE(FC2_OUTPUT_SIZE),
    .ACTIV_BITS(ACTIV_BITS)
) fc2 (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(fc1_out),

```



```

        .data_valid(fc1_valid),
        .data_out(fc2_out),
        .data_out_valid(fc2_valid),
        .weights_in(fc2_weights),
        .biases_in(fc2_biases),
        .load_weights(fc2_load_weights),
        .load_biases(fc2_load_biases)
    );

```

```

// Softmax layer

```

```

softmax #(
    .INPUT_SIZE(NUM_KEYWORDS),
    .ACTIV_BITS(ACTIV_BITS)
) softmax (
    .clk(clk),
    .rst_n(rst_n),
    .data_in(fc2_out),
    .data_valid(fc2_valid),
    .data_out(softmax_out),
    .data_out_valid(softmax_valid)
);

```

```

// Output assignment

```

```

always @(posedge clk or negedge rst_n) begin
    if (!rst_n) begin
        kws_result <= 'b0;
        kws_valid <= 1'b0;
    end else begin
        kws_result <= softmax_out[NUM_KEYWORDS-1:0];
        kws_valid <= softmax_valid;
    end
end

```

end

endmodule

Changes made:

Removed the parameters specific to mfcc_accelerator.

Adjusted the instantiation of the MFCC module to use mfcc_accel with the corresponding input and output signals.

Adjusted signal names and connections to match those used in mfcc_accel.