





- There were issues affecting this run of Lighthouse:
- There may be stored data affecting loading performance in this location: IndexedDB. Audit this page in an incognito window to prevent those resources from affecting your scores.



Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)

0-49 50-89 90-100

METRICS

Expand view


First Contentful Paint
14.2 s

Largest Contentful Paint
31.2 s

Total Blocking Time
220 ms

Cumulative Layout Shift
0

Speed Index
14.2 s



Show audits relevant to: All FCP LCP TBT

INSIGHTS


Render-blocking requests — Est savings of 1,060 ms

Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. FCP LCP Unscored

URL	Transfer Size	Duration
Google Fonts Cdn	1.7 KiB	840 ms
/css2?family=... (fonts.googleapis.com)	1.7 KiB	840 ms

Improve image delivery — Est savings of 145 KiB

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) FCP LCP Unscored

	URL	Resource Size	Est Savings
localhost 1st Party		306.2 KiB	144.8 KiB
 video.absolute.inset-0.w-full.h-full.object-cover.z-0	/assets/pub_exterior_or_hero.jpg (localhost)	122.0 KiB	87.5 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		87.5 KiB
 img.w-full.h-full.object-cover.transition-transform.duration-500.group-hover:scale-105	/assets/interior_dining_2.webp (localhost)	95.1 KiB	28.4 KiB
	Increasing the image compression factor could improve this image's download size.		28.4 KiB
 img.w-8.h-[38px].object-cover.rounded-[2px].shadow-[0_2px_6px_rgba(0,0,0,0.4)]	/assets/logo_thumb_sharp.png (localhost)	16.2 KiB	15.8 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		15.0 KiB
	This image file is larger than it needs to be (80x94) for its displayed dimensions (48x58). Use responsive images to reduce the image download size.		10.3 KiB
 img.w-full.h-full.object-cover.transition-transform.duration-500.group-hover:scale-105	/assets/pub_building_or_interior.jpg (localhost)	73.0 KiB	13.2 KiB
	This image file is larger than it needs to be (705x704) for its displayed dimensions (745x546). Use responsive images to reduce the image download size.		13.2 KiB

▲ Forced reflow

A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about [forced reflows](#) and possible mitigations. Unscored

Top function callTotal reflow time

framer-motion.js?v=8949bc48:392	90 ms
---------------------------------	-------

SourceTotal reflow time

[unattributed]	1 ms
framer-motion.js?v=8949bc48:7161	90 ms

▲ LCP request discovery

[Optimize LCP](#) by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading LCP Unscored

- fetchpriority=high should be applied
- Request is discoverable in initial document
- LCP resources should not use loading=lazy

video.absolute.inset-0.w-full.h-full.object-cover.z-0

▲ Network dependency tree

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. LCP Unscored

Maximum critical path latency: **376 ms**

Initial Navigation

http://localhost:3000 - 28 ms, 1.71 KiB

- /css2?family=... (fonts.googleapis.com) - 130 ms, 1.75 KiB**
 - ...v24/pxiEyp8kv....woff2 (fonts.gstatic.com) - 376 ms, 7.74 KiB**
 - ...v16/VuJ2dNDF2....woff2 (fonts.gstatic.com) - 372 ms, 12.32 KiB**
 - ...v24/pxiByp8kv....woff2 (fonts.gstatic.com) - 372 ms, 7.83 KiB**
 - ...v16/VuJpdNDF2....woff2 (fonts.gstatic.com) - 371 ms, 12.20 KiB**
 - ...v24/pxiByp8kv....woff2 (fonts.gstatic.com) - 371 ms, 7.69 KiB**
- /src/main.jsx?t=178... (localhost) - 45 ms, 2.76 KiB**
 - /src/App.jsx?t=178... (localhost) - 65 ms, 20.03 KiB**
 - ...deps/framer-motion.js?v=8949bc48 (localhost) - 144 ms, 458.99 KiB**
 - ...deps/chunk-RLMGAKMB.js?v=8949bc48 (localhost) - 148 ms, 36.72 KiB**
 - ...deps/lucide-react.js?v=8949bc48 (localhost) - 142 ms, 913.96 KiB**
 - ...pages/MenuPage.jsx?t=178... (localhost) - 97 ms, 90.18 KiB**
 - ...data/menuData.js?t=178... (localhost) - 121 ms, 181.77 KiB**
 - ...components/TopBar.jsx?t=178... (localhost) - 80 ms, 17.94 KiB**
 - ...data/siteData.js (localhost) - 114 ms, 119.59 KiB**
 - ...pages/ChristmasPage.jsx?t=178... (localhost) - 106 ms, 24.85 KiB**
 - ...pages/ContactPage.jsx?t=178... (localhost) - 106 ms, 59.99 KiB**
 - ...pages/PartyVenuePage.jsx?t=178... (localhost) - 102 ms, 69.52 KiB**
 - ...pages/WhatsOnPage.jsx?t=178... (localhost) - 102 ms, 32.33 KiB**
 - ...pages/ReservationsPage.jsx?t=178... (localhost) - 101 ms, 75.80 KiB**
 - ...pages/HomePage.jsx?t=178... (localhost) - 97 ms, 103.12 KiB**
 - ...pages/OffersPage.jsx?t=178... (localhost) - 96 ms, 23.02 KiB**
 - ...components/PageTransition.jsx (localhost) - 92 ms, 4.10 KiB**
 - ...components/BookingModal.jsx?t=178... (localhost) - 87 ms, 60.52 KiB**
 - ...components/Footer.jsx?t=178... (localhost) - 86 ms, 37.28 KiB**
 - ...components/Navbar.jsx?t=178... (localhost) - 82 ms, 42.75 KiB**
 - ...deps/react-dom_client.js?v=8949bc48 (localhost) - 60 ms, 1.33 KiB**
 - ...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost) - 99 ms, 910.33 KiB**
 - ...deps/react_jsx-dev-runtime.js?v=8949bc48 (localhost) - 59 ms, 36.40 KiB**
 - ...deps/chunk-2YIMICFJ.js?v=8949bc48 (localhost) - 76 ms, 77.66 KiB**
 - ...deps/react-router-dom.js?v=8949bc48 (localhost) - 75 ms, 466.46 KiB**
 - ...styles/index.css?t=178... (localhost) - 67 ms, 79.07 KiB**
 - ...deps/react.js?v=8949bc48 (localhost) - 60 ms, 1.01 KiB**
- /@react-refresh (localhost) - 59 ms, 110.77 KiB**
- /@vite/client (localhost) - 44 ms, 178.54 KiB**
 - ...client/env.mjs (localhost) - 54 ms, 4.05 KiB**

Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://fonts.googleapis.com/	link
https://fonts.gstatic.com/	link

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

Optimize DOM size


A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size.](#) (Unscored)

Statistic	Element		Value
Total elements			542
DOM depth	path		14
Most children		main	10

LCP breakdown

Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. (LCP) (Unscored)

Subpart	Duration
Time to first byte	10 ms
Resource load delay	250 ms
Resource load duration	10 ms
Element render delay	210 ms



3rd parties

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content. (Unscored)

3rd party	Transfer size	Main thread time
fcoeoabgfenejglbffdggkbbkcdhcgfn	0 KiB	2 ms
chrome-extension://fcoeoabgfenejglbffdggkbbkcdhcgfn/assets/agent-visual-indicator.js-Cwioqi0d.js	0 KiB	1 ms
chrome-extension://fcoeoabgfenejglbffdggkbbkcdhcgfn/assets/accessibility-tree.js-B-oUarrX.js	0 KiB	0 ms
Google Fonts (Cdn)	50 KiB	0 ms
...v16/VuJ2dNDF2....woff2 (fonts.gstatic.com)	12 KiB	0 ms
...v16/VuJpdNDF2....woff2 (fonts.gstatic.com)	12 KiB	0 ms
...v24/pxiByp8kv....woff2 (fonts.gstatic.com)	8 KiB	0 ms
...v24/pxiEyp8kv....woff2 (fonts.gstatic.com)	8 KiB	0 ms
...v24/pxiByp8kv....woff2 (fonts.gstatic.com)	8 KiB	0 ms
/css2?family=... (fonts.googleapis.com)	2 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

DIAGNOSTICS

▲ Minify JavaScript — Est savings of 1,817 KiB

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript](#) FCP LCP
Unscored

URL	Transfer Size	Est Savings
localhost 1st Party	4,145.3 KiB	1,816.7 KiB
...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost)	910.0 KiB	335.4 KiB
...deps/lucide-react.js?v=8949bc48 (localhost)	913.7 KiB	215.1 KiB
...data/menuData.js?t=178... (localhost)	181.5 KiB	159.8 KiB
/@vite/client (localhost)	178.3 KiB	155.3 KiB
...deps/framer-motion.js?v=8949bc48 (localhost)	458.7 KiB	131.9 KiB
...deps/react-router-dom.js?v=8949bc48 (localhost)	466.2 KiB	128.2 KiB
...data/siteData.js (localhost)	119.3 KiB	102.2 KiB
/@react-refresh (localhost)	110.5 KiB	100.3 KiB
...pages/HomePage.jsx?t=178... (localhost)	102.8 KiB	67.8 KiB
...pages/MenuPage.jsx?t=178... (localhost)	89.9 KiB	60.0 KiB
...pages/ReservationsPage.jsx?t=178... (localhost)	75.5 KiB	50.7 KiB
...pages/PartyVenuePage.jsx?t=178... (localhost)	69.2 KiB	46.3 KiB
...components/BookingModal.jsx?t=178... (localhost)	60.2 KiB	39.8 KiB
...pages/ContactPage.jsx?t=178... (localhost)	59.7 KiB	39.5 KiB
...deps/chunk-2YIMICFJ.js?v=8949bc48 (localhost)	77.4 KiB	31.5 KiB
...components/Navbar.jsx?t=178... (localhost)	42.5 KiB	28.2 KiB
...components/Footer.jsx?t=178... (localhost)	37.0 KiB	23.7 KiB
...pages/WhatsOnPage.jsx?t=178... (localhost)	32.0 KiB	19.3 KiB
...pages/ChristmasPage.jsx?t=178... (localhost)	24.6 KiB	14.7 KiB
...deps/chunk-RLMGAKMB.js?v=8949bc48 (localhost)	36.4 KiB	14.1 KiB
...deps/react_jsx-dev-runtime.js?v=8949bc48 (localhost)	36.1 KiB	14.0 KiB
...pages/OffersPage.jsx?t=178... (localhost)	22.7 KiB	13.7 KiB
/src/App.jsx?t=178... (localhost)	19.7 KiB	11.9 KiB
...components/TopBar.jsx?t=178... (localhost)	17.7 KiB	10.1 KiB
...client/env.mjs (localhost)	3.8 KiB	3.3 KiB

▲ Reduce unused JavaScript — Est savings of 1,328 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity.
[Learn how to reduce unused JavaScript](#) FCP LCP Unscored

URL	Transfer Size	Est Savings
localhost 1st Party	3,120.1 KiB	1,328.3 KiB
...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost)	910.0 KiB	439.3 KiB

URL	Transfer Size	Est Savings
...react-dom/cjs/react-dom.development.js	891.7 KiB	435.6 KiB
...scheduler/cjs/scheduler.development.js	16.5 KiB	3.7 KiB
...deps/react-router-dom.js?v=8949bc48 (localhost)	466.1 KiB	407.1 KiB
...react-router/dist/development/chunk-BV7QT456.mjs	365.3 KiB	314.6 KiB
...react-router/dist/development/chunk-HT4INDD5.mjs	74.3 KiB	73.2 KiB
...cookie/src/index.ts	7.7 KiB	6.8 KiB
...react-router/dist/development/dom-export.mjs	6.9 KiB	6.6 KiB
...set-cookie-parser/lib/set-cookie.js	6.0 KiB	5.5 KiB
...deps/framer-motion.js?v=8949bc48 (localhost)	458.7 KiB	280.9 KiB
...motion-dom/src/projection/node/create-projection-node.ts	41.5 KiB	34.9 KiB
...framer-motion/src/gestures/drag/VisualElementDragControls.ts	13.8 KiB	13.7 KiB
...motion-dom/src/view/start.ts	13.6 KiB	13.3 KiB
...motion-dom/src/animation/generators/spring.ts	8.4 KiB	7.9 KiB
...motion-dom/src/layout/LayoutAnimationBuilder.ts	8.1 KiB	7.9 KiB
...deps/chunk-2YIMCFJ.js?v=8949bc48 (localhost)	77.4 KiB	38.6 KiB
...cjs/react.development.js	75.2 KiB	38.6 KiB
...pages/MenuPage.jsx?t=178... (localhost)	89.8 KiB	37.6 KiB
...	39.7 KiB	37.3 KiB
...pages/ReservationsPage.jsx?t=178... (localhost)	75.5 KiB	37.0 KiB
...	37.6 KiB	36.8 KiB
...pages/PartyVenuePage.jsx?t=178... (localhost)	69.2 KiB	34.3 KiB
...	34.9 KiB	34.0 KiB
...pages/ContactPage.jsx?t=178... (localhost)	59.7 KiB	29.3 KiB
...	29.8 KiB	29.0 KiB
...deps/lucide-react.js?v=8949bc48 (localhost)	913.7 KiB	24.2 KiB
...lucide-react/dist/esm/icons/index.js	48.4 KiB	24.2 KiB

▲ Page prevented back/forward cache restoration — 1 failure reason ^

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#) (Unscored)

Failure reason	Failure type
CacheLimitPrunedOnCriticalMemoryPressure http://localhost:3000	Not actionable

Minify CSS — Est savings of 3 KiB ^

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS](#). FCP LCP (Unscored)

URL	Transfer Size	Est Savings
/*! tailwindcss v4.3.3 MIT License https://tailwindcss.com */ @layer properties; @layer theme, ...	14.9 KiB	2.9 KiB

Avoid enormous network payloads — Total size was 12,999 KiB ^

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes](#). (Unscored)

URL	Transfer Size
localhost 1st Party	11,751.2 KiB
/assets/hero.mp4 (localhost)	7,680.3 KiB
...deps/lucide-react.js?v=8949bc48 (localhost)	914.0 KiB
...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost)	910.3 KiB
/assets/logo.png (localhost)	719.0 KiB
...deps/react-router-dom.js?v=8949bc48 (localhost)	466.5 KiB
...deps/framer-motion.js?v=8949bc48 (localhost)	459.0 KiB
...data/menuData.js?t=178... (localhost)	181.8 KiB
/@vite/client (localhost)	178.5 KiB
/assets/pub_exterior_or_hero.jpg (localhost)	122.2 KiB
...data/siteData.js (localhost)	119.6 KiB

○ Avoid long main-thread tasks — 5 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT Unscored

URL	Start Time	Duration
localhost 1st Party		444 ms
...deps/framer-motion.js?v=8949bc48 (localhost)	26,958 ms	185 ms
...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost)	29,214 ms	122 ms
http://localhost:3000	7,419 ms	79 ms
http://localhost:3000	827 ms	58 ms
Unattributable		217 ms
Unattributable	610 ms	217 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (15) Hide

Use efficient cache lifetimes ^

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#) FCP LCP Unscored

Layout shift culprits ^

Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. CLS Unscored

Document request latency ^

Your first network request is the most important. [Reduce its latency](#), by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored

- Avoids redirects
- Server responds quickly (observed 3 ms)

Applies text compression

Duplicated JavaScript

Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. FCP
LCP Unscored

Font display

Consider setting [font-display](#) to swap or optional to ensure text is consistently visible. swap can be further optimized to mitigate layout shifts with [font metric overrides](#). Unscored

INP breakdown

Start investigating [how to improve INP](#) by looking at the longest subpart. Unscored

Legacy JavaScript

Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) FCP LCP Unscored

Modern HTTP

HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. [Learn more about using modern HTTP](#). FCP
LCP Unscored

Optimize viewport for mobile

Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimized for mobile. Unscored

meta

Reduce unused CSS

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS](#). FCP LCP Unscored

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks](#). Unscored

JavaScript execution time — 0.3 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time](#). TBT Unscored

URL	Total CPU Time	Script Evaluation	Script Parse
localhost 1st Party	974 ms	301 ms	10 ms
...deps/framer-motion.js?v=8949bc48 (localhost)	487 ms	48 ms	2 ms
http://localhost:3000	309 ms	92 ms	2 ms
...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost)	178 ms	162 ms	6 ms
Unattributable	563 ms	20 ms	0 ms
Unattributable	563 ms	20 ms	0 ms

Minimizes main-thread work — 1.6 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT Unscored

Category	Time Spent
Other	714 ms
Style & Layout	491 ms
Script Evaluation	332 ms
Rendering	46 ms
Script Parsing & Compilation	29 ms
Parse HTML & CSS	10 ms

☐ Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS Unscored

Image elements have explicit [width](#) and [height](#)

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS Unscored



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

NAMES AND LABELS

☒ Buttons do not have an accessible name

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible](#).

Failing Elements

button.bg-black/40.text-white.border.border-white/10.rounded-full.w-8.h-8.flex.items-center.justify-ce...

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

CONTRAST

☒ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast](#).

Failing Elements



span.font-sans.text-[0.54rem].font-bold.tracking-[0.16em].text-maroon.uppercase.mt-[3px]



header.sticky.top-0.z-[1000].bg-navy-header.border-t.border-black.border-b.border-white/10.shadow-...

Failing Elements

span.inline-flex.items-center.gap-1.5.px-[14px].py-[5px].text-[0.76rem].font-bold.tracking-[0.08em].upp...

section.py-[100px].bg-white

div.text-[0.78rem].text-[#888]

div.bg-white.p-8.rounded-[8px].shadow-sm.border.border-[#e5e7eb].flex.flex-col.justify-between

div.text-[0.78rem].text-[#888]

div.bg-white.p-8.rounded-[8px].shadow-sm.border.border-[#e5e7eb].flex.flex-col.justify-between

div.text-[0.78rem].text-[#888]

div.bg-white.p-8.rounded-[8px].shadow-sm.border.border-[#e5e7eb].flex.flex-col.justify-between

These are opportunities to improve the legibility of your content.

NAVIGATION

▲ Heading elements are not in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

Failing Elements

h4.text-[1.25rem].font-serif.text-white.font-bold.tracking-[0.02em].mb-5.pb-3.border-b.border-white/1...

These are opportunities to improve keyboard navigation in your application.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

○ Interactive controls are keyboard focusable

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#) (Unscored)

○ Interactive elements indicate their purpose and state

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#) (Unscored)

○ The page has a logical tab order

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#) (Unscored)

○ Visual order on the page follows DOM order

DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#) (Unscored)

○ User focus is not accidentally trapped in a region

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#) (Unscored)

○ The user's focus is directed to new content added to the page

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new](#)

content (Unscored)	
HTML5 landmark elements are used to improve navigation	^
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more about landmark elements . (Unscored)	
Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. Learn how to properly hide offscreen content . (Unscored)	
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more about custom controls and labels . (Unscored)	
Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. Learn how to add roles to custom controls . (Unscored)	
These items address areas which an automated testing tool cannot cover. Learn more in our guide on conducting an accessibility review .	
PASSED AUDITS (19)	Hide
[aria-*] attributes match their roles	^
Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. Learn how to match ARIA attributes to their roles .	
[aria-hidden="true"] is not present on the document <body>	^
Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. Learn how aria-hidden affects the document body .	
[aria-*] attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more about valid values for ARIA attributes .	
[aria-*] attributes are valid and not misspelled	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more about valid ARIA attributes .	
Image elements have [alt] attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the alt attribute .	
Form elements have associated labels	^
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more about form element labels .	
[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.	^
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more about the viewport meta tag .	
ARIA attributes are used as specified for the element's role	^
Some ARIA attributes are only allowed on an element under certain conditions. Learn more about conditional ARIA attributes .	
[aria-hidden="true"] elements do not contain focusable descendents	^

Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn how aria-hidden affects focusable elements.	
Elements use only permitted ARIA attributes	^
Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. Learn more about prohibited ARIA roles.	
Document has a <title> element	^
The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.	
<html> element has a [lang] attribute	^
If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute.	
<html> element has a valid value for its [lang] attribute	^
Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the lang attribute.	
Links have a discernible name	^
Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn how to make links accessible.	
Lists contain only elements and script supporting elements (<script> and <template>).	^
Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more about proper list structure.	
List items () are contained within , or <menu> parent elements	^
Screen readers require list items () to be contained within a parent , or <menu> to be announced properly. Learn more about proper list structure.	
Touch targets have sufficient size and spacing.	^
Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets.	
Cells in a <table> element that use the [headers] attribute refer to table cells within the same table.	^
Screen readers have features to make navigating tables easier. Ensuring <td> cells using the [headers] attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more about the headers attribute.	
Document has a main landmark.	^
One main landmark helps screen reader users navigate a web page. Learn more about landmarks.	
NOT APPLICABLE (41)	Hide
☐ [accesskey] values are unique	^
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more about access keys. (Unscored)	
☐ button, link, and menuitem elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to make command elements more accessible. (Unscored)	
☐ Deprecated ARIA roles were not used	^

Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#)
(Unscored)

- ☐ Elements with `role="dialog"` or `role="alertdialog"` have accessible names. ^

ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#) (Unscored)

- ☐ ARIA input fields have accessible names ^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#) (Unscored)

- ☐ ARIA `meter` elements have accessible names ^

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#) (Unscored)

- ☐ ARIA `progressbar` elements have accessible names ^

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#) (Unscored)

- ☐ `[role]`s have all required `[aria-*)` attributes ^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#) (Unscored)

- ☐ Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children. ^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#) (Unscored)

- ☐ `[role]`s are contained by their required parent element ^

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#) (Unscored)

- ☐ `[role]` values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#) (Unscored)

- ☐ Elements with the `role=text` attribute do not have focusable descendents. ^

Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the role=text attribute.](#) (Unscored)

- ☐ ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#) (Unscored)

- ☐ ARIA `tooltip` elements have accessible names ^

When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#) (Unscored)

- ☐ ARIA `treeitem` elements have accessible names ^

When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling treeitem elements.](#) (Unscored)

- ☐ The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#) (Unscored)

- ☐ `<d1>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#) (Unscored)

- ☐ Definition list items are wrapped in `<d1>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<d1>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#) (Unscored)

- ☐ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#) (Unscored)

- ☐ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#) (Unscored)

- ☐ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#) (Unscored)

- ☐ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#) (Unscored)

- ☐ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#) (Unscored)

- ☐ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#) (Unscored)

- ☐ Links are distinguishable without relying on color. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#) (Unscored)

- ☐ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#) (Unscored)

- ☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#) (Unscored)

- ☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#) (Unscored)

- ☐ Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#) (Unscored)

- ☐ No element has a `[tabindex]` value greater than 0 ^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating

experiences for users who rely on assistive technologies. [Learn more about the tabindex attribute.](#) (Unscored)

- ☐ <th> elements and elements with [role="columnheader"/"rowheader"] have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#) (Unscored)

- ☐ [lang] attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#) (Unscored)

- ☐ <video> elements contain a <track> element with [kind="captions"] ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#) (Unscored)

- ☐ autocomplete attributes are used correctly ^

The autocomplete attribute values must be valid and correctly applied for screen readers to function correctly. [Learn more about valid autocomplete values.](#) (Unscored)

- ☐ Elements with role="none" or role="presentation" do not have conflicts ^

There are certain cases where the semantic role of an element with role="none" or role="presentation" does not resolve to none or presentation. To ensure the element remains removed from the accessibility tree, you should not add any global ARIA attributes to the element or make it focusable. [Learn more about presentation role conflict.](#) (Unscored)

- ☐ SVG elements with an img role have an accessible text alternative ^

Ensures SVG elements with an img, graphics-document or graphics-symbol role have an accessible text alternative. [Learn more about SVG alt text.](#) (Unscored)

- ☐ Tables have different content in the summary attribute and <caption>. ^

The summary attribute should describe the table structure, while <caption> should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) (Unscored)

- ☐ All heading elements contain content. ^

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#) (Unscored)

- ☐ Uses ARIA roles only on compatible elements ^

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) (Unscored)

- ☐ Image elements do not have [alt] attributes that are redundant text. ^

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#) (Unscored)

- ☐ Identical links have the same purpose. ^

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) (Unscored)



Best Practices

TRUST AND SAFETY

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#) Unscored

Description	Directive	Severity
No CSP found in enforcement mode		High

Use a strong HSTS policy

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy](#) Unscored

Description	Directive	Severity
No HSTS header found		High

Ensure proper origin isolation with COOP

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header](#) Unscored

Description	Directive	Severity
No COOP header found		High

Mitigate clickjacking with XFO or CSP

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking](#) Unscored

Description	Severity
No frame control policy found	High

Mitigate DOM-based XSS with Trusted Types

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types](#) Unscored

Description	Severity
No 'Content-Security-Policy' header with Trusted Types directive found	High

BROWSER COMPATIBILITY

Baseline Features

Lists web features used on the page and their Baseline status as of 2026-07-15. [Learn more about Baseline](#) Unscored

Web-features	Baseline Status	Source
localhost 1st Party		
page-visibility-state	Limited Availability	(index):2
long-animation-frames	Limited Availability	(index):2

Web-features	Baseline Status	Source
layout-instability	Limited Availability	(index):2
beforeunload	Limited Availability	client:856
accent-color	Limited Availability	client:1102
requestidlecallback	Limited Availability	(index):2
backdrop-filter	Newly Available (2024-09-16)	client:1102
relative-color	Newly Available (2024-09-16)	client:1102
registered-custom-properties	Newly Available (2024-07-09)	client:1102
gradient-interpolation	Newly Available (2024-06-11)	framer-motion.js?v=8949bc48:7161
nesting	Widely Available (2023-12-11)	client:1102
contain-intrinsic-size	Widely Available (2023-09-18)	client:1102
calc-constants	Widely Available (2023-06-06)	client:1102
color-mix	Widely Available (2023-05-09)	client:1102
oklab	Widely Available (2023-05-09)	framer-motion.js?v=8949bc48:7161
media-query-range-syntax	Widely Available (2023-03-27)	client:1102
individual-transforms	Widely Available (2022-08-05)	client:1102
cascade-layers	Widely Available (2022-03-14)	client:1102
appearance	Widely Available (2022-03-14)	client:1102
logical-properties	Widely Available (2021-09-20)	client:1102
aspect-ratio	Widely Available (2021-09-20)	client:1102
file-selector-button	Widely Available (2021-04-26)	client:1102
weak-references	Widely Available (2021-04-26)	(index):2
where	Widely Available (2021-01-21)	client:1102
is	Widely Available (2021-01-21)	client:1102
not	Widely Available (2021-01-21)	client:1102
clip-path	Widely Available (2021-01-21)	client:1102
nullish-coalescing	Widely Available (2020-09-16)	(index):1
webp	Widely Available (2020-09-16)	(index):-1
web-animations	Widely Available (2020-09-16)	framer-motion.js?v=8949bc48:2024
aborting	Widely Available (2019-03-25)	(index):2
js-modules	Widely Available (2018-05-09)	(index):-1
grid	Widely Available (2017-10-17)	framer-motion.js?v=8949bc48:7161
flexbox	Widely Available (2015-09-30)	framer-motion.js?v=8949bc48:7161
text-indent	Widely Available (2015-07-29)	client:1102

Web-features	Baseline Status	Source
request-animation-frame	Widely Available (2015-07-29)	<code>framer-motion.js?v=8949bc48:418</code>

PASSED AUDITS (13)

Hide

Uses HTTPS	^
All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more about HTTPS.	
Avoids deprecated APIs	^
Deprecated APIs will eventually be removed from the browser. Learn more about deprecated APIs.	
Avoids third-party cookies	^
Third-party cookies may be blocked in some contexts. Learn more about preparing for third-party cookie restrictions.	
Allows users to paste into input fields	^
Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. Learn more about user-friendly input fields.	
Avoids requesting the geolocation permission on page load	^
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission. Also consider using the <code><geolocation></code> element.	
Avoids requesting the notification permission on page load	^
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications.	
Displays images with correct aspect ratio	^
Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio.	
Serves images with appropriate resolution	^
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images.	
Page has the HTML doctype	^
Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration.	
Properly defines charset	^
A character encoding declaration is required. It can be done with a <code><meta></code> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more about declaring the character encoding.	
No browser errors logged to the console	^
Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more about this errors in console diagnostic audit	
No issues in the Issues panel in Chrome Devtools	^
Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.	

Page has valid source maps



Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps](#). Unscored

URL	Map URL
localhost 1st Party	
...pages/WhatsOnPage.jsx?t=178... (localhost)	
...pages/ReservationsPage.jsx?t=178... (localhost)	
...pages/PartyVenuePage.jsx?t=178... (localhost)	
...pages/OffersPage.jsx?t=178... (localhost)	
...pages/MenuPage.jsx?t=178... (localhost)	
...pages/HomePage.jsx?t=178... (localhost)	
...pages/ContactPage.jsx?t=178... (localhost)	
...pages/ChristmasPage.jsx?t=178... (localhost)	
/src/main.jsx?t=178... (localhost)	
...data/siteData.js (localhost)	
...data/menuData.js?t=178... (localhost)	
...components/TopBar.jsx?t=178... (localhost)	
...components/PageTransition.jsx (localhost)	
...components/Navbar.jsx?t=178... (localhost)	
...components/Footer.jsx?t=178... (localhost)	
...components/BookingModal.jsx?t=178... (localhost)	
/src/App.jsx?t=178... (localhost)	
...client/env.mjs (localhost)	
...deps/react.js?v=8949bc48 (localhost)	
...deps/react-router-dom.js?v=8949bc48 (localhost)	...deps/react-router-dom.js.map (localhost)
...deps/react-dom_client.js?v=8949bc48 (localhost)	...deps/react-dom_client.js.map (localhost)
...deps/react_jsx-dev-runtime.js?v=8949bc48 (localhost)	...deps/react_jsx-dev-runtime.js.map (localhost)
...deps/lucide-react.js?v=8949bc48 (localhost)	...deps/lucide-react.js.map (localhost)
...deps/framer-motion.js?v=8949bc48 (localhost)	...deps/framer-motion.js.map (localhost)
...deps/chunk-SVG7M4VJ.js?v=8949bc48 (localhost)	...deps/chunk-SVG7M4VJ.js.map (localhost)
...deps/chunk-RLMGAKMB.js?v=8949bc48 (localhost)	...deps/chunk-RLMGAKMB.js.map (localhost)
...deps/chunk-2YIMICFJ.js?v=8949bc48 (localhost)	...deps/chunk-2YIMICFJ.js.map (localhost)
/@vite/client (localhost)	
/@react-refresh (localhost)	

NOT APPLICABLE (2)	Hide
Redirects HTTP traffic to HTTPS	^
Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. Learn more. (Unscored)	
Detected JavaScript libraries	^
All front-end JavaScript libraries detected on the page. Learn more about this JavaScript library detection diagnostic audit. (Unscored)	



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials](#).

CRAWLING AND INDEXING

robots.txt is not valid — 23 errors found			^
If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more about robots.txt .			
Line #	Content	Error	
1	<!DOCTYPE html>	Syntax not understood	
2	<html lang="en">	Syntax not understood	
3	<head>	Syntax not understood	
4	<script type="module">import { injectIntoGlobalHook } from "@react-refresh";	Syntax not understood	
5	injectIntoGlobalHook(window);	Syntax not understood	
6	window.\$RefreshReg\$ = () => {};	Syntax not understood	
7	window.\$RefreshSig\$ = () => (type) => type;</script>	Syntax not understood	
9	<script type="module" src="@vite/client"></script>	Syntax not understood	
11	<meta charset="UTF-8" />	Syntax not understood	
12	<link rel="icon" type="image/png" href="/assets/logo.png" />	Syntax not understood	
13	<meta name="viewport" content="width=device-width, initial-scale=1.0" />	Syntax not understood	
14	<title>The White Lion Amersham - Pubs, Restaurant & Indian Cuisine, Little Chalfont</title>	Syntax not understood	
15	<meta name="description" content="The White Lion Amersham, your friendly local pub! Enjoy a mix of traditional pub classics and authentic Indian Cuisine, live	Syntax not understood	

Line #	Content	Error
	sports, and a lively quiz night every Thursday, family friendly, dog-friendly, large free car park, Perfect for Sunday roast and Private Hire" />	
17	<!-- Google Fonts: Noticia Text (official brand title font), Cormorant Garamond, Barlow, Poppins -->	Unknown directive
18	<link rel="preconnect" href="https://fonts.googleapis.com">	Unknown directive
19	<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>	Unknown directive
20	<link href="https://fonts.googleapis.com/css?family=Barlow:wght@400;500;600;700&family=Cormorant+Garamond:ital,wght@0,400;0,600;0,700;1,400&family=Noticia+Text:ital,wght@0,400;0,700;1,400&family=Poppins:wght@300;400;500;600;700&display=swap" rel="stylesheet">	Unknown directive
21	</head>	Syntax not understood
22	<body>	Syntax not understood
23	<div id="root"></div>	Syntax not understood
24	<script type="module" src="/src/main.jsx?t=1788628834873"></script>	Syntax not understood
25	</body>	Syntax not understood
26	</html>	Syntax not understood

To appear in search results, crawlers need access to your app.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

Structured data is valid

Run the [Structured Data Testing Tool](#) to validate structured data. [Learn more about Structured Data](#) Unscored

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (8)

Hide

Page isn't blocked from indexing

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives](#).

Document has a <title> element

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles](#).

Document has a meta description

Meta descriptions may be included in search results to concisely summarize page content. [Learn more about the meta description](#).

Page has successful HTTP status code

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes](#).

Links have descriptive text	^
Descriptive link text helps search engines understand your content. Learn how to make links more accessible.	
Links are crawlable	^
Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn how to make links crawlable	
Image elements have <code>[alt]</code> attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the alt attribute.	
Document has a valid <code>hreflang</code>	^
hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more about hreflang.	
NOT APPLICABLE (1)	Hide
☐ Document has a valid <code>rel=canonical</code>	^
Canonical links suggest which URL to show in search results. Learn more about canonical links. Unscored	

▲ 1/3

Agentic Browsing

These checks ensure high-quality, [browsable websites for AI agents](#) and validate the correctness of WebMCP integrations. This category is still under development and subject to change.

AGENT ACCESSIBILITY

▲ Accessibility tree is not well-formed	^
A well-formed accessibility tree helps AI agents to navigate and interact with the page.	
<u>Failed Audits</u>	
Description	Failing Element
Buttons must have discernible text	button.bg-black/40.text-white.border.border-white/10.rounded-full.w-8.h-8...
▲ llms.txt does not follow recommendations	^
If your llms.txt file does not follow recommendations, large language models may not be able to understand how you want your website to be crawled or used for training. The llms.txt file should be a Markdown file containing at least one H1 header. Learn more about the llms.txt audit.	
Error	
File is missing a required H1 header (e.g., "# Title").	
File does not appear to contain any links.	

These audits highlight best practices for improving the accessibility of the website for AI agents.

PASSED AUDITS (1)

Hide

Cumulative Layout Shift — 0

^

Cumulative Layout Shift measures the movement of visible elements within the viewport. [Learn more about the Cumulative Layout Shift metric.](#)

NOT APPLICABLE (3)

Hide

WebMCP form coverage

^

Consider adding [WebMCP](#) annotations to the forms listed below. This helps AI agents identify and interact with these forms more reliably. (Unscored)

WebMCP tools registered

^

Lists the [WebMCP tools](#) registered at the time of analysis. (Unscored)

WebMCP schemas are valid

^

Valid [WebMCP schemas](#) are required for AI agents to understand and interact with tools correctly. Please fix any errors or warnings reported by the browser. (Unscored)

Captured at Sep 5, 2026, 10:51 PM GMT+5:30

Initial page load

Emulated Moto G Power with Lighthouse 13.4.1

Slow 4G throttling

Single page session

Using Chromium 152.0.0.0 with devtools

Generated by **Lighthouse** 13.4.1 | [File an issue](#)

about:blank

23/23