

# Computer Systems, B1-2 2022-23

## Introduction

Troels Henriksen, Michael Kirkedal Thomsen

DIKU, September 5, 2022

## Course structure

### Representing information as bits

- Everything is bits

- Bit-level manipulation

- Integers

# Overall outline

Week 36-37 Data representation and machine model

Week 38 C programming

Week 39-40 Memory and operating systems

Week 41 Concurrent and parallel programming

Week 42 Fall break

Week 43-45 Computer networks - application and transport layer

Week 46 No activities (reexam week)

Week 47 Computer networks - security and efficiency

Week 48-51 Machine architecture

Week 52 Christmas vacation

Week 1-2 Computer networks and security - network and link layer

Week 4 4-hour written exam

# Lectures

- Mondays 13:15-15:00
- Wednesdays 10:15-12:00


# Lecturers



Michael Kirkedal Thomsen: Course root, Networks and Security



Finn Schirmer Andersen: Computer Architecture



Troels Henriksen: C programming, Operating Systems



David Gray Marchant: Network programming

# Teaching Material

**COD** Computer Organization and Design (RISC-V Edition), David A. Patterson and John L. Hennessy, second edition, ISBN: 978-0-12-820331-6

**KR** Computer Networking: A Top-Down Approach, James F. Kurose and Keith W. Ross, Pearson, 8th and Global Edition, ISBN 13: 978-1-292-40546-0 (This book will not be used before December)–7th edition is also acceptable

**JG** Modern C, Jens Gustedt,  
<https://hal.inria.fr/hal-02383654/document>

**OSTEP** Operating Systems: Three Easy Pieces, Remzi H. Arpaci-Dusseau and Andrea C. Arpaci-Dusseau,  
<https://pages.cs.wisc.edu/~remzi/OSTEP/>

**??** Some notes and book chapters that will be made available through the detailed course schedule

COD is (and KR will be) available at Academic Books at Panum (<http://www.academicbooks.dk/>) and Polyteknisk Boghandel at Biocenteret (<http://www.polyteknisk.dk/>).

TAs:

- Asbjørn Munk
- Christian Arboe Franck
- Iben Lilholm
- Johan Topp
- Julian Pedersen
- Jóhann Utne
- Kjartan Johannesen

TAs will gladly help with

- Group members
- The right way to the administration
- A fellow student that can answer questions (or help find the answers)

# Exercises and Assignment Cafés

## Exercises

- Mondays 15:15-17:00
- Wednesdays 13:15-15:00

Exercises are only for posted exercises. Work on the exercises as they will prepare you both for the exam and assignments.

## Cafés

- Wednesdays 15:15-17:00
- Fridays 13:15-15:00

Cafés are primarily for help with assignments.

Details: <https://github.com/diku-compSys/compSys-e2022-pub>.  
Also on Discord. See Absalon/Modules.



## Size

2-3 student advised. 1 can be accepted but not recommended. More than 3 is only allowed is on special circumstances

- Sign up for classes with your group-mates on Absalon
- If you need one or more members
  - ▶ Look on announcements for details
  - ▶ Course ambassadors will facilitate

# Assignments

- There are 7 assignment in total during the course with deadline roughly every week or second week (all Sundays). The assignments will be evaluated with points.
- Assignments will be awarded zero to 4 points.
- You are required to achieve at least 50 % of the total number of points (equal to 12).
- Also we will require that you achieve points in each the of topics of the course to ensure that you have touched all parts of the curriculum.
- Assignments are made to be solved in groups of 2-3 students, but you can also do them alone.

# Assignment rules

## The Fundamental Principle of Group Assignments

Each group must make their own solution.

This means

- You can talk with other people about the assignments: Teachers, TAs, other students, etc.
- You cannot share written code with other groups.
- You are not allowed to use code that you did not write yourself without proper citation.
- You cannot share written text with other groups.
- You are not allowed to use text of material without proper citation
  - ▶ This also includes material provided on the course.

# Assignments vs. exercises

- Note! Both are equally important
- Assignments:
  - ▶ Seek to test learning goals that relates to implementation and development of computer systems.
  - ▶ Do not fully prepare you for the written exam.
- Exercises:
  - ▶ Help you understand the theoretical parts of the material.
  - ▶ Prepare you for part of the exam.

# Tools

- C compiler – gcc (clang on macOS)
- C debugger – gdb (lldb on macOS)
- You can also install all tools on you laptop
  - ▶ Linux: most available though apt
  - ▶ macOS: most available though Homebrew
  - ▶ Windows: Windows Subsystem for Linux
- Set up your tool chain
  - ▶ recommended using git to share code and reports in your group
  - ▶ Sign-up at GitHub today and apply for the *Student Developer Pack*
  - ▶ <https://education.github.com/>
- Tool-site is available on GitHub

- Said to be: a 4-hour written exam; Jan 2022.
- Exact format is not fixed; It will *maybe* be ITX.
- The course syllabus is the exercises, assignments and reading material.
- Previous exams will available.

Questions?

## Course structure

### Representing information as bits

- Everything is bits

- Bit-level manipulation

- Integers



# Everything is bits


- Each bit is 0 or 1.
- By interpreting sets of bits in various ways...
  - ▶ ...computers determine what to do.
  - ▶ ...represent and manipulate numbers, sets, strings—*data*.

**Why bits? Why not decimals? Could it have been some other way?**

# Everything is bits

- **Why bits? Electronic implementation.**

- ▶ Easy to store with bistable elements.
- ▶ Reliably transmitted on noisy and inaccurate wires (error correction).



- **... But there exist models that do not use bits.**

- ▶ The Soviet Setun computer used ternary *trits*.
- ▶ Quantum computers use *qubits* that are in a superposition of the two states.
  - ▶ ...error correction is the main challenge here.

# Binary numbers

- **Base 2 number representation.**

- ▶ Represent  $15213_{10}$  as  $11101101101101_2$
- ▶ Represent  $1.20_{10}$  as  $1.0011001100110011[0011] \dots_2$
- ▶ Represent  $1.5213 \times 10^4$  as  $1.1101101101101_2 \times 2^{13}$

- **Machine numbers are of some finite size.**

- ▶ If we use  $k$  bits to represent a number, only  $2^k$  distinct values are possible.
- ▶ How we interpret those bits can vary.
- ▶ **Why do we use finite-sized numbers?**

# Binary numbers

- **Base 2 number representation.**

- ▶ Represent  $15213_{10}$  as  $11101101101101_2$
- ▶ Represent  $1.20_{10}$  as  $1.0011001100110011[0011] \dots_2$
- ▶ Represent  $1.5213 \times 10^4$  as  $1.1101101101101_2 \times 2^{13}$

- **Machine numbers are of some finite size.**

- ▶ If we use  $k$  bits to represent a number, only  $2^k$  distinct values are possible.
- ▶ How we interpret those bits can vary.
- ▶ **Why do we use finite-sized numbers?**
- ▶ A “ $k$ -bit machine” handles numbers of up to  $k$  bits “natively” (meaning fast).

# Encoding byte values

## Byte = 8 bits

- (Machine-specific, but is true for all mainstream machines.)
- 256 different values.
- Binary  $00000000_2$  to  $11111111_2$ .
- Decimal  $0_{10}$  to  $255_{10}$ .
- Hexadecimal  $00_{16}$  to  $FF_{16}$ .
  - ▶ Base 16 number representation.
  - ▶ Uses characters 0–9 and A–F.
  - ▶ In C we write  $FA1D37B_{16}$  as
    - ▶  $0xFA1D37B$
    - ▶  $0xfa1d37b$  (case does not matter)

Hex	Dec	Bin
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

## Example sizes of C types on various computers

C data type	Typical 16-bit	Typical 32-bit	Typical 64-bit	x86-64
char	1	1	1	1
short	1	2	2	2
int	2	4	4	4
long	4	4	8	8
int32_t	4	4	4	4
int64_t	8	8	8	8
float	4	4	4	4
double	8	8	8	8
long double	-	-	-	10
pointer	2	4	8	8

## Course structure

### Representing information as bits

Everything is bits

Bit-level manipulation

Integers

# Boolean algebra

## Developed by George Boole in 19th century

- Algebraic representation of logic (“truth values”).
- Encode *true* as 1 and *false* as 0.

### And

&	0	1
0	0	0
1	0	1

### Or

	0	1
0	0	1
1	1	1

### Not

~	
0	1
1	0

### Exclusive-or

^	0	1
0	0	1
1	1	0

- These operations can be implemented with tiny electronic *gates*.



# General boolean algebras

- The truth tables generalise to operate on *bit vectors*, applied elementwise.

01101001	01101001	01101001	
& 01010101	01010101	^ 01010101	~ 01101001
<hr/>	<hr/>	<hr/>	<hr/>
01000001	01111101	00111100	10010110

- This is the form they take in programming languages such as C.

# Bit-level operations in most C-like languages

## Operations `&`, `|`, `~`, `^` available in C.

- Apply to any integral type.
  - ▶ E.g. `long`, `int`, `short`, `char`...
- Interpret operands as bit vectors.
- Applied bit-wise.

## Examples

- $\sim 0x41 = 0xBE$ 
  - ▶  $\sim 01000001_2 = 10111110_2$
- $\sim 0x00 = 0xFF$ 
  - ▶  $\sim 00000000_2 = 11111111_2$
- $0x69 \ \& \ 0x55 = 0x41$ 
  - ▶  $01101001_2 \ \& \ 01010101_2 = 01000001_2$
- $0x69 \ \& \ 0x55 = 0x7D$ 
  - ▶  $01101001_2 \ \& \ 01010101_2 = 01111101_2$

# Shift operations

## ■ Left shift $x \ll y$

- ▶ Shift bit-vector  $x$  left by  $y$  positions.
  - ▶ Throws away excess bits on the left.
  - ▶ Fills with zeroes on right.

## ■ Right shift $x \gg y$

- ▶ Shift bit-vector  $x$  right by  $y$  positions.
  - ▶ Throws away excess bits on the left.
- ▶ Logical shift: Fill with 0s on left.
- ▶ Arithmetic shift: Replicate most significant bit on left.

## ■ Undefined behaviour

- ▶ Shifting a negative amount or by the vector size or more.

$x$		01100010
<hr/>		
$x \ll 3$		00010000
$x \gg 2$	(log)	00011000
$x \gg 2$	(arith)	00011000

$x$		10100010
<hr/>		
$x \ll 3$		00010000
$x \gg 2$	(log)	00101000
$x \gg 2$	(arith)	11101000

## Course structure

### Representing information as bits

Everything is bits

Bit-level manipulation

**Integers**

# Encoding integers

Suppose  $x_i$  is the  $i$ th bit of a  $w$ -bit word (with  $x_0$  being the least significant bit).

## Unsigned

$$B2U(X) = \sum_{i=0}^{w-1} x_i \cdot 2^i$$

## Two's complement

$$B2S(X) = -x_{w-1} \cdot 2^{w-1} + \sum_{i=0}^{w-2} x_i \cdot 2^i$$

```
int16_t x = 15213;  
int16_t y = -15213;
```

	Decimal	Hex	Binary
x	15213	3 B 5 D	0011 1011 0110 1101
y	-15213	C 4 9 3	1100 0100 1001 0011

## Sign bit

- For 2's complement, most significant bit ( $x_{w-1}$ ) indicates sign.
  - ▶ 0 for non-negative.
  - ▶ 1 for negative.

## Two's complement encoding example

```
int16_t x = 15213; // 0011 1011 0110 1101  
int16_t y = -15213; // 1100 0100 1001 0011
```

Weight	15213		-15213	
1	1	1	1	1
2	0	0	1	2
4	1	4	0	0
8	1	8	0	0
16	0	0	1	16
32	1	32	0	0
64	1	64	0	0
128	0	0	1	128
256	1	256	0	0
512	1	512	0	0
1024	0	0	1	1024
2048	1	2047	0	0
4096	1	4096	0	0
8192	1	8192	0	0
16384	0	0	1	16384
-32768	0	0	1	-32768
Sum	15213		-15213	

## Let's play a game

`http://topps.diku.dk/compsys/integers.html`

# Numeric ranges, here for 16-bit signed and unsigned integers

## Unsigned

$$\text{UMin} = 0 = 0 \dots 0_2$$

$$\text{UMax} = 2^w - 1 = 1 \dots 1_2$$

## Two's complement signed

$$\text{SMin} = -2^{w-1} = 10 \dots 0_2$$

$$\begin{aligned} \text{SMax} &= 2^{w-1} - 1 = 01 \dots 1_2 \\ &= -1 \qquad \qquad \qquad = 1 \dots 1_2 \end{aligned}$$

Values for  $w = 16$ :

	Decimal	Hex	Binary
<b>UMax</b>	65535	F F F F	1111 1111 1111 1111
<b>SMax</b>	32767	7 F F F	0111 1111 1111 1111
<b>SMin</b>	-32768	8 0 0 0	1000 0000 0000 0000
-1	-1	F F F F	1111 1111 1111 1111
0	0	0 0 0 0	0000 0000 0000 0000



## Values for different word sizes

	W			
	8	16	32	64
UMax	255	65,535	4,294,967,295	18,446,744,073,709,551,615
SMax	127	32,767	2,147,483,647	9,223,372,036,854,775,807
SMin	-128	-32,768	-2,147,483,648	-9,223,372,036,854,775,808

### Observations

$$|SMin| = SMax + 1$$

$$|UMax| = 2 \cdot SMax + 1$$

**Note the assymetric range.**

### C Programming

- `#include <limits.h>`
- Declares constants, e.g:
  - ▶ `ULONG_MAX`
  - ▶ `LONG_MAX`
  - ▶ `LONG_MIN`
- Values are platform-specific.

## Unsigned and signed numeric values (here $w = 4$ )

$x$	$B2U(x)$	$B2S(x)$
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	8	-8
1001	9	-7
1010	10	-6
1011	11	-5
1100	12	-4
1101	13	-3
1110	14	-2
1111	15	-1

- **Equivalence**

- ▶ Same encoding for non-negative values.

- **Uniqueness**

- ▶ Every bit pattern represents distinct integer value.
- ▶ Each representable integer has unique bit encoding.
- ▶ The representation is **bijective**.

- **Can invert mappings**

- ▶  $U2B(x) = B2U^{-1}(x)$ 
  - ▶ Bit pattern for unsigned integer.
- ▶  $S2B(x) = B2S^{-1}(x)$ 
  - ▶ Bit pattern for two's complement integer.

# Main takeaways

- Distinguish between **representation** and **interpretation**.
- Low-level values **do not describe their own structure**.
- Everything is built in layers.
- A good computer scientist adds new, clean, layers of abstraction.
  - ▶ A bad one adds layers that hide without simplifying.
  - ▶ A terrible one adds layers that complicate and obfuscate.
- **The point of this course is to show that there is no magic, only the work of careful people who put in a lot of effort.**