run_config.yaml

TEM_UW_APP run configuration, key reference

Lehigh TEM Felzer Lab

November 2026

Contents

1 Overview **1**

0. Job environment **2**

1. Job submission **2**

2. Case metadata **3**

3. Grid and time **3**

4. NetCDF inputs and varmap **3**

5. Model options **4**

6. Parameter files **5**

7. Output and model state **5**

1 Overview

`config/run_config.yaml` is the run configuration of TEM_UW_APP. A case-local `run_config.yaml` sets only the keys it changes; unknown keys are an error. The sections below are the file itself. Keys of the section Model options are written to `tem_config.yaml` of TEM_2026, whose template describes them in more detail.

0. Job environment

```yaml
tem_src: null # TEM_2026 checkout: templates/tem_config.yaml, params/ and the build (REQUIRED)
# Executable built with make (build/xtem_competition for cohort competition); for n_cpus > 1
# use the MPI build, {tem_src}/build_mpi/xtem
tem_exe: "{tem_src}/build/xtem"
modules: [] # Modules loaded before the run (the libraries the executable was built with)
```

1. Job submission

```yaml
# Parameters forwarded to sbatch by launchers/case_submit.py, as in pyUFS:
#
#   key              sbatch flag
#   constraint_node  --constraint=<value>   (omitted when null)
#   exclusive_node   --exclusive            (omitted when false)
#   walltime         --time=<walltime>:00:00
#   n_nodes          --nodes
#   n_cpus           --ntasks and --ntasks-per-node
#   n_cpus_per_task  --cpus-per-task
#   partition        --partition            (omitted when null)
#   mem              --mem=<mem>g on one node, --mem-per-cpu=<mem // tasks>g on several
#   sbatch_options   appended to the sbatch call unchanged
#
# Tasks per node are n_cpus // n_nodes and the task count submitted is (n_cpus // n_nodes) *
# n_nodes. The model runs on that many MPI tasks; the cells are shared between them.

run_mode: local # local: build and run in the foreground | slurm: submit with sbatch
run_model: true # false: only build the case (INPUT/ and tem_config.yaml)
# Node constraint passed as --constraint=<value>, for example a CPU architecture or feature
# tag defined by the host
constraint_node: null
exclusive_node: false # true requests exclusive node access (--exclusive)
walltime: 1 # Walltime in whole hours, submitted as <walltime>:00:00
n_nodes: 1 # Number of nodes to request
n_cpus: 1 # Total number of tasks to request, rounded down to a multiple of n_nodes
partition: null # Partition to submit the job to
n_cpus_per_task: 1 # CPUs per task
# Total job memory [GB]. Used only when above 2 GB per task (mem > 2 * tasks); otherwise, and
# for 0, the scheduler default applies.
mem: 0
# Additional raw options passed directly to sbatch, for example "--account=myproj --mail-
# type=END"
sbatch_options: ""
logfile: tem_driver # Basename of the driver log written in the case directory (<logfile>.log)
```

2. Case metadata

```yaml
case_name: null # Case identifier and SLURM job name; null falls back to the directory name
region: TEM # Label written to the output files
```

3. Grid and time

```yaml
horizontal_resolution: 0.5 # degrees
lon_min: null # REQUIRED
lon_max: null # REQUIRED
lat_min: null # REQUIRED
lat_max: null # REQUIRED
# box_mean (area average, when the source is finer) | bilinear | nearest. Categorical fields
# always use nearest.
regrid_method: box_mean
start_year: null # First year of the transient run (REQUIRED); the model runs monthly
end_year: null # Last year of the transient run (REQUIRED)
```

4. NetCDF inputs and varmap

```yaml
# Each key is a path, a glob or a list of them (null: not used). The files are regridded to
# the grid above and written to INPUT/ as climate.nc, static.nc, lulc.nc, co2.nc, lightning.nc
# and population.nc. Floats are written as float32 and categorical fields as int64.

# Climate (REQUIRED), merged by coordinates; units come from the "units" attribute
netcdf_climate_in_file: null
# hourly | daily | monthly, the time step of netcdf_climate_in_file
netcdf_climate_in_frequency: monthly
# elev, sand, silt, clay, ndep (lat, lon); wind, ozone (month, lat, lon)
netcdf_static_in_file: null
netcdf_lulc_in_file: null # Land cover, (cohort, lat, lon); the fields of TEM_2026 docs/data.md
netcdf_co2_in_file: null # co2 (time), annual
# lightning_flashes, km-2 month-1 (12 months, lat, lon); needed when veg_fire is 1
netcdf_fire_in_file: null
netcdf_population_in_file: null # population_density, km-2 (lat, lon); needed when veg_fire is 1
surface_pressure_hpa: 1013.25 # Used for vpr from huss when ps is not in varmap

# varmap (flat): <model variable>: <variable in your files>. The model variable is used as it
# is when a file has a variable of that name; list the others here. Keys:
# climate (REQUIRED, derived to TEM units):  tair or tmin + tmax;  dtr or tmin + tmax;  prec;
# nirr;
#       vpr or dewpoint or huss (+ ps)
#   optional from the climate files:  wind or u10 + v10;  elev
#   passed to the model for the other files:  texture (sand+silt+clay), lulc, co2, ozone,
#       ndep, wind, elev, lightning, popdens, nfertcrop, nfertpasture, mask
varmap: {}
```

5. Model options

```
# Initialization and equilibrium
# 0: equilibrate to long-term average climate | 1: then numspin spins | 2: dynamic equilibrium
spinflag: 0
numspin: 3 # Spins when spinflag is 1
spintime: 40 # Years per spin
de_nyears: 30 # Years of climate used in dynamic equilibration
equil_min_years: 500 # Years before the first equilibrium check
equil_max_years: 3000 # Upper limit of years to reach equilibrium
equil_max_attempts: 1 # Restarts of the equilibration of a cell
equil_tau_years: 500.0 # Averaging time of the equilibrium test
equil_rh: 1 # 1: decomposition must reach equilibrium
wtol: 1.0 # Tolerance of the water cycle
ctol: 100.0 # Tolerance of the carbon cycle
ntol: 20.0 # Tolerance of the nitrogen cycle

# Processes
avlnflag: 1 # Available N may vary
nfeed: 1 # N feedback on GPP
baseline: 0 # Solve for baseline soil N
moistlim: 1 # Moisture limitation of GPP
o3flag: 1 # Ozone damage to GPP
ode_solver: 1 # 1 Bogacki-Shampine | 2 Runge-Kutta-Fehlberg
rsoil_method: 2 # 1 Q10 | 2 SiB
rhmoist_method: 1 # 1 WFPS | 2 DNDC | 3 sech
wood_pools: 0 # 0: standing dead only | 1: GDSTEM-FIRE standing dead, CWD and FWD pools
dc2n: 0.0 # Relative change of C:N per change in CO2
inittol: 0.01 # Proportional tolerance of the integrator
maxit: 20 # Iterations of the integrator per month
maxitmon: 200 # Times maxit can be reached in a month

# Atmosphere, fire and fertilizer
initco2: 286.596 # ppmv at the start
xco2level: 286.596 # ppmv of the equilibrium
xtco2flag: 1 # 1: transient CO2 from netcdf_co2_in_file | 0: static
xto3flag: 0 # 1: transient ozone | 0: long-term average
xtndepflag: 0 # 1: transient N deposition | 0: long-term average
xtws10flag: 0 # 1: transient wind | 0: long-term average
# 0: built-in fertilizer series | 1: annual input without time | 2: transient input
xnfertflag: 0
# 1: wildfire; needs netcdf_fire_in_file, netcdf_population_in_file and monthly steps
veg_fire: 0
fire_mode: 0 # 0: random draw | 1: expected burn
fire_topography: 0 # 1: fire 250 times less likely above 2500 m
fire_seed: 0 # Fixes the random sequence (0: not fixed)
fire_prescribed_end: 2014 # Last year in which the vegetation return interval applies
tlulcflag: 0 # 1: transient land use

# Agriculture
agtillflag: 0 # Tilling
agirrgflag: 0 # Irrigation
agfertflag: 0 # Fertilizer
```

6. Parameter files

```
# One set of params/ per run: biogeography, gdstem, gdstem_fire or glstem.

cmntecd: "{tem_src}/params/biogeography/tcomm50_lulc.yaml" # Vegetation mosaics
rootzecd: "{tem_src}/params/biogeography/trotz50_lulc.yaml" # Rooting depth
vegecd: "{tem_src}/params/biogeography/tveg50_lulc.yaml" # Vegetation
conductecd: "{tem_src}/params/biogeography/tconduct50_lulc.yaml" # Hydraulic conductance
mcrbecd: "{tem_src}/params/biogeography/tmcrv50_lulc.yaml" # Microbial
agecd: "{tem_src}/params/biogeography/ag50_lulc.yaml" # Agriculture
# Site files, comma separated
datfilenames:
 ↪  "{tem_src}/params/biogeography/hvc50_openn_dndc.yaml,{tem_src}/params/biogeography/hvd50_openn_dndc.yaml"
```

7. Output and model state

```
clmoutvars: [tair] # Climate variables written (lowercase model names)
temoutvars: [gpp, npp, nep, vegc, soilorgc] # TEM variables written
spinoutflag: 0 # 1: also write the spin-up years
spinoutyrs: 0 # Number of spin-up years written
# 0: initialize | 1: read the state at equilibrium | 2: read the state of istateyear
istateflag: 0
istatefile: ./OUTPUT/temstate.nc # State file read
istateyear: missing # Year of the state read when istateflag is 2
ostateflag: 0 # 0: no state written | 1: at equilibrium | 2: at ostateyear
ostatefile: ./OUTPUT/temstate.nc # State file written (ranks are merged into it)
ostateyear: missing # Year of the state written when ostateflag is 2
```