

NAME: Lejo C

ROLL NO: 241801136

BASIC C PROGRAMMING

PROGRAM 1:

Question 1 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Given two numbers, write a C program to swap the given numbers.

For example:

Input	Result
10 20	20 10

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d",&a,&b);
6     c=a;
7     a=b;
8     b=c;
9     printf("%d %d",a,b);
10 }
```

	Input	Expected	Got	
✓	10 20	20 10	20 10	✓

Passed all tests! ✓

PROGRAM 2:

Question 2 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Write a C program to find the eligibility of admission for a professional course based on the following criteria:

Marks in Maths ≥ 65

Marks in Physics ≥ 55

Marks in Chemistry ≥ 50

Or

Total in all three subjects ≥ 180

Sample Test Cases

Test Case 1

Input

70 60 80

Output

The candidate is eligible

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,t;
5     scanf("%d %d %d",&a,&b,&c);
6     t=a+b+c;
7     if((a>=65&&b>=55&&c>=50)|| (t>=180))
8     {
9         printf("The candidate is eligible");
10    }
11    else
12    {
13        printf("The candidate is not eligible");
14    }
15 }
```

	Input	Expected	Got	
✓	70 60 80	The candidate is eligible	The candidate is eligible	✓
✓	50 80 80	The candidate is eligible	The candidate is eligible	✓

Passed all tests! ✓

PROGRAM 3:

Question 3 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Malini goes to BestSave hyper market to buy grocery items. BestSave hyper market provides 10% discount on the bill amount B when ever the bill amount B is more than Rs.2000.

The bill amount B is passed as the input to the program. The program must print the final amount A payable by Malini.

Input Format:

The first line denotes the value of B.

Output Format:

The first line contains the value of the final payable amount A.

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int a,r;
5      scanf("%d",&a);
6      if(a<=2000)
7      {
8          r=a;
9      }
10     if(a>2000)
11     {
12         r=a-(a*0.1);
13     }
14     printf("%d",r);
15 }
```

	Input	Expected	Got	
✓	1900	1900	1900	✓
✓	3000	2700	2700	✓

Passed all tests! ✓

Correct

PROGRAM 4:

Question 4 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Baba is very kind to beggars and every day Baba donates half of the amount he has when ever a beggar requests him. The money M left in Baba's hand is passed as the input and the number of beggars B who received the alms are passed as the input. The program must print the money Baba had in the beginning of the day.

Input Format:

The first line denotes the value of M .

The second line denotes the value of B .

Output Format:

The first line denotes the value of money with Baba in the beginning of the day.

PROGRAM 5:

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int b,p,r;
5     scanf("%d %d",&b,&p);
6     r=b*(2*p);
7     printf("%d",r);
8 }
```

	Input	Expected	Got	
✓	100	400	400	✓
	2			

Passed all tests! ✓

Question 5 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

The CEO of company ABC Inc wanted to encourage the employees coming on time to the office. So he announced that for every consecutive day an employee comes on time in a week (starting from Monday to Saturday), he will be awarded Rs.200 more than the previous day as "Punctuality Incentive". The incentive I for the starting day (ie on Monday) is passed as the input to the program. The number of days N an employee came on time consecutively starting from Monday is also passed as the input. The program must calculate and print the "Punctuality Incentive" P of the employee.

Input Format:

The first line denotes the value of I.

The second line denotes the value of N.

Output Format:

The first line denotes the value of P.

PROGRAM 6:

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,r=0;
5     scanf("%d %d",&a,&b);
6     for(int i=0;i<b;i++)
7     {
8         r+=a+(200*i);
9     }
10    printf("%d",r);
11 }
```

	Input	Expected	Got	
✓	500 3	2100	2100	✓
✓	100 3	900	900	✓

Passed all tests! ✓

PROGRAM 7:

Question 6 | Correct | Mark 1.00 out of 1.00 | Flag question

Two numbers M and N are passed as the input. A number X is also passed as the input. The program must print the numbers divisible by X from N to M (inclusive of M and N).

Input Format:

The first line denotes the value of M
The second line denotes the value of N
The third line denotes the value of X

Output Format:

Numbers divisible by X from N to M, with each number separated by a space.

Boundary Conditions:

1 <= M <= 9999999
M < N <= 9999999
1 <= X <= 9999

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int m,n,x;
5      scanf("%d %d %d",&m,&n,&x);
6      for(int i=n;i>=m;i--)
7      {
8          if(i%x==0)
9          {
10             printf("%d ",i);
11         }
12     }
13 }
```

	Input	Expected	Got	
✓	2 40 7	35 28 21 14 7	35 28 21 14 7	✓

Passed all tests! ✓

PROGRAM 8:

Write a C program to find the quotient and remainder of given integers.

For example:

Input	Result
12	4
3	0

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,q,r;
5     scanf("%d %d",&a,&b);
6     q=a/b;
7     r=a%b;
8     printf("%d\n%d",q,r);
9 }
```

	Input	Expected	Got	
✓	12	4	4	✓
	3	0	0	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 9:

Write a C program to find the biggest among the given 3 integers?

For example:

Input	Result
10 20 30	30

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int a,b,c,r;
5      scanf("%d %d %d",&a,&b,&c);
6      if(a>b&&a>c)
7      {
8          r=a;
9      }
10     else if(b>a&&b>c)
11     {
12         r=b;
13     }
14     else
15     {
16         r=c;
17     }
18     printf("%d",r);
19 }
```

	Input	Expected	Got	
✓	10 20 30	30	30	✓

Passed all tests! ✓

PROGRAM 10:

Write a C program to find whether the given integer is odd or even?

For example:

Input	Result
12	Even
11	Odd

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int a;
5      scanf("%d",&a);
6      if(a%2==0)
7      {
8          printf("Even");
9      }
10     else
11     {
12         printf("Odd");
13     }
14 }
```

PROGRAM 11:

	Input	Expected	Got	
✓	12	Even	Even	✓
✓	11	Odd	Odd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 12:

Write a C program to find the factorial of given n.

For example:

Input	Result
5	120

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int factorial(int n)
3 {
4     if(n==0 || n==1)
5     {
6         return 1;
7     }
8     return n*factorial(n-1);
9 }
10 int main()
11 {
12     int a,fact=0;
13     scanf("%d",&a);
14     fact+=factorial(a);
15     printf("%d",fact);
16 }
17
```

	Input	Expected	Got	
✓	5	120	120	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 13:

Write a C program to find the sum first N natural numbers.

For example:

Input	Result
3	6

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,sum=0;
5     scanf("%d",&a);
6     for(int i=1;i<=a;i++)
7     {
8         sum+=i;
9     }
10    printf("%d",sum);
11 }
```

	Input	Expected	Got	
✓	3	6	6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 14:

Question 12 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Write a C program to find the Nth term in the fibonacci series.

For example:

Input	Result
0	0
1	1
4	3

PROGRAM 15:

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n;
5      scanf("%d",&n);
6      int a=0,b=1,c;
7      for(int i=2;i<=n;i++)
8      {
9          c=a+b;
10         a=b;
11         b=c;
12     }
13     if(n==0)
14     {
15         c=a;
16     }
17     if(n==1)
18     {
19         c=b;
20     }
21     printf("%d",c);
22 }
```

	Input	Expected	Got	
✓	0	0	0	✓
✓	1	1	1	✓
✓	4	3	3	✓

Passed all tests! ✓

PROGRAM 16:

Question 13 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find the power of integers.

input:

a b

output:

a^b value

For example:

Input	Result
2 5	32

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int main()
4 {
5     int a,b,r;
6     scanf("%d %d",&a,&b);
7     r=pow(a,b);
8     printf("%d",r);
9 }
```


PROGRAM 17:

	Input	Expected	Got	
✓	2 5	32	32	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 14 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find Whether the given integer is prime or not.

For example:

Input	Result
7	Prime
9	No Prime

PROGRAM 18:

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int prime(int n,int d)
3  {
4      if(n<=1)
5      {
6          return 0;
7      }
8      if(d==1)
9      {
10         return 1;
11     }
12     if(n%d==0)
13     {
14         return 0;
15     }
16     return prime(n,d-1);
17 }
18 int main()
19 {
20     int n;
21     scanf("%d",&n);
22     if(prime(n,n/2))
23     {
24         printf("Prime");
25     }
26     else
27     {
28         printf("No Prime");
29     }
30 }
```

	Input	Expected	Got	
✓	7	Prime	Prime	✓
✓	9	No Prime	No Prime	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 15:

Question 15 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find the reverse of the given integer?

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int a;
5      scanf("%d",&a);
6      int digit,rev=0;
7      while(a!=0)
8      {
9          digit=a%10;
10         rev=(rev*10)+digit;
11         a/=10;
12     }
13     printf("%d",rev);
14 }
```

	Input	Expected	Got	
✓	123	321	321	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.