

ROLL NO:250701573

EXPERIMENT NO: 7 EXPERIMENT TO UNDERSTAND EDA QUANTITATIVE AND
QUALITATIVE ANALYSIS

PROGRAM:

```
import warnings
warnings.filterwarnings("ignore")

import seaborn as sns
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt

%matplotlib inline

tips = sns.load_dataset('tips')

tips.head()

sns.displot(tips.total_bill, kde=True)
plt.show()

sns.displot(tips.total_bill, kde=False)
plt.show()

sns.jointplot(x=tips.tip, y=tips.total_bill)
plt.show()
```

```
sns.jointplot(x=tips.tip, y=tips.total_bill, kind="reg")  
plt.show()
```

```
sns.jointplot(x=tips.tip, y=tips.total_bill, kind="hex")  
plt.show()
```

```
sns.pairplot(tips)  
plt.show()
```

```
tips.time.value_counts()
```

```
sns.pairplot(tips, hue='time')  
plt.show()
```

```
sns.pairplot(tips, hue='day')  
plt.show()
```

```
sns.heatmap(tips.corr(numeric_only=True), annot=True)  
plt.show()
```

```
sns.boxplot(tips.total_bill)  
plt.show()
```

```
sns.boxplot(tips.tip)  
plt.show()
```

```
sns.countplot(tips.day)
```

```
plt.show()
```

```
sns.countplot(tips.sex)
```

```
plt.show()
```

```
tips.sex.value_counts().plot(kind='pie')
```

```
plt.show()
```

```
tips.sex.value_counts().plot(kind='bar')
```

```
plt.show()
```

```
sns.countplot(tips[tips.time == 'Dinner']['day'])
```

```
plt.show()
```

Output:















