

Placement Module - API Routes

Complete documentation for all placement test API endpoints.

Base URL: <http://localhost:3000>

Table of Contents

- [1. Start Session](#)
 - [2. Load Exam](#)
 - [3. Submit Section](#)
 - [4. Get Session Status](#)
 - [5. Full Flow Example](#)
 - [6. Response Reference](#)
-

1. Start Session

Initiates a new placement test session and returns the first section to take.

Endpoint

POST /api/placement/progression/start

Request Body

```
{
  "estimatedLevel": "A1"    // Required: A1 | A2 | B1 | B2 | C1 | C2
}
```

Success Response (201)

```
{
  "sessionId":    "uuid",      // Unique session identifier
  "level":        "A1",        // The level you selected
  "nextSection":  "reading"    // First section to take
}
```

Error Response (400)

```
{
  "error": "Invalid level: \"X\""
}
```

2. Load Exam

Fetches a random exam for the specified level and section from ContentBank.

Endpoint

GET /api/placement/:level/:section

Path Parameters

- level - A1, A2, B1, B2, C1, C2
- section - reading | listening | writing | speaking

Example Request

GET /api/placement/A1/reading

Success Response (200)

Returns the full exam JSON from ContentBank. Structure varies by section:

- examId - Unique exam identifier (auto-added if missing from file)
 - section - reading | listening | writing | speaking
 - level - CEFR level
 - title - Exam title
 - questions - Array of question objects
 - passage - (reading) Text passage
 - transcript / audioUri - (listening) Audio reference
 - instruction / prompts - (writing/speaking) Task description
-

3. Submit Section

Submits answers for a section. The backend saves the result and returns the next step.

Endpoint

POST /api/placement/:level/:section/submit

Path Parameters

- level - A1, A2, B1, B2, C1, C2
- section - reading | listening | writing | speaking

Request Body

Common fields:

```
{
  "sessionId": "uuid",           // Required - from /start
  "examId": "exam_001",         // Required - from GET exam
}
```

Reading / Listening

Add answers array:

```
{
  "answers": [0, 1, 2]           // Array of selected option indices
}
```

Writing

Add text and self-assessment percentage:

```
{
  "text": "My written answer...", // Written response
  "percentage": 70                 // Self-assessment 0-100
}
```

Speaking

Add conversation and self-assessment percentage:

```
{
  "conversation": "My recorded speech...", // Spoken response
  "percentage": 80                          // Self-assessment 0-100
}
```

Response - Continue (Sections 1-3)

After reading, listening, or writing:

```
{
  "status": "continue"
  "nextSection": "listening" // Next section to take
}
```

Response - Final (After Speaking)

Three possible outcomes:

PASS (average > 75%)

```
{
  "status": "next_level"
  "nextLevel": "A2" // Move to this level
}
```

STAY (40% <= average <= 75%)

```
{
  "status": "finished"
  "placementLevel": "A1"
  "percentage": 68
}
```

LOWER (average < 40%)

```
{
  "status":    "lower_level"
  "nextLevel": "A1"           // Move down to this level
}
```

4. Get Session Status

Returns the current state of a session (all results, percentages, progression).

Endpoint

GET /api/placement/progression/status/:sessionId

Example Request

GET /api/placement/progression/status/3d7fcc92-f8c6-442b-9e1b-60bb426b9b84

Success Response (200)

```
{
  "sessionId":      "uuid"
  "level":          "A1"
  "results":        { "reading": 80, "listening": 70, "writing": 60, "speaking": 90 }
  "completedSections": 4
  "totalSections":  4
  "allCompleted":    true
  "finalPercentage": 75
  "progression":     { "status": "finished", "placementLevel": "A1" }
}
```

5. Full Flow Example

Complete sequence for a placement test from start to finish.

Step 1 - Start Session

```
POST /api/placement/progression/start
Body: { "estimatedLevel": "A1" }
Reply: { "sessionId": "abc", "level": "A1", "nextSection": "reading" }
```

Step 2 - Load Reading Exam

```
GET /api/placement/A1/reading
Reply: { examId, passage, questions, ... }
```

Step 3 - Submit Reading

```
POST /api/placement/A1/reading/submit
Body: { "sessionId": "abc", "examId": "exam_001", "answers": [1, 2, 1] }
Reply: { "status": "continue", "nextSection": "listening" }
```

Step 4 - Submit Listening

```
POST /api/placement/A1/listening/submit
Body: { "sessionId": "abc", "examId": "exam_002", "answers": [1, 2, 1] }
Reply: { "status": "continue", "nextSection": "writing" }
```

Step 5 - Submit Writing

```
POST /api/placement/A1/writing/submit
Body: { "sessionId": "abc", "examId": "exam_003", "text": "...", "percentage": 70 }
Reply: { "status": "continue", "nextSection": "speaking" }
```

Step 6 - Submit Speaking (Final)

```
POST /api/placement/A1/speaking/submit
Body: { "sessionId": "abc", "examId": "exam_004", "conversation": "...", "percentage": 80 }
Reply: { "status": "finished", "placementLevel": "A1", "percentage": 68 }
```

Optional - Check Session Status

```
GET /api/placement/progression/status/abc
```

6. Response Reference

HTTP Status Codes

- 200 - Success
- 201 - Session created
- 400 - Bad request (missing/invalid fields)
- 404 - Level, section, exam, or session not found

Error Response Format

```
{
  "error": "Descriptive error message"
}
```

Placement Rules Summary

Score	Result	Response
> 75%	Next Level	{ status: "next_level", nextLevel: "A2" }
40% - 75%	Finished	{ status: "finished", placementLevel: "A1", percentage: 68 }
< 40% (not A1)	Lower Level	{ status: "lower_level", nextLevel: "A1" }

< 40% (A1)

Finished (A1)

```
{ status: "finished", placementLevel: "A1",  
percentage }
```


