Assignment 2, Part 3(b): RTT–Loss AIMD

Ayusha Patra Kabileswaran Krishna Kumar Vihaan Kodeboyina Millan Kumar

Idea and evidence

Our algorithm, RTT–Loss AIMD (RLA), grows the congestion window when the connection is using it well, backs off when RTT rises, and cuts back more strongly when TCP detects loss. The goal is to get good throughput without building an unnecessarily large queue.

Our measurements suggest that one signal alone is not enough. In a five-destination comparison with 60-second transfers, BBR at LeaseWeb averaged 144.5 Mbit/s versus CUBIC's 93.2 Mbit/s, but its mean RTT was 90.9 ms versus 76.5 ms and its retransmitted-byte fraction was 12.64% versus 0.04%. On Mauritius, CUBIC averaged 30.0 Mbit/s versus Reno's 20.2 Mbit/s despite similar mean RTTs (321 and 316 ms). In a separate four-destination comparison with 20-second transfers, the ranking changed: at Multinet24, Reno averaged 151.8 Mbit/s versus CUBIC's 98.1 Mbit/s and BBR's 147.0 Mbit/s, with no retransmitted segments in those Part 3 tests. These observations motivate using RTT to detect increasing delay, loss feedback to trigger stronger backoff, and acknowledged throughput to check whether the current window is being used effectively. They motivate RLA's design but do not establish its performance.

Compared with Reno, CUBIC, and BBR

Reno grows its window roughly one segment per RTT in congestion avoidance and halves it on loss. It is simple, but recovery can be slow on high-capacity, long-RTT paths. RLA keeps the simple additive/loss-backoff idea and adds delay and throughput checks; those checks can also make it grow slower.

CUBIC uses a time-based cubic growth curve to probe capacity faster on large-window paths. Its loss-based probing can build queues. RLA tries to back off before loss when delay rises, trading some throughput for less queueing.

BBR estimates bandwidth and minimum RTT to control its sending rate. It can achieve high throughput without waiting for loss, but depends on the quality of those estimates and can have sharing issues with competing flows. RLA is simpler and uses throughput only to decide whether to grow; it may leave more bandwidth unused.

How the window changes

Starting up. Keep Linux's initial window, normally ten segments, and use standard slow start: increase the window as packets are acknowledged. This avoids spending the transfer at a tiny window.

Regular updates. Use a control interval of at least 100 ms and at least the RTT measured at the interval's start. Remember the lowest positive smoothed RTT seen so far as the baseline. Measure goodput as eight times newly acknowledged bytes divided by the actual elapsed time. Compare it with the starting window's approximate supported rate:

$$\text{window rate} = \frac{8 \times \text{cwnd} \times \text{MSS}}{\text{RTT}} \quad \text{bits/s, with RTT in seconds.}$$

Here, cwnd is in segments and MSS is bytes per segment. This rate is only an approximation, not a measurement of the link's capacity.

Backing off. At a completed control interval, if RTT rises more than 25% above the baseline, reduce cwnd by 10% and leave slow start. On a native TCP loss/congestion event, request a threshold of half the window and let Linux handle recovery. Respond once through that recovery mechanism, rather than halving for every retransmitted packet in a burst.

Growing carefully. After slow start, add one segment per completed interval only if RTT is less than 10% above baseline, goodput is at least 80% of the window rate, and the sender is constrained by its congestion window. Otherwise hold it steady. The gap between the RTT thresholds avoids switching between growth and backoff for every small RTT change. The throughput check avoids enlarging a window that is not being fully used.

Terms

Term	Meaning
ACK	An acknowledgment telling the sender that data arrived.
cwnd	Congestion window: the limit on data sent but not yet acknowledged, measured here in segments.
MSS	Maximum segment size: the number of data bytes in a full TCP segment.
RTT	Round-trip time: how long data and its acknowledgment take to travel. We use a smoothed estimate.
Baseline RTT	The lowest positive smoothed RTT seen so far; a reference for spotting extra delay.
Goodput	The rate of newly acknowledged data, counting each byte once even if retransmitted.
Queueing	Packets waiting in network buffers, which adds delay and can raise RTT.
Slow start	The initial phase where ACKs let the window grow quickly.
AIMD	Additive increase, multiplicative decrease: grow by a fixed amount and back off by a fraction.

Pseudocode

```
Start with Linux's initial cwnd and slow-start threshold.
Remember the lowest positive smoothed RTT as base_RTT.
At each interval start, save time, ACKed bytes, cwnd, MSS, RTT.
Interval length = max(100 ms, starting RTT).

On a TCP loss/congestion event:
    threshold = max(2, floor(cwnd / 2))
    let Linux handle recovery; discard the current interval

On an ACK outside recovery:
    skip invalid measurements
    update base_RTT with the positive smoothed RTT
    if no interval is active, begin one
    if interval finished:
        goodput = 8 * ACKed bytes since interval start / elapsed time
        window_rate = 8 * starting cwnd * starting MSS / starting RTT
    if interval finished and RTT > 1.25 * base_RTT:
        cwnd = max(2, floor(0.90 * cwnd))
        threshold = cwnd
    else if in slow start and constrained by cwnd:
        cwnd += newly ACKed segments, up to the threshold
    else if interval finished and RTT < 1.10 * base_RTT:
        if goodput >= 0.80 * window_rate and constrained by cwnd:
            cwnd += 1
    otherwise hold cwnd

    respect Linux's maximum window
    if interval finished, begin a new interval
```

Skip invalid measurements and restart the interval after recovery or an idle restart. RTT is expressed in seconds in the rate equations. Two segments is the normal minimum, but Linux can temporarily use one after a timeout. The 10%/25% RTT thresholds provide a hold region, the 10% delay backoff is gentler than the loss response, and the 80% utilization check discourages growth when the old window is underused. These are heuristic choices, not values optimized or validated by our experiments.

Fairness, stability, and limitations

Fairness. With similar RTTs and packet sizes, flows eligible for the same additive increases and experiencing congestion together should tend toward equal windows: equal additive increments preserve the window difference, while a shared percentage decrease shrinks it. In practice, longer-RTT flows update less often, low-goodput flows may fail the growth check, and RLA may yield to CUBIC or Reno by backing off earlier. Fairness is not guaranteed.

Stability. Growth at low delay and backoff at high delay should keep the rate near an operating range on a stable path. Holding between the two thresholds should reduce small fluctuations. We expect some oscillation, rather than exact convergence, especially with delayed feedback or changing traffic. The utilization condition can also prevent further growth at an underused operating point, so convergence to full utilization is not guaranteed.

Limitations. We assume usable measurements and a reasonably stable path. Route changes can make the minimum RTT outdated, wireless loss can cause unnecessary backoff, and ACK bursts can distort throughput. A minimum smoothed RTT can already contain queueing delay. The growth check can leave spare bandwidth unused. Our measurements have not tested competing RLA flows or established fairness and stability.