Cache optimizations in Garbage Collection Bachelor Thesis

David Himmelstrup
Department of Computer Science



Memory management

Top 10 programming languages (GitHub 2017):

- Javascript
- 2 Python
- 3 Java
- 4 Ruby
- 6 PHP
- 6 C++
- **⑦** C#
- **8** Go
- 9 C
- Swift




Memory management

Top 10 programming languages (GitHub 2017):

- Javascript
- 2 Python
- 3 Java
- 4 Ruby
- 6 PHP
- **6** C++
- □ C#
- 8 Go
- **9** C
- Swift




Semi-space garbage collection






Memory hierarchy






Memory hierarchy



RAM: Random-Access Memory?




Depth-first copying



Each branch lives in continuous memory.




Breadth-first copying





Breadth-first copying



No stack but poor locality of reference.




A middle ground: tail-first copying

- No stack
- No reserved heap
- 3 Puts branches in chunks of continuous memory




A middle ground: tail-first copying



- No stack
- No reserved heap
- 3 Puts branches in *chunks* of continuous memory



New opportunity: tail compaction





LLC Load Misses (millions):				
Name	Baseline	Tail-copy	Tail-compact	
Allocate	3.9	+5.5%	+6.2%	
BinTree	60.9	-4.5%	-4.9%	
Bush	33.5	+4.1%	+2.8%	
BushTail	50.9	+0.8%	+0.6%	
Imbalanced	40.9	-10.3%	-11.0%	
MemBench	84.1	-80.3%	-80.0%	
PowerSet	130.3	-78.7%	-78.7%	
Min		-80.3%	-80.0%	
Max		5.5%	6.2%	
Mean		-23.3%	-23.6%	

Mostly fewer LLC misses (-80% to +6%)



Branch Misses (millions):					
Name	Baseline	Tail-copy	Tail-compact		
Allocate	3.7	-6.1%	-13.8%		
BinTree	29.0	+107.5%	+102.5%		
Bush	17.4	+78.3%	+77.0%		
BushTail	16.2	+44.4%	+44.2%		
Imbalanced	39.4	+6.7%	+4.3%		
MemBench	10.7	-7.9%	-12.8%		
PowerSet	20.0	-6.7%	-10.7%		
Min		-7.9%	-13.8%		
Max		107.5%	102.5%		
Mean		30.9%	27.3%		

- Mostly fewer LLC misses (-80% to +6%)
- More complex algorithm ⇒ more branch misses



Heap size:				
Name	Baseline	Tail-copy	Tail-compact	
Allocate	1.8 gb	+0.0%	-8.3%	
BinTree	1.8 gb	+0.0%	-6.2%	
Bush	1.3 gb	+0.0%	-3.1%	
BushTail	5.1 gb	+0.0%	-1.7%	
Imbalanced	1.6 gb	+0.0%	-6.2%	
MemBench	6.7 gb	+0.0%	-5.0%	
PowerSet	10.4 gb	+0.0%	-5.0%	
Min		0.0%	-8.3%	
Max		0.0%	-1.7%	
Mean		0.0%	-5.0%	

- Mostly fewer LLC misses (-80% to +6%)
- More complex algorithm ⇒ more branch misses
- 5.0% smaller heap on average



GC times:				
Name	Baseline	Tail-copy	Tail-compact	
Allocate	1.5s	+14.5%	+3.1%	
BinTree	4.6s	+16.2%	+10.2%	
Bush	2.8s	+12.5%	+9.6%	
BushTail	3.6s	+10.7%	+5.9%	
Imbalanced	4.0s	-0.7%	-6.2%	
MemBench	7.8s	-27.5%	-31.4%	
PowerSet	12.6s	-31.1%	-34.5%	
Min		-31.1%	-34.5%	
Max		16.2%	10.2%	
Mean		-0.8%	-6.2%	

- Mostly fewer LLC misses (-80% to +6%)
- More complex algorithm ⇒ more branch misses
- 5.0% smaller heap on average
- All in all, four programs are slower and three are faster.

