

Dictating L^AT_EX using Mathfly

Mike Roberts

February 2, 2019

Contents

1	Introduction	1
2	Bibliography management	2
3	Document classes	2
4	Packages	2
5	Environments	4
6	Commands	5
6.1	With arguments	5
6.2	No arguments	6
7	Greek letters	6
8	Mathematical symbols	7
9	Templates	10

1 Introduction

All of these commands can be modified or added to by editing “config/latex.toml” or using the voice command “configure latex”.

2 Bibliography management

Once you have added the location of your .bib file (using regular slashes) to your LaTeX config file, Mathfly includes a number of commands to make bibliography management easy:

Insert my (bib resource — bibliography)	<code>\addbibresource{your_bibliography.bib}</code>
Add paper to bibliography	Searches google scholar for the highlighted text (paper title), appends the first resulting bib-Tex citation to your bibliography file and adds the tag to the clipboard, ready to be pasted into a document.
Add book to bibliography	Same as above, but searches goodreads instead.
Add link to bibliography	Same as above, but constructs a citation from a url instead.
(edit — open) bibliography	Opens your .bib file in your text editor, for manual alterations and searching.

3 Document classes

Prefixed by "document class", these commands produce for example:

```
\documentclass{article}
```

article	article
beamer	beamer
book	book
letter	letter
proceedings	proc
report	report

4 Packages

Prefixed by "use package", these commands produce for example:

```
\usepackage{geometry}
```

The second column represents additional arguments.

AMS math		AMS math
bib latex	[style=authoryear]	biblatex
colour		color
geometry		geometry
hyper ref		hyperref
graphic X		graphicx
math tools		mathtools
multi col		multicol
long table		longtable
tabular X		tabularx
X color		xcolor
wrap figure		wrapfig

5 Environments

Prefixed by "begin", these commands produce for example

```
\begin{abstract}
\end{abstract}
```

The third column represents additional arguments.

abstract	abstract	
add margin	addmargin	
center	center	
columns	columns	
description	description	
document	document	
(enumerate — numbered list)	enumerate	
equation	equation	
figure	figure	[h!]
flush left	flushleft	
flush right	flushright	
frame	frame	
(list — itemise)	itemize	
mini page	minipage	
multi (cols — columns)	multicols	{2}
quotation	quotation	
quote	quote	
table	table	[h!]
long table	longtable	{lll}

tabular	tabular	{llll}
tabular X	tabular X	{l X}
title page	titlepage	
verbatim	verbatim	
verse	verse	
wrap figure	wrapfigure	

6 Commands

All of these commands are prefixed with "insert".

6.1 With arguments

These commands finish in a set of curly brackets, ready for an argument, for example "\author {}"

author	author
[add] bib resource	addbibresource
caption	caption
chapter	chapter
frame title	frametitle
footnote	footnote
footnote text	footnotetext[]
graphics path	graphicspath
[include] graphics	includegraphics[width=1\textwidth]
label	label
new command	newcommand{}[]
paragraph	paragraph
paren cite	parencite
part	part
reference	ref
renew command	renewcommand
sub paragraph	subparagraph
(section — heading)	section
sub (section — heading)	subsection
sub sub (section — heading)	subsubsection
text cite	textcite
[text] bold	textbf
[text] italics	textit
[text] slanted	textsl

title	title
use theme	usetheme

6.2 No arguments

For example “\linebreak”.

centering	centering
column	column{0.5\textwidth}
footnote mark	footnotemark[]
horizontal line	hline
LaTeX	L ^A T _E X
line break	linebreak
item	item
make title	maketitle
new page	newpage
no indent	noindent
page break	pagebreak
print bibliography	printbibliography
table of contents	tableofcontents
TeX	T _E X
text backslash	textbackslash
text height	textheight
text width	textwidth
vertical line	vline

7 Greek letters

Prefixed by “greek”. Where relevant I have provided pronunciation tips for best results.

alpha	α	
beta	β	beater
gamma	γ	Γ
delta	δ	Δ
epsilon	ε	
zeta	ζ	
eta	η	eater
theta	θ	Θ they-tah
iota	ι	
kappa	κ	

lambda	λ	Λ	
mu	μ		moo
nu	ν		new
xi	ξ	Ξ	zee
pi	π	Π	
rho	ρ		
sigma	σ	Σ	
tau	τ		
upsilon	υ	Υ	
phi	ϕ	Φ	
chi	χ		kie
psi	ψ	Ψ	sigh
omega	ω	Ω	

8 Mathematical symbols

In normal L^AT_EX mode, these must all be prefixed with “symbol”. if you are dictating a large block of mathematics, then use “enable latex maths” to remove the need for prefixes before numbers and symbol, so that you can dictate more naturally.

super [script]	x^a
sub [script]	x_a
squared	x^2
cubed	x^3
inverse	x^{-1}
degrees	x°
(parens — parentheses)	(x)
square brackets	$[x]$
(curly brackets — braces)	$\{ \}$
square root	\sqrt{a}
[generic] root	$\sqrt[n]{a}$
integral	\int
double integral	\iint
triple integral	\iiint
infinity	∞
times	\times
divide	\div
intersection	\cap
union	\cup

C dot	\cdot
summation	\sum
product	\prod
(direct sum — oh plus)	\oplus
(big direct sum — big oh plus)	\bigoplus
(direct product — oh times)	\otimes
(big direct product — big oh times)	\bigotimes
plus or minus	\pm
partial	∂
fraction	$\frac{a}{b}$
binomial	$\binom{a}{b}$
sine	\sin
cosine	\cos
tangent	\tan
secant	\sec
cosecant	\csc
cotangent	\cot
arc sine	\arcsin
arc cosine	\arccos
arc tan	\arctan
hyperbolic sine	\sinh
hyperbolic cosine	\cosh
hyperbolic cotangent	\coth
hyperbolic tangent	\tanh
argument	\arg
modulus	mod
degree	deg
determinant	\det
dimension	\dim
exp	\exp
GCD	gcd
cat hom	hom
kernel	\ker
infimum	\inf
supremum	\sup
limit	\lim
liminf	\liminf
(natural (log — logarithm) — log natural)	\ln
logarithm	\log
max	\max

min	\min
probability	\Pr
[is] not equal [to]	\neq
[is] greater [than] [or] equal [to]	\geq
[is] less [than] [or] equal [to]	\leq
[is] approximately [equal] [to]	\approx
proportional [to]	\propto
preference less [than]	\prec
preference less equals	\preceq
preference greater [than]	\succ
preference greater equals	\succeq
subset	\subset
superset	\supset
strict subset	\subsetneq
strict superset	\supsetneq
member	\in
(and—logic and)	\wedge
logic or	\vee
primer	$'$
logic not	\neg
for all	\forall
there exists	\exists
real numbers	\mathbb{R}
complex numbers	\mathbb{C}
integer numbers	\mathbb{Z}
rational numbers	\mathbb{Q}
natural numbers	\mathbb{N}
left arrow	\leftarrow
right arrow	\rightarrow
up arrow	\uparrow
down arrow	\downarrow
left right arrow	\leftrightarrow
dot dot dot	\dots
diagonal dots	\ddots
horizontal dots	\cdots
vertical dots	\vdots

9 Templates

Templates provide a way to insert larger sections of text into your documents, for example you may have a particular set of packages which you always want to import at the head of your files, or a particular diagram which you need to draw over and over again. They are defined in the templates section of `config/latex.toml` and by default are executed using the “`template template_name`” command. A couple are included as standard for illustrative purposes but these are designed to be edited to suit your needs. For example, the command “`template wrap figure`” will insert:

```
\begin{wrapfigure}{l}{0.5\textwidth}  
\centering  
\label{}  
\includegraphics[width=0.4\textwidth]{}  
\caption{}  
\end{wrapfigure}
```