

# NETWERKPROGRAMMATIE JAVA

Veerle Ongenae

## Overzicht


2

- Herhaling

Industrieel Ingenieur Informatica, UGent

## TCP - UDP


3



Industrieel Ingenieur Informatica, UGent  
<https://docs.oracle.com/javase/tutorial/networking/overview/networking.html>

## Poorten

4



Industrieel Ingenieur Informatica, UGent  
<https://docs.oracle.com/javase/tutorial/networking/overview/networking.html>

## Netwerkprogrammatie Java

5

- Package `java.net`
- TCP
  - URL
  - URLConnection
  - Socket
  - ServerSocket
- UDP
  - DatagramPacket
  - DatagramSocket
  - MulticastSocket

Industrieel Ingenieur Informatica, UGent

## Overzicht


6

- Herhaling
- Client-Serverapplicatie

Industrieel Ingenieur Informatica, UGent


## Client-server

7



## Socket

8



<https://docs.oracle.com/javase/tutorial/networking/sockets/definition.html>

Industriële Ingenieur Informatica, UGent

## Client

9

```
String hostName = "localhost";
int portNumber = 4444;


try (Socket echoSocket = new Socket(hostName, portNumber);
    PrintWriter out = new PrintWriter(echoSocket.getOutputStream(), true);
    BufferedReader in = new BufferedReader(
        new InputStreamReader(echoSocket.getInputStream()));
    BufferedReader stdIn = new BufferedReader(new InputStreamReader(System.in))) {

    String userInput = leesTekst(stdIn);
    while (!userInput.equals("exit")) {
        out.println(userInput); // naar server
        System.out.println("echo: " + in.readLine()); // van server
        userInput = leesTekst(stdIn);
    }
} catch (IOException ex) {
    Logger.getLogger(EchoClient.class.getName()).log(Level.SEVERE, null, ex);
}
```

Industriële Ingenieur Informatica, UGent

## Server


10



Industriële Ingenieur Informatica, UGent

## Server

11



Industriële Ingenieur Informatica, UGent

## KnockKnockServer

12

```

← Knock! Knock!
→ Who's there?
← Turnip
→ Turnip who?
← Turnip the heat, it's cold in here! Want another? (y/n)
→ y
← Knock! Knock!
→ Who's there?
← Little Old Lady
→ Little Old Lady who?
← I didn't know you could yodel! Want another? (y/n)
→ y
← Knock! Knock!
→ Who's there?
← Atch
→ Atch who?
← Bless you! Want another? (y/n)
→ n
← Bye.
```

## KnockKnockServer

```

13 try {
    ServerSocket serverSocket = new ServerSocket(4444);
    while (true) {
        try (Socket clientSocket = serverSocket.accept())
        try (PrintWriter out
            = new PrintWriter(clientSocket.getOutputStream(), true);
            BufferedReader in = new BufferedReader(
                new InputStreamReader(clientSocket.getInputStream())){
            String inputLine, outputLine;
            while ((inputLine = in.readLine()) != null) {
                outputLine = kkp.processInput(inputLine);
                out.println(outputLine);
                if (outputLine.equals("Bye.")) {break;}
            }
        } ...
    }

```


Industrieel Ingenieur Informatica, UGent

## Overzicht

- ☐ Herhaling
- ☐ Client-Serverapplicatie
- ☐ Concurrency

Industrieel Ingenieur Informatica, UGent


## Concurrency



<http://sourcecodemania.com/thread-programming-in-java/>

Industrieel Ingenieur Informatica, UGent

## Processen - threads



Industrieel Ingenieur Informatica, UGent

## Thread - Executor



<http://crunchify.com/java-simple-thread-example/>

Industrieel Ingenieur Informatica, UGent

## Overzicht

- ☐ Herhaling
- ☐ Client-Serverapplicatie
- ☐ Concurrency
  - ☒ Threads

Industrieel Ingenieur Informatica, UGent

## Thread – optie 1

19

```
public class HelloRunnable implements Runnable {
    public void run() {
        System.out.println("Hello from a thread!");
    }

    public static void main(String args[]) {
        (new Thread(new HelloRunnable())).start();
    }
}
```

Industrieel Ingenieur Informatica, UGent

## Thread – optie 2

20

```
public class HelloThread extends Thread {
    public void run() {
        System.out.println("Hello from a thread!");
    }

    public static void main(String args[]) {
        (new HelloThread()).start();
    }
}
```

Industrieel Ingenieur Informatica, UGent

## Thread – optie 3

21

```
public static void main(String args[]) {
    Runnable task = () -> {
        System.out.println("Hello from a thread!");
    };
    new Thread(task).start();
}
```

Industrieel Ingenieur Informatica, UGent

## Overzicht


22

- ☐ Herhaling
- ☐ URL's in Java
- ☐ Client-Serverapplicatie
- ☐ Concurrency
  - ☐ Threads
  - ☐ Synchronisatie

Industrieel Ingenieur Informatica, UGent

## Data delen

23




Industrieel Ingenieur Informatica, UGent

<http://blog.baysolutions.com/2011/10/06/java-threading-and-concurrency-introduction/>

## Synchronisatie

24


<http://crunchify.com/java-simple-thread-example/>

Running Java Thread



Higher Priority Threads waiting...

<http://avaldes.com/java-thread-starvation-livelock-with-examples/>

## High level concurrency

25

- Lock-objecten
- Executors
- Concurrent collections
- Atomic variables
- ThreadLocalRandom

Industrieel Ingenieur Informatica, UGent

## Overzicht

26

- Herhaling
- URL's in Java
- Client-Serverapplicatie
- Concurrency
  - ▣ Threads
  - ▣ Synchronisatie
  - ▣ Executor

Industrieel Ingenieur Informatica, UGent

## Executor


27

- Scheiding
  - ▣ Beheren threads
  - ▣ Aanmaken threads

Industrieel Ingenieur Informatica, UGent

## Executor interfaces

28


<https://myshadesofgray.wordpress.com/2014/04/13/java-executor-framework/>

Industrieel Ingenieur Informatica, UGent

## ExecutorService - aanmaken

29

```

ExecutorService execServ1 = Executors.newSingleThreadExecutor();
ExecutorService execServ2 = Executors.newFixedThreadPool(10);
ExecutorService execServ3 = Executors.newScheduledThreadPool(10);
  
```

Industrieel Ingenieur Informatica, UGent

## ExecutorService - gebruik

30

```

executorService.execute(new Runnable() {
    @Override
    public void run() {
        System.out.println("Asynchronous task");
    }
});

executorService.submit() -> {
    System.out.println("Asynchronous task");
});

Future<String> future = executorService.submit(new Callable(){
    @Override
    public String call() throws Exception {
        System.out.println("Asynchronous Callable");
        return "Callable Result";
    }
});

try {
    System.out.println("future.get() = " + future.get());
} catch (InterruptedException | ExecutionException ex) { ... }
  
```

## ExecutorService – reeks opdrachten

31

```
ExecutorService executorService = Executors.newSingleThreadExecutor();

Set<Callable<String>> callables = new HashSet<>();
callables.add((Callable<String>) () -> "Task 1");
callables.add((Callable<String>) () -> "Task 2");
callables.add((Callable<String>) () -> "Task 3");

try {
    List<Future<String>> futures = executorService.invokeAll(callables);

    for(Future<String> future : futures)
        System.out.println("future.get = " + future.get());
} catch (InterruptedException | ExecutionException ex) { ... }

executorService.shutdown();
```

Industrieel Ingenieur Informatica, UGent

## ExecutorService – reeks opdrachten

32

```
ExecutorService executorService = Executors.newSingleThreadExecutor();


Set<Callable<String>> callables = new HashSet<>();
for (int i = 1; i <= 100; i++) {
    final int j = i;
    callables.add((Callable<String>) () -> {
        String opdracht = "Task " + j;
        System.out.println(opdracht);
        return opdracht;
    });
}

try {
    String result = executorService.invokeAny(callables);
    System.out.println("result = " + result);
} catch (InterruptedException | ExecutionException ex) {
    Logger.getLogger(...);
}
```

Industrieel Ingenieur Informatica, UGent

## Thread Pools

33


[https://en.wikipedia.org/wiki/Thread\\_pool\\_pattern](https://en.wikipedia.org/wiki/Thread_pool_pattern)

Industrieel Ingenieur Informatica, UGent

## Overzicht


34

- ☐ Herhaling
- ☐ URL's in Java
- ☐ Client-Serverapplicatie
- ☐ Concurrency
  - ☐ Threads
  - ☐ Synchronisatie
  - ☐ Executor
  - ☐ Concurrent Collections

Industrieel Ingenieur Informatica, UGent

## Concurrent Collections

35


<http://tutorials.jenkov.com/java-util-concurrent/blockingqueue.html>

## Overzicht


36

- ☐ Herhaling
- ☐ Client-Serverapplicatie
- ☐ Concurrency
  - ☐ Threads
  - ☐ Synchronisatie
  - ☐ Executor
  - ☐ Concurrent Collections
- ☐ Multithreaded Server

Industrieel Ingenieur Informatica, UGent

## Singlethreaded Server

37



<https://myshadesofgray.wordpress.com/2014/04/13/java-executor-framework/>  
Industriële Ingenieur Informatica, UGent

## KnockKnockServer

38

```
int portNumber = 9999;
boolean listening = true;
try (ServerSocket serverSocket = new ServerSocket(portNumber)) {
    while (listening) {
        new KnockKnockThread(serverSocket.accept()).start();
    }
} catch (IOException e) {
    Logger.getLogger(
        KnockKnockMultiServer.class.getName()).log(Level.SEVERE,
        null, e);
    System.err.println("Could not listen on port " + portNumber);
    throw new RuntimeException(e);
}
```

Industriële Ingenieur Informatica, UGent

## KnockKnockServer - Thread

39

```
public class KnockKnockThread extends Thread {
    private Socket socket = null;
    public KnockKnockThread(Socket socket) {
        super("KKMultiServerThread");
        this.socket = socket;
    }
    @Override
    public void run() {
        try {
            PrintWriter out = new PrintWriter(socket.getOutputStream(), true);
            BufferedReader in = new BufferedReader(
                new InputStreamReader(socket.getInputStream()));
            {...}
            socket.close();
        } catch (IOException e) {
            Logger.getLogger(
                KnockKnockThread.class.getName()).log(Level.SEVERE, null, e);
            System.err.println("Could not listen on port " + portNumber);
            throw new RuntimeException(e);
        }
    }
}
```

Industriële Ingenieur Informatica, UGent

## KnockKnockServer - Executor

40

```
int portNumber = 9999;
boolean listening = true;
try (ServerSocket serverSocket = new ServerSocket(portNumber)) {
    ExecutorService execServ = Executors.newFixedThreadPool(10);
    while (listening) {
        try {
            Socket clientSocket = serverSocket.accept();
            execServ.submit(new KnockKnockRunnable(clientSocket));
        } catch (IOException ex) {...}
    }
} catch (IOException e) {
    Logger.getLogger(
        KnockKnockPool.class.getName()).log(Level.SEVERE, null, e);
    System.err.println("Could not listen on port " + portNumber);
    throw new RuntimeException(e);
}
```

Industriële Ingenieur Informatica, UGent