

Representation Learning with SimCLR

In this exercise, we would like to implement the SimCLR model and train it on the FashionMNIST dataset. As described in the lecture the SimCLR model is used to learn representations with a contrastive loss.

```
In [1]: from torchvision.datasets import FashionMNIST
        from torchvision import transforms as T
        import matplotlib.pyplot as plt
        import torch
        from torch.utils.data import DataLoader
        import solution
        import random
```

```
In [2]: # use this device on your laptop
        device = 'cpu'
        # uncomment below if you want to use a gpu (e.g. on Google Colab)
        #device = 'cuda'
```

Load Dataset

First, we will load the FashionMNIST dataset and display some of the samples.

```
In [3]: data_root = './data'
        train_dataset = FashionMNIST(data_root, train=True,
                                     download=True, transform=T.ToTensor())
        test_dataset = FashionMNIST(data_root, train=False,
                                    download=True, transform=T.ToTensor())

        h, w = 5, 10
        fig, ax = plt.subplots(h, w)
        fig.set_size_inches((w, h))
        ax = ax.ravel()
        for i in range(h * w):
            img, label = train_dataset[i]
            ax[i].imshow(torch.permute(img, (1, 2, 0)), cmap='gray')
            ax[i].axis('off')
        plt.show()
```

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/train-images-idx3-ubyte.gz>
Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/train-images-idx3-ubyte.gz> to ./data\FashionMNIST\raw\train-images-idx3-ubyte.gz

100%|██████████| 26.4M/26.4M [00:00<00:00, 34.8MB/s]

Extracting ./data\FashionMNIST\raw\train-images-idx3-ubyte.gz to ./data\FashionMNIST\raw

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/train-labels-idx1-ubyte.gz>

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/train-labels-idx1-ubyte.gz> to ./data\FashionMNIST\raw\train-labels-idx1-ubyte.gz

100%|██████████| 29.5k/29.5k [00:00<00:00, 4.35MB/s]

Extracting ./data\FashionMNIST\raw\train-labels-idx1-ubyte.gz to ./data\FashionMNIST\raw

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/t10k-images-idx3-ubyte.gz>

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/t10k-images-idx3-ubyte.gz> to ./data\FashionMNIST\raw\t10k-images-idx3-ubyte.gz

100%|██████████| 4.42M/4.42M [00:00<00:00, 20.5MB/s]

Extracting ./data\FashionMNIST\raw\t10k-images-idx3-ubyte.gz to ./data\FashionMNIST\raw

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/t10k-labels-idx1-ubyte.gz>

Downloading <http://fashion-mnist.s3-website.eu-central-1.amazonaws.com/t10k-labels-idx1-ubyte.gz> to ./data\FashionMNIST\raw\t10k-labels-idx1-ubyte.gz

100%|██████████| 5.15k/5.15k [00:00<?, ?B/s]

Extracting ./data\FashionMNIST\raw\t10k-labels-idx1-ubyte.gz to ./data\FashionMNIST\raw



Model Architecture

We use a small convolutional network as an encoder and an MLP with 2 as non-linear projection head. The encoder transforms the 28x28x1 image into a 64-dimensional representation. The projection head encoder, projects the representation to a dimension of 32.

```
In [4]: import torch.nn as nn

def conv_block(in_channels, out_channels, kernel=3, stride=1):
    return nn.Sequential(
        nn.Conv2d(in_channels, out_channels=out_channels,
                  kernel_size=kernel, stride=stride),
        nn.BatchNorm2d(num_features=out_channels),
        nn.ReLU()
    )

## Creating the encoder
def create_encoder():
    encoder = nn.Sequential(conv_block(in_channels=1, out_channels=16),
                            nn.MaxPool2d(kernel_size=2),
                            conv_block(in_channels=16, out_channels=32),
                            nn.MaxPool2d(kernel_size=2),
                            conv_block(in_channels=32, out_channels=64),
                            nn.AdaptiveAvgPool2d((1,1)), nn.Flatten())

    return encoder

## Creating the projection head
def create_projection_head():
    dim = 64
    proj_layers = []
    for _ in range(2):
        proj_layers.append(nn.Linear(dim, dim))
        proj_layers.append(nn.BatchNorm1d(dim))
        proj_layers.append(nn.ReLU(dim))
    projection_head = nn.Sequential(*proj_layers, nn.Linear(dim, 32))
    return projection_head
```

```
In [5]: encoder = create_encoder()
        projection_head = create_projection_head()

x = torch.zeros((1, 1, 28, 28))
encoder.eval()
projection_head.eval()
h = encoder(x)
print('h', h.shape)
z = projection_head(h)
print('z', z.shape)

h torch.Size([1, 64])
z torch.Size([1, 32])
```

Task 1: SimCLR Loss (30P)

Task: Given the embeddings from both of the views, implement the SimCLR loss function.

$$\mathcal{L} = -\frac{1}{N} \sum_{i,j \in MB} \log \frac{\exp(\text{sim}(\mathbf{z}_i, \mathbf{z}_j) / \tau)}{\sum_{k=1}^{2N} \mathbf{1}_{[k \neq i]} \exp(\text{sim}(\mathbf{z}_i, \mathbf{z}_k) / \tau)}$$

where $\mathbf{z}_i, \mathbf{z}_j$ are hidden representations of two augmented views of the same example; $\text{sim}(u, v) = \frac{u^T v}{\|u\| \|v\|}$ is the cosine similarity between two vectors. τ is a temperature scalar and MB is a randomly sampled mini-batch consisting of augmented pairs of images.

In [6]: **import** solution

```
def simclr_loss(z1, z2):
    # z1 contains the first view for all examples and z2 the second view
    # this means that z1[i] and z2[i] correspond to the same original image
    # N = z1.shape[0]
    # use tau/temperature = 0.1

    # TODO: implement this
    simclr_loss = solution.simclr_loss(z1, z2, device=device, temperature=0.1)
    return simclr_loss
```

In [7]: *# Let's compute the simclr loss for random embeddings*
and for embeddings where the two views have exactly the same embedding
Our loss should be in this range during the optimization process
here you can test if your computation is efficient and gives the right loss range
The computation should take less than a second for the batch size below

```
torch.manual_seed(0)
z1 = torch.rand(size=(1024, 32)) - 0.5
z2 = torch.rand(size=(1024, 32)) - 0.5

random_loss = simclr_loss(z1, z2).item()
print('random loss', random_loss)

loss = simclr_loss(z1, z1).item()
print('views matching exactly', loss)
```

random loss 9.223624229431152
views matching exactly 0.3490881025791168

Augmentations

Given an image x , we want to create two views x_1 and x_2 which are created by augmenting the image x . The following torchvision augmentation does a random horizontal flip of the image and does a random resized crop. As the image is grayscale in this example, we do not do any color jitter augmentation.

In [8]: **augment** = T.Compose([T.RandomResizedCrop(28, scale=(0.1, 1.0),
interpolation=T.InterpolationMode('bicubic')),
T.RandomHorizontalFlip(),
T.ToTensor(),
T.Normalize((0.5,), (0.5,))
])

Task 2: Generate Two views (10P)

Implement the view generating torchvision transform below. Given a batch of images x , we want to generate two augmented versions of the image (views). Use the augment function to augment the image.


In [9]: **class** ViewTransform(object):

```
    # TODO implement this __call__ function to create
    # two views from the image x and return them as tuple
    def __call__(self, x):
        return solution.sample_two_views(x)
```

```
train_dataset.transform = ViewTransform()
```

In [10]: *# We show two views of the same image below, here you can test your implementation.*
torch.manual_seed(0)
random.seed(0)

```
(x1, x2), y = train_dataset[1]
fig, ax = plt.subplots(1, 2)
ax[0].imshow(x1[0], cmap='gray')
ax[0].set_title('View 1')
ax[0].axis('off')
ax[1].imshow(x2[0], cmap='gray')
ax[1].set_title('View 2')
ax[1].axis('off')
plt.show()
```



Training Loop

The following method contains the SimCLR training code. We use the data loader which generates two views for each image, pass the views through the encoder and the projection head and then compute the SimCLR loss.

```
In [11]: import torch.optim
import torch.nn
from tqdm.auto import tqdm
import os
import numpy as np

def train(loader, epochs=5):
    torch.manual_seed(0)
    random.seed(0)

    encoder = create_encoder()
    projection_head = create_projection_head()
    model = torch.nn.Sequential(encoder, projection_head)
    model = model.to(device)
    model.train()

    optimizer = torch.optim.SGD(model.parameters(), lr=0.3,
                                  momentum=0.9, weight_decay=0.0001,
                                  nesterov=True)

    i = 0
    for k in range(epochs):
        losses = []
        for (x1, x2), _ in tqdm(loader):
            optimizer.zero_grad()

            x1 = x1.to(device)
            x2 = x2.to(device)

            z1 = model(x1)
            z2 = model(x2)
            loss = simclr_loss(z1, z2)
            loss.backward()
            optimizer.step()

            i += 1
            losses.append(loss.detach().item())

        print(f'epoch: {k}, loss: {np.mean(losses)}')

        # save model after each epoch
        os.makedirs('models', exist_ok=True)
        torch.save(encoder.state_dict(), f'models/model_{k}.pt')

    return encoder
```

Run Training

Run the training loop for 5 epochs. This should take around 5 minutes on a cpu. We use a large batch size of 1024.

```
In [12]: train_loader = DataLoader(train_dataset, batch_size=1024, shuffle=True)
encoder = train(train_loader)
```

```
epoch: 0, loss: 5.465329509670451
epoch: 1, loss: 4.651930352388802
epoch: 2, loss: 4.345086946325787
epoch: 3, loss: 4.124221959356534
epoch: 4, loss: 3.962371195776988
```

```
In [13]: transform = T.Compose([T.ToTensor(), T.Normalize((0.5,), (0.5,))])
train_eval = FashionMNIST(data_root, train=True,
                           download=True, transform=transform)
test_eval = FashionMNIST(data_root, train=False,
                          download=True, transform=transform)
```

Task 3: Linear Probing (20P)

Now we want to test how good the encoder maps the images into semantically meaningful representations. Therefore, we compute the embeddings and then fit a linear classifier on top of the representations. Given the data loader and encoder, implement a method that extracts the embeddings/representations and corresponding labels. Run the linear classifier after this to check the quality of the embeddings. We evaluate the encoder after the first and last epoch.

```
In [14]: def compute_embeddings(dataset, encoder):
        dl = DataLoader(dataset, batch_size=32)
        # TODO: implement this function
        X, Y = solution.compute_embeddings(dl, encoder, device)
        return X, Y
```

```
In [15]: from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score
for k in [0, 4]:
    encoder = create_encoder()
    encoder.load_state_dict(torch.load(f'models/model_{k}.pt'))
    encoder.eval()

    xtrain, ytrain = compute_embeddings(train_eval, encoder)
    xtest, ytest = compute_embeddings(test_eval, encoder)

    clf = LogisticRegression(random_state=0, max_iter=1000, C=0.3)
    clf.fit(xtrain, ytrain)
    ypred = clf.predict(xtest)
    acc = accuracy_score(ytest, ypred)
    print(f"Accuracy: {acc}")
```

```
C:\Users\marco\AppData\Local\Temp\ipykernel_25144\774031215.py:5: FutureWarning: You are using `torch.load` with
`weights_only=False` (the current default value), which uses the default pickle module implicitly. It is possible
to construct malicious pickle data which will execute arbitrary code during unpickling (See https://github.com/py
torch/pytorch/blob/main/SECURITY.md#untrusted-models for more details). In a future release, the default value fo
r `weights_only` will be flipped to `True`. This limits the functions that could be executed during unpickling. A
rbitrary objects will no longer be allowed to be loaded via this mode unless they are explicitly allowlisted by t
he user via `torch.serialization.add_safe_globals`. We recommend you start setting `weights_only=True` for any us
e case where you don't have full control of the loaded file. Please open an issue on GitHub for any issues relate
d to this experimental feature.
```

```
encoder.load_state_dict(torch.load(f'models/model_{k}.pt'))
```

Accuracy: 0.7426

```
C:\Users\marco\AppData\Local\Temp\ipykernel_25144\774031215.py:5: FutureWarning: You are using `torch.load` with
`weights_only=False` (the current default value), which uses the default pickle module implicitly. It is possible
to construct malicious pickle data which will execute arbitrary code during unpickling (See https://github.com/py
torch/pytorch/blob/main/SECURITY.md#untrusted-models for more details). In a future release, the default value fo
r `weights_only` will be flipped to `True`. This limits the functions that could be executed during unpickling. A
rbitrary objects will no longer be allowed to be loaded via this mode unless they are explicitly allowlisted by t
he user via `torch.serialization.add_safe_globals`. We recommend you start setting `weights_only=True` for any us
e case where you don't have full control of the loaded file. Please open an issue on GitHub for any issues relate
d to this experimental feature.
```

```
encoder.load_state_dict(torch.load(f'models/model_{k}.pt'))
```

Accuracy: 0.781

We see that the linear probing accuracy improves during training. The numbers do not have to match exactly to the ones

provided in the pdf. We just want to see that the representation quality improves over the training time. Further training and a model with more capacity further increases the accuracy.