

# Project Configuration Report

## Question-2

### Target Device:

**Target Part: EFR32MG24B310F1536IM48**

Boards:

- EFR32xG24 Dev Kit Board (BRD2601B Rev A01)

### Target SDK

Simplicity SDK Suite v2025.12.2: Connect, Connect, EmberZNet 9.0.1.0, Multiprotocol 1.0.1.0, OpenThread 3.0.1.0 (GitHub-61e43cffb), Platform 5.2.0.0, SDK, Sidewalk 2.8.1, Silicon Labs AI/ML SDK 2.2.1, Silicon Labs Matter 2.8.1-1.5, Wi-Fi SDK 4.0.1-alpha.71, Z-Wave SDK 8.0.1.0  
SDK Version: 2025.12.2

### Project Generators

- VS Code (GCC)

### Installed Software Components:

- Application

- Utility

- Log**

- Sources: app\_log.c

- Configurable: true

- Configs: app\_log\_config.h

- Platform

- Board

- Starter Kit

- BRD2601B**

- Configurable: false

- Device

- EFR32MG24

- EFR32MG24B310F1536IM48**

- Sources: startup\_efr32mg24.c, system\_efr32mg24.c

- Configurable: true

- Configs: device.yaml

- Driver

- Button

- Simple Button**

- Configurable: true

- Configs: sl\_simple\_button\_btn0\_config.h

- LED

### Simple LED

Configurable: true

Configs: sl\_simple\_led\_led0\_config.h

## • Services

### - Clock Manager

#### Clock Manager

Sources: sl\_clock\_manager\_init.c

Configurable: true

Configs: sl\_clock\_manager\_oscillator\_config.h, sl\_clock\_manager\_ext\_flash\_config.h, sl\_clock\_manager\_tree\_config.h

### - Device Initialization

#### Automatic Device Initialization

Configurable: false

### - Power Manager

#### Power Manager

Configurable: true

Configs: sl\_power\_manager\_config.h

### - System Setup

#### System Setup (sl\_main)

Configurable: true

Configs: sl\_main\_start\_task\_config.h

## Pins:

## Peripherals:

| Peripheral | Software Component       | Custom Peripheral Name |
|------------|--------------------------|------------------------|
| ACMP0      |                          |                        |
| ACMP1      |                          |                        |
| CMU        | Clock Manager            |                        |
| EUSART0    | IO Stream: EUSART (vcom) |                        |
| EUSART1    | IO Stream: EUSART (vcom) |                        |
| GPIO       | SWO Debug                |                        |
| HFXO0      |                          |                        |
| I2C0       |                          |                        |
| I2C1       |                          |                        |
| IADC0      |                          |                        |
| KEYSCAN    |                          |                        |
| LETIMER0   |                          |                        |
| LFXO       |                          |                        |

|                      |  |  |
|----------------------|--|--|
| MODEM                |  |  |
| PCNT0                |  |  |
| PRS Channel ASYNCH0  |  |  |
| PRS Channel ASYNCH1  |  |  |
| PRS Channel ASYNCH10 |  |  |
| PRS Channel ASYNCH11 |  |  |
| PRS Channel ASYNCH12 |  |  |
| PRS Channel ASYNCH13 |  |  |
| PRS Channel ASYNCH14 |  |  |
| PRS Channel ASYNCH15 |  |  |
| PRS Channel ASYNCH2  |  |  |
| PRS Channel ASYNCH3  |  |  |
| PRS Channel ASYNCH4  |  |  |
| PRS Channel ASYNCH5  |  |  |
| PRS Channel ASYNCH6  |  |  |
| PRS Channel ASYNCH7  |  |  |
| PRS Channel ASYNCH8  |  |  |
| PRS Channel ASYNCH9  |  |  |
| PRS Channel SYNCH0   |  |  |
| PRS Channel SYNCH1   |  |  |
| PRS Channel SYNCH2   |  |  |
| PRS Channel SYNCH3   |  |  |
| PTI                  |  |  |
| TIMER0               |  |  |
| TIMER1               |  |  |
| TIMER2               |  |  |
| TIMER3               |  |  |
| TIMER4               |  |  |
| USART0               |  |  |
| VDAC0                |  |  |
| VDAC1                |  |  |