

# Smart Roads: Real-Time Pothole Detection

Samer Bujana, Rasmus Clausen, Alba Gonzalo, Robert Jarvi, Leonardo Rodovero




## INTRODUCTION

Potholes pose a serious threat to road safety, increasing the risk of accidents and causing significant damage to vehicles. In this project, we aim to develop an advanced deep-learning object detection system capable of automatically identifying potholes in images captured from real-world environments. To achieve this, we will leverage a Region-based Convolutional Neural Network (RCNN) architecture, utilizing Selective Search (SS) and Edge Boxes as region proposal methods. This innovative approach addresses the challenges of detecting and mitigating potholes, ultimately contributing to safer and more reliable road conditions.

## ENCODER-DECODER PROPOSAL EXTRACTION



When analysing the resolutions of the images we found a big difference between individual images, With the largest images being 720x720, while the smallest are around 300 in width or lower. This means that rescaling the pictures to the same resolution breaks a lot of details. We choose instead to not rescale the images before running Selective Search.



Threshold used to determine a match for recall and ABO calculation:  $k = 0.5$ .

$$Recall = \frac{Number of True Positives}{Total Number of Ground Truth Objects}$$


$$IoU = \frac{Area of Intersection}{Area of Union}$$

$$ABO = \frac{1}{N} \sum_{g_i^c \in G^c} \max_{l_j \in L} (IoU(g_i^c, l_j))$$

## SELECTIVE SEARCH

Used the fast mode of SS, and tune-up the proposals by changing the different parameters:


- **MinSize:** Minimum size of segments.
- **Scale (k):** Controls the level of segmentation for selective search.
- **Sigma:** Smoothness parameter for the selective search segmentation.



## EDGE BOXES

Tune-up the proposals by changing the different parameters:

- **Alpha:** Finer granularity in sliding window. Set to 0.8.
- **Beta:** Increased sensitivity to edge density. Set to 0.6.
- **minScore:** Minimum score for boxes. Set to 0.05.
- **maxBoxes:** Allow more proposals for potential potholes.



**Better proposals were obtained using SS.** The maximum Recall and ABO are achieved with **1200** proposals, beyond which increasing the number of proposals appears to yield no significant improvement.

## DATA AND CLASS IMBALANCE


- Data attributes:**

  - 665 images, not already split .
  - Image and grounded boxes provided.
  - Original image resolution 720x720. The different proposals are resized to 64x64.
  - 70-15-15 Train / Validation / Test split.
- Data transformations (Data Augmentation):**


  - RandomGrayScale
    - p: 0.1
  - ColorJitter
    - Brightness: 0.2, Contrast: 0.2
    - Saturation: 0.2, Hue: 0.1
  - Normalization
    - mean: (0.485, 0.456, 0.406)
    - std: (0.229, 0.224, 0.225)

**Class imbalance** was addressed through batch sampling, ensuring that each batch contains a sufficient number of foreground objects, with a 50-50 split. Instead of using all background proposals for training, random background proposals are selected for each batch.

## CNN ARCHITECTURE



## CLASSIFICATION ACCURACY




**Average Validation Accuracy 86.9 %:** Indicates that the model correctly predicts the presence or absence of potholes for most proposals.

## POTHOLE DETECTION EVALUATION

<b>TP</b> 399879	<b>FN</b> 99851
<b>FP</b> 2553	<b>TN</b> 10107

Non-Maximum Suppression (NMS) is implemented to discard overlapping bounding boxes, keeping only the most relevant ones. The model's performance is then evaluated using the Average Precision (AP) metric, which provides a comprehensive measure of detection accuracy.



**Average Precision AP = 0.4078:** show room for improvement in distinguishing true positives from false positives.