

Compact Electro-Pneumatic Regulator ITV0000 Series



How to Order

For single unit and single unit for manifold

ITV00 **1** **0** - **0** [] [] [] **N**

Pressure range

1	0.1 MPa
3	0.5 MPa
5	0.9 MPa

Power supply voltage

0	24 VDC $\pm 10\%$
1	12 to 15 VDC

Input signal

0	Current type 4 to 20 mA DC (Sink type)
1	Current type 0 to 20 mA DC (Sink type)
2	Voltage type 0 to 5 VDC
3	Voltage type 0 to 10 VDC

Built-in One-touch fittings type

For single unit

	Symbol	SUP. [1]	OUT. [2]	EXH. [3]
NII	Metric size (Light gray)		$\phi 4$	
U	Inch size (Orange)		$\phi 5/32"$	



For manifold

	Symbol	SUP. [1]	OUT. [2]	EXH. [3]
NII	Metric size (Light gray)	$\phi 6$	$\phi 4$	$\phi 6$
U	Inch size (Orange)	$\phi 1/4"$	$\phi 5/32"$	$\phi 1/4"$

Cable connector (Option)

N	Without cable connector
S	Straight type 3 m
L	Right angle type 2 m

Bracket/Option for single unit only

NII	Without bracket
B	Flat Bracket 
C	L-bracket 

Base type

NII	For single unit
M	For manifolds

Manifold

IITV00 - **02** [] - **n**

Stations

02	2 stations
03	3 stations
:	:
10	10 stations

Option

If a DIN rail longer than the specified stations is required, specify the applicable stations in two digits.
(Maximum 10 stations)
Example) IITV00-05-07

One-touch fitting size for supply/exhaust parts (End plate)

NII	$\phi 6$ (Light gray)
U	$\phi 1/4"$ (Orange)

Note) A DIN rail with the length specified by the number of stations is attached to the manifold. For dimensions of the DIN rail, refer to the external dimensions.

How to Order Manifold Assembly (Example)

Indicate the part numbers of electro-pneumatic regulators to be mounted below the manifold part number.

Example)

Due to the common supply/exhaust feature, note that different pressure range combinations are not available.

IITV00-03.....1 set (Manifold part no.)

*ITV0030-3MS.....2 sets (Electro-pneumatic regulator part no. (1, 2 stations))

*ITV0030-3ML.....1 set (Electro-pneumatic regulator part no. (3 stations))

Indicate part numbers in order starting from the first station on the D side.

Note) Combination with having different pressure ranges is not available due to common supply/exhaust features.

The asterisk (*) specifies mounting. Add an asterisk (*) at the beginning of electro-pneumatic regulator part numbers to be mounted.

