

Rock Lee do Pagode Namora D+

University of Brasilia

Contents

0.1	Template	3	3.6	Blossom Algorithm for Weighted General Matching	16
1	Data Structures	3	3.7	Small to Large	18
1.1	Merge Sort Tree	3	3.8	Centroid Decomposition	18
1.2	Fenwick Tree 2D	3	3.9	Kosaraju	18
1.3	Wavelet Tree	3	3.10	Tarjan	18
1.4	Order Set	4	3.11	Max Clique	18
1.5	Hash table	4	3.12	Dominator Tree	19
1.6	Convex Hull Trick Simple	4	3.13	Min Cost Matching	19
1.7	Convex Hull Trick	4	4	Strings	20
1.8	Convex Hull Trick	5	4.1	Aho Corasick	20
1.9	Min queue	5	4.2	Suffix Array	20
1.10	Sparse Table	5	4.3	Adamant Suffix Tree	20
1.11	Treap	5	4.4	Z Algorithm	21
1.12	ColorUpdate	6	4.5	Prefix function/KMP	21
1.13	Heavy Light Decomposition	6	4.6	Min rotation	21
1.14	Iterative Segtree	7	4.7	Manacher	21
1.15	Recursive Segtree + lazy	7	4.8	Suffix Automaton	21
1.16	LiChao's Segtree	7	4.9	Suffix Tree	22
1.17	Palindromic tree	8	5	Geometry	22
2	Math	8	5.1	2D basics	22
2.1	Extended Euclidean Algorithm	8	5.2	Circle line intersection	24
2.2	Chinese Remainder Theorem	8	5.3	Half plane intersection	24
2.3	Diophantine Solver	8	5.4	Detect empty Half plane intersection	25
2.4	Prefix inverse	9	5.5	Circle Circle intersection	25
2.5	Pollard Rho	9	5.6	Tangents of two circles	25
2.6	Miller Rabin	9	5.7	Convex Hull	25
2.7	Totiente	9	5.8	Check point inside polygon	26
2.8	Primitive root	9	5.9	Check point inside polygon without lower/up- per hull	26
2.9	Mobius Function	10	5.10	Minkowski sum	26
2.10	Mulmod TOP	10	5.11	Geo Notes	26
2.11	Modular multiplication TOPPER	10	5.11.1	Center of mass	26
2.12	Division Trick	10	5.11.2	Pick's Theorem	26
2.13	Matrix Determinant	10	6	Miscellaneous	26
2.14	Simplex Method	10	6.1	LIS	26
2.15	FFT	11	6.2	DSU rollback	26
2.16	FFT Tourist	11	6.3	Buildings	27
2.17	NTT	12	6.4	Rand	27
2.18	Gauss	13	6.5	Klondike	27
2.19	Gauss Xor	13	6.6	Hilbert Order	27
2.20	Simpson	13	6.7	Modular Factorial	28
2.21	Modular Arithmetic	13	6.8	Enumeration all submasks of a bitmask	28
2.22	Matrix	14	6.9	Slope Trick	28
3	Graphs	14	6.10	Knapsack Bounded with Cost	28
3.1	Bipartite Matching	14	6.11	LCA $<O(n \lg n), O(1)>$	28
3.2	Dinic	14	6.12	Buffered reader	28
3.3	Push relabel	15	6.13	Modular summation	28
3.4	Min Cost Max Flow	15	6.14	Edge coloring CPP	29
3.5	Blossom Algorithm for General Matching	15	6.15	Burnside's Lemma	29

6.16 Wilson's Theorem	29
6.17 Fibonacci	29
6.18 Lucas's Theorem	29
6.19 Kirchhoff's Theorem	29
6.19.1 Multigraphs	29
6.19.2 Directed multigraphs	29
6.20 Matroid	30
6.20.1 Matroid intersection	30
6.20.2 Matroid Union	30
6.21 Notes	30

```
set ts=4 sw=4 sta nu rnu sc stl+=%F cindent
set bg=dark ruler timeoutlen=100
imap {<CR> {<CR>}<Esc>O
nmap <F2> 0V$%d
nmap <C-down> :m+1<CR>
nmap <C-up> :m-2<CR>
nmap <C-a> ggVG
vmap <C-c> "+y
syntax on
alias cmp='g++ -Wall -Wformat=2 -Wshadow -Wconversion -
fsanitize=address -fsanitize=undefined -fno-sanitize-
recover -std=c++14'
```

Template

```
#include <bits/stdc++.h>

#define ff first
#define ss second
#define pb push_back

using namespace std;
using ll = long long;
using ii = pair<int, int>;

const int N = 100005;

int main() {

    return 0;
}
```

Data Structures

Merge Sort Tree

```
struct MergeTree{
    int n;
    vector<vector<int>> st;

    void build(int p, int L, int R, const int v[]){
        if(L == R){
            st[p].push_back(v[L]);
            return;
        }
        int mid = (L+R)/2;
        build(2*p, L, mid, v);
        build(2*p+1, mid+1, R, v);
        st[p].resize(R-L+1);
        merge(st[2*p].begin(), st[2*p].end(),
              st[2*p+1].begin(), st[2*p+1].end(),
              st[p].begin());
    }

    int query(int p, int L, int R, int i, int j, int x)
    const{
```

```
        if(L > j || R < i) return 0;
        if(L >= i && R <= j){
            int id = lower_bound(st[p].begin(), st[p].end()
                                (), x) - st[p].begin();
            return int(st[p].size()) - id;
        }
        int mid = (L+R)/2;
        return query(2*p, L, mid, i, j, x) +
               query(2*p+1, mid+1, R, i, j, x);
    }

public:
    MergeTree(int sz, const int v[]): n(sz), st(4*sz){
        build(1, 1, n, v);
    }

    //number of elements >= x on segment [i, j]
    int query(int i, int j, int x) const{
        if(i > j) swap(i, j);
        return query(1, 1, n, i, j, x);
    }
};
```

Fenwick Tree 2D

```
vector<int> go[N];
vector<int> ft[N];

void prec_add(int x, int y) {
    for(; x < N; x += x & -x) {
        go[x].push_back(y);
    }
}

void init() {
    for(int i = 1; i < N; i++) {
        sort(go[i].begin(), go[i].end());
        ft[i].assign(go[i].size() + 1, 0);
    }
}

void add(int x, int y, int val) {
    for(; x < N; x += x & -x) {
        int id = int(upper_bound(go[x].begin(), go[x].end()
                                (), y) - go[x].begin());
        for(; id < (int)ft[x].size(); id += id & -id)
            ft[x][id] += val;
    }
}

int sum(int x, int y) {
    int ans = 0;
    for(; x > 0; x -= x & -x) {
        int id = int(upper_bound(go[x].begin(), go[x].end()
                                (), y) - go[x].begin());
        for(; id > 0; id -= id & -id)
            ans += ft[x][id];
    }
    return ans;
}
```

Wavelet Tree

```
template<typename T>
class wavelet{
    T L, R;
    vector<int> l;
    vector<T> sum; // <<
    wavelet *lef, *rig;

    int r(int i) const{ return i - l[i]; }
}
```

```

public:
    template<typename ITER>
    wavelet(ITER bg, ITER en){
        lef = rig = nullptr;
        L = *bg, R = *bg;

        for(auto it = bg; it != en; it++){
            L = min(L, *it), R = max(R, *it);
        }
        if(L == R) return;

        T mid = L + (R - L)/2;
        l.reserve(std::distance(bg, en) + 1);
        sum.reserve(std::distance(bg, en) + 1);
        l.push_back(0), sum.push_back(0);
        for(auto it = bg; it != en; it++){
            l.push_back(l.back() + (*it <= mid)),
            sum.push_back(sum.back() + *it);
        }

        auto tmp = stable_partition(bg, en, [mid](T x){
            return x <= mid;
        });

        if(bg != tmp) lef = new wavelet(bg, tmp);
        if(tmp != en) rig = new wavelet(tmp, en);
    }
    ~wavelet(){
        delete lef;
        delete rig;
    }
    // 1 index, first is 1st
    T kth(int i, int j, int k) const{
        if(L >= R) return L;
        int c = l[j] - l[i-1];
        if(c >= k) return lef->kth(l[i-1]+1, l[j], k);
        else return rig->kth(r(i-1)+1, r(j), k - c);
    }
    // # elements > x on [i, j]
    int cnt(int i, int j, T x) const{
        if(L > x) return j - i + 1;
        if(R <= x || L == R) return 0;
        int ans = 0;
        if(lef) ans += lef->cnt(l[i-1]+1, l[j], x);
        if(rig) ans += rig->cnt(r(i-1)+1, r(j), x);
        return ans;
    }
    // sum of elements <= k on [i, j]
    T sumk(int i, int j, T k){
        if(L == R) return R <= k ? L * (j - i + 1) : 0;
        if(R <= k) return sum[j] - sum[i-1];
        int ans = 0;
        if(lef) ans += lef->sumk(l[i-1]+1, l[j], k);
        if(rig) ans += rig->sumk(r(i-1)+1, r(j), k);
        return ans;
    }
    // swap (i, i+1) just need to update "array" l[i]
};

```

Order Set

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

#include <ext/pb_ds/detail/standard_policies.hpp>

using namespace __gnu_pbds; // or pb_ds;

template<typename T, typename B = null_type>
using oset = tree<T, B, less<T>, rb_tree_tag,

```

```

    tree_order_statistics_node_update>;
// find_by_order / order_of_key

Hash table

#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;

struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM = chrono::
            steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};

gp_hash_table<long long, int, custom_hash> table;
unordered_map<long long, int, custom_hash> uhash;
uhash.reserve(1 << 15);
uhash.max_load_factor(0.25);

Convex Hull Trick Simple

struct Line{
    ll m, b;
    inline ll eval(ll x) const{
        return x * m + b;
    }
};

// min => cht.back().m >= L.m
// max => cht.back().m <= L.m
void push_line(vector<Line> &cht, Line L){
    while((int)cht.size() >= 2){
        int sz = (int)cht.size();
        if((long double)(L.b-cht[sz-1].b)*(cht[sz-2].m-L.m)
            <= (long double)(L.b-cht[sz-2].b)*(cht[sz-1].m-L.m)){
            cht.pop_back();
        }
        else break;
    }
    cht.push_back(L);
}

// x increasing; pos = 0 in first call
ll linear_search(const vector<Line> &cht, ll x, int &pos){
    while(pos+1 < (int)cht.size()){
        /*>>*/ if(cht[pos].eval(x) >= cht[pos+1].eval(x)) pos++;
        else break;
    }
    return cht[pos].eval(x);
}

ll binary_search(const vector<Line> &cht, ll x){
    int L = 0, R = (int)cht.size()-2;
    int bans = (int)cht.size()-1;
    while(L <= R){
        int mid = (L+R)/2;
        if(cht[mid].eval(x) >= cht[mid+1].eval(x)) // <<<
            L = mid + 1;
        else bans = mid, R = mid - 1;
    }
}

```

```

    }
    return cht[bans].eval(x);
}

```

Convex Hull Trick

```

const ll is_query = -(1LL<<62);
struct Line{
    ll m, b;
    mutable function<const Line*> succ;
    bool operator<(const Line& rhs) const{
        if(rhs.b != is_query) return m < rhs.m;
        const Line* s = succ();
        if(!s) return 0;
        ll x = rhs.m;
        return b - s->b < (s->m - m) * x;
    }
};
struct Cht : public multiset<Line>{ // maintain max
    bool bad(iterator y){
        auto z = next(y);
        if(y == begin()){
            if(z == end()) return 0;
            return y->m == z->m && y->b <= z->b;
        }
        auto x = prev(y);
        if(z == end()) return y->m == x->m && y->b <= x->b;
        return (long double)(x->b - y->b)*(z->m - y->m)
            >= (long double)(y->b - z->b)*(y->m - x->m);
    }
    void insert_line(ll m, ll b){
        auto y = insert({m, b});
        y->succ = [=]{ return next(y) == end() ? 0 : &*
            next(y); };
        if(bad(y)){ erase(y); return; }
        while(next(y) != end() && bad(next(y))) erase(
            next(y));
        while(y != begin() && bad(prev(y))) erase(prev(y)
        );
    }
    ll eval(ll x){
        auto l = *lower_bound((Line) { x, is_query });
        return l.m * x + l.b;
    }
};

```

Convex Hull Trick

```

/**
 * Author: Simon Lindholm
 * source: https://github.com/kth-competitive-
 * programming/kactl/blob/master/content/data-structures
 * /LineContainer.h
 * License: CC0
 */

```

```

struct Line {
    mutable ll m, b, p;
    bool operator<(const Line& o) const { return m < o.m
        ; }
    bool operator<(ll x) const { return p < x; }
};

```

```

struct LineContainer : multiset<Line, less<>> { // CPP14
    only
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division

```

```

        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = inf; return false; }
        if (x->m == y->m) x->p = x->b > y->b ? inf : -inf
            ;
        else x->p = div(y->b - x->b, x->m - y->m);
        return x->p >= y->p;
    }
    void add(ll m, ll b) {
        auto z = insert({m, b, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y =
            erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.m * x + l.b;
    }
};

```

Min queue

```

template<typename T>
class minQ{
    deque<tuple<T, int, int> > p;
    T delta;
    int sz;
public:
    minQ() : delta(0), sz(0) {}
    inline int size() const{ return sz; }
    inline void add(T x){ delta += x; }
    inline void push(T x, int id){
        x -= delta, sz++;
        int t = 1;
        while(p.size() > 0 && get<0>(p.back()) >= x)
            t += get<1>(p.back()), p.pop_back();
        p.emplace_back(x, t, id);
    }
    inline void pop(){
        get<1>(p.front())--, sz--;
        if(!get<1>(p.front())) p.pop_front();
    }
    T getmin() const{ return get<0>(p.front())+delta; }
    int getid() const{ return get<2>(p.front()); }
};

```

Sparse Table

```

int fn(int i, int j){
    if(j == 0) return v[i];
    if(~dn[i][j]) return dn[i][j];
    return dn[i][j] = min(fn(i, j-1), fn(i + (1 << (j-1)
        ), j-1));
}

```

```

int getmn(int l, int r){ // [l, r]
    int lz = lg(r - l + 1);
    return min(fn(l, lz), fn(r - (1 << lz) + 1, lz));
}

```

Treap

```

// source: https://github.com/victorsenam/caderno/blob/
// master/code/treap.cpp
//const int N = ; typedef int num;
num X[N]; int en = 1, Y[N], sz[N], L[N], R[N];
void calc (int u) { // update node given children info

```

```

    if(!u) return;
    sz[u] = sz[L[u]] + 1 + sz[R[u]];
    // code here, no recursion
}
void unlaze (int u) {
    if(!u) return;
    // code here, no recursion
}
void split_val(int u, num x, int &l, int &r) { // l gets
    <= x, r gets > x
    unlaze(u); if(!u) return (void) (l = r = 0);
    if(X[u] <= x) { split_val(R[u], x, l, r); R[u] = l;
        l = u; }
    else { split_val(L[u], x, l, r); L[u] = r; r = u; }
    calc(u);
}
void split_sz(int u, int s, int &l, int &r) { // l gets
    first s, r gets remaining
    unlaze(u); if(!u) return (void) (l = r = 0);
    if(sz[L[u]] < s) { split_sz(R[u], s - sz[L[u]] - 1,
        l, r); R[u] = l; l = u; }
    else { split_sz(L[u], s, l, r); L[u] = r; r = u; }
    calc(u);
}
int merge(int l, int r) { // els on l <= els on r
    unlaze(l); unlaze(r); if(!l || !r) return l + r; int
    u;
    if(Y[l] > Y[r]) { R[l] = merge(R[l], r); u = l; }
    else { L[r] = merge(l, L[r]); u = r; }
    calc(u); return u;
}
void init(int n=N-1) { // XXX call before using other
    funcs
    for(int i = en = 1; i <= n; i++) { Y[i] = i; sz[i] =
        1; L[i] = R[i] = 0; }
    random_shuffle(Y + 1, Y + n + 1);
}
void insert(int &u, int it){
    unlaze(u);
    if(!u) u = it;
    else if(Y[it] > Y[u]) split_val(u, X[it], L[it], R[
        it]), u = it;
    else insert(X[it] < X[u] ? L[u] : R[u], it);
    calc(u);
}
void erase(int &u, num key){
    unlaze(u);
    if(!u) return;
    if(X[u] == key) u = merge(L[u], R[u]);
    else erase(key < X[u] ? L[u] : R[u], key);
    calc(u);
}
int create_node(num key){
    X[en] = key;
    sz[en] = 1;
    L[en] = R[en] = 0;
    return en++;
}
int query(int u, int l, int r){//0 index
    unlaze(u);
    if(u! or r < 0 or l >= sz[u]) return
        identity_element;
    if(l <= 0 and r >= sz[u] - 1) return subt_data[u];
    int ans = query(L[u], l, r);
    if(l <= sz[ L[u] ] and sz[ L[u] ] <= r)
        ans = max(ans, st[u]);
    ans = max(ans, query(R[u], l-sz[L[u]]-1, r-sz[L[u]

```

```

    ]-1));
    return ans;
}

```

ColorUpdate

// source: <https://github.com/tfg50/Competitive-Programming/tree/master/Biblioteca/Data%20Structures>

```

#include <set>
#include <vector>

template <class Info = int>
class ColorUpdate {
public:
    struct Range {
        Range(int l = 0) { this->l = l; }
        Range(int l, int r, Info v) {
            this->l = l;
            this->r = r;
            this->v = v;
        }
        int l, r;
        Info v;

        bool operator < (const Range &b) const { return l
            < b.l; }
    };

    std::vector<Range> upd(int l, int r, Info v) {
        std::vector<Range> ans;
        if(l >= r) return ans;
        auto it = ranges.lower_bound(l);
        if(it != ranges.begin()) {
            it--;
            if(it->r > l) {
                auto cur = *it;
                ranges.erase(it);
                ranges.insert(Range(cur.l, l, cur.v));
                ranges.insert(Range(l, cur.r, cur.v));
            }
            it = ranges.lower_bound(r);
            if(it != ranges.begin()) {
                it--;
                if(it->r > r) {
                    auto cur = *it;
                    ranges.erase(it);
                    ranges.insert(Range(cur.l, r, cur.v));
                    ranges.insert(Range(r, cur.r, cur.v));
                }
            }
            for(it = ranges.lower_bound(l); it != ranges.end
                () && it->l < r; it++) {
                ans.push_back(*it);
            }
            ranges.erase(ranges.lower_bound(l), ranges.
                lower_bound(r));
            ranges.insert(Range(l, r, v));
            return ans;
        }
    private:
        std::set<Range> ranges;
    };
}

```

Heavy Light Decomposition

```

void dfs_sz(int u){
    sz[u] = 1;

```

```

    for(auto &v : g[u]) if(v == p[u]){
        swap(v, g[u].back()); g[u].pop_back();
        break;
    }
    for(auto &v : g[u]){
        p[v] = u; dfs_sz(v); sz[u] += sz[v];
        if(sz[v] > sz[ g[u][0] ])
            swap(v, g[u][0]);
    }
}
// nxt[u] = start of path with u
// set nxt[root] = root beforehand
void dfs_hld(int u){
    in[u] = t++;
    rin[in[u]] = u;
    for(auto v : g[u]){
        nxt[v] = (v == g[u][0] ? nxt[u] : v); dfs_hld(v);
    }
    out[u] = t;
}
// subtree of u => [ in[u], out[u] )
// path from nxt[u] to u => [ in[ nxt[u] ], in[u] ]

```

Iterative Segtree

```

T query(int l, int r){ // [l, r]
    T rl, rr;
    for(l += n, r += n+1; l < r; l >>= 1, r >>= 1){
        if(l & 1) rl = merge(rl, st[l++]);
        if(r & 1) rr = merge(st[--r], rr);
    }
    return merge(rl, rr);
}

// initially save v[i] in st[n+i] for all i in [0, n)
void build(){
    for(int p = n-1; p > 0; p--){
        st[p] = merge(st[2*p], st[2*p+1]);
    }

    void update(int p, T val){
        st[p += n] = val;
        while(p >>= 1) st[p] = merge(st[2*p], st[2*p+1]);
    }
}

```

Recursive Segtree + lazy

```

class SegTree{
    vi st;
    vi lazy;
    int size;

    int el_neutro = -oo;

    inline int f(int a, int b){
        return max(a,b);
    }

    inline int left(int i) {return 2 * i + 1;};
    inline int right(int i) {return 2 * i + 2;};
    void build(int sti, int stl, int str, vi& nums) {
        if(stl == str) {
            st[sti] = nums[stl];
            return;
        }
        int mid = (stl + str) / 2;
        build(left(sti), stl, mid, nums);
        build(right(sti), mid + 1, str, nums);
        st[sti] = f(st[left(sti)], st[right(sti)]);
    }
}

```

```

void propagate(int sti, int stl, int str){
    if(lazy[sti]){
        st[sti] += lazy[sti];
        if(stl != str)
        {
            lazy[left(sti)] += lazy[sti];
            lazy[right(sti)] += lazy[sti];
        }
        lazy[sti] = 0;
    }
}

int query(int sti, int stl, int str, int l, int r){
    propagate(sti, stl, str);

    if(str < l || r < stl)
        return el_neutro;

    if(stl >= l and str <= r)
        return st[sti];

    int mid = (str+stl)/2;

    return f(query(left(sti),stl,mid,l,r),query(right
        (sti),mid+1,str,l,r));
}

void update_range(int sti, int stl, int str, int l,
    int r, int ammm){
    propagate(sti, stl, str);
    if(stl >= l and str <= r){
        lazy[sti] = ammm;
        propagate(sti, stl, str);
        return;
    }
    if(stl > r or str < l)
        return;
    int mid = (stl + str)/2;
    update_range(left(sti),stl,mid,l,r,ammm);
    update_range(right(sti),mid+1,str,l,r,ammm);
    st[sti] = f(st[left(sti)],st[right(sti)]);
}

void update(int sti, int stl, int str, int i, int
    ammm){
    propagate(sti, stl, str);
    if(stl == i and str == i){
        st[sti] = ammm;
        return;
    }
    if(stl > i or str < i)
        return;
    int mid = (stl + str)/2;
    update(left(sti),stl,mid,i,ammm);
    update(right(sti),mid+1,str,i,ammm);
    st[sti] = f(st[left(sti)],st[right(sti)]);
}

public:
    SegTree(vi& v) : st(4*v.size(),0), lazy(4*v.size
        (),0) {size = v.size(); build(0,0,size - 1, v)
        ;}
    SegTree(int n) : st(4*n,0), lazy(4*n,0){size = n
        ;}
    int query(int l, int r){return query(0,0,size-1,l
        ,r);}
    void update_range(int l, int r, int ammm){
        update_range(0,0,size-1,l,r,ammm);}
    void update(int i, int ammm){update(0,0,size-1,i,

```

```
    amm);}
};
```

LiChao's Segtree

```
void add_line(line nw, int v = 1, int l = 0, int r =
    maxn) { // [l, r)
    int m = (l + r) / 2;
    bool lef = nw.eval(l) < st[v].eval(l);
    bool mid = nw.eval(m) < st[v].eval(m);
    if(mid) swap(st[v], nw);
    if(r - l == 1) {
        return;
    } else if(lef != mid) {
        add_line(nw, 2 * v, l, m);
    } else {
        add_line(nw, 2 * v + 1, m, r);
    }
}

int get(int x, int v = 1, int l = 0, int r = maxn) {
    int m = (l + r) / 2;
    if(r - l == 1) {
        return st[v].eval(x);
    } else if(x < m) {
        return min(st[v].eval(x), get(x, 2*v, l, m));
    } else {
        return min(st[v].eval(x), get(x, 2*v+1, m, r));
    }
}
```

Palindromic tree

```
#include <bits/stdc++.h>
```

```
using namespace std;
```

```
const int maxn = 3e5 + 1, sigma = 26;
int len[maxn], link[maxn], to[maxn][sigma];
int slink[maxn], diff[maxn], series_ans[maxn];
int sz, last, n;
char s[maxn];
```

```
void init()
{
    s[n++] = -1;
    link[0] = 1;
    len[1] = -1;
    sz = 2;
}
```

```
int get_link(int v)
{
    while(s[n - len[v] - 2] != s[n - 1]) v = link[v];
    return v;
}
```

```
void add_letter(char c)
{
    s[n++] = c - 'a';
    last = get_link(last);
    if(!to[last][c])
    {
        len[sz] = len[last] + 2;
        link[sz] = to[get_link(link[last])][c];
        diff[sz] = len[sz] - len[link[sz]];
        if(diff[sz] == diff[link[sz]])
            slink[sz] = slink[link[sz]];
        else
```

```
            slink[sz] = link[sz];
            to[last][c] = sz++;
    }
    last = to[last][c];
}

int main()
{
    ios::sync_with_stdio(0);
    cin.tie(0);
    init();
    string s;
    cin >> s;
    int n = s.size();
    int ans[n + 1];
    memset(ans, 63, sizeof(ans));
    ans[0] = 0;
    for(int i = 1; i <= n; i++)
    {
        add_letter(s[i - 1]);
        for(int v = last; len[v] > 0; v = slink[v])
        {
            series_ans[v] = ans[i - (len[slink[v]] + diff
                [v])];
            if(diff[v] == diff[link[v]])
                series_ans[v] = min(series_ans[v],
                    series_ans[link[v]]);
            ans[i] = min(ans[i], series_ans[v] + 1);
        }
        cout << ans[i] << "\n";
    }
    return 0;
}
```

Math

Extended Euclidean Algorithm

```
// a*x + b*y = gcd(a, b), <gcd, x, y>
tuple<int, int, int> gcd(int a, int b) {
    if(b == 0) return make_tuple(a, 1, 0);
    int q, w, e;
    tie(q, w, e) = gcd(b, a % b);
    return make_tuple(q, e, w - e * (a / b));
}
```

Chinese Remainder Theorem

```
// x = vet[i].first (mod vet[i].second)
ll crt(const vector<pair<ll, ll>> &vet){
    ll ans = 0, lcm = 1;
    ll a, b, g, x, y;
    for(const auto &p : vet) {
        tie(a, b) = p;
        tie(g, x, y) = gcd(lcm, b);
        if((a - ans) % g != 0) return -1; // no solution
        ans = ans + x * ((a - ans) / g) % (b / g) * lcm;
        lcm = lcm * (b / g);
        ans = (ans % lcm + lcm) % lcm;
    }
    return ans;
}
```

Diophantine Solver

```
template<typename T>
T extgcd(T a, T b, T &x, T &y) {
    if (a == 0) {
        x = 0;
```

```

    y = 1;
    return b;
}
T p = b / a;
T g = extgcd(b - p * a, a, y, x);
x -= p * y;
return g;
}

template<typename T>
bool diophantine(T a, T b, T c, T &x, T &y, T &g) {
    if (a == 0 && b == 0) {
        if (c == 0) {
            x = y = g = 0;
            return true;
        }
        return false;
    }
    if (a == 0) {
        if (c % b == 0) {
            x = 0;
            y = c / b;
            g = abs(b);
            return true;
        }
        return false;
    }
    if (b == 0) {
        if (c % a == 0) {
            x = c / a;
            y = 0;
            g = abs(a);
            return true;
        }
        return false;
    }
    g = extgcd(a, b, x, y);
    if (c % g != 0) {
        return false;
    }
    T dx = c / a;
    c -= dx * a;
    T dy = c / b;
    c -= dy * b;
    x = dx + mulmod(x, c / g, b);
    y = dy + mulmod(y, c / g, a);
    g = abs(g);
    return true;
}

```

Prefix inverse

```

inv[1] = 1;
for(int i = 2; i < p; i++)
    inv[i] = (p - (p/i) * inv[p%i] % p) % p;

```

Pollard Rho

```

ll rho(ll n){
    if(n % 2 == 0) return 2;
    ll d, c, x, y;
    do{
        c = llrand() % n, x = llrand() % n, y = x;
        do{
            x = add(mul(x, x, n), c, n);
            y = add(mul(y, y, n), c, n);
            y = add(mul(y, y, n), c, n);
            d = __gcd(abs(x - y), n);
        }while(d == 1);
    }
}

```

```

    }while(d == n);
    return d;
}
ll pollard_rho(ll n){
    ll x, c, y, d, k;
    int i;
    do{
        i = 1;
        x = llrand() % n, c = llrand() % n;
        y = x, k = 4;
        do{
            if(++i == k) y = x, k *= 2;
            x = add(mul(x, x, n), c, n);
            d = __gcd(abs(x - y), n);
        }while(d == 1);
    }while(d == n);
    return d;
}
void factorize(ll val, map<ll, int> &fac){
    if(rabin(val)) fac[ val ]++;
    else{
        ll d = pollard_rho(val);
        factorize(d, fac);
        factorize(val / d, fac);
    }
}
map<ll, int> factor(ll val){
    map<ll, int> fac;
    if(val > 1) factorize(val, fac);
    return fac;
}

```

Miller Rabin

```

bool rabin(ll n){
    if(n <= 1) return 0;
    if(n <= 3) return 1;
    ll s = 0, d = n - 1;
    while(d % 2 == 0) d /= 2, s++;
    for(int k = 0; k < 64; k++){
        ll a = (llrand() % (n - 3)) + 2;
        ll x = fexp(a, d, n);
        if(x != 1 && x != n-1){
            for(int r = 1; r < s; r++){
                x = mul(x, x, n);
                if(x == 1) return 0;
                if(x == n-1) break;
            }
            if(x != n-1) return 0;
        }
    }
    return 1;
}

```

Totiente

```

ll totiente(ll n){
    ll ans = n;
    for(ll i = 2; i*i <= n; i++){
        if(n % i == 0){
            ans = ans / i * (i - 1);
            while(n % i == 0) n /= i;
        }
    }
    if(n > 1) ans = ans / n * (n - 1);
    return ans;
}

```


Primitive root

```
// a primitive root modulo n is any number g such that
// any c coprime to n is congruent to a power of g modulo
// n.
bool exists_root(ll n){
    if(n == 1 || n == 2 || n == 4) return true;
    if(n % 2 == 0) n /= 2;
    if(n % 2 == 0) return false;
    // test if n is a power of only one prime
    for(ll i = 3; i * i <= n; i += 2) if(n % i == 0){
        while(n % i == 0) n /= i;
        return n == 1;
    }
    return true;
}

ll primitive_root(ll n){
    if(n == 1 || n == 2 || n == 4) return n - 1;
    if(not exists_root(n)) return -1;
    ll x = phi(n);
    auto pr = factorize(x);
    auto check = [x, n, pr](ll m){
        for(ll p : pr) if(fexp(m, x / p, n) == 1)
            return false;
        return true;
    };
    for(ll m = 2; ; m++) if(__gcd(m, n) == 1)
        if(check(m)) return m;
}

// Let's denote R(n) as the set of primitive roots
// modulo n, p is prime
// g \in R(p) => (pow(g, p-1, p * p) == 1 ? g+p : g) \in
// R(pow(p, k)), for all k > 1
// g \in R(pow(p, k)) => (g % 2 == 1 ? g : g + pow(p, k))
// \in R(2*pow(p, k))
```

Mobius Function

```
memset(mu, 0, sizeof mu);
mu[1] = 1;
for(int i = 1; i < N; i++){
    for(int j = i + i; j < N; j += i)
        mu[j] -= mu[i];
}
// g(n) = sum{f(d)} => f(n) = sum{mu(d)*g(n/d)}
```

Mulmod TOP

```
constexpr uint64_t mod = (1ull<<61) - 1;
uint64_t modmul(uint64_t a, uint64_t b){
    uint64_t l1 = (uint32_t)a, h1 = a>>32, l2 = (
        uint32_t)b, h2 = b>>32;
    uint64_t l = l1*l2, m = l1*h2 + l2*h1, h = h1*h2;
    uint64_t ret = (l&mod) + (l>>61) + (h << 3) + (m >>
        29) + (m << 35 >> 3) + 1;
    ret = (ret & mod) + (ret>>61);
    ret = (ret & mod) + (ret>>61);
    return ret-1;
}
```

Modular multiplication TOPPER

```
ll mulmod(ll a, ll b, ll mod) {
    ll q = ll((long double)a * (long double)b / (long
        double)mod);
    ll r = (a * b - mod * q) % mod;
    if(r < 0) r += mod;
    return r;
}
```

Division Trick

```
for(int l = 1, r; l <= n; l = r + 1) {
    r = n / (n / l);
    // n / x yields the same value for l <= x <= r
}
for(int l, r = n; r > 0; r = l - 1) {
    int tmp = (n + r - 1) / r;
    l = (n + tmp - 1) / tmp;
    // (n+x-1) / x yields the same value for l <= x <= r
}
```

Matrix Determinant

```
int n;
long double a[n][n];

long double gauss(){
    long double det = 1;
    for(int i = 0; i < n; i++){
        int q = i;
        for(int j = i+1; j < n; j++){
            if(abs(a[j][i]) > abs(a[q][i]))
                q = j;
        }
        if(abs(a[q][i]) < EPS){
            det = 0;
            break;
        }
        if(i != q){
            for(int w = 0; w < n; w++){
                swap(a[i][w], a[q][w]);
                det = -det;
            }
        }
        det *= a[i][i];
        for(int j = i+1; j < n; j++) a[i][j] /= a[i][i];

        for(int j = 0; j < n; j++) if(j != i){
            if(abs(a[j][i]) > EPS)
                for(int k = i+1; k < n; k++)
                    a[j][k] -= a[i][k] * a[j][i];
        }
    }

    return det;
}
```

Simplex Method

```
typedef long double dbl;
const dbl eps = 1e-6;
const int N = , M = ;

mt19937 rng(chrono::steady_clock::now().time_since_epoch
    ().count());
struct simplex {
    int X[N], Y[M];
    dbl A[M][N], b[M], c[N];
    dbl ans;
    int n, m;
    dbl sol[N];

    void pivot(int x, int y){
        swap(X[y], Y[x]);
        b[x] /= A[x][y];
        for(int i = 0; i < n; i++){
            if(i != y)
                A[x][i] /= A[x][y];
            A[x][y] = 1. / A[x][y];
        }
    }
}
```

```

for(int i = 0; i < m; i++){
    if(i != x && abs(A[i][y]) > eps) {
        b[i] -= A[i][y] * b[x];
        for(int j = 0; j < n; j++) if(j != y)
            A[i][j] -= A[i][y] * A[x][j];
        A[i][y] = -A[i][y] * A[x][y];
    }
    ans += c[y] * b[x];
    for(int i = 0; i < n; i++){
        if(i != y)
            c[i] -= c[y] * A[x][i];
        c[y] = -c[y] * A[x][y];
    }

    // maximiza sum(x[i] * c[i])
    // sujeito a
    // sum(a[i][j] * x[j]) <= b[i] para 0 <= i < m (Ax
    // <= b)
    // x[i] >= 0 para 0 <= i < n (x >= 0)
    // (n variaveis, m restricoes)
    // guarda a resposta em ans e retorna o valor otimo
    dbl solve(int _n, int _m) {
        this->n = _n; this->m = _m;

        for(int i = 1; i < m; i++){
            int id = uniform_int_distribution<int>(0, i)(
                rng);
            swap(b[i], b[id]);
            for(int j = 0; j < n; j++)
                swap(A[i][j], A[id][j]);
        }

        ans = 0.;
        for(int i = 0; i < n; i++) X[i] = i;
        for(int i = 0; i < m; i++) Y[i] = i + n;
        while(true) {
            int x = min_element(b, b + m) - b;
            if(b[x] >= -eps)
                break;
            int y = find_if(A[x], A[x] + n, [](dbl d) {
                return d < -eps; }) - A[x];
            if(y == n) throw 1; // no solution
            pivot(x, y);
        }
        while(true) {
            int y = max_element(c, c + n) - c;
            if(c[y] <= eps) break;
            int x = -1;
            dbl mn = 1. / 0.;
            for(int i = 0; i < m; i++){
                if(A[i][y] > eps && b[i] / A[i][y] < mn)
                    mn = b[i] / A[i][y], x = i;
                if(x == -1) throw 2; // unbounded
                pivot(x, y);
            }
            memset(sol, 0, sizeof(dbl) * n);
            for(int i = 0; i < m; i++){
                if(Y[i] < n)
                    sol[Y[i]] = b[i];
            }
            return ans;
        }
    }
};

```

FFT

```

void fft(vector<base> &a, bool inv){
    int n = (int)a.size();

```

```

    for(int i = 1, j = 0; i < n; i++){
        int bit = n >> 1;
        for(; j >= bit; bit >>= 1) j -= bit;
        j += bit;
        if(i < j) swap(a[i], a[j]);
    }

    for(int sz = 2; sz <= n; sz <<= 1) {
        double ang = 2 * PI / sz * (inv ? -1 : 1);
        base wlen(cos(ang), sin(ang));
        for(int i = 0; i < n; i += sz){
            base w(1, 0);
            for(int j = 0; j < sz / 2; j++){
                base u = a[i+j], v = a[i+j + sz/2] * w;
                a[i+j] = u + v;
                a[i+j+sz/2] = u - v;
                w *= wlen;
            }
        }
        if(inv) for(int i = 0; i < n; i++) a[i] /= 1.0 * n;
    }
}

```

FFT Tourist

```

namespace fft {
    typedef double dbl;

    struct num {
        dbl x, y;
        num() { x = y = 0; }
        num(dbl x, dbl y) : x(x), y(y) {}
    };

    inline num operator+(num a, num b) { return num(a.x +
        b.x, a.y + b.y); }
    inline num operator-(num a, num b) { return num(a.x -
        b.x, a.y - b.y); }
    inline num operator*(num a, num b) { return num(a.x *
        b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
    inline num conj(num a) { return num(a.x, -a.y); }

    int base = 1;
    vector<num> roots = {{0, 0}, {1, 0}};
    vector<int> rev = {0, 1};

    const dbl PI = acos(-1.0);

    void ensure_base(int nbase) {
        if(nbase <= base) return;

        rev.resize(1 << nbase);
        for(int i = 0; i < (1 << nbase); i++) {
            rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (nbase -
                1));
        }
        roots.resize(1 << nbase);

        while(base < nbase) {
            dbl angle = 2*PI / (1 << (base + 1));
            for(int i = 1 << (base - 1); i < (1 << base); i++)
                {
                    roots[i << 1] = roots[i];
                    dbl angle_i = angle * (2 * i + 1 - (1 << base));
                    roots[(i << 1) + 1] = num(cos(angle_i), sin(
                        angle_i));
                }
            base++;
        }
    }
}

```

```

    }
}

void fft(vector<num> &a, int n = -1) {
    if(n == -1) {
        n = a.size();
    }
    assert((n & (n-1)) == 0);
    int zeros = __builtin_ctz(n);
    ensure_base(zeros);
    int shift = base - zeros;
    for(int i = 0; i < n; i++) {
        if(i < (rev[i] >> shift)) {
            swap(a[i], a[rev[i] >> shift]);
        }
    }
    for(int k = 1; k < n; k <= 1) {
        for(int i = 0; i < n; i += 2 * k) {
            for(int j = 0; j < k; j++) {
                num z = a[i+j+k] * roots[j+k];
                a[i+j+k] = a[i+j] - z;
                a[i+j] = a[i+j] + z;
            }
        }
    }
}

vector<num> fa, fb;
vector<int> multiply(vector<int> &a, vector<int> &b) {
    int need = a.size() + b.size() - 1;
    int nbase = 0;
    while((1 << nbase) < need) nbase++;
    ensure_base(nbase);
    int sz = 1 << nbase;
    if(sz > (int) fa.size()) {
        fa.resize(sz);
    }
    for(int i = 0; i < sz; i++) {
        int x = (i < (int) a.size() ? a[i] : 0);
        int y = (i < (int) b.size() ? b[i] : 0);
        fa[i] = num(x, y);
    }
    fft(fa, sz);
    num r(0, -0.25 / sz);
    for(int i = 0; i <= (sz >> 1); i++) {
        int j = (sz - i) & (sz - 1);
        num z = (fa[j] * fa[j] - conj(fa[i] * fa[i])) * r;
        if(i != j) {
            fa[j] = (fa[i] * fa[i] - conj(fa[j] * fa[j])) * r;
        }
        fa[i] = z;
    }
    fft(fa, sz);
    vector<int> res(need);
    for(int i = 0; i < need; i++) {
        res[i] = fa[i].x + 0.5;
    }
    return res;
}

vector<int> multiply_mod(vector<int> &a, vector<int> &
    b, int m, int eq = 0) {
    int need = a.size() + b.size() - 1;
    int nbase = 0;
    while ((1 << nbase) < need) nbase++;
    ensure_base(nbase);

```

```

    int sz = 1 << nbase;
    if (sz > (int) fa.size()) {
        fa.resize(sz);
    }
    for (int i = 0; i < (int) a.size(); i++) {
        int x = (a[i] % m + m) % m;
        fa[i] = num(x & ((1 << 15) - 1), x >> 15);
    }
    fill(fa.begin() + a.size(), fa.begin() + sz, num {0,
        0});
    fft(fa, sz);
    if (sz > (int) fb.size()) {
        fb.resize(sz);
    }
    if (eq) {
        copy(fa.begin(), fa.begin() + sz, fb.begin());
    } else {
        for (int i = 0; i < (int) b.size(); i++) {
            int x = (b[i] % m + m) % m;
            fb[i] = num(x & ((1 << 15) - 1), x >> 15);
        }
        fill(fb.begin() + b.size(), fb.begin() + sz, num
            {0, 0});
        fft(fb, sz);
    }
    dbl ratio = 0.25 / sz;
    num r2(0, -1);
    num r3(ratio, 0);
    num r4(0, -ratio);
    num r5(0, 1);
    for (int i = 0; i <= (sz >> 1); i++) {
        int j = (sz - i) & (sz - 1);
        num a1 = (fa[i] + conj(fa[j]));
        num a2 = (fa[i] - conj(fa[j])) * r2;
        num b1 = (fb[i] + conj(fb[j])) * r3;
        num b2 = (fb[i] - conj(fb[j])) * r4;
        if (i != j) {
            num c1 = (fa[j] + conj(fa[i]));
            num c2 = (fa[j] - conj(fa[i])) * r2;
            num d1 = (fb[j] + conj(fb[i])) * r3;
            num d2 = (fb[j] - conj(fb[i])) * r4;
            fa[i] = c1 * d1 + c2 * d2 * r5;
            fb[i] = c1 * d2 + c2 * d1;
        }
        fa[j] = a1 * b1 + a2 * b2 * r5;
        fb[j] = a1 * b2 + a2 * b1;
    }
    fft(fa, sz);
    fft(fb, sz);
    vector<int> res(need);
    for (int i = 0; i < need; i++) {
        long long aa = fa[i].x + 0.5;
        long long bb = fb[i].x + 0.5;
        long long cc = fa[i].y + 0.5;
        res[i] = (aa + ((bb % m) << 15) + ((cc % m) << 30))
            % m;
    }
    return res;
}

vector<int> square_mod(vector<int> &a, int m) {
    return multiply_mod(a, a, m, 1);
}

}

NTT

const int mod = 7340033;

```

```

const int root = 5;
const int root_1 = 4404020;
const int root_pw = 1<<20;

void fft (vector<int> & a, bool invert) {
    int n = (int) a.size();

    for (int i=1, j=0; i<n; ++i) {
        int bit = n >> 1;
        for (; j>=bit; bit>>=1)
            j -= bit;
        j += bit;
        if (i < j)
            swap (a[i], a[j]);
    }

    for (int len=2; len<=n; len<=1) {
        int wlen = invert ? root_1 : root;
        for (int i=len; i<root_pw; i<=1)
            wlen = int (wlen * 111 * wlen % mod);
        for (int i=0; i<n; i+=len) {
            int w = 1;
            for (int j=0; j<len/2; ++j) {
                int u = a[i+j], v = int (a[i+j+len/2] * 1
                    11 * w % mod);
                a[i+j] = u+v < mod ? u+v : u+v-mod;
                a[i+j+len/2] = u-v >= 0 ? u-v : u-v+mod;
                w = int (w * 111 * wlen % mod);
            }
        }
    }
    if (invert) {
        int nrev = reverse (n, mod);
        for (int i=0; i<n; ++i)
            a[i] = int (a[i] * 111 * nrev % mod);
    }
}

```

Gauss

// Solves systems of linear equations.
 // To use, build a matrix of coefficients and call run(
 mat, R, C). If the i-th variable is free, row[i] will
 be -1, otherwise it's value will be ans[i].

```

namespace Gauss {
    const int MAXC = 1001;
    int row[MAXC];
    double ans[MAXC];

    void run(double mat[][MAXC], int R, int C) {
        REP(i, C) row[i] = -1;

        int r = 0;
        REP(c, C) {
            int k = r;
            FOR(i, r, R) if(fabs(mat[i][c]) > fabs(mat[k][c]))
                k = i;
            if(fabs(mat[k][c]) < eps) continue;

            REP(j, C+1) swap(mat[r][j], mat[k][j]);
            REP(i, R) if (i != r) {
                double w = mat[i][c] / mat[r][c];
                REP(j, C+1) mat[i][j] -= mat[r][j] * w;
            }
            row[c] = r++;
        }
    }
}

```

```

REP(i, C) {
    int r = row[i];
    ans[i] = r == -1 ? 0 : mat[r][C] / mat[r][i];
}
}

```

Gauss Xor

```

const ll MAX = 1e9;
const int LOG_MAX = 64 - __builtin_clzll((ll)MAX);

struct Gauss {
    array<ll, LOG_MAX> vet;
    int size;
    Gauss() size(0) {}
    Gauss(vector<ll> vals) size(0) {
        for(ll val : vals) add(val);
    }
    bool add(ll val) {
        for(int i = 0; i < LOG_MAX; i++) if(val & (1LL <<
            i)) {
            if(vet[i] == 0) {
                vet[i] = val;
                size++;
                return true;
            }
            val ^= vet[i];
        }
        return false;
    }
};

```

Simpson

```

inline double simpson(double fl,double fr,double fmid,
    double l,double r) {
    return (fl + fr + 4.0 * fmid) * (r - l) / 6.0;
}

double rsimpson(double slr,double fl,double fr,double
    fmid,double l,double r) {
    double mid = (l+r)*0.5;
    double fml = f((l+mid)*0.5), fmr = f((mid+r)*0.5);
    double slm = simpson(fl, fmid, fml, l, mid);
    double smr = simpson(fmid, fr, fmr, mid, r);
    if(fabs(slr-slm-smr) < eps and r - l < delta) return
        slr;
    return rsimpson(slm,fl,fmid,fml,l,mid) + rsimpson(
        smr,fmid,fr,fmr,mid,r);
}

double integrate(double l,double r) {
    double mid = (l+r)*0.5;
    double fl = f(l), fr = f(r), fmid = f(mid);
    return rsimpson(simpson(fl,fr,fmid,l,r),fl,fr,fmid,l
        ,r);
}

```

Modular Arithmetic

```

template <int mod = MOD>
struct modBase {
    modBase(int val = 0) : val(val) {}
    int val;

    modBase<mod> operator*(modBase<mod> o) {
        return (long long)val * o.val % mod;
    }
    modBase<mod> operator+(modBase<mod> o) {
        return val + o.val > mod ? val + o.val - mod : val +
            o.val;
    }
}

```

```

    }
};

template <class T>
T fexp(T x, long long e) {
    T ans(1);
    for (; e > 0; e /= 2) {
        if (e & 1) ans = ans * x;
        x = x * x;
    }
    return ans;
}

```

Matrix

```

template <const size_t n, const size_t m, class T =
    modBase<>>
struct Matrix {
    T v[n][m];

    Matrix(int d = 0) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) {
                v[i][j] = T(0);
            }
            if (i < m) {
                v[i][i] = T(d);
            }
        }
    }

    template <size_t mm>
    Matrix<n, mm, T> operator*(Matrix<m, mm, T> &o) {
        Matrix<n, mm, T> ans;
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < mm; j++) {
                for (int k = 0; k < m; k++) {
                    ans.v[i][j] = ans.v[i][j] + v[i][k] * o.v[k][j];
                }
            }
        }
        return ans;
    }
};

```

Graphs

Bipartite Matching

```

// O(V * E)
int match[N];
int vis[N], pass;
vector<int> g[N];

bool dfs(int u) {
    vis[u] = pass;

    for(int v : g[u]) if(vis[v] != pass) {
        vis[v] = pass;
        if(match[v] == -1 or dfs(match[v])) {
            match[v] = u;
            match[u] = v;
            return true;
        }
    }
    return false;
}

```

```

int max_matching() {
    memset(match, -1, sizeof match);
    int max_matching_size = 0;
    for(int u : vertices_on_side_A) {
        pass++;
        if(dfs(u)) max_matching_size++;
    }
    return max_matching_size;
}

```

Dinic

```

const int N = 100005;
const int E = 2000006;
vector<int> g[N];
int ne;
struct Edge{
    int from, to; ll flow, cap;
} edge[E];
int lvl[N], vis[N], pass, start = N-2, target = N-1;
int qu[N], qt, px[N];

ll run(int s, int sink, ll minE){
    if(s == sink) return minE;

    ll ans = 0;

    for(; px[s] < (int)g[s].size(); px[s]++){
        int e = g[s][ px[s] ];
        auto &v = edge[e], &rev = edge[e^1];
        if(lvl[v.to] != lvl[s]+1 || v.flow >= v.cap)
            continue; // v.cap - v.flow < lim
        ll tmp = run(v.to, sink, min(minE, v.cap-v.flow));
        v.flow += tmp, rev.flow -= tmp;
        ans += tmp, minE -= tmp;
        if(minE == 0) break;
    }
    return ans;
}

bool bfs(int source, int sink){
    qt = 0;
    qu[qt++] = source;
    lvl[source] = 1;
    vis[source] = ++pass;
    for(int i = 0; i < qt; i++){
        int u = qu[i];
        px[u] = 0;
        if(u == sink) return true;
        for(auto& ed : g[u]) {
            auto v = edge[ed];
            if(v.flow >= v.cap || vis[v.to] == pass)
                continue; // v.cap - v.flow < lim
            vis[v.to] = pass;
            lvl[v.to] = lvl[u]+1;
            qu[qt++] = v.to;
        }
    }
    return false;
}

ll flow(int source = start, int sink = target){
    ll ans = 0;
    //for(lim = (1LL << 62); lim >= 1; lim /= 2)
    while(bfs(source, sink))
        ans += run(source, sink, oo);
    return ans;
}

void addEdge(int u, int v, ll c = 1, ll rc = 0){
    edge[ne] = {u, v, 0, c};
}

```

```

    g[u].push_back(ne++);
    edge[ne] = {v, u, 0, rc};
    g[v].push_back(ne++);
}
void reset_flow(){
    for(int i = 0; i < ne; i++){
        edge[i].flow = 0;
    }
}

```

Push relabel

```

// Push relabel in  $O(V^2 E^{0.5})$  with gap heuristic
// It's quite fast
template<typename flow_t = long long>
struct PushRelabel {
    struct Edge { int to, rev; flow_t f, c; };
    vector<vector<Edge> > g;
    vector<flow_t> ec;
    vector<Edge*> cur;
    vector<vector<int> > hs;
    vector<int> H;
    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
    void add_edge(int s, int t, flow_t cap, flow_t rcap = 0) {
        if (s == t) return;
        Edge a = {t, (int)g[t].size(), 0, cap};
        Edge b = {s, (int)g[s].size(), 0, rcap};
        g[s].push_back(a);
        g[t].push_back(b);
    }
    void add_flow(Edge& e, flow_t f) {
        Edge &back = g[e.to][e.rev];
        if (!ec[e.to] && f)
            hs[H[e.to]].push_back(e.to);
        e.f += f, ec[e.to] += f;
        back.f -= f, ec[back.to] -= f;
    }
    flow_t max_flow(int s, int t) {
        int v = g.size();
        H[s] = v; ec[t] = 1;
        vector<int> co(2 * v);
        co[0] = v-1;
        for(int i = 0; i < v; ++i) cur[i] = g[i].data();
        for(auto &e : g[s]) add_flow(e, e.c);

        if(hs[0].size())
            for (int hi = 0; hi >= 0; ) {
                int u = hs[hi].back();
                hs[hi].pop_back();
                while (ec[u] > 0) // discharge u
                    if (cur[u] == g[u].data() + g[u].size()) {
                        H[u] = 1e9;
                        for(auto &e:g[u])
                            if (e.c - e.f && H[u] > H[e.to]+1)
                                H[u] = H[e.to]+1, cur[u] = &e;
                        if (++co[H[u]], !--co[hi] && hi < v)
                            for(int i = 0; i < v; ++i)
                                if (hi < H[i] && H[i] < v){
                                    --co[H[i]];
                                    H[i] = v + 1;
                                }
                        hi = H[u];
                    } else if (cur[u]->c - cur[u]->f && H[u]
                            == H[cur[u]->to]+1)
                        add_flow(*cur[u], min(ec[u], cur[u]->c
                            - cur[u]->f));
                    else ++cur[u];
            }
    }
}

```

```

        while (hi >= 0 && hs[hi].empty()) --hi;
    }
    return -ec[s];
}
};

```

Min Cost Max Flow

```

const ll oo = 1e18;
const int N = 222, E = 2 * 1000006;

vector<int> g[N];
int ne;
struct Edge{
    int from, to; ll cap, cost;
} edge[E];
int start = N-1, target = N-2, p[N]; int inqueue[N];
ll d[N];
bool spfa(int source, int sink){
    for(int i = 0; i < N; i++) d[i] = oo;
    inqueue[i] = 0;

    d[source] = 0; queue<int> q; q.push(source);
    inqueue[source] = 1;

    while(!q.empty()){
        int u = q.front(); q.pop();
        inqueue[u] = 0;
        for(int e : g[u]){
            auto v = edge[e];
            if(v.cap > 0 and d[u] + v.cost < d[v.to]){
                d[v.to] = d[u] + v.cost; p[v.to] = e;
                if(!inqueue[v.to]){
                    q.push(v.to); inqueue[v.to] = 1;
                }
            }
        }
    }
    return d[sink] != oo;
}

// <max flow, min cost>
pair<ll, ll> mincost(int source = start, int sink = target){
    ll ans = 0, mf = 0;
    while(spfa(source, sink)){
        ll f = oo;
        for(int u = sink; u != source; u = edge[ p[u] ].from)
            f = min(f, edge[ p[u] ].cap);
        for(int u = sink; u != source; u = edge[ p[u] ].from){
            edge[ p[u] ].cap -= f;
            edge[ p[u] ^ 1 ].cap += f;
        }
        mf += f;
        ans += f * d[sink];
    }
    return {mf, ans};
}

void addEdge(int u, int v, ll c, ll cost){
    edge[ne] = {u, v, c, cost};
    g[u].push_back(ne++);
    edge[ne] = {v, u, 0, -cost};
    g[v].push_back(ne++);
}

Blossom Algorithm for General Matching

const int MAXN = 2020 + 1;

```

```

// 1-based Vertex index
int vis[MAXN], par[MAXN], orig[MAXN], match[MAXN], aux[
    MAXN], t, N;
vector<int> conn[MAXN];
queue<int> Q;
void addEdge(int u, int v) {
    conn[u].push_back(v); conn[v].push_back(u);
}
void init(int n) {
    N = n; t = 0;
    for(int i=0; i<=n; ++i)
        conn[i].clear(), match[i] = aux[i] = par[i] = 0;
}
void augment(int u, int v) {
    int pv = v, nv;
    do {
        pv = par[pv]; nv = match[pv];
        match[pv] = v; match[v] = pv;
        v = nv;
    } while(u != pv);
}
int lca(int v, int w) {
    ++t;
    while(true) {
        if(v) {
            if(aux[v] == t) return v; aux[v] = t;
            v = orig[par[match[v]]];
        }
        swap(v, w);
    }
}
void blossom(int v, int w, int a) {
    while(orig[v] != a) {
        par[v] = w; w = match[v];
        if(vis[w] == 1) Q.push(w), vis[w] = 0;
        orig[v] = orig[w] = a; v = par[w];
    }
}
bool bfs(int u) {
    fill(vis+1, vis+1+N, -1); iota(orig + 1, orig + N +
        1, 1);
    Q = queue<int>(); Q.push(u); vis[u] = 0;
    while(!Q.empty()) {
        int v = Q.front(); Q.pop();
        for(int x: conn[v]) {
            if(vis[x] == -1) {
                par[x] = v; vis[x] = 1;
                if(!match[x]) return augment(u, x), true;
                Q.push(match[x]); vis[match[x]] = 0;
            }
            else if(vis[x] == 0 && orig[v] != orig[x]) {
                int a = lca(orig[v], orig[x]);
                blossom(x, v, a); blossom(v, x, a);
            }
        }
    }
    return false;
}
int Match() {
    int ans = 0;
    // find random matching (not necessary, constant
    // improvement)
    vector<int> V(N-1); iota(V.begin(), V.end(), 1);
    shuffle(V.begin(), V.end(), mt19937(0x94949));
    for(auto x: V) if(!match[x]){
        for(auto y: conn[x]) if(!match[y]) {
            match[x] = y, match[y] = x;

```

```

            ++ans; break;
        }
    }
    for(int i=1; i<=N; ++i) if(!match[i] && bfs(i)) ++
        ans;
    return ans;
}

Blossom Algorithm for Weighted General Match-
ing

// N^3 (but fast in practice)
static const int INF = INT_MAX;
static const int N = 514;
struct edge{
    int u,v,w; edge(){}
    edge(int ui,int vi,int wi)
        :u(ui),v(vi),w(wi){}
};
int n,n_x;
edge g[N*2][N*2];
int lab[N*2];
int match[N*2],slack[N*2],st[N*2],pa[N*2];
int flo_from[N*2][N+1],S[N*2],vis[N*2];
vector<int> flo[N*2];
queue<int> q;
int e_delta(const edge &e){
    return lab[e.u]+lab[e.v]-g[e.u][e.v].w*2;
}
void update_slack(int u,int x){
    if(!slack[x] || e_delta(g[u][x])<e_delta(g[slack[x]][x]
        ))slack[x]=u;
}
void set_slack(int x){
    slack[x]=0;
    for(int u=1;u<=n;++u)
        if(g[u][x].w>0&&st[u]!=x&&S[st[u]]==0)
            update_slack(u,x);
}
void q_push(int x){
    if(x<=n)q.push(x);
    else for(size_t i=0;i<flo[x].size();i++)
        q_push(flo[x][i]);
}
void set_st(int x,int b){
    st[x]=b;
    if(x>n)for(size_t i=0;i<flo[x].size();++i)
        set_st(flo[x][i],b);
}
int get_pr(int b,int xr){
    int pr=find(flo[b].begin(),flo[b].end(),xr)-flo[b].
        begin();
    if(pr%2==1){
        reverse(flo[b].begin()+1,flo[b].end());
        return (int)flo[b].size()-pr;
    }else return pr;
}
void set_match(int u,int v){
    match[u]=g[u][v].v;
    if(u<=n) return;
    edge e=g[u][v];
    int xr=flo_from[u][e.u],pr=get_pr(u,xr);
    for(int i=0;i<pr;++i)set_match(flo[u][i],flo[u][i
        ^1]);
    set_match(xr,v);
    rotate(flo[u].begin(),flo[u].begin()+pr,flo[u].end()
        );
}
}

```

```

void augment(int u,int v){
    for(;;){
        int xnv=st[match[u]];
        set_match(u,v);
        if(!xnv)return;
        set_match(xnv,st[pa[xnv]]);
        u=st[pa[xnv]],v=xnv;
    }
}
int get_lca(int u,int v){
    static int t=0;
    for(++t;u||v;swap(u,v)){
        if(u==0)continue;
        if(vis[u]==t)return u;
        vis[u]=t;
        u=st[match[u]];
        if(u)u=st[pa[u]];
    }
    return 0;
}
void add_blossom(int u,int lca,int v){
    int b=n+1;
    while(b<=n_x&&st[b])++b;
    if(b>n_x)++n_x;
    lab[b]=0,S[b]=0;
    match[b]=match[lca];
    flo[b].clear();
    flo[b].push_back(lca);
    for(int x=u,y;x!=lca;x=st[pa[y]])
        flo[b].push_back(x),flo[b].push_back(y=st[match[x]]),q_push(y);
    reverse(flo[b].begin()+1,flo[b].end());
    for(int x=v,y;x!=lca;x=st[pa[y]])
        flo[b].push_back(x),flo[b].push_back(y=st[match[x]]),q_push(y);
    set_st(b,b);
    for(int x=1;x<=n_x;++x)g[b][x].w=g[x][b].w=0;
    for(int x=1;x<=n;++x)flo_from[b][x]=0;
    for(size_t i=0;i<flo[b].size();++i){
        int xs=flo[b][i];
        for(int x=1;x<=n_x;++x)
            if(g[b][x].w==0||e_delta(g[xs][x])<e_delta(g[b][x]))
                g[b][x]=g[xs][x],g[x][b]=g[x][xs];
        for(int x=1;x<=n;++x)
            if(flo_from[xs][x])flo_from[b][x]=xs;
    }
    set_slack(b);
}
void expand_blossom(int b){
    for(size_t i=0;i<flo[b].size();++i)
        set_st(flo[b][i],flo[b][i]);
    int xr=flo_from[b][g[b][pa[b]].u],pr=get_pr(b,xr);
    for(int i=0;i<pr;i+=2){
        int xs=flo[b][i],xns=flo[b][i+1];
        pa[xs]=g[xns][xs].u;
        S[xs]=1,S[xns]=0;
        slack[xs]=0,set_slack(xns);
        q_push(xns);
    }
    S[xr]=1,pa[xr]=pa[b];
    for(size_t i=pr+1;i<flo[b].size();++i){
        int xs=flo[b][i];
        S[xs]=-1,set_slack(xs);
    }
    st[b]=0;
}

```

```

bool on_found_edge(const edge &e){
    int u=st[e.u],v=st[e.v];
    if(S[v]==-1){
        pa[v]=e.u,S[v]=1;
        int nu=st[match[v]];
        slack[v]=slack[nu]=0;
        S[nu]=0,q_push(nu);
    }else if(S[v]==0){
        int lca=get_lca(u,v);
        if(!lca)return augment(u,v),augment(v,u),true;
        else add_blossom(u,lca,v);
    }
    return false;
}
bool matching(){
    memset(S+1,-1,sizeof(int)*n_x);
    memset(slack+1,0,sizeof(int)*n_x);
    q=queue<int>();
    for(int x=1;x<=n_x;++x)
        if(st[x]==x&&!match[x])pa[x]=0,S[x]=0,q_push(x);
    if(q.empty())return false;
    for(;;){
        while(q.size()){
            int u=q.front();q.pop();
            if(S[st[u]]==1)continue;
            for(int v=1;v<=n;++v)
                if(g[u][v].w>0&&st[u]!=st[v]){
                    if(e_delta(g[u][v])==0){
                        if(on_found_edge(g[u][v]))return true;
                    }else update_slack(u,st[v]);
                }
        }
        int d=INF;
        for(int b=n+1;b<=n_x;++b)
            if(st[b]==b&&S[b]==1)d=min(d,lab[b]/2);
        for(int x=1;x<=n_x;++x)
            if(st[x]==x&&slack[x]){
                if(S[x]==-1)d=min(d,e_delta(g[slack[x]][x]));
                else if(S[x]==0)d=min(d,e_delta(g[slack[x]][x])/2);
            }
        for(int u=1;u<=n;++u){
            if(S[st[u]]==0){
                if(lab[u]<=d)return 0;
                lab[u]-=d;
            }else if(S[st[u]]==1)lab[u]+=d;
        }
        for(int b=n+1;b<=n_x;++b)
            if(st[b]==b){
                if(S[st[b]]==0)lab[b]+=d*2;
                else if(S[st[b]]==1)lab[b]-=d*2;
            }
        q=queue<int>();
        for(int x=1;x<=n_x;++x)
            if(st[x]==x&&slack[x]&&st[slack[x]]!=x&&
                e_delta(g[slack[x]][x])==0)
                if(on_found_edge(g[slack[x]][x]))return true;
        for(int b=n+1;b<=n_x;++b)
            if(st[b]==b&&S[b]==1&&lab[b]==0)
                expand_blossom(b);
    }
    return false;
}
pair<long long,int> solve(){

```



```

memset(match+1,0,sizeof(int)*n);
n_x=n;
int n_matches=0;
long long tot_weight=0;
for(int u=0;u<=n;++u)st[u]=u,flo[u].clear();
int w_max=0;
for(int u=1;u<=n;++u)
    for(int v=1;v<=n;++v){
        flo_from[u][v]=(u==v?u:0);
        w_max=max(w_max,g[u][v].w);
    }
for(int u=1;u<=n;++u)lab[u]=w_max;
while(matching())++n_matches;
for(int u=1;u<=n;++u)
    if(match[u]&&match[u]<u)
        tot_weight+=g[u][match[u]].w;
return make_pair(tot_weight,n_matches);
}
void add_edge( int ui , int vi , int wi ){
    g[ui][vi].w = g[vi][ui].w = wi;
}
void init( int _n ){
    n = _n;
    for(int u=1;u<=n;++u)
        for(int v=1;v<=n;++v)
            g[u][v]=edge(u,v,0);
}

```

Small to Large

```

void cnt_sz(int u, int p = -1){
    sz[u] = 1;
    for(int v : g[u]) if(v != p)
        cnt_sz(v, u), sz[u] += sz[v];
}
void add(int u, int p, int big = -1){
    // Update info about this vx in global answer
    for(int v : g[u]) if(v != p && v != big)
        add(v, u);
}
void dfs(int u, int p, int keep){
    int big = -1, mmx = -1;
    for(int v : g[u]) if(v != p && sz[v] > mmx)
        mmx = sz[v], big = v;
    for(int v : g[u]) if(v != p && v != big)
        dfs(v, u, 0);
    if(big != -1) dfs(big, u, 1);
    add(u, p, big);
    for(auto x : q[u]){
        // answer all queries for this vx
    }
    if(!keep){ /*Remove data from this subtree*/ }
}

```

Centroid Decomposition

```

void decomp(int v, int p){
    int treesize = calc_sz(v, v);
    if(treesize < k) return;
    int cent = centroid(v, v, treesize);
    erased[cent] = 1;

    for(int i = 1; i <= treesize; i++) dist[i] = 1e18;

    for(pair<int,int> x : G[cent]) if(!erased[x.ff]){
        procurar_ans(x.ff, cent, 1, x.ss); // linear
        atualiza_dist(x.ff, cent, 1, x.ss); // linear
    }
}

```

```

for(pair<int,int> x : G[cent]) if(!erased[x.ff])
    decomp(x.ff, cent);
}

```

Kosaraju

```

vector<int> g[N], gt[N], S; int vis[N], cor[N];
void dfs(int u){
    vis[u] = 1; for(int v : g[u]) if(!vis[v]) dfs(v);
    S.push_back(u);
}
void dfst(int u, int e){
    cor[u] = e;
    for(int v : gt[u]) if(!cor[v]) dfst(v, e);
}
void kosaraju(){
    for(int i = 1; i <= n; i++) if(!vis[i]) dfs(i);
    for(int i = 1; i <= n; i++) for(int j : g[i])
        gt[j].push_back(i);
    int e = 0; reverse(S.begin(), S.end());
    for(int u : S) if(!cor[u]) dfst(u, ++e);
}

```

Tarjan

```

int cnt = 0, root;
void dfs(int u, int p = -1){
    low[u] = num[u] = ++t;
    for(int v : g[u]){
        if(!num[v]){
            dfs(v, u);
            if(u == root) cnt++;
            if(low[v] >= num[u]) u PONTO DE ARTICULACAO;
            if(low[v] > num[u]) ARESTA u->v PONTE;
            low[u] = min(low[u], low[v]);
        }
        else if(v != p) low[u] = min(low[u], num[v]);
    }
}

```

root PONTO DE ARTICULACAO <=> cnt > 1

```

void tarjanSCC(int u){
    low[u] = num[u] = ++cnt;
    vis[u] = 1;
    S.push_back(u);
    for(int v : g[u]){
        if(!num[v]) tarjanSCC(v);
        if(vis[v]) low[u] = min(low[u], low[v]);
    }
    if(low[u] == num[u]){
        ssc[u] = ++ssc_cnt; int v;
        do{
            v = S.back(); S.pop_back(); vis[v] = 0;
            ssc[v] = ssc_cnt;
        }while(u != v);
    }
}

```

Max Clique

```

long long adj[N], dp[N];

for(int i = 0; i < n; i++){
    for(int j = 0; j < n; j++){
        int x;
        scanf("%d",&x);
        if(x || i == j)
            adj[i] |= 1LL << j;
    }
}

```

```

}

int resto = n - n/2;
int C = n/2;
for(int i = 1; i < (1 << resto); i++){
    int x = i;
    for(int j = 0; j < resto; j++){
        if(i & (1 << j))
            x &= adj[j + C] >> C;
        if(x == i){
            dp[i] = __builtin_popcount(i);
        }
    }
}

for(int i = 1; i < (1 << resto); i++){
    for(int j = 0; j < resto; j++){
        if(i & (1 << j))
            dp[i] = max(dp[i], dp[i ^ (1 << j)]);
    }
}

int maxCliq = 0;
for(int i = 0; i < (1 << C); i++){
    int x = i, y = (1 << resto) - 1;
    for(int j = 0; j < C; j++){
        if(i & (1 << j))
            x &= adj[j] & ((1 << C) - 1), y &= adj[j] >> C;
        if(x != i) continue;
        maxCliq = max(maxCliq, __builtin_popcount(i) + dp[y]);
    }
}

```

Dominator Tree

```

vector<int> g[N], gt[N], T[N];
vector<int> S;
int dsu[N], label[N];
int sdom[N], idom[N], dfs_time, id[N];

vector<int> bucket[N];
vector<int> down[N];

void prep(int u){
    S.push_back(u);
    id[u] = ++dfs_time;
    label[u] = sdom[u] = dsu[u] = u;

    for(int v : g[u]){
        if(!id[v])
            prep(v), down[u].push_back(v);
        gt[v].push_back(u);
    }
}

int fnd(int u, int flag = 0){
    if(u == dsu[u]) return u;
    int v = fnd(dsu[u], 1), b = label[dsu[u]];
    if(id[sdom[b]] < id[sdom[label[u]]])
        label[u] = b;
    dsu[u] = v;
    return flag ? v : label[u];
}

void build_dominator_tree(int root, int sz){
    // memset(id, 0, sizeof(int) * (sz + 1));
    // for(int i = 0; i <= sz; i++) T[i].clear();
    prep(root);
    reverse(S.begin(), S.end());
}

```

```

int w;
for(int u : S){
    for(int v : gt[u]){
        w = fnd(v);
        if(id[sdom[w]] < id[sdom[u]])
            sdom[u] = sdom[w];
    }
    gt[u].clear();

    if(u != root) bucket[sdom[u]].push_back(u);

    for(int v : bucket[u]){
        w = fnd(v);
        if(sdom[w] == sdom[v]) idom[v] = sdom[v];
        else idom[v] = w;
    }
    bucket[u].clear();

    for(int v : down[u]) dsu[v] = u;
    down[u].clear();
}

reverse(S.begin(), S.end());
for(int u : S) if(u != root){
    if(idom[u] != sdom[u]) idom[u] = idom[idom[u]];
    T[idom[u]].push_back(u);
}
S.clear();
}

```

Min Cost Matching

```

// Min cost matching
// O(n^2 * m)
// n == nro de linhas
// m == nro de colunas
// n <= m | flow == n
// a[i][j] = custo pra conectar i a j
vector<int> u(n + 1), v(m + 1), p(m + 1), way(m + 1);
for(int i = 1; i <= n; ++i){
    p[0] = i;
    int j0 = 0;
    vector<int> minv(m + 1, oo);
    vector<char> used(m + 1, false);
    do{
        used[j0] = true;
        int i0 = p[j0], delta = oo, j1;
        for(int j = 1; j <= m; ++j)
            if(!used[j]){
                int cur = a[i0][j] - u[i0] - v[j];
                if(cur < minv[j])
                    minv[j] = cur, way[j] = j0;
                if(minv[j] < delta)
                    delta = minv[j], j1 = j;
            }
        for(int j = 0; j <= m; ++j)
            if(used[j])
                u[p[j]] += delta, v[j] -= delta;
            else
                minv[j] -= delta;
        j0 = j1;
    }while(p[j0] != 0);

    do{
        int j1 = way[j0];
        p[j0] = p[j1];
        j0 = j1;
    }while(j0);
}

```

```

}

// match[i] = coluna escolhida para linha i
vector<int> match(n + 1);
for(int j = 1; j <= m; ++j)
    match[p[j]] = j;

int cost = -v[0];

```

Strings

Aho Corasick

```

int to[N][A];
int ne = 2, fail[N], term[N];
void add_string(const char *str, int id){
    int p = 1;
    for(int i = 0; str[i]; i++){
        int ch = str[i] - 'a';
        if(!to[p][ch]) to[p][ch] = ne++;
        p = to[p][ch];
    }
    term[p]++;
}
void init(){
    for(int i = 0; i < ne; i++) fail[i] = 1;
    queue<int> q; q.push(1);
    int u, v; char c;
    while(!q.empty()){
        u = q.front(); q.pop();
        for(int i = 0; i < A; i++){
            if(to[u][i]){
                v = to[u][i]; q.push(v);
                if(u != 1){
                    fail[v] = to[ fail[u] ][i];
                    term[v] += term[ fail[v] ];
                }
            }
            else if(u != 1) to[u][i] = to[ fail[u] ][i];
            else to[u][i] = 1;
        }
    }
}
void clean() {
    memset(to, 0, ne * sizeof(to[0]));
    memset(fail, 0, ne * sizeof(fail[0]));
    memset(term, 0, ne * sizeof(term[0]));
    memset(to, 0, ne * sizeof(to[0]));
    ne = 2;
}

```

Suffix Array

```

int lcp[N], c[N];

// Caractere final da string '\0' esta sendo considerado
// parte da string s
void build_sa(char s[], int n, int a[]){
    const int A = 300; // Tamanho do alfabeto
    int c1[n], a1[n], h[n + A];
    memset(h, 0, sizeof h);

    for(int i = 0; i < n; i++) {
        c[i] = s[i];
        h[c[i] + 1]++;
    }

    partial_sum(h, h + A, h);
    for(int i = 0; i < n; i++)

```

```

        a[h[c[i]]++] = i;
    for(int i = 0; i < n; i++)
        h[c[i]]--;

    for(int L = 1; L < n; L <= 1) {
        for(int i = 0; i < n; i++) {
            int j = (a[i] - L + n) % n;
            a1[h[c[j]]++] = j;
        }

        int cc = -1;
        for(int i = 0; i < n; i++) {
            if(i == 0 || c[a1[i]] != c[a1[i-1]] || c[(a1[i] + L) % n] != c[(a1[i-1] + L) % n])
                h[++cc] = i;
            c1[a1[i]] = cc;
        }

        memcpy(a, a1, sizeof a1);
        memcpy(c, c1, sizeof c1);

        if(cc == n-1) break;
    }
}

void build_lcp(char s[], int n, int a[]){ // lcp[i] =
    lcp(s[:i], s[:i+1])
    int k = 0;

    //memset(lcp, 0, sizeof lcp);
    for(int i = 0; i < n; i++){
        if(c[i] == n-1) continue;
        int j = a[c[i]+1];
        while(i+k < n && j+k < n && s[i+k] == s[j+k]) k
            ++;
        lcp[c[i]] = k;
        if(k) k--;
    }
}

int comp_lcp(int i, int j){
    if(i == j) return n - i;
    if(c[i] > c[j]) swap(i, j);
    return min(lcp[k] for k in [c[i], c[j]-1]);
}

```

Adamant Suffix Tree

```

namespace sf {

const int inf = 1e9;
const int maxn = 200005;
char s[maxn];
map<int, int> to[maxn];
int len[maxn], fpos[maxn], link[maxn];
int node, pos;
int sz = 1, n = 0;

int make_node(int _pos, int _len) {
    fpos[sz] = _pos;
    len[sz] = _len;
    return sz++;
}

void go_edge() {
    while (pos > len[to[node]][s[n - pos]]) {
        node = to[node][s[n - pos]];
        pos -= len[node];
    }
}

```

```

}
void add_letter(int c) {
    s[n++] = (char)c;
    pos++;
    int last = 0;
    while (pos > 0) {
        go_edge();
        int edge = s[n - pos];
        int &v = to[node][edge];
        int t = s[fpos[v] + pos - 1];
        if (v == 0) {
            v = make_node(n - pos, inf);
            link[last] = node;
            last = 0;
        } else if (t == c) {
            link[last] = node;
            return;
        } else {
            int u = make_node(fpos[v], pos - 1);
            to[u][c] = make_node(n - 1, inf);
            to[u][t] = v;
            fpos[v] += pos - 1;
            len[v] -= pos - 1;
            v = u;
            link[last] = u;
            last = u;
        }
    }
    if (node == 0)
        pos--;
    else
        node = link[node];
}
}
void add_string(char *str) {
    for (int i = 0; str[i]; i++) add_letter(str[i]);
    add_letter('$');
}
bool is_leaf(int u) { return len[u] > n; }
int get_len(int u) {
    if (!u) return 0;
    if (is_leaf(u)) return n - fpos[u];
    return len[u];
}
int leafs[maxn];
int calc_leafs(int u = 0) {
    leafs[u] = is_leaf(u);
    for (const auto &c : to[u]) leafs[u] += calc_leafs(c.
        second);
    return leafs[u];
}
}; // namespace sf

int main() { sf::len[0] = sf::inf; }

```

Z Algorithm

```

vector<int> z_algo(const string &s) {
    int n = s.size(), L = 0, R = 0;
    vector<int> z(n, 0);
    for(int i = 1; i < n; i++){
        if(i <= R) z[i] = min(z[i-L], R - i + 1);
        while(z[i]+i < n && s[z[i]+i] == s[z[i]])
            z[i]++;
        if(i+z[i]-1 > R) L = i, R = i + z[i] - 1;
    }
    return z;
}

```

Prefix function/KMP

```

vector<int> prefix_function(const string &s){
    int n = s.size(); vector<int> b(n+1);
    b[0] = -1; int i = 0, j = -1;
    while(i < n){
        while(j >= 0 && s[i] != s[j]) j = b[j];
        b[++i] = ++j;
    }
    return b;
}

void kmp(const string &t, const string &p){
    vector<int> b = prefix_function(p);
    int n = t.size(), m = p.size();
    int j = 0;
    for(int i = 0; i < n; i++){
        while(j >= 0 && t[i] != p[j]) j = b[j];
        j++;
        if(j == m){
            //patern of p found on t
            j = b[j];
        }
    }
}

```

Min rotation

```

int min_rotation(int *s, int N) {
    REP(i, N) s[N+i] = s[i];

    int a = 0;
    REP(b, N) REP(i, N) {
        if (a+i == b || s[a+i] < s[b+i]) { b += max(0, i-1);
            break; }
        if (s[a+i] > s[b+i]) { a = b; break; }
    }
    return a;
}

```

Manacher

```

// rad[2 * i] = largest palindrome cetered at char i
// rad[2 * i + 1] = largest palindrome cetered between
// chars i and i+i
void manacher(char *s, int n, int *rad) {
    static char t[2*MAX];
    int m = 2 * n - 1;

    for(int i = 0; i < m; i++) t[i] = -1;
    for(int i = 0; i < n; i++) t[2 * i] = s[i];

    int x = 0;
    for(int i = 1; i < m; i++) {
        int &r = rad[i] = 0;
        if(i <= x+rad[x]) r = min(rad[x+x-i], x+rad[x]-i);
        while(i - r - 1 >= 0 and i + r + 1 < m and
            t[i - r - 1] == t[i + r + 1]) ++r;
        if(i + r >= x + rad[x]) x = i;
    }

    for(int i = 0; i < m; i++) {
        if(i-rad[i] == 0 || i+rad[i] == m-1) ++rad[i];
    }
    // for(int i = 0; i < m; i++) rad[i] /= 2;
}

```

Suffix Automaton

```

map<char, int> to[2*N];
int link[2*N], len[2*N], last = 0, sz = 1;

```

```

void add_letter(char c){
    int p = last;
    last = sz++;
    len[last] = len[p] + 1;
    for(; !to[p][c]; p = link[p]) to[p][c] = last;
    if(to[p][c] == last){
        link[last] = 0;
        return;
    }
    int u = to[p][c];
    if(len[u] == len[p]+1){
        link[last] = u;
        return;
    }
    int c1 = sz++;
    to[c1] = to[u];
    link[c1] = link[u];
    len[c1] = len[p]+1;
    link[last] = link[u] = c1;
    for(; to[p][c] == u; p = link[p]) to[p][c] = c1;
}

```

Suffix Tree

```

namespace sf {
    // const int NS = ; const int N = * 2;
    int cn, cd, ns, en = 1, lst;
    string S[NS]; int si = -1;
    vector<int> sufn[N]; // sufn[si][i] no do sufixo S[si][i]
    ...
    struct node {
        int l, r, si, p, suf;
        map<char, int> adj;
        node() : l(0), r(-1), suf(0), p(0) {}
        node(int L, int R, int S, int P) : l(L), r(R), si(S), p(P) {}
        inline int len() { return r - l + 1; }
        inline int operator[](int i) { return S[si][l + i]; }
        inline int& operator()(char c) { return adj[c]; }
    } t[N];
    inline int new_node(int L, int R, int S, int P) { t[en] = node(L, R, S, P); return en++; }
    void add_string(string s) {
        s += '$'; S[++si] = s; sufn[si].resize(s.size() + 1);
        ; cn = cd = 0;
        int i = 0; const int n = s.size();
        for(int j = 0; j < n; j++)
            for(; i <= j; i++) {
                if(cd == t[cn].len() && t[cn][s[j]]) { cn = t[cn][s[j]]; cd = 0; }
                if(cd < t[cn].len() && t[cn][cd] == s[j]) { cd++; if(j < s.size() - 1) break; }
                else {
                    if(i) t[lst].suf = cn;
                    for(; i <= j; i++) { sufn[si][i] = cn; cn = t[cn].suf; }
                }
            }
        } else if(cd == t[cn].len()) {
            sufn[si][i] = en;
            if(i) t[lst].suf = en; lst = en;
            t[cn][s[j]] = new_node(j, n - 1, si, cn);
            cn = t[cn].suf; cd = t[cn].len();
        } else {
            int mid = new_node(t[cn].l, t[cn].l + cd - 1, t[cn].si, t[cn].p);

```

```

        t[t[cn].p](t[cn][0]) = mid;
        if(ns) t[ns].suf = mid;
        if(i) t[lst].suf = en; lst = en;
        sufn[si][i] = en;
        t[mid](s[j]) = new_node(j, n - 1, si, mid);
        ;
        t[mid](t[cn][cd]) = cn;
        t[cn].p = mid; t[cn].l += cd; cn = t[mid].p;
        int g = cn? j - cd : i + 1; cn = t[cn].suf;
        ;
        while(g < j && g + t[t[cn](S[si][g])).len() <= j) {
            cn = t[cn](S[si][g]); g += t[cn].len();
        }
        if(g == j) { ns = 0; t[mid].suf = cn; cd = t[cn].len(); }
        else { ns = mid; cn = t[cn](S[si][g]); cd = j - g; }
    }
}
};

```

Geometry

2D basics

```

typedef double cod;
double eps = 1e-7;
bool eq(cod a, cod b){ return abs(a - b) <= eps; }

struct vec{
    cod x, y; int id;
    vec(cod a = 0, cod b = 0) : x(a), y(b) {}
    vec operator+(const vec &o) const{
        return {x + o.x, y + o.y};
    }
    vec operator-(const vec &o) const{
        return {x - o.x, y - o.y};
    }
    vec operator*(cod t) const{
        return {x * t, y * t};
    }
    vec operator/(cod t) const{
        return {x / t, y / t};
    }
    cod operator*(const vec &o) const{ // cos
        return x * o.x + y * o.y;
    }
    cod operator^(const vec &o) const{ // sin
        return x * o.y - y * o.x;
    }
    bool operator==(const vec &o) const{
        return eq(x, o.x) && eq(y, o.y);
    }
    bool operator<(const vec &o) const{
        if(!eq(x, o.x)) return x < o.x;
        return y < o.y;
    }
    cod cross(const vec &a, const vec &b) const{
        return (a-(*this)) ^ (b-(*this));
    }
    int ccw(const vec &a, const vec &b) const{
        cod tmp = cross(a, b);
        return (tmp > eps) - (tmp < -eps);
    }
    cod dot(const vec &a, const vec &b) const{

```

```

    return (a-(*this)) * (b-(*this));
}
cod len() const{
    return sqrt(x * x + y * y); // <
}
double angle(const vec &a, const vec &b) const{
    return atan2(cross(a, b), dot(a, b));
}
double tan(const vec &a, const vec &b) const{
    return cross(a, b) / dot(a, b);
}
vec unit() const{
    return operator/(len());
}
int quad() const{
    if(x > 0 && y >=0) return 0;
    if(x <=0 && y > 0) return 1;
    if(x < 0 && y <=0) return 2;
    return 3;
}
bool comp(const vec &a, const vec &b) const{
    return (a - *this).comp(b - *this);
}
bool comp(vec b){
    if(quad() != b.quad()) return quad() < b.quad();
    if(!eq(operator^(b), 0)) return operator^(b) > 0;
    return (*this) * (*this) < b * b;
}
template<class T>
void sort_by_angle(T first, T last) const{
    std::sort(first, last, [=](const vec &a, const
        vec &b){
        return comp(a, b);
    });
}
vec rot90() const{ return {-y, x}; }
vec rot(double a) const{
    return {cos(a)*x -sin(a)*y, sin(a)*x +cos(a)*y};
}
vec proj(const vec &b) const{ // proj of *this onto
    b
    cod k = operator*(b) / (b * b);
    return b * k;
}
// proj of (*this) onto the plane orthogonal to b
vec rejection(vec b) const{
    return (*this) - proj(b);
}
};

struct line{
    cod a, b, c; vec n;
    line(vec q, vec w){ // q.cross(w, (x, y)) = 0
        a = -(w.y-q.y);
        b = w.x-q.x;
        c = -(a * q.x + b * q.y);
        n = {a, b};
    }
    cod dist(const vec &o) const{
        return abs(eval(o)) / n.len();
    }
    bool contains(const vec &o) const{
        return eq(a * o.x + b * o.y + c, 0);
    }
    cod dist(const line &o) const{
        if(!parallel(o)) return 0;
        if(!eq(o.a * b, o.b * a)) return 0;

```

```

        if(!eq(a, 0))
            return abs(c - o.c * a / o.a) / n.len();
        if(!eq(b, 0))
            return abs(c - o.c * b / o.b) / n.len();
        return abs(c - o.c);
    }
    bool parallel(const line &o) const{
        return eq(n ^ o.n, 0);
    }
    bool operator==(const line &o) const{
        if(!eq(a*o.b, b*o.a)) return false;
        if(!eq(a*o.c, c*o.a)) return false;
        if(!eq(c*o.b, b*o.c)) return false;
        return true;
    }
    bool intersect(const line &o) const{
        return !parallel(o) || *this == o;
    }
    vec inter(const line &o) const{
        if(parallel(o)){
            if(*this == o){ }
            else{ /* dont intersect */ }
        }

        auto tmp = n ^ o.n;
        return {(o.c*b -c*o.b)/tmp, (o.a*c -a*o.c)/tmp};
    }
    vec at_x(cod x) const{
        return {x, (-c-a*x)/b};
    }
    vec at_y(cod y) const{
        return {(-c-b*y)/a, y};
    }
    cod eval(const vec &o) const{
        return a * o.x + b * o.y + c;
    }
};

struct segment{
    vec p, q;
    segment(vec a = vec(), vec b = vec()): p(a), q(b) {}
    bool onstrip(const vec &o) const{ // onstrip strip
        return p.dot(o, q) >= -eps && q.dot(o, p) >= -eps
            ;
    }
    cod len() const{
        return (p-q).len();
    }
    cod dist(const vec &o) const{
        if(onstrip(o)) return line(p, q).dist(o);
        return min((o-q).len(), (o-p).len());
    }
    bool contains(const vec &o) const{
        return eq(p.cross(q, o), 0) && onstrip(o);
    }
    bool intersect(const segment &o) const{
        if(contains(o.p)) return true;
        if(contains(o.q)) return true;
        if(o.contains(q)) return true;
        if(o.contains(p)) return true;
        return p.ccw(q, o.p) * p.ccw(q, o.q) == -1
            && o.p.ccw(o.q, q) * o.p.ccw(o.q, p) == -1;
    }
    bool intersect(const line &o) const{
        return o.eval(p) * o.eval(q) <= 0;
    }
    cod dist(const segment &o) const{

```

```

    if(line(p, q).parallel(line(o.p, o.q))) {
        if(onstrip(o.p) || onstrip(o.q)
           || o.onstrip(p) || o.onstrip(q))
            return line(p, q).dist(line(o.p, o.q));
    }
    else if(intersect(o)) return 0;
    return min(min(dist(o.p), dist(o.q)),
               min(o.dist(p), o.dist(q)));
}
cod dist(const line &o) const {
    if(line(p, q).parallel(o))
        return line(p, q).dist(o);
    else if(intersect(o)) return 0;
    return min(o.dist(p), o.dist(q));
}
};

struct hray {
    vec p, q;
    hray(vec a = vec(), vec b = vec()): p(a), q(b) {}
    bool onstrip(const vec &o) const { // onstrip strip
        return p.dot(q, o) >= -eps;
    }
    cod dist(const vec &o) const {
        if(onstrip(o)) return line(p, q).dist(o);
        return (o-p).len();
    }
    bool intersect(const segment &o) const {
        if(!o.intersect(line(p,q))) return false;
        if(line(o.p, o.q).parallel(line(p,q)))
            return contains(o.p) || contains(o.q);
        return contains(line(p,q).inter(line(o.p,o.q)));
    }
    bool contains(const vec &o) const {
        return eq(line(p, q).eval(o), 0) && onstrip(o);
    }
    cod dist(const segment &o) const {
        if(line(p, q).parallel(line(o.p, o.q))) {
            if(onstrip(o.p) || onstrip(o.q))
                return line(p, q).dist(line(o.p, o.q));
            return o.dist(p);
        }
        else if(intersect(o)) return 0;
        return min(min(dist(o.p), dist(o.q)),
                   o.dist(p));
    }
    bool intersect(const hray &o) const {
        if(!line(p, q).parallel(line(o.p, o.q)))
            return false;
        auto pt = line(p, q).inter(line(o.p, o.q));
        return contains(pt) && o.contains(pt); // <<
    }
    bool intersect(const line &o) const {
        if(line(p, q).parallel(o)) return line(p, q) == o;
        if(o.contains(p) || o.contains(q)) return true;
        return (o.eval(p) >= -eps) ^ (o.eval(p) < o.eval(q));
        return contains(o.inter(line(p, q)));
    }
    cod dist(const line &o) const {
        if(line(p,q).parallel(o))
            return line(p,q).dist(o);
        else if(intersect(o)) return 0;
        return o.dist(p);
    }
    cod dist(const hray &o) const {
        if(line(p, q).parallel(line(o.p, o.q))) {
            if(onstrip(o.p) || o.onstrip(p))

```

```

            return line(p,q).dist(line(o.p, o.q));
            return (p-o.p).len();
        }
        else if(intersect(o)) return 0;
        return min(dist(o.p), o.dist(p));
    }
};

double heron(cod a, cod b, cod c) {
    cod s = (a + b + c) / 2;
    return sqrt(s * (s - a) * (s - b) * (s - c));
}

line mediatrix(const vec &a, const vec &b) {
    auto tmp = (b - a) * 2;
    return line(tmp.x, tmp.y, a * a - b * b);
}

struct circle {
    vec c; cod r;
    circle() : c(0, 0), r(0) {}
    circle(const vec o) : c(o), r(0) {}
    circle(const vec &a, const vec &b) {
        c = (a + b) * 0.5; r = (a - c).len();
    }
    circle(const vec &a, const vec &b, const vec &cc) {
        c = mediatrix(a, b).inter(mediatrix(b, cc));
        r = (a - c).len();
    }
    bool inside(const vec &a) const {
        return (a - c).len() <= r;
    }
};

circle min_circle_cover(vector<vec> v) {
    random_shuffle(v.begin(), v.end());
    circle ans;
    int n = (int)v.size();
    for(int i = 0; i < n; i++) if(!ans.inside(v[i])) {
        ans = circle(v[i]);
        for(int j = 0; j < i; j++) if(!ans.inside(v[j])) {
            ans = circle(v[i], v[j]);
            for(int k = 0; k < j; k++) if(!ans.inside(v[k])) {
                ans = circle(v[i], v[j], v[k]);
            }
        }
    }
    return ans;
}

```

Circle line intersection

```

// intersection of line  $a * x + b * y + c = 0$ 
// and circle centered at the origin with radius r
double r, a, b, c; // given as input
double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
if(c*c > r*r*(a*a+b*b)+EPS)
    puts("no points");
else if(abs(c*c - r*r*(a*a+b*b)) < EPS) {
    puts("1 point");
    cout << x0 << ' ' << y0 << '\n';
}
else {
    double d = r*r - c*c/(a*a+b*b);
    double mult = sqrt(d / (a*a+b*b));
    double ax, ay, bx, by;
    ax = x0 + b * mult;
    bx = x0 - b * mult;
    ay = y0 - a * mult;
    by = y0 + a * mult;
    puts("2 points");
}

```

```
cout<<ax<<' ' <<ay<<'\\n'<<bx<<' ' <<by<<'\\n';
}
```

Half plane intersection

```
const double eps = 1e-8;
typedef pair<long double, long double> pi;
bool z(long double x){ return fabs(x) < eps; }
struct line{
    long double a, b, c;
    bool operator<(const line &l) const{
        bool flag1 = pi(a, b) > pi(0, 0);
        bool flag2 = pi(l.a, l.b) > pi(0, 0);
        if(flag1 != flag2) return flag1 > flag2;
        long double t = ccw(pi(0, 0), pi(a, b), pi(l.a, l.b));
        return z(t) ? c * hypot(l.a, l.b) < l.c * hypot(a, b) : t > 0;
    }
    pi slope(){ return pi(a, b); }
};
pi cross(line a, line b){
    long double det = a.a * b.b - b.a * a.b;
    return pi((a.c * b.b - a.b * b.c) / det, (a.a * b.c - a.c * b.a) / det);
}
bool bad(line a, line b, line c){
    if(ccw(pi(0, 0), a.slope(), b.slope()) <= 0) return false;
    pi crs = cross(a, b);
    return crs.first * c.a + crs.second * c.b >= c.c;
}
bool solve(vector<line> v, vector<pi> &solution){ // ax + by <= c;
    sort(v.begin(), v.end());
    deque<line> dq;
    for(auto &i : v){
        if(!dq.empty() && z(ccw(pi(0, 0), dq.back().slope(), i.slope()))) continue;
        while(dq.size() >= 2 && bad(dq[dq.size()-2], dq.back(), i)) dq.pop_back();
        while(dq.size() >= 2 && bad(i, dq[0], dq[1])) dq.pop_front();
        dq.push_back(i);
    }
    while(dq.size() > 2 && bad(dq[dq.size()-2], dq.back(), dq[0])) dq.pop_back();
    while(dq.size() > 2 && bad(dq.back(), dq[0], dq[1])) dq.pop_front();
    vector<pi> tmp;
    for(int i=0; i<dq.size(); i++){
        line cur = dq[i], nxt = dq[(i+1)%dq.size()];
        if(ccw(pi(0, 0), cur.slope(), nxt.slope()) <= eps) return false;
        tmp.push_back(cross(cur, nxt));
    }
    solution = tmp;
    return true;
}
```

Detect empty Half plane intersection

```
// abs(point a) = absolute value of a
// ccw(a, b, c) = a.ccw(b, c)
pair<bool, point> half_inter(vector<pair<point, point> > &vet){
    random_shuffle(all(vet));
    point p;
    rep(i, 0, sz(vet)) if(ccw(vet[i].x, vet[i].y, p) != 1){
```

```
point dir = (vet[i].y - vet[i].x) / abs(vet[i].y - vet[i].x);
point l = vet[i].x - dir*1e15;
point r = vet[i].x + dir*1e15;
if(r < l) swap(l, r);
rep(j, 0, i){
    if(ccw(point(), vet[i].x-vet[i].y, vet[j].x-vet[j].y) == 0){
        if(ccw(vet[j].x, vet[j].y, p) == 1) continue;
        return mp(false, point());
    }
    if(ccw(vet[j].x, vet[j].y, l) != 1) l = max(l, line_intersect(vet[i].x, vet[i].y, vet[j].x, vet[j].y));
    if(ccw(vet[j].x, vet[j].y, r) != 1) r = min(r, line_intersect(vet[i].x, vet[i].y, vet[j].x, vet[j].y));
    if(!(l < r)) return mp(false, point());
}
p = r;
}
return mp(true, p);
}
```

Circle Circle intersection

Assume that the first circle is centered at the origin and second at (x_2, y_2) . Find circle line intersection of first circle and line $Ax + By + C = 0$, where $A = -2x_2$, $B = -2y_2$, $C = x_2^2 + y_2^2 + r_1^2 - r_2^2$.

Be aware of corner case with two circles centered at the same point.

Tangents of two circles

```
// solve first for same circle(and infinitely many tangents)
// Find up to four tangents of two circles
void tangents(pt c, double r1, double r2, vector<line> &ans){
    double r = r2 - r1;
    double z = c.x * c.x + c.y * c.y;
    double d = z - r * r;
    if(d < -EPS) return;
    d = sqrt(abs(d));
    line l;
    l.a = (c.x * r + c.y * d) / z;
    l.b = (c.y * r - c.x * d) / z;
    l.c = r1;
    ans.push_back(l);
}
```

```
vector<line> tangents(circle a, circle b){
    vector<line> ans;
    pt aux = a.center - b.center;
    for(int i = -1; i <= 1; i += 2)
        for(int j = -1; j <= 1; j += 2)
            tangents(aux, a.r * i, b.r * j, ans);
    for(size_t i = 0; i < ans.size(); ++i)
        ans[i].c -= ans[i].a * a.x + ans[i].b * a.y;
    return ans;
}
```

Convex Hull

```
vector<vec> monotone_chain_ch(vector<vec> P){
    sort(P.begin(), P.end());
```



```

vector<vec> L, U;
for(auto p : P){
    while(L.size() >= 2 && L[L.size() - 2].cross(L.
        back(), p) < 0)
        L.pop_back();

    L.push_back(p);
}

reverse(P.begin(), P.end());
for(auto p : P){
    while(U.size() >= 2 && U[U.size() - 2].cross(U.
        back(), p) < 0)
        U.pop_back();

    U.push_back(p);
}

L.pop_back(), U.pop_back();

L.reserve(L.size() + U.size());
L.insert(L.end(), U.begin(), U.end());

return L;
}

```

Check point inside polygon

```

bool below(const vector<vec> &vet, vec p){
    auto it = lower_bound(vet.begin(), vet.end(), p);
    if(it == vet.end()) return false;
    if(it == vet.begin()) return *it == p;
    return prev(it)->cross(*it, p) <= 0;
}

bool above(const vector<vec> &vet, vec p){
    auto it = lower_bound(vet.begin(), vet.end(), p);
    if(it == vet.end()) return false;
    if(it == vet.begin()) return *it == p;
    return prev(it)->cross(*it, p) >= 0;
}

// lowerhull, upperhull and point, borders included
bool inside_poly(const vector<vec> &lo, const vector<vec>
    &hi, vec p){
    return below(hi, p) && above(lo, p);
}

```

Check point inside polygon without lower/upper hull

```

// borders included
// must not have 3 colinear consecutive points
bool inside_poly(const vector<vec> &v, vec p){
    if(v[0].ccw(v[1], p) < 0) return false;
    if(v[0].ccw(v.back(), p) > 0) return 0;
    if(v[0].ccw(v.back(), p) == 0)
        return v[0].dot(p, v.back()) >= 0
            && v.back().dot(p, v[0]) >= 0;

    int L = 1, R = (int)v.size() - 1, ans = 1;

    while(L <= R){
        int mid = (L+R)/2;
        if(v[0].ccw(v[mid], p) >= 0) ans = mid, L = mid
            +1;
        else R = mid-1;
    }
}

```

```

return v[ans].ccw(v[(ans+1)%v.size()], p) >= 0;
}

```

Minkowski sum

```

vector<vec> mk(const vector<vec> &a, const vector<vec> &b){
    int i = 0, j = 0;
    for(int k = 0; k < (int)a.size(); k++){
        if(a[k] < a[i])
            i = k;
        for(int k = 0; k < (int)b.size(); k++){
            if(b[k] < b[j])
                j = k;

            vector<vec> c;
            c.reserve(a.size() + b.size());
            for(int k = 0; k < int(a.size()+b.size()); k++){
                vec pt{a[i] + b[j]};
                if((int)c.size() >= 2
                    && c[c.size()-2].ccw(c.back(), pt) == 0)
                    c.pop_back();
                c.push_back(pt);
                int q = i+1, w = j+1;
                if(q == int(a.size())) q = 0;
                if(w == int(b.size())) w = 0;
                if(c.back().ccw(a[i]+b[w], a[q]+b[j]) < 0) i = q;
                else j = w;
            }
            c.shrink_to_fit();

            return c;
        }
    }
}

```

Geo Notes

Center of mass

System of points(2D/3D): Mass weighted average of points.

Frame(2D/3D): Get middle point of each segment solve as previously.

Triangle: Average of vertices.

2D Polygon: Compute **signed** area and center of mass of triangle $((0,0), p_i, p_{i+1})$. Then solve as system of points.

Polyhedron surface: Solve each face as a 2D polygon (be aware of $(0,0)$) then replace each face with its center of mass and solve as system of points.

Tetrahedron(Triangular pyramid): As triangles, its the average of points.

Polyhedron: Can be done as 2D polygon, but with tetrahedralization instead of triangulation.

Pick's Theorem

Given a polygon without self-intersections and all its vertices on integer coordinates in some 2D grid. Let A be its area, I the number of points with integer coordinates strictly inside the polygon and B the number of points with integer coordinates in the border of the polygon. The following formula holds: $A = I + \frac{B}{2} - 1$.

Miscellaneous

LIS

```

multiset<int> S;
for(int i = 0; i < n; i++){
    auto it = S.upper_bound(a[i]); // low for inc
    if(it != S.end()) S.erase(it);
    S.insert(a[i]);
}

```

```
}
ans = S.size();
```

DSU rollback

```
struct DSU{
    vector<int> sz, p, change;
    vector<tuple<int, int, int>> modifications;
    vector<size_t> saves;
    bool bipartite;

    DSU(int n): sz(n+1, 1), p(n+1), change(n+1),
        bipartite(true){
        iota(p.begin(), p.end(), 0);
    }

    void add_edge(int u, int v){
        if(!bipartite) return;
        int must_change = get_colour(u) == get_colour(v);
        int a = rep(u), b = rep(v);
        if(sz[a] < sz[b]) swap(a, b);
        if(a != b){
            p[b] = a;
            modifications.emplace_back(b, change[b],
                bipartite);
            change[b] ^= must_change;
            sz[a] += sz[b];
        }
        else if(must_change){
            modifications.emplace_back(0, change[0],
                bipartite);
            bipartite = false;
        }
    }

    int rep(int u){
        return p[u] == u ? u : rep(p[u]);
    }

    int get_colour(int u){
        if(p[u] == u) return change[u];
        return change[u] ^ get_colour(p[u]);
    }

    void reset(){
        modifications.clear();
        saves.clear();
        iota(p.begin(), p.end(), 0);
        fill(sz.begin(), sz.end(), 1);
        fill(change.begin(), change.end(), 0);
        bipartite = true;
    }

    void rollback(){
        int u = get<0>(modifications.back());
        tie(ignore, change[u], bipartite) = modifications
            .back();
        sz[ p[u] ] -= sz[u];
        p[u] = u;
        modifications.pop_back();
    }

    void reload(){
        while(modifications.size() > saves.back())
            rollback();
        saves.pop_back();
    }
}
```

```
void save(){
    saves.push_back(modifications.size());
}
};
```

Buildings

```
// count the number of circular arrays of size m, with
// elements on range [1, c**(n*n)]
int n, m, c; cin >> n >> m >> c;
int x = f_exp(c, n * n); int ans = f_exp(x, m);
for(int i = 1; i <= m; i++) if(m % i == 0) {
    int y = f_exp(x, i);
    for(int j = 1; j < i; j++) if(i % j == 0)
        y = sub(y, mult(j, dp[j]));
    dp[i] = mult(y, inv(i));
    ans = sub(ans, mult(i - 1, dp[i]));
}
cout << ans << '\n';
```

Rand

```
#include <random>
#include <chrono>
cout << RAND_MAX << endl;
mt19937 rng(chrono::steady_clock::now().time_since_epoch
    ().count());
vector<int> permutation(N);
iota(permutation.begin(), permutation.end(), 0);
shuffle(permutation.begin(), permutation.end(), rng);
iota(permutation.begin(), permutation.end(), 0);
for(int i = 1; i < N; i++){
    swap(permutation[i], permutation[
        uniform_int_distribution<int>(0, i)(rng)]);
}
}
```

Klondike

```
// minimum number of moves to make
// all elements equal
// move: change a segment of equal value
// elements to any value

int v[305], dp[305][305], rec[305][305];
```

```
int f(int l, int r){
    if(r == l) return 1;
    if(r < l) return 0;
    if(dp[l][r] != -1) return dp[l][r];
    int ans = f(l+1, r) + 1;
    for(int i = l+1; i <= r; i++){
        if(v[i] == v[l])
            ans = min(ans, f(l, i - 1) + f(i+1, r));
    }
    return dp[l][r] = ans;
}
```

Hilbert Order

```
// maybe use B = n / sqrt(q)
inline int64_t hilbertOrder(int x, int y, int pow = 21,
    int rotate = 0) {
    if(pow == 0) return 0;
    int hpow = 1 << (pow-1);
    int seg = (x < hpow) ? (
        (y < hpow) ? 0 : 3
    ) : (
        (y < hpow) ? 1 : 2
    );
    seg = (seg + rotate) & 3;
    const int rotateDelta[4] = {3, 0, 0, 1};
    int nx = x & (x ^ hpow), ny = y & (y ^ hpow);
```

```

int nrot = (rotate + rotateDelta[seg]) & 3;
int64_t subSquareSize = int64_t(1) << (2*pow - 2);
int64_t ans = seg * subSquareSize;
int64_t add = hilbertOrder(nx, ny, pow-1, nrot);
ans += (seg == 1 || seg == 2) ? add : (subSquareSize
    - add - 1);
return ans;
}

```

Modular Factorial

```

// Compute (1*2*...*(p-1)*1*(p+1)*(p+2)*...*n) % p
// in O(p*lg(n))
int factmod(int n, int p){
    int ans = 1;
    while(n > 1){
        for(int i = 2; i <= n % p; i++){
            ans = (ans * i) % p;
            n /= p;
            if(n % 2) ans = p - ans;
        }
        return ans % p;
    }
int fac_pow(int n, int p){
    int ans = 0;
    while(n) n /= p, ans += n;
    return ans;
}
int C(int n, int k, int p){
    if(fac_pow(n, p) > fac_pow(n-k, p) + fac_pow(k, p))
        return 0;
    int tmp = factmod(k, p) * factmod(n-k, p) % p;
    return (f_exp(tmp, p - 2, p) * factmod(n, p)) % p;
}

```

Enumeration all submasks of a bitmask

```

// loop through all submask of a given bitmask
// it does not include mask 0
for(int sub = mask; sub; sub = (sub-1)&mask){

}

```

Slope Trick

```

///By woqja125, contest: Codeforces Round #371 (Div. 1),
    problem: (C) Sonya and Problem Wihtout a Legend,
    Accepted, #
int main() {
    int n, t; long long ans = 0; priority_queue<int> Q;
    scanf("%d%d", &n, &t); Q.push(t);
    for(int i = 1; i < n; i++) {
        scanf("%d", &t); t -= i; Q.push(t);
        if(Q.top() > t) {
            ans += Q.top() - t; Q.pop(); Q.push(t);
        }
    }
    printf("%lld", ans);
}

```

Knapsack Bounded with Cost

```

// menor custo para conseguir peso ate M usando N tipos
    diferentes de elementos, sendo que o i-esimo elemento
    pode ser usado b[i] vezes, tem peso w[i] e custo c[i]
// O(N * M)

int b[N], w[N], c[N];
MinQueue Q[M]
int d[M] //d[i] = custo minimo para conseguir peso i

```

```

for(int i = 0; i <= M; i++) d[i] = i ? oo : 0;
for(int i = 0; i < N; i++){
    for(int j = 0; j < w[i]; j++){
        Q[j].clear();
        for(int j = 0; j <= M; j++){
            q = Q[j % w[i]];
            if(q.size() >= q) q.pop();
            q.add(c[i]);
            q.push(d[j]);
            d[j] = q.getmin();
        }
    }
}

```

LCA <O(nlgn), O(1)>

```

int start[N], dfs_time;
int tour[2*N], id[2*N];

void dfs(int u){
    start[u] = dfs_time;
    id[dfs_time] = u;
    tour[dfs_time++] = start[u];
    for(int v : g[u]){
        dfs(v);
        id[dfs_time] = u;
        tour[dfs_time++] = start[u];
    }
}

int LCA(int u, int v){
    if(start[u] > start[v]) swap(u, v);
    return id[min(tour[k] for k in [start[u], start[v]])];
}

```

Buffered reader

```

// source: https://github.com/ngthanhtung23/
    ACM_Notebook_new/blob/master/buffered_reader.h
int INP, AM, REACHEOF;
#define BUFSIZE (1<<12)
char BUF[BUFSIZE+1], *inp=BUF;
#define GETCHAR(INP) { \
    if(!*inp && !REACHEOF) { \
        memset(BUF, 0, sizeof BUF); \
        int inpzzz = fread(BUF, 1, BUFSIZE, stdin); \
        if (inpzzz != BUFSIZE) REACHEOF = true; \
        inp=BUF; \
    } \
    INP=*inp++; \
}
#define DIG(a) (((a)>='0')&&((a)<='9'))
#define GN(j) { \
    AM=0; \
    GETCHAR(INP); while(!DIG(INP) && INP!='-') GETCHAR(
        INP); \
    if (INP=='-') {AM=1; GETCHAR(INP);} \
    j=INP-'0'; GETCHAR(INP); \
    while(DIG(INP)){j=10*j+(INP-'0'); GETCHAR(INP);} \
    if (AM) j=-j; \
}

```

Modular summation

```

//calcula (sum(0 <= i <= n) P(i)) % mod,
//onde P(i) eh uma PA modular (com outro modulo)
namespace sum_pa_mod{
    ll calc(ll a, ll b, ll n, ll mod){
        assert(a&&b);
        if(a >= b){
            ll ret = ((n*(n+1)/2)%mod)*(a/b);

```

```

        if(a%b) ret = (ret + calc(a%b,b,n,mod))%mod;
        else ret = (ret+n+1)%mod;
        return ret;
    }
    return ((n+1)*(((n*a)/b+1)%mod) - calc(b,a,(n*a)/
        b,mod) + mod + n/b + 1)%mod;
}

//P(i) = a*i mod m
ll solve(ll a, ll n, ll m, ll mod){
    a = (a%m + m)%m;
    if(!a) return 0;
    ll ret = (n*(n+1)/2)%mod;
    ret = (ret*a)%mod;
    ll g = __gcd(a,m);
    ret -= m*(calc(a/g,m/g,n,mod)-n-1);
    return (ret%mod + mod)%mod;
}

//P(i) = a + r*i mod m
ll solve(ll a, ll r, ll n, ll m, ll mod){
    a = (a%m + m)%m;
    r = (r%m + m)%m;
    if(!r) return (a*(n+1))%mod;
    if(!a) return solve(r, n, m, mod);
    ll g, x, y;
    g = gcdExtended(r, m, x, y);
    x = (x%m + m)%m;
    ll d = a - (a/g)*g;
    a -= d;
    x = (x*(a/g))%m;
    return (solve(r, n+x, m, mod) - solve(r, x-1, m,
        mod) + mod + d*(n+1))%mod;
}
};

```

Edge coloring CPP

```

const int MX = 300;
int C[MX][MX] = {}, G[MX][MX] = {};

void solve(vector<pii> &E, int N){
    int X[MX] = {}, a, b;

    auto update = [&](int u){ for(X[u] = 1; C[u][X[u]];
        X[u]++); };
    auto color = [&](int u, int v, int c){
        int p = G[u][v];
        G[u][v] = G[v][u] = c;
        C[u][c] = v; C[v][c] = u;
        C[u][p] = C[v][p] = 0;
        if( p ) X[u] = X[v] = p;
        else update(u), update(v);
        return p; };
    auto flip = [&](int u, int c1, int c2){
        int p = C[u][c1], q = C[u][c2];
        swap(C[u][c1], C[u][c2]);
        if( p ) G[u][p] = G[p][u] = c2;
        if( !C[u][c1] ) X[u] = c1;
        if( !C[u][c2] ) X[u] = c2;
        return p; };

    for(int i = 1; i <= N; i++) X[i] = 1;
    for(int t = 0; t < E.size(); t++){
        int u = E[t].first, v0 = E[t].second, v = v0, c0
            = X[u], c = c0, d;
        vector<pii> L;
        int vst[MX] = {};

```

```

        while(!G[u][v0]){
            L.emplace_back(v, d = X[v]);
            if(!C[v][c]) for(a = (int)L.size()-1; a >= 0;
                a--) c = color(u, L[a].first, c);
            else if(!C[u][d])for(a=(int)L.size()-1;a>=0;a
                --)color(u,L[a].first,L[a].second);
            else if( vst[d] ) break;
            else vst[d] = 1, v = C[u][d];
        }
        if( !G[u][v0] ){
            for(;v; v = flip(v, c, d), swap(c, d));
            if(C[u][c0]){
                for(a = (int)L.size()-2; a >= 0 && L[a].
                    second != c; a--);
                for(; a >= 0; a--) color(u, L[a].first, L[
                    a].second);
            } else t--;
        }
    }
}

```

Burnside's Lemma

Let (G, \oplus) be a finite group that acts on a set X . It should hold that $e_g * x = x$ and $g_1 * (g_2 * x) = (g_1 \oplus g_2) * x, \forall x \in X, g_1, g_2 \in G$. For each $g \in G$ let $X^g = \{x \in X \mid g * x = x\}$. The number of orbits its given by:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

Wilson's Theorem

$(n-1)! = -1 \pmod n \iff n$ is prime

Fibonacci

- $F_{n-1}F_{n+1} - F_n^2 = (-1)^n$
- $F_{n+k} = F_k F_{n+1} + F_{k-1} F_n$
- $GCD(F_n, F_m) = F_{GCD(n,m)}$
- $F_n = \frac{(\frac{1+\sqrt{5}}{2})^n - (\frac{1-\sqrt{5}}{2})^n}{\sqrt{5}}$

Lucas's Theorem

For non-negative integers m and n and a prime p , the following congruence holds:

$$\binom{m}{n} \equiv \prod_{i=0}^k \binom{m_i}{n_i} \pmod p$$

where m_i is the i -th digit of m in base p . $\binom{a}{b} = 0$ if $a < b$.

Kirchhoff's Theorem

Laplacian matrix is $L = D - A$, where D is a diagonal matrix with vertex degrees on the diagonals and A is adjacency matrix.

The number of spanning trees is any cofactor of L . i -th cofactor is determinant of the matrix gotten by removing i -th row and column of L .

Multigraphs

In $D[i][i]$ all loops are excluded. $A[i][j]$ = number of edges from i to j .

Directed multigraphs

$D[i][i]$ = indegree of i minus the number of loops at i . $A[i][j]$ = number of edges from i to j .

The number of oriented spanning trees rooted at a vertex i is the determinant of the matrix gotten by removing the i th row and column of L .

Matroid

Let X set of objects, $I \subseteq 2^X$ set of independent sets such that:

1. $\emptyset \in I$
2. $A \in I, B \subseteq A \implies B \in I$
3. Exchange axiom, $A \in I, B \in I, |B| > |A| \implies \exists x \in B \setminus A : A \cup \{x\} \in I$
4. $A \subseteq X$ and I and I' are maximal independent subsets of A then $|I| = |I'|$

Then (X, I) is a matroid. The combinatorial optimization problem associated with it is: Given a weight $w(e) \geq 0 \forall e \in X$, find an independent subset that has the largest possible total weight.

Matroid intersection

```
// Input two matroids (X, I_a) and (X, I_b)
// output set I of maximum size, I \in I_a and I \in I_b
set<> I;
while(1){
    for(e_i : X \ I)
        if(I + e_i \in I_a and I + e_i \in I_b)
            I = I + e_i;
    set<> A, T; queue<> Q;
    for(x : X) label[x] = MARK1;
    for(e_i : X \ I){
        if(I + e_i \in I_a)
            Q.push(e_i), label[e_i] = MARK2;
        else{
            for(x such that I - x + e_i \in I_a)
                A[x].push(e_i);
        }
        if(I + e_i \in I_b)
            T = T + {e_i}
        else{
            for(x such that I - x + e_i \in I_b)
                A[e_i].push(x);
        }
    }
    if(T.empty()) break;
    bool found = false;
    while(!Q.empty() and !found){
        auto e = Q.front(); Q.pop();
        for(x : A[e]) if(label[x] == MARK1){
            label[x] = e; Q.push(x);
            if(x \in T){
                found = true; put = 1;
                while(label[x] != MARK2){
                    I = put ? (I + x) : (I - x);
                    put = 1 - put;
                }
                I = I + x;
            }
        }
    }
}
```

```
break;
    }
    }
    }
    if(!found) break;
}
```

return I;

Where $\text{path}(e) = [e]$ if $\text{label}[e] = \text{MARK2}$, $\text{path}(\text{label}[e]) + [e]$ otherwise.

Matroid Union

Given k matroids over the same set of objects $(X, I_1), (X, I_2), \dots, (X, I_k)$ find $A_1 \in I_1, A_2 \in I_2, \dots, A_k \in I_k$ such that $i \neq j, A_i \cap A_j = \emptyset$ and $|\bigcup_{i=1}^k A_i|$ is maximum. Matroid union can be reduced to matroid intersection as follows.

Let $X' = X \times \{1, 2, \dots, k\}$, ie, k copies of each element of X with different colors. $M1 = (X', Q)$ where $B \in Q \iff \forall 1 \leq i \leq k, \{x \mid (x, i) \in B\} \in I_i$, ie, for each color, B is independent. $M2 = (X', W)$ where $B \in W \iff i \neq j \implies \neg((x, i) \in B \wedge (x, j) \in B)$, ie, each element is picked by at most one color.

Intersection of $M1$ and $M2$ is the answer for the combinatorial problem of matroid union.

Notes

When we repeat something and each time we have probability p to succeed then the expected number of tries is $\frac{1}{p}$, till we succeed.

Small to large

Trick in statement If k sets are given you should note that the amount of different set sizes is $O(\sqrt{s})$ where s is total size of those sets. And no more than \sqrt{s} sets have size greater than \sqrt{s} . For example, a path to the root in Aho-Corasick through suffix links will have at most $O(\sqrt{s})$ vertices.

gcd on subsegment, we have at most $\log(a_i)$ different values in $\{\text{gcd}(a_j, a_{j+1}, \dots, a_i) \mid j < i\}$.

From static set to expandable. To insert, create a new set with the new element. While there are two sets with same size, merge them. There will be at most $\log(n)$ disjoint sets.

Matrix exponentiation optimization. Save binary power of $A_{n \times n}$ and answer q queries $b = A^m x$ in $O((n^3 + qn^2)\log(m))$.

Ternary search on integers into binary search, comparing $f(\text{mid})$ and $f(\text{mid}+1)$, binary search on derivative

Dynamic offline set For each element we will wind segment of time $[a, b]$ such that element is present in the set during this whole segment. Now we can come up with recursive procedure which handles $[l, r]$ time segment considering that all elements such that $[l, r] \subset [a, b]$ are already included into the set. Now, keeping this invariant we recursively go into $[l, m]$ and $[m+1, r]$ subsegments. Finally when we come into segment of length 1.

$$a > b \implies a \bmod b < \frac{a}{2}$$

Convex Hull. The expected number of points in the convex hull of a random set of points is $O(\log(n))$. The number of points in a convex hull with points coordinates limited by L is $O(L^{2/3})$.

Tree path query. Sometimes the linear query is fast enough. Just do adamant's hld sorting subtrees by their size and remap vertices indexes.