


# Clifford Tableaus and the Stabilizer Algorithm

**Leonard Uscinowicz**

Technical University of Munich

December 20<sup>th</sup>, 2024



## 1 Preliminary Definitions

## 2 Stabilizer Formalism

## 3 Stabilizer Algorithm

$$I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \quad Y = \begin{pmatrix} 0 & -i \\ i & 0 \end{pmatrix} \quad Z = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Pauli Matrices

$$I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \quad X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \quad Y = \begin{pmatrix} 0 & -i \\ i & 0 \end{pmatrix} \quad Z = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}$$

## Products of Pauli matrices:

$$\begin{aligned} I^2 &= X^2 = Y^2 = Z^2 = I \\ IX &= XI = X & IY &= YI = Y & IZ &= ZI = Z \\ XY &= iZ & YX &= -iZ \\ YZ &= iX & ZY &= -iX \\ ZX &= iY & XZ &= -iY \end{aligned}$$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

**Group**  $(G, \cdot)$  is a non-empty set  $G$  with a binary group multiplication operation " $\cdot$ ".

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Group Theory

**Group**  $(G, \cdot)$  is a non-empty set  $G$  with a binary group multiplication operation " $\cdot$ ".

Properties:

■ **Closure:**  $\forall g_1, g_2 \in G \implies g_1 \cdot g_2 \in G$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Group Theory

**Group**  $(G, \cdot)$  is a non-empty set  $G$  with a binary group multiplication operation " $\cdot$ ".

Properties:

■ **Closure:**  $\forall g_1, g_2 \in G \implies g_1 \cdot g_2 \in G$

■ **Associativity:**  $\forall g_1, g_2, g_3 \in G \implies g_1 \cdot (g_2 \cdot g_3) = (g_1 \cdot g_2) \cdot g_3$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Group Theory

**Group**  $(G, \cdot)$  is a non-empty set  $G$  with a binary group multiplication operation " $\cdot$ ".

Properties:

■ **Closure:**  $\forall g_1, g_2 \in G \implies g_1 \cdot g_2 \in G$

■ **Associativity:**  $\forall g_1, g_2, g_3 \in G \implies g_1 \cdot (g_2 \cdot g_3) = (g_1 \cdot g_2) \cdot g_3$

■ **Identity:**  $\exists e \in G$  such that  $\forall g \in G \implies e \cdot g = g \cdot e = g$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Group Theory

**Group**  $(G, \cdot)$  is a non-empty set  $G$  with a binary group multiplication operation " $\cdot$ ".

Properties:

■ **Closure:**  $\forall g_1, g_2 \in G \implies g_1 \cdot g_2 \in G$

■ **Associativity:**  $\forall g_1, g_2, g_3 \in G \implies g_1 \cdot (g_2 \cdot g_3) = (g_1 \cdot g_2) \cdot g_3$

■ **Identity:**  $\exists e \in G$  such that  $\forall g \in G \implies e \cdot g = g \cdot e = g$

■ **Inverse:**  $\forall g \in G \implies \exists g^{-1} \in G$  such that  $g \cdot g^{-1} = g^{-1} \cdot g = e$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Pauli Group

## Definitions

$\mathcal{P}_n$  is defined as the group of  $n$ -qubit Pauli operators.

It consists of all tensor products of  $n$  Pauli matrices, with a phase factor  $\pm 1$  or  $\pm i$ .

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Pauli Group

## Definitions

$\mathcal{P}_n$  is defined as the group of  $n$ -qubit Pauli operators.

It consists of all tensor products of  $n$  Pauli matrices, with a phase factor  $\pm 1$  or  $\pm i$ .

$$\mathcal{P}_1 = \{\pm I, \pm iI, \pm X, \pm iX, \pm Y, \pm iY, \pm Z, \pm iZ\}$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Pauli Group

## Definitions

$\mathcal{P}_n$  is defined as the group of  $n$ -qubit Pauli operators.

It consists of all tensor products of  $n$  Pauli matrices, with a phase factor  $\pm 1$  or  $\pm i$ .

$$\mathcal{P}_1 = \{\pm I, \pm iI, \pm X, \pm iX, \pm Y, \pm iY, \pm Z, \pm iZ\}$$

$$\mathcal{P}_n = \left\{ i^m \bigotimes_{j=1}^n \sigma_{k_j} \mid m, k_j \in \{0, 1, 2, 3\}, \sigma_0 = I, \sigma_1 = X, \sigma_2 = Y, \sigma_3 = Z \right\}$$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Pauli Group

## Definitions

$\mathcal{P}_n$  is defined as the group of  $n$ -qubit Pauli operators.

It consists of all tensor products of  $n$  Pauli matrices, with a phase factor  $\pm 1$  or  $\pm i$ .

$$\mathcal{P}_1 = \{\pm I, \pm iI, \pm X, \pm iX, \pm Y, \pm iY, \pm Z, \pm iZ\}$$

$$\mathcal{P}_n = \left\{ i^m \bigotimes_{j=1}^n \sigma_{k_j} \mid m, k_j \in \{0, 1, 2, 3\}, \sigma_0 = I, \sigma_1 = X, \sigma_2 = Y, \sigma_3 = Z \right\}$$

Size of a Pauli Group:  $|\mathcal{P}_n| = 4^{n+1}$

[1] [Scott Aaronson and Daniel Gottesman](#). “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

[2] [Michael A Nielsen and Isaac L Chuang](#). *Quantum computation and quantum information*. Cambridge university press, 2010

# Pauli Group

## Operations

Given two Pauli operators  $P = i^{m_P} \bigotimes_{j=1}^n P_j$  and  $Q = i^{m_Q} \bigotimes_{j=1}^n Q_j$ , their product, as necessitated by Group Definition, is:

$$P \cdot Q = i^{m_P + m_Q} \bigotimes_{j=1}^n P_j Q_j$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

## Pauli Group Operations

Given two Pauli operators  $P = i^{m_P} \bigotimes_{j=1}^n P_j$  and  $Q = i^{m_Q} \bigotimes_{j=1}^n Q_j$ , their product, as necessitated by Group Definition, is:

$$P \cdot Q = i^{m_P+m_Q} \bigotimes_{j=1}^n P_j Q_j$$

$P$  commutes with  $Q$  if the number of indices  $j$  such that  $P_j$  anti-commutes with  $Q_j$  is even.

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Group Generators

A set of  $l$  elements  $\{g_i\}_{1 \leq i \leq l}$  generates a group  $G$  if every element  $g \in G$  can be written as a product of the generators.

In this case, the group  $G$  can be written in terms of its generators:

$$G = \langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Group Generators

A set of  $l$  elements  $\{g_i\}_{1 \leq i \leq l}$  generates a group  $G$  if every element  $g \in G$  can be written as a product of the generators.

In this case, the group  $G$  can be written in terms of its generators:

$$G = \langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$$

**Examples:**

$$\begin{aligned} \mathcal{P}_1 &= \langle X, Z, iI \rangle \\ \langle X \rangle &= \{I, X\} \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

- 1 Preliminary Definitions
- 2 Stabilizer Formalism**
- 3 Stabilizer Algorithm

# Stabilizer Groups

## Definitions

- Element  $g \in \mathcal{P}_n$  **stabilizes**  $|\psi\rangle$  iff  $g|\psi\rangle = |\psi\rangle$ .  
 $|\psi\rangle$  is eigenstate of  $g$  with eigenvalue  $+1$ .

# Stabilizer Groups

## Definitions

- Element  $g \in \mathcal{P}_n$  **stabilizes**  $|\psi\rangle$  iff  $g|\psi\rangle = |\psi\rangle$ .  
 $|\psi\rangle$  is eigenstate of  $g$  with eigenvalue  $+1$ .
- $S \triangleq$  Subgroup of the Pauli Group  $\mathcal{P}_n$ :  $S \subseteq \mathcal{P}_n$ .

# Stabilizer Groups

## Definitions

- Element  $g \in \mathcal{P}_n$  **stabilizes**  $|\psi\rangle$  iff  $g|\psi\rangle = |\psi\rangle$ .  
 $|\psi\rangle$  is eigenstate of  $g$  with eigenvalue  $+1$ .

- $S \triangleq$  Subgroup of the Pauli Group  $\mathcal{P}_n$ :  $S \subseteq \mathcal{P}_n$ .

- $V_S \triangleq$  Set of  $n$ -qubit states stabilized by  $S$ :

$$V_S = \{|\psi\rangle \mid S \subseteq \mathcal{P}_n, \forall g \in S \text{ holds: } g|\psi\rangle = |\psi\rangle\}$$

# Stabilizer Groups

## Properties

Not just any subgroup  $S$  of the Pauli group can be used as the stabilizer for a non-trivial vector space  $V_S$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Groups

## Properties

Not just any subgroup  $S$  of the Pauli group can be used as the stabilizer for a non-trivial vector space  $V_S$ .

**Example:**  $S = \{\pm I, \pm X\}$

# Stabilizer Groups

## Properties

Not just any subgroup  $S$  of the Pauli group can be used as the stabilizer for a non-trivial vector space  $V_S$ .

**Example:**  $S = \{\pm I, \pm X\}$

$$(-I) \in S \text{ and } (-I) |\psi\rangle = -|\psi\rangle \implies |\psi\rangle = \vec{0} \implies V_S = \{\vec{0}\} \text{ (trivial)}$$



# Stabilizer Groups

## Properties

Not just any subgroup  $S$  of the Pauli group can be used as the stabilizer for a non-trivial vector space  $V_S$ .

**Example:**  $S = \{\pm I, \pm X\}$

$$(-I) \in S \text{ and } (-I) |\psi\rangle = -|\psi\rangle \implies |\psi\rangle = \vec{0} \implies V_S = \{\vec{0}\} \text{ (trivial)}$$

Conditions for  $S$  such that  $V_S$  not trivial:

■ **Commutativity:**  $\forall g_1, g_2 \in S$  holds:  $g_1 g_2 = g_2 g_1$

# Stabilizer Groups

## Properties

Not just any subgroup  $S$  of the Pauli group can be used as the stabilizer for a non-trivial vector space  $V_S$ .

**Example:**  $S = \{\pm I, \pm X\}$

$$(-I) \in S \text{ and } (-I) |\psi\rangle = -|\psi\rangle \implies |\psi\rangle = \vec{0} \implies V_S = \{\vec{0}\} \text{ (trivial)}$$

Conditions for  $S$  such that  $V_S$  not trivial:

■ **Commutativity:**  $\forall g_1, g_2 \in S$  holds:  $g_1 g_2 = g_2 g_1$

■ **Strict Identity:**  $-I \notin S, iI \notin S, -iI \notin S$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Commutativity Proof

Let  $V_S$  be non-trivial and let  $g_1, g_2 \in S$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Commutativity Proof

Let  $V_S$  be non-trivial and let  $g_1, g_2 \in S$ .

$\implies g_1$  and  $g_2$  are tensor products of Pauli matrices.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Commutativity Proof

Let  $V_S$  be non-trivial and let  $g_1, g_2 \in S$ .

$\implies g_1$  and  $g_2$  are tensor products of Pauli matrices.

$\implies g_1$  and  $g_2$  must either commute or anti-commute.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Commutativity Proof

Let  $V_S$  be non-trivial and let  $g_1, g_2 \in S$ .

$\implies g_1$  and  $g_2$  are tensor products of Pauli matrices.

$\implies g_1$  and  $g_2$  must either commute or anti-commute.

Suppose  $g_1$  and  $g_2$  anti-commute:

$$|\psi\rangle = g_1 g_2 |\psi\rangle = -g_2 g_1 |\psi\rangle = -|\psi\rangle \iff |\psi\rangle = \vec{0} \implies V_S \text{ is trivial.}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Commutativity Proof

Let  $V_S$  be non-trivial and let  $g_1, g_2 \in S$ .

$\implies g_1$  and  $g_2$  are tensor products of Pauli matrices.

$\implies g_1$  and  $g_2$  must either commute or anti-commute.

Suppose  $g_1$  and  $g_2$  anti-commute:

$$|\psi\rangle = g_1 g_2 |\psi\rangle = -g_2 g_1 |\psi\rangle = -|\psi\rangle \iff |\psi\rangle = \vec{0} \implies V_S \text{ is trivial.}$$

$\implies g_1$  and  $g_2$  anti-commuting leads to a contradiction.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Commutativity Proof

Let  $V_S$  be non-trivial and let  $g_1, g_2 \in S$ .

$\implies g_1$  and  $g_2$  are tensor products of Pauli matrices.

$\implies g_1$  and  $g_2$  must either commute or anti-commute.

Suppose  $g_1$  and  $g_2$  anti-commute:

$$|\psi\rangle = g_1 g_2 |\psi\rangle = -g_2 g_1 |\psi\rangle = -|\psi\rangle \iff |\psi\rangle = \vec{0} \implies V_S \text{ is trivial.}$$

$\implies g_1$  and  $g_2$  anti-commuting leads to a contradiction.

$\implies g_1$  and  $g_2$  commute.

[2] [Michael A Nielsen and Isaac L Chuang](#). *Quantum computation and quantum information*. Cambridge university press, 2010



# Stabilizer Conditions

## Strict Identity Proof

Let  $V_S$  be non-trivial.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Strict Identity Proof

Let  $V_S$  be non-trivial.

$$(-I) \in S \quad \implies \quad |\psi\rangle = (-I) |\psi\rangle = -|\psi\rangle \quad \iff \quad |\psi\rangle = \vec{0} \quad \implies \quad V_S \text{ is trivial.}$$

$$(iI) \in S \quad \implies \quad |\psi\rangle = (iI) |\psi\rangle = i|\psi\rangle \quad \iff \quad |\psi\rangle = \vec{0} \quad \implies \quad V_S \text{ is trivial.}$$

$$(-iI) \in S \quad \implies \quad |\psi\rangle = (-iI) |\psi\rangle = -i|\psi\rangle \quad \iff \quad |\psi\rangle = \vec{0} \quad \implies \quad V_S \text{ is trivial.}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Conditions

## Strict Identity Proof

Let  $V_S$  be non-trivial.

$$(-I) \in S \implies |\psi\rangle = (-I) |\psi\rangle = -|\psi\rangle \iff |\psi\rangle = \vec{0} \implies V_S \text{ is trivial.}$$

$$(iI) \in S \implies |\psi\rangle = (iI) |\psi\rangle = i|\psi\rangle \iff |\psi\rangle = \vec{0} \implies V_S \text{ is trivial.}$$

$$(-iI) \in S \implies |\psi\rangle = (-iI) |\psi\rangle = -i|\psi\rangle \iff |\psi\rangle = \vec{0} \implies V_S \text{ is trivial.}$$

$-I \in S, iI \in S, -iI \in S$  lead to contradictions.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

## Check Matrix Structure

Suppose  $S = \langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

## Check Matrix Structure

Suppose  $S = \langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

Extremely useful way of presenting the generators: **Check Matrix**  $H_S$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

## Check Matrix Structure

Suppose  $S = \langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

Extremely useful way of presenting the generators: **Check Matrix**  $H_S$

$H_S$  is an  $l \times 2n$  binary matrix whose rows correspond to the generators  $g_1$  through  $g_l$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix Structure

Suppose  $S = \langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

Extremely useful way of presenting the generators: **Check Matrix**  $H_S$

$H_S$  is an  $l \times 2n$  binary matrix whose rows correspond to the generators  $g_1$  through  $g_l$ .

Example:

$$l \left\{ \left[ \begin{array}{cccccccc|cccccccc} 0 & 0 & 0 & 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 1 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 \end{array} \right] \right.$$

$\underbrace{\hspace{10em}}_n \qquad \underbrace{\hspace{10em}}_n$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.
- Right  $l \times n$  submatrix contains 1s to indicate which generators contain  $Z$ s.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.
- Right  $l \times n$  submatrix contains 1s to indicate which generators contain  $Z$ s.
- Presence of 1 in both submatrices indicates  $Y$  in that generator.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.
- Right  $l \times n$  submatrix contains 1s to indicate which generators contain  $Z$ s.
- Presence of 1 in both submatrices indicates  $Y$  in that generator.

More explicitly, with  $h_{i,j}$  denoting the element of  $H_S$  at row  $i$  and column  $j$ :

- If  $g_i$  contains  $I$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 0$  and  $h_{i,n+j} = 0$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.
- Right  $l \times n$  submatrix contains 1s to indicate which generators contain  $Z$ s.
- Presence of 1 in both submatrices indicates  $Y$  in that generator.

More explicitly, with  $h_{i,j}$  denoting the element of  $H_S$  at row  $i$  and column  $j$ :

- If  $g_i$  contains  $I$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 0$  and  $h_{i,n+j} = 0$ .
- If  $g_i$  contains  $X$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 1$  and  $h_{i,n+j} = 0$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.
- Right  $l \times n$  submatrix contains 1s to indicate which generators contain  $Z$ s.
- Presence of 1 in both submatrices indicates  $Y$  in that generator.

More explicitly, with  $h_{i,j}$  denoting the element of  $H_S$  at row  $i$  and column  $j$ :

- If  $g_i$  contains  $I$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 0$  and  $h_{i,n+j} = 0$ .
- If  $g_i$  contains  $X$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 1$  and  $h_{i,n+j} = 0$ .
- If  $g_i$  contains  $Z$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 0$  and  $h_{i,n+j} = 1$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Interpretation

- Row  $i$  corresponds to generator  $g_i \in S$ .
- Left  $l \times n$  submatrix contains 1s to indicate which generators contain  $X$ s.
- Right  $l \times n$  submatrix contains 1s to indicate which generators contain  $Z$ s.
- Presence of 1 in both submatrices indicates  $Y$  in that generator.

More explicitly, with  $h_{i,j}$  denoting the element of  $H_S$  at row  $i$  and column  $j$ :

- If  $g_i$  contains  $I$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 0$  and  $h_{i,n+j} = 0$ .
- If  $g_i$  contains  $X$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 1$  and  $h_{i,n+j} = 0$ .
- If  $g_i$  contains  $Z$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 0$  and  $h_{i,n+j} = 1$ .
- If  $g_i$  contains  $Y$  on the  $j^{\text{th}}$  qubit  $\implies h_{i,j} = 1$  and  $h_{i,n+j} = 1$ .

[2] [Michael A Nielsen and Isaac L Chuang](#). *Quantum computation and quantum information*. Cambridge university press, 2010

# Check Matrix

## Example Steane Code

For Readability tensor product operator signs are left out.  $\sigma_i \sigma_j$  corresponds to  $\sigma_i \otimes \sigma_j$ .

$$\left[ \begin{array}{cccccc|cccccccc} 0 & 0 & 0 & 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 1 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 0 & 1 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 \end{array} \right] \cong$$

Generator	Operator
$g_1$	$IIIXXXX$
$g_2$	$IXXIIXX$
$g_3$	$XIXIXIX$
$g_4$	$IIIZZZZ$
$g_5$	$IZZIIZZ$
$g_6$	$ZIZIZIZ$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Unitary Operations

## Main Revelation

Suppose  $U$  is a unitary operator,  $|\psi\rangle \in V_S$  and  $g \in S$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Unitary Operations

## Main Revelation

Suppose  $U$  is a unitary operator,  $|\psi\rangle \in V_S$  and  $g \in S$ .

$$U |\psi\rangle = U g |\psi\rangle = U g I |\psi\rangle = U g U^\dagger U |\psi\rangle = (U g U^\dagger) U |\psi\rangle$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Unitary Operations

## Main Revelation

Suppose  $U$  is a unitary operator,  $|\psi\rangle \in V_S$  and  $g \in S$ .

$$U |\psi\rangle = U g |\psi\rangle = U g I |\psi\rangle = U g U^\dagger U |\psi\rangle = (U g U^\dagger) U |\psi\rangle$$

$\implies$  State  $U |\psi\rangle$  is stabilized by  $U g U^\dagger$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Unitary Operations

## Main Revelation

Suppose  $U$  is a unitary operator,  $|\psi\rangle \in V_S$  and  $g \in S$ .

$$U |\psi\rangle = U g |\psi\rangle = U g I |\psi\rangle = U g U^\dagger U |\psi\rangle = (U g U^\dagger) U |\psi\rangle$$

$\implies$  State  $U |\psi\rangle$  is stabilized by  $U g U^\dagger$ .

$\implies$  If we can describe a state by its stabilizers, we can easily compute the stabilizers of the state that emerges from the previous state under a unitary operation.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Unitary Operations

## Advantages for Computation

For certain special unitary operations  $U$  this transformation of the generators takes on a particularly appealing form.

# Unitary Operations

## Advantages for Computation

For certain special unitary operations  $U$  this transformation of the generators takes on a particularly appealing form.

$$HXH^\dagger = Z \quad HYH^\dagger = -Y \quad HZH^\dagger = X$$

# Unitary Operations

## Advantages for Computation

For certain special unitary operations  $U$  this transformation of the generators takes on a particularly appealing form.

$$HXH^\dagger = Z \quad HYH^\dagger = -Y \quad HZH^\dagger = X$$

### Example:

(Unkown) State  $|\psi\rangle$  stabilized by  $X$ .

# Unitary Operations

## Advantages for Computation

For certain special unitary operations  $U$  this transformation of the generators takes on a particularly appealing form.

$$HXH^\dagger = Z \quad HYH^\dagger = -Y \quad HZH^\dagger = X$$

### Example:

(Unknown) State  $|\psi\rangle$  stabilized by  $X$ .

→ Apply Hadamard gate  $H$  to  $|\psi\rangle$ .



# Unitary Operations

## Advantages for Computation

For certain special unitary operations  $U$  this transformation of the generators takes on a particularly appealing form.

$$HXH^\dagger = Z \quad HYH^\dagger = -Y \quad HZH^\dagger = X$$

### Example:

(Unkown) State  $|\psi\rangle$  stabilized by  $X$ .

→ Apply Hadamard gate  $H$  to  $|\psi\rangle$ .

⇒ Resulting (Unkown) state  $|\psi'\rangle$  stabilized by  $Z$ .

# Unitary Operations

## Transformation under Conjugation

Operation	Input	Output
$CX$	$X_1$	$X_1X_2$
	$X_2$	$X_2$
	$Z_1$	$Z_1$
	$Z_2$	$Z_1Z_2$
$H$	$X$	$Z$
	$Z$	$X$
$S$	$X$	$Y$
	$Z$	$Z$

Operation	Input	Output
$X$	$X$	$X$
	$Z$	$-Z$
$Y$	$X$	$-X$
	$Z$	$-Z$
$Z$	$X$	$-X$
	$Z$	$Z$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Main Principles

We want to measure observable  $g \in \mathcal{P}_n$  of state  $|\psi\rangle$ , stabilized by  $\langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Main Principles

We want to measure observable  $g \in \mathcal{P}_n$  of state  $|\psi\rangle$ , stabilized by  $\langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

### Two possibilities:

1.  $g$  commutes with all generators of the stabilizer.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Main Principles

We want to measure observable  $g \in \mathcal{P}_n$  of state  $|\psi\rangle$ , stabilized by  $\langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

### Two possibilities:

1.  $g$  commutes with all generators of the stabilizer.  
 $\implies$  Measurement outcome is deterministic.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Main Principles

We want to measure observable  $g \in \mathcal{P}_n$  of state  $|\psi\rangle$ , stabilized by  $\langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

### Two possibilities:

1.  $g$  commutes with all generators of the stabilizer.  
 $\implies$  Measurement outcome is deterministic.
2.  $g$  anti-commutes with at least 1 generator of the stabilizer.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Main Principles

We want to measure observable  $g \in \mathcal{P}_n$  of state  $|\psi\rangle$ , stabilized by  $\langle g_i \mid i \in \mathbb{N}, 1 \leq i \leq l \rangle$ .

### Two possibilities:

1.  $g$  commutes with all generators of the stabilizer.  
 $\implies$  Measurement outcome is deterministic.
2.  $g$  anti-commutes with at least 1 generator of the stabilizer.  
 $\implies$  Measurement outcome is not deterministic.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Deterministic case

$g$  commutes with all  $g_i$  and assume  $g$  does not have a global phase.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Measurement

## Deterministic case

$g$  commutes with all  $g_i$  and assume  $g$  does not have a global phase.

$$\forall i \text{ holds: } g_i g |\psi\rangle = g g_i |\psi\rangle = g |\psi\rangle \implies g |\psi\rangle \in V_S$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Deterministic case

$g$  commutes with all  $g_i$  and assume  $g$  does not have a global phase.

$$\forall i \text{ holds: } g_i g |\psi\rangle = g g_i |\psi\rangle = g |\psi\rangle \implies g |\psi\rangle \in V_S$$

$$g^2 |\psi\rangle = I |\psi\rangle = |\psi\rangle \implies g |\psi\rangle = \pm |\psi\rangle \implies g \in S \vee (-g) \in S$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Deterministic case

$g$  commutes with all  $g_i$  and assume  $g$  does not have a global phase.

$$\forall i \text{ holds: } g_i g |\psi\rangle = g g_i |\psi\rangle = g |\psi\rangle \implies g |\psi\rangle \in V_S$$

$$g^2 |\psi\rangle = I |\psi\rangle = |\psi\rangle \implies g |\psi\rangle = \pm |\psi\rangle \implies g \in S \vee (-g) \in S$$

$$g \in S \implies g |\psi\rangle = |\psi\rangle \implies \text{Measurement yields } +1$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Deterministic case

$g$  commutes with all  $g_i$  and assume  $g$  does not have a global phase.

$$\forall i \text{ holds: } g_i g |\psi\rangle = g g_i |\psi\rangle = g |\psi\rangle \implies g |\psi\rangle \in V_S$$

$$g^2 |\psi\rangle = I |\psi\rangle = |\psi\rangle \implies g |\psi\rangle = \pm |\psi\rangle \implies g \in S \vee (-g) \in S$$

$$g \in S \implies g |\psi\rangle = |\psi\rangle \implies \text{Measurement yields } +1$$

$$(-g) \in S \implies g |\psi\rangle = -|\psi\rangle \implies \text{Measurement yields } -1$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Deterministic case

$g$  commutes with all  $g_i$  and assume  $g$  does not have a global phase.

$$\forall i \text{ holds: } g_i g |\psi\rangle = g g_i |\psi\rangle = g |\psi\rangle \implies g |\psi\rangle \in V_S$$

$$g^2 |\psi\rangle = I |\psi\rangle = |\psi\rangle \implies g |\psi\rangle = \pm |\psi\rangle \implies g \in S \vee (-g) \in S$$

$$g \in S \implies g |\psi\rangle = |\psi\rangle \implies \text{Measurement yields } +1$$

$$(-g) \in S \implies g |\psi\rangle = -|\psi\rangle \implies \text{Measurement yields } -1$$

In both cases the measurement does not disturb the state of the system, and leaves the stabilizer invariant.

[2] [Michael A Nielsen and Isaac L Chuang](#). *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case preliminaries

Without loss of generality, let  $g$  anti-commute with  $g_1$  and  $g$  does not have a global phase.

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case preliminaries

Without loss of generality, let  $g$  anti-commute with  $g_1$  and  $g$  does not have a global phase.

$\forall g_j$  with  $j \neq 1$  and  $g_j g = -g g_j$  : Replace  $g_j$  with  $g'_j = g_1 g_j$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case preliminaries

Without loss of generality, let  $g$  anti-commute with  $g_1$  and  $g$  does not have a global phase.

$$\begin{aligned} \forall g_j \text{ with } j \neq 1 \text{ and } g_j g = -g g_j : & \text{ Replace } g_j \text{ with } g'_j = g_1 g_j \\ \implies g'_j g = g_1 g_j g = -g_1 g g_j = g g_1 g_j = g g'_j \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Measurement

## Non-deterministic case preliminaries

Without loss of generality, let  $g$  anti-commute with  $g_1$  and  $g$  does not have a global phase.

$$\begin{aligned} \forall g_j \text{ with } j \neq 1 \text{ and } g_j g = -g g_j : & \text{ Replace } g_j \text{ with } g'_j = g_1 g_j \\ \implies g'_j g = g_1 g_j g = -g_1 g g_j = g g_1 g_j = g g'_j \\ \implies g \text{ commutes with } g'_j \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case preliminaries

Without loss of generality, let  $g$  anti-commute with  $g_1$  and  $g$  does not have a global phase.

$\forall g_j$  with  $j \neq 1$  and  $g_j g = -g g_j$  : Replace  $g_j$  with  $g'_j = g_1 g_j$

$$\implies g'_j g = g_1 g_j g = -g_1 g g_j = g g_1 g_j = g g'_j$$

$$\implies g \text{ commutes with } g'_j$$

$\implies g$  only commutes with  $g_1$ .

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case preliminaries

Without loss of generality, let  $g$  anti-commute with  $g_1$  and  $g$  does not have a global phase.

$$\begin{aligned} \forall g_j \text{ with } j \neq 1 \text{ and } g_j g = -g g_j : & \text{ Replace } g_j \text{ with } g'_j = g_1 g_j \\ \implies g'_j g = g_1 g_j g = -g_1 g g_j = g g_1 g_j = g g'_j \\ \implies g \text{ commutes with } g'_j \end{aligned}$$

$\implies g$  only commutes with  $g_1$ .

Because  $g$  has eigenvalues  $\pm 1$ , the measurement operators are:  $M_{\pm g} = \frac{I \pm g}{2}$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I + g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I - g}{2} |\psi\rangle \langle\psi| \right)$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right)$$

[2] [Michael A Nielsen and Isaac L Chuang](#). *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right)$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right) = \text{tr} \left( g_1 \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$\begin{aligned} p(+1) &= \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right) = \text{tr} \left( g_1 \frac{I-g}{2} |\psi\rangle \langle\psi| \right) \\ &= \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1 \right) \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010



# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$\begin{aligned} p(+1) &= \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right) = \text{tr} \left( g_1 \frac{I-g}{2} |\psi\rangle \langle\psi| \right) \\ &= \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1 \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1^\dagger \right) \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$\begin{aligned} p(+1) &= \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right) = \text{tr} \left( g_1 \frac{I-g}{2} |\psi\rangle \langle\psi| \right) \\ &= \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1 \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1^\dagger \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right) \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$\begin{aligned} p(+1) &= \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right) = \text{tr} \left( g_1 \frac{I-g}{2} |\psi\rangle \langle\psi| \right) \\ &= \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1 \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1^\dagger \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right) = p(-1) \end{aligned}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

# Measurement

## Non-deterministic case continuation

Measurement probabilities:

$$p(+1) = \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) \quad \wedge \quad p(-1) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right)$$

$$\begin{aligned} p(+1) &= \text{tr} \left( \frac{I+g}{2} |\psi\rangle \langle\psi| \right) = \text{tr} \left( \frac{I+g}{2} g_1 |\psi\rangle \langle\psi| \right) = \text{tr} \left( g_1 \frac{I-g}{2} |\psi\rangle \langle\psi| \right) \\ &= \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1 \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| g_1^\dagger \right) = \text{tr} \left( \frac{I-g}{2} |\psi\rangle \langle\psi| \right) = p(-1) \end{aligned}$$

$$p(+1) = p(-1) \text{ and } p(+1) + p(-1) = 1 \implies p(+1) = p(-1) = \frac{1}{2}$$

[2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010

- 1 Preliminary Definitions
- 2 Stabilizer Formalism
- 3 Stabilizer Algorithm**

# Gottesman–Knill Theorem

Suppose a quantum computation is performed which involves only the following elements:

- State preparations in the computational basis
- Hadamard gates
- Phase gates
- Controlled-NOT gates
- Pauli gates
- Measurements of observables in the Pauli group

Together with the possibility of classical control conditioned on the outcome of such measurements. Such a computation may be efficiently simulated on a classical computer.

[2] [Michael A Nielsen and Isaac L Chuang](#). *Quantum computation and quantum information*. Cambridge university press, 2010

# Stabilizer Circuit

**Mainly:**

Circuit consisting solely of  $CX$ ,  $H$ ,  $S$  and  $M$  gates.

# Stabilizer Circuit

**Mainly:**

Circuit consisting solely of  $CX$ ,  $H$ ,  $S$  and  $M$  gates.

Can actually also implement  $X$ ,  $Y$ ,  $Z$  and  $SWAP$ .



# Stabilizer Circuit

**Mainly:**

Circuit consisting solely of  $CX$ ,  $H$ ,  $S$  and  $M$  gates.

Can actually also implement  $X$ ,  $Y$ ,  $Z$  and  $SWAP$ .

$$Z = SS$$

# Stabilizer Circuit

**Mainly:**

Circuit consisting solely of  $CX$ ,  $H$ ,  $S$  and  $M$  gates.

Can actually also implement  $X$ ,  $Y$ ,  $Z$  and  $SWAP$ .

$$Z = SS$$

$$X = HZH$$

# Stabilizer Circuit

## Mainly:

Circuit consisting solely of  $CX$ ,  $H$ ,  $S$  and  $M$  gates.

Can actually also implement  $X$ ,  $Y$ ,  $Z$  and  $SWAP$ .

$$Z = SS$$

$$X = HZH$$

$$Y = SXSSS$$

# Stabilizer Circuit

## Mainly:

Circuit consisting solely of  $CX$ ,  $H$ ,  $S$  and  $M$  gates.

Can actually also implement  $X$ ,  $Y$ ,  $Z$  and  $SWAP$ .

$$Z = SS$$

$$X = HZH$$

$$Y = SXSSS$$

$$SWAP(a, b) = CX(a, b)CX(b, a)CX(a, b)$$

# Clifford Tableau Structure

Basically an expanded Check Matrix.

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Structure

Basically an expanded Check Matrix.

$$\left( \begin{array}{ccc|ccc|c} x_{1,1} & \cdots & x_{1,n} & z_{1,1} & \cdots & z_{1,n} & r_1 \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{n,1} & \cdots & x_{n,n} & z_{n,1} & \cdots & z_{n,n} & r_n \\ \hline x_{(n+1),1} & \cdots & x_{(n+1),n} & z_{(n+1),1} & \cdots & z_{(n+1),n} & r_{n+1} \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{(2n),1} & \cdots & x_{(2n),n} & z_{(2n),1} & \cdots & z_{(2n),n} & r_{2n} \\ \hline x_{(2n+1),1} & \cdots & x_{(2n+1),n} & z_{(2n+1),1} & \cdots & z_{(2n+1),n} & r_{2n+1} \end{array} \right)$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Interpretation

Developers of the following algorithm introduce additional  $n$  "Destabilizer" generators, which are Pauli operators that together with the stabilizer generators generate the full Pauli group.

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Interpretation

Developers of the following algorithm introduce additional  $n$  "Destabilizer" generators, which are Pauli operators that together with the stabilizer generators generate the full Pauli group.

- Rows 1 to  $n$  represent Destabilizers.

$x_{1,1}$	$\cdots$	$x_{1,n}$	$z_{1,1}$	$\cdots$	$z_{1,n}$	$r_1$
$\vdots$	$\ddots$	$\vdots$	$\vdots$	$\ddots$	$\vdots$	$\vdots$
$x_{n,1}$	$\cdots$	$x_{n,n}$	$z_{n,1}$	$\cdots$	$z_{n,n}$	$r_n$
$x_{(n+1),1}$	$\cdots$	$x_{(n+1),n}$	$z_{(n+1),1}$	$\cdots$	$z_{(n+1),n}$	$r_{n+1}$
$\vdots$	$\ddots$	$\vdots$	$\vdots$	$\ddots$	$\vdots$	$\vdots$
$x_{(2n),1}$	$\cdots$	$x_{(2n),n}$	$z_{(2n),1}$	$\cdots$	$z_{(2n),n}$	$r_{2n}$
$x_{(2n+1),1}$	$\cdots$	$x_{(2n+1),n}$	$z_{(2n+1),1}$	$\cdots$	$z_{(2n+1),n}$	$r_{2n+1}$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)



# Clifford Tableau

## Interpretation

Developers of the following algorithm introduce additional  $n$  "Destabilizer" generators, which are Pauli operators that together with the stabilizer generators generate the full Pauli group.

- Rows 1 to  $n$  represent Destabilizers.
- Rows  $n + 1$  to  $2n$  represent Stabilizers.

$$\left( \begin{array}{ccc|ccc|c} x_{1,1} & \cdots & x_{1,n} & z_{1,1} & \cdots & z_{1,n} & r_1 \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{n,1} & \cdots & x_{n,n} & z_{n,1} & \cdots & z_{n,n} & r_n \\ \hline x_{(n+1),1} & \cdots & x_{(n+1),n} & z_{(n+1),1} & \cdots & z_{(n+1),n} & r_{n+1} \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{(2n),1} & \cdots & x_{(2n),n} & z_{(2n),1} & \cdots & z_{(2n),n} & r_{2n} \\ \hline x_{(2n+1),1} & \cdots & x_{(2n+1),n} & z_{(2n+1),1} & \cdots & z_{(2n+1),n} & r_{2n+1} \end{array} \right)$$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Interpretation

Developers of the following algorithm introduce additional  $n$  "Destabilizer" generators, which are Pauli operators that together with the stabilizer generators generate the full Pauli group.

- Rows 1 to  $n$  represent Destabilizers.
- Rows  $n + 1$  to  $2n$  represent Stabilizers.
- Row  $2n + 1$  is scratch-space.

$$\left( \begin{array}{ccc|ccc|c} x_{1,1} & \cdots & x_{1,n} & z_{1,1} & \cdots & z_{1,n} & r_1 \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{n,1} & \cdots & x_{n,n} & z_{n,1} & \cdots & z_{n,n} & r_n \\ \hline x_{(n+1),1} & \cdots & x_{(n+1),n} & z_{(n+1),1} & \cdots & z_{(n+1),n} & r_{n+1} \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots & \vdots \\ x_{(2n),1} & \cdots & x_{(2n),n} & z_{(2n),1} & \cdots & z_{(2n),n} & r_{2n} \\ \hline x_{(2n+1),1} & \cdots & x_{(2n+1),n} & z_{(2n+1),1} & \cdots & z_{(2n+1),n} & r_{2n+1} \end{array} \right)$$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Interpretation

Developers of the following algorithm introduce additional  $n$  "Destabilizer" generators, which are Pauli operators that together with the stabilizer generators generate the full Pauli group.

- Rows 1 to  $n$  represent Destabilizers.
- Rows  $n + 1$  to  $2n$  represent Stabilizers.
- Row  $2n + 1$  is scratch-space.
- $r_i$  of row  $i$  represents the global phase,  
 $r_i = 0$  for  $+1$  and  $r_i = 1$  for  $-1$ .

$x_{1,1}$	$\cdots$	$x_{1,n}$	$z_{1,1}$	$\cdots$	$z_{1,n}$	$r_1$
$\vdots$	$\ddots$	$\vdots$	$\vdots$	$\ddots$	$\vdots$	$\vdots$
$x_{n,1}$	$\cdots$	$x_{n,n}$	$z_{n,1}$	$\cdots$	$z_{n,n}$	$r_n$
$x_{(n+1),1}$	$\cdots$	$x_{(n+1),n}$	$z_{(n+1),1}$	$\cdots$	$z_{(n+1),n}$	$r_{n+1}$
$\vdots$	$\ddots$	$\vdots$	$\vdots$	$\ddots$	$\vdots$	$\vdots$
$x_{(2n),1}$	$\cdots$	$x_{(2n),n}$	$z_{(2n),1}$	$\cdots$	$z_{(2n),n}$	$r_{2n}$
$x_{(2n+1),1}$	$\cdots$	$x_{(2n+1),n}$	$z_{(2n+1),1}$	$\cdots$	$z_{(2n+1),n}$	$r_{2n+1}$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Initial Tableau

Pauli- $Z$  gates stabilize  $|0\rangle$  states and Pauli- $X$  gates destabilize  $|0\rangle$  states.

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Initial Tableau

Pauli- $Z$  gates stabilize  $|0\rangle$  states and Pauli- $X$  gates destabilize  $|0\rangle$  states.

$\implies$  Tableau for  $|0\rangle^{\otimes n}$  has an Identity submatrix for its first  $(2n) \times (2n)$  submatrix.

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Initial Tableau

Pauli- $Z$  gates stabilize  $|0\rangle$  states and Pauli- $X$  gates destabilize  $|0\rangle$  states.

$\implies$  Tableau for  $|0\rangle^{\otimes n}$  has an Identity submatrix for its first  $(2n) \times (2n)$  submatrix.

Tableau for  $|00\rangle$  is

$$\left( \begin{array}{cc|cc|c} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ \hline 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ \hline 0 & 0 & 0 & 0 & 0 \end{array} \right)$$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Clifford Tableau

## Initial Tableau

Pauli- $Z$  gates stabilize  $|0\rangle$  states and Pauli- $X$  gates destabilize  $|0\rangle$  states.

$\implies$  Tableau for  $|0\rangle^{\otimes n}$  has an Identity submatrix for its first  $(2n) \times (2n)$  submatrix.

$$\text{Tableau for } |00\rangle \text{ is } \left( \begin{array}{cc|cc|c} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ \hline 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ \hline 0 & 0 & 0 & 0 & 0 \end{array} \right)$$

In the following slides, let  $R_i$  denote the  $i$ -th row of the stabilizer tableau.

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)



# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Hadamard gate application in the following way:

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Hadamard gate application in the following way:

$$\blacksquare \quad x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = H I H^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Hadamard gate application in the following way:

$$\blacksquare \quad x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = H I H^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$$

$$\blacksquare \quad x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = H Z H^\dagger = X \implies x'_{i,a}z'_{i,a} = 10 \wedge r'_i = r_i$$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Hadamard gate application in the following way:

- $x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = H I H^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = H Z H^\dagger = X \implies x'_{i,a}z'_{i,a} = 10 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 10 \implies P_{i,a} = X \implies P'_{i,a} = H X H^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Hadamard gate application in the following way:

- $x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = H I H^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = H Z H^\dagger = X \implies x'_{i,a}z'_{i,a} = 10 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 10 \implies P_{i,a} = X \implies P'_{i,a} = H X H^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 11 \implies P_{i,a} = Y \implies P'_{i,a} = H Y H^\dagger = -Y \implies x'_{i,a}z'_{i,a} = 11 \wedge r'_i = \neg r_i$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Hadamard Gate Algorithm

Suppose we apply a Hadamard gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Hadamard gate application in the following way:

- $x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = H I H^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = H Z H^\dagger = X \implies x'_{i,a}z'_{i,a} = 10 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 10 \implies P_{i,a} = X \implies P'_{i,a} = H X H^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 11 \implies P_{i,a} = Y \implies P'_{i,a} = H Y H^\dagger = -Y \implies x'_{i,a}z'_{i,a} = 11 \wedge r'_i = \neg r_i$

**Operation summary:**  $x'_{i,a} = z_{i,a} \quad \wedge \quad z'_{i,a} = x_{i,a} \quad \wedge \quad r'_i = r_i \oplus (x_{i,a} \cdot z_{i,a})$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Phase gate application in the following way:

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)



# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Phase gate application in the following way:

$$\blacksquare \quad x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = SIS^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Phase gate application in the following way:

$$\blacksquare \quad x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = SIS^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$$

$$\blacksquare \quad x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = SZS^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$$

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Phase gate application in the following way:

- $x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = SIS^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = SZS^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 10 \implies P_{i,a} = X \implies P'_{i,a} = SXS^\dagger = Y \implies x'_{i,a}z'_{i,a} = 11 \wedge r'_i = r_i$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Phase gate application in the following way:

- $x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = SIS^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = SZS^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 10 \implies P_{i,a} = X \implies P'_{i,a} = SXS^\dagger = Y \implies x'_{i,a}z'_{i,a} = 11 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 11 \implies P_{i,a} = Y \implies P'_{i,a} = SY S^\dagger = -X \implies x'_{i,a}z'_{i,a} = 10 \wedge r'_i = \neg r_i$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Phase Gate Algorithm

Suppose we apply a Phase gate to qubit  $a$  of current state  $|\psi\rangle$ .

$\implies$  For all stabilizers and destabilizers  $R_i$  the entries  $x_{i,a}$  and  $z_{i,a}$  determine the entries  $x'_{i,a}$  and  $z'_{i,a}$  of the new stabilizers and destabilizers  $R'_i$  after the Phase gate application in the following way:

- $x_{i,a}z_{i,a} = 00 \implies P_{i,a} = I \implies P'_{i,a} = SIS^\dagger = I \implies x'_{i,a}z'_{i,a} = 00 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 01 \implies P_{i,a} = Z \implies P'_{i,a} = SZS^\dagger = Z \implies x'_{i,a}z'_{i,a} = 01 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 10 \implies P_{i,a} = X \implies P'_{i,a} = SXS^\dagger = Y \implies x'_{i,a}z'_{i,a} = 11 \wedge r'_i = r_i$
- $x_{i,a}z_{i,a} = 11 \implies P_{i,a} = Y \implies P'_{i,a} = SY S^\dagger = -X \implies x'_{i,a}z'_{i,a} = 10 \wedge r'_i = \neg r_i$

**Operation summary:**  $x'_{i,a} = x_{i,a} \quad \wedge \quad z'_{i,a} = x_{i,a} \oplus z_{i,a} \quad \wedge \quad r'_i = r_i \oplus (x_{i,a} \cdot z_{i,a})$

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Measurement Algorithm

## Deterministic Case

Measuring qubit  $a$

# Measurement Algorithm

## Deterministic Case

Measuring qubit  $a \implies$  Stabilizers have  $I$  or  $Z$  on  $a$  and  $g$  is either  $-Z_a$  or  $Z_a$ .

# Measurement Algorithm

## Deterministic Case

Measuring qubit  $a \implies$  Stabilizers have  $I$  or  $Z$  on  $a$  and  $g$  is either  $-Z_a$  or  $Z_a$ .

Invariants:  $\forall i \in [1, n]$  holds:  $R_i$  anti-commutes with  $R_{n+i}$  and commutes with all  $R_{j \neq n+i}$



# Measurement Algorithm

## Deterministic Case

Measuring qubit  $a \implies$  Stabilizers have  $I$  or  $Z$  on  $a$  and  $g$  is either  $-Z_a$  or  $Z_a$ .

Invariants:  $\forall i \in [1, n]$  holds:  $R_i$  anti-commutes with  $R_{n+i}$  and commutes with all  $R_{j \neq n+i}$   
 $Z_a$  anti-commutes with all  $R_i$  for which  $x_{i,a} = 1$ .

$g$  the product of  $R_{n+i}$  for such  $i \longleftrightarrow$  it anti-commutes exactly with these  $R_i$ .

# Measurement Algorithm

## Deterministic Case

Measuring qubit  $a \implies$  Stabilizers have  $I$  or  $Z$  on  $a$  and  $g$  is either  $-Z_a$  or  $Z_a$ .

Invariants:  $\forall i \in [1, n]$  holds:  $R_i$  anti-commutes with  $R_{n+i}$  and commutes with all  $R_{j \neq n+i}$   
 $Z_a$  anti-commutes with all  $R_i$  for which  $x_{i,a} = 1$ .

$g$  the product of  $R_{n+i}$  for such  $i \longleftrightarrow$  it anti-commutes exactly with these  $R_i$ .

$$g = \prod_{i=1}^n (R_{n+i})^{x_{i,a}} = \pm Z_a$$

# Measurement Algorithm

## Deterministic Case

Measuring qubit  $a \implies$  Stabilizers have  $I$  or  $Z$  on  $a$  and  $g$  is either  $-Z_a$  or  $Z_a$ .

Invariants:  $\forall i \in [1, n]$  holds:  $R_i$  anti-commutes with  $R_{n+i}$  and commutes with all  $R_{j \neq n+i}$   
 $Z_a$  anti-commutes with all  $R_i$  for which  $x_{i,a} = 1$ .

$g$  the product of  $R_{n+i}$  for such  $i \longleftrightarrow$  it anti-commutes exactly with these  $R_i$ .

$$g = \prod_{i=1}^n (R_{n+i})^{x_{i,a}} = \pm Z_a$$

Compute  $g$  in scratch-space row  $2n + 1$  and extract  $r_{2n+1}$ :

$$r_{2n+1} = 0 \implies g = Z_a \implies \text{Measurement: } 0$$

$$r_{2n+1} = 1 \implies g = -Z_a \implies \text{Measurement: } 1$$

Measurement result is just  $r_{2n+1}$ .

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Measurement Algorithm

## Non-deterministic Case

Measuring qubit  $a$ :  $\implies g$  is either  $-Z_a$  or  $Z_a$ .

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Measurement Algorithm

## Non-deterministic Case

Measuring qubit  $a$ :  $\implies g$  is either  $-Z_a$  or  $Z_a$ .

1. Find  $p \in [n + 1, 2n]$  such that  $x_{p,a} = 1$ .

This  $R_p$  corresponds to our previous  $g_1$ , which anti-commutes with  $g$ .

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Measurement Algorithm

## Non-deterministic Case

Measuring qubit  $a$ :  $\implies g$  is either  $-Z_a$  or  $Z_a$ .

1. Find  $p \in [n + 1, 2n]$  such that  $x_{p,a} = 1$ .

This  $R_p$  corresponds to our previous  $g_1$ , which anti-commutes with  $g$ .

2. Multiply  $g_1$  on to all  $g_j$  for which  $x_{j,a} = 1$ .

This transforms all  $g_j$  anti-commuting with  $g$  to  $g'_j$  commuting with  $g$ .

[1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Measurement Algorithm

## Non-deterministic Case

Measuring qubit  $a$ :  $\implies g$  is either  $-Z_a$  or  $Z_a$ .

1. Find  $p \in [n + 1, 2n]$  such that  $x_{p,a} = 1$ .

This  $R_p$  corresponds to our previous  $g_1$ , which anti-commutes with  $g$ .

2. Multiply  $g_1$  on to all  $g_j$  for which  $x_{j,a} = 1$ .

This transforms all  $g_j$  anti-commuting with  $g$  to  $g'_j$  commuting with  $g$ .

3. Push  $R_p$  onto  $R_{p-n}$ .

After measurement, the stabilizer anti-commuting with  $g$  becomes a destabilizer.

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)

# Measurement Algorithm

## Non-deterministic Case

Measuring qubit  $a$ :  $\implies g$  is either  $-Z_a$  or  $Z_a$ .

1. Find  $p \in [n+1, 2n]$  such that  $x_{p,a} = 1$ .

This  $R_p$  corresponds to our previous  $g_1$ , which anti-commutes with  $g$ .

2. Multiply  $g_1$  on to all  $g_j$  for which  $x_{j,a} = 1$ .

This transforms all  $g_j$  anti-commuting with  $g$  to  $g'_j$  commuting with  $g$ .

3. Push  $R_p$  onto  $R_{p-n}$ .

After measurement, the stabilizer anti-commuting with  $g$  becomes a destabilizer.

4. Assign  $R_p = g$ , either  $Z_a$  or  $-Z_a$  with equal probability.

Retrieve the measurement result from  $r_p$  like before.

[1] Scott Aaronson and Daniel Gottesman. "Improved simulation of stabilizer circuits". In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004)



Simulation of stabilizer circuit runs  
in polynomial  $O(n^2)$  time complexity.

Measurement and state update during simulation run  
in polynomial  $O(n^2)$  time complexity.

## References

- [1] Scott Aaronson and Daniel Gottesman. “Improved simulation of stabilizer circuits”. In: *Physical Review A—Atomic, Molecular, and Optical Physics* (2004).
- [2] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010.