

NeoVim Cheat - Normal Mode

~ toggle case	! 1 2	@. play macro 2	# find (rev) identifier 2	\$ eol 2	% goto match 2	^ "soft" bol 2	& repeat :s 2	* find identifier 2	(begin sentence 2	) end sentence	- "soft" bol down previous line	+ next line = auto format 9	Backsp delete left char
` goto mark													
Q play last macro	W next WORD	E end WORD	R replace mode	T till char backward	Y yank to eol	U undo line	I insert at bol	O open above	P paste prev line 1	{ prev aerial section	} next aerial section	bol / go to column	
q record macro	w next word	e end word	r replace char	t till char forward	y yank 1,7 8,9	u undo	i insert mode	o open below	p paste next line 1	[previous 3	] next 3	\ resume telescope	
Caps = Esc normal mode	A append at eol	S delete line	D delete to eol	F find char backward	G eof/ goto line	H screen top	J join lines	K help / doc	L screen bottom	: command line	" choose register 1	Enter change word	
	a append	s delete char	d delete 1,7 8,9	f find char forward	g extra cmds 5	h	j	k	l	; hop char full screen	' goto mark bol		
Z scroll cmds 4	X back-space	C delete to eol	V visual lines	B back WORD	N previous (find)	M screen middle	< un-indent 7,9	> indent 7,9	? find (rev)				
Z scroll cmds 4	X delete char	c change 1,7 8,9	v visual mode 7	b back word	n next (find)	m set mark 6	,	.	/ find				

bol = beginning of line
eol = end of line,

motion

moves the cursor, or defines the range for an operator

command

direct action command, if **red** it enters insert mode

operator

requires a motion afterwards, operates between cursor & destination

extra

special functions, requires extra input

q.

commands with a dot need a char argument afterwards

main command line commands ('ex'):

:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s\+\$// (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)

visual mode:

operator use selection instead of motion
o: exchange cursor position with start of selection
J: join all selected lines
S:: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a..z,*) (e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times (e.g.: 2p, d2w, 5i, d4j)
- (3) [m /]m - go to previous / next method start [M /]M - go to previous / next method end [t /]t - go to previous / next TODO or NOTE [e /]e - go to previous / next diagnostic [g /]g - go to previous / next git hunk zz: scroll cursor to center, zt: top, zb:bottom
- (4) gg: top of file, gi: go to last insertion and switch to insert mode gv: reselect last visual selection gm: middle of screen line, gM: middle of line ge: previous end of word gn / gN: go to next/previous find and select gt / gT: go to next/previous tab
- (6) m, - set next available mark (alphabetical) m; - toggle mark at current line m] and m[- go to next/previous mark dmx and dm<space> - delete mark x / delete all marks
- (7) after v, y, c, d, <, > use a (around) or i (inside) followed by (,), [,], {, }, <., >., ', ', w (word), p (paragraph) f (function), c (class), s (statement), l (loop) b (block), m (method call), a (argument), k (comment)
- (8) ys{motion}{new} - add surrounding {new} to {motion} cs{old}{new} - change surrounding {old} with {new} ds{old} - delete surrounding {old} yss{new} - add surrounding {new} to line [space]b - change brackets (same as csb) {new/old} = (,), [,], {, }, <., >., ', ', s (any of those) b (brackets:),], >., q (quotes: ', ', t (html-tags), f (function), i (individual start and end)
- (9) duplicate operator to act on current line (dd: delete line, cc: change line, yy: yank line, >>: indent line)

NeoVim Cheat Sheet - [Space]-Commands

~ change inside ...	! 1	@ 2	# 3	\$ 4	% 5	^ 6	& 7	* 8	(change inside (...)	) change inside (...)	= -	+ =	Backsp
------------------------	--------	--------	--------	---------	--------	--------	--------	--------	--------------------------	--------------------------	--------	--------	--------

Q q write buf & quit win	W w write buf	E e render cur error render next error	R r• rename / rust cmds	T t peek type definition type definitions	Y y	U u list uses/refs uses/ references	I i list defs, types, refs incoming calls	O o	P p format	{ change inside [...]	} change inside [...]	 nvim mappings nvim options
-----------------------------	------------------	--	----------------------------	---	--------	---	---	--------	---------------	--------------------------	--------------------------	-----------------------------------

Caps = Esc	A• a copilot chat code action	S• s• spectre global spectre local	D d peek definition	F f• telescope	G g• git cmds	H h toggle inlay hints	J j	K k	L l toggle lsp lines	: ;	" ' change inside "..." change inside "..."	Enter change inside (...)
------------	-------------------------------------	--	------------------------	-------------------	------------------	---------------------------	--------	--------	-------------------------	--------	---	------------------------------

Z z	X x	C c change quotes change brackets	V v	B b• debugging	N n• neotest	M m select all visual-mul search visual-mul	< change inside <..>	> change inside <..>	? keymap overview cheat sheets
--------	--------	---	--------	-------------------	-----------------	---	-------------------------	-------------------------	--------------------------------------

cheat sheets:
[Space]/n - normal_mode.pdf
[Space]/s - space.pdf
[Space]/c - ctrl.pdf
[Space]/a - alt.pdf

lsp

commands that uses the language server protocol

edit

direct action command, if **red** it enters insert mode

open

open a sidebar or floating window

extra

cargo / rust commands
git commands

f•

commands with a dot need need additional inputs

spectre:

[Space]SR - search & replace in project (normal/visual)
[Space]SW - search current word in project (normal)
[Space]sr - search and replace in file (normal/visual)
[Space]sr - search current word in file (normal mode)

github copilot chat:

[Space]Aq - quick chat full buffer
[Space]Ac - open chat window
[Space]Ax - explain code
[Space]Ar - review code
[Space]Ao - optimize code
[Space]Af - fix code
[Space]Ae - fix diagnostic
[Space]At - generate tests
[Space]Ad - add documentation
[Space]Ap - format comment (100)
[Space]As - correct spelling
[Space]Aw - improve wording
[Space]Am - summarize
[Space]Ag - git commit message

git:

[Space]gb - toggle git blame
[Space]gs - toggle git signs (line diff in signcolumn)
[Space]gw - toggle git inline changes (word diff)
[Space]gl - open git log of current file to open vimdiff
[Space]gh / [Space]gH - open git DiffviewFileHistory current file / all
[Space]gd - open git Diffview against current index (close with Ctrl-c)
[Space]ga - stages / unstages git hunk (in visual mode only selected lines)

rename and rust / cargo commands:

[Space]rn - rename symbol (refactoring)
[Space]rt - run test under cursor
[Space]rT - run all tests
[Space]rb - cargo build
[Space]rc - cargo clippy
[Space]rr - cargo run
[Space]rd - open docs in browser
[Space]re / [Space]cE - explain next / current error
[Space]rlb - build test coverage (cargo llvm-cov) and show signs
[Space]rtl - toggle test coverage signs
[Space]rls - show test coverage summary

visual-multi (multiple cursors):

Ctrl-Up/Down/Left/Right - toggle cursor at current location and move
[Tab] - switch between cursor and extend mode
Up/Down/Left/Right - move independent of other cursors
Shift-Up/Down/Left/Right - switch to extend mode and select in direction
n/N - go to next/previous match and add a cursor there
q/Q - remove current cursor and go the next/previous match
]/[- go the next/previous cursor
o - switch to other side of selection (in extend mode)
[Space][Space]a - algin at cursors
[Space][Space]C - case conversion menu
[Space][Space]n / [Space][Space]0n - add increasing numbers starting at 1/0

telescope:

[Space]ff - find files
[Space]ff - find files (incl. hidden/ignored)
[Space]fo - select old / recent files
[Space]fb - select buffers
[Space]fg - live grep (normal & visual)
[Space]fG - live grep (word under cursor)
[Space]fw - find word under cursor
[Space]fu - fuzzy find in current file
[Space]fs - select spell suggestions
[Space]ft - select TODOs and NOTEs
[Space]fzc - select colorscheme
[Space]fzo - find vim-options
[Space]fzh - find highlights
[Space]fza - find autocommands
[Space]fp - select from yanks for pasting
[Space]fj - select jumplist
[Space]fm - select marks
[Space]fr - select from register
[Space]fl - select from search history
[Space]fc - select from command history
[Space]f - find commands
[Space]fh - find help tags
[Space]fk - find keymaps
[Space]fe - list diagnostics
[Space]fv - list symbols (variable names) of current file
[Space]fV - list symbols (variable names) of workspace
[Space]fa - open aerial picker
[Space]fq - select quickfix
[Space]fzz - find telescope picker

Up/Down - cycle through history
Ctrl-V / Ctrl-T (in normal mode also v / t) - open in new vsplit / tab
Ctrl-Left/Right/Up/Down - scroll preview window

debugging:

[Space]bp - toggle breakpoint
[Space]bs - start new debugging session
[Space]bt - terminate
[Space]bc - continue to next breakpoint
[Space]bn - next step / step over
[Space]bi - step in
[Space]bo - step out
[Space]bu - toggle dap-ui

neotest:

[Space]bt - run test under cursor
[Space]nf - run all tests in file
[Space]na - run all tests in project
[Space]ns - stop running tests
[Space]np - toggle output panel
[Space]nn - toggle summary panel
[Space]nw - toggle watch under cursor
[Space]nc - clear output panel

NeoVim Cheat Sheet - [Ctrl]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs
Q	W	E	R	T	Y	U	I	O	P	[	]	\	
insert literal key	del next word	scroll line up toggle fn signature	redo paste register	indent line	scroll line down	half-page down delete to bol	[Tab]	previous jump pos ac copilot word	next jump pos ac copilot line	[Esc]		open floating terminal	
Esc	A	S	D	F	G	H	J	K	L	;	'	Enter	
	aerial view del to eol	write buf del prev char	half-page up unindent line	page up		prev yank entry	comment ▼	▲ comment ▲	next yank entry ▶			ac copilot all	
Z	X	C	V	B	N	M	,	.	/				
	del next char	copilot chat	block visual paste clipboard	page down del prev word	open nvim-tree	[Enter]			toggle comment				

in nvim-tree:
? or g? - show mappings
Enter - open file

- motion** moves the cursor, or the screen
- edit** changes the text
- open** open a sidebar or floating window
- mode** changes the nvim mode

Space	
	open auto-complete menu / confirm autocompletion

	normal mode
	insert mode

visual mode:
 Ctrl-C/X: copy/cut selection to register + (system clipboard)

additional copilot commands:
 Ctrl-Right: request suggestion
 Ctrl-Up/Down: next/previous suggestion
 Ctrl-Left: dismiss suggestion

autocompletion:
 Ctrl-Space / Tab: open autocompletion

in menu:
 Ctrl-j / Ctrl-k / Tab / Shift-Tab: move down/up
 Enter / Ctrl-Space: confirm suggestion
 Ctrl-e: toggle docs
 Ctrl-u / Ctrl-d: scroll docs up/down
 Esc - close menu

in function snippet:
 Tab / Shift-Tab: next / previous placeholder

in nvim-tree:
 ? or g? - show mappings
 Enter - open file
 v / Ctrl-v - open file in vertical split
 t / Ctrl-t - open file in new tab
 r - rename show full path
 Ctrl-R - rename omit base name
 Backspace - Close directory
 Tab - open preview (stay in nvim-tree)
 f / F - start/clear filter
 c / p - copy/paste node
 d - delete
 R - refresh view
 K - info about node
 Ctrl-] - change root
 a - create new file
 H / I - toggle hidden/gitignored files
 P - go to parent directory
 E / W or C - expand/collapse all

NeoVim Cheat Sheet - [Alt]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs						
Q	close all other windows	W	maximize window	E	rotate window left	R	rotate windows right	T	move to new tab	Y	U	I	O	P	[	]	\		
Esc	A	go to previous window	S	equalize all windows	D	go to next window	F	G	H	go to previous window	J	go to window below	K	go to window above	L	go to next window	;	'	Enter
Z	close window	X	open new buffer	C	close tab	V	split window vertically	B	N	go to previous tab	M	go to next tab	,	.	/				