

NeoVim Cheat - Normal Mode

~ toggle case	! 1 2	@. play macro 2	# find (rev) ident 2	\$ eol 2	% goto match 2	^ "soft" bol 2	& repeat :s 2	* find ident 2	(begin sentence 2	) end sentence	- "soft" bol down	+ next line	Backsp delete left char
` goto mark										0 "hard" bol	- prev line	= auto format 3	
Q play last macro	W next WORD	E end WORD	R replace mode	T. hop char full screen	Y yank to eol	U undo line	I insert at bol	O open above	P paste before	{ begin parag	}	end parag	bol/ goto col
q. record macro	w next word	e end word	r. replace char	t. hop char cur buffer	y yank 1,3 8	u undo	i insert mode	o open below	p paste after 1	[. misc	]. misc	\ resume telescope	
Caps = Esc normal mode	A append at eol	S delete line	D delete to eol	F. find char backward	G eof/ goto line	H screen top	J join lines	K help / doc	L screen bottom	: ex cmd line	'' reg. spec 1	Enter change word	
	a append 7	s delete char	d delete 1,3 7,8	f. find char forward	g. extra cmds 5	h	j	k	l →	; hop word full screen	' goto mk. bol		
	Z scroll cmds 4	X back-space	C delete to eol	V visual lines	B back WORD	N prev (find)	M screen mid'l	< un-indent 3	> indent 3	? find (rev)			
	Z. scroll cmds 4	X delete char	c change 1,3 7,8	v visual mode	b back word	n next (find)	m. set mark 6	,	. repeat cmd	/ find			

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s\+\$/ (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)

visual mode:

operator use selection instead of motion
o: exchange cursor position with start of selection
J: join all selected lines
S:: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a..z,*) (e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times (e.g.: 2p, d2w, 5i, d4j)
- (3) duplicate operator to act on current line (dd = delete line, yy = yank line, >> = indent line)
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file, gi: go to last insertion and switch to insert mode gv: reselect last visual selection gm: middle of screen line, gM: middle of line ge: prev end of word gn / gN: go to next/prev find and select gt / gT: go to next/prev tab
- (6) m, - set next available mark (alphabetical) m; - toggle mark at current line dm and m[- go to next/previous mark dm x and dm<space> - delete mark x / delete all marks
- (7) ci(- change inside brackets; also),[,.{,}<,>,"','; w,s,p ca(- change around brackets di(, da(, yi(, ya(, vi(, va(for delete, yank, select inside/around
- (8) ys{motion}{new} - add surrounding {new} to {motion} cs{old}{new} - change surrounding {old} with {new} ds{old} - delete surrounding {old} yss{new} - add surrounding {new} to line [space]b - change brackets (same as csb) {new/old} = (,.[,].{,}<,>,"','; s (any of those) b (brackets:),,},>), q (quotes: ',',;), t (html-tags), f (function), i (individual start and end)