

NeoVim Cheat - Normal Mode

Diagram illustrating Emacs keyboard shortcuts categorized into three rows:

- Row 1 (Basic Navigation and Editing):**
 - ~ toggle case
 - ! goto mark
 - @ play macro
 - # find (rev) identifier
 - \$ eol
 - % goto match
 - ^ "soft" bol
 - & repeat :s
 - * find identifier
 - (begin sentence
 -) end sentence
 - _ "soft" bol down
 - previous line
 - + next line
 - = auto format
 - Backsp delete left char
- Row 2 (Complex Navigation and Editing):**
 - Q play last macro
 - W next word
 - E end word
 - R replace mode
 - T hop char full screen
 - Y yank to eol
 - U undo line
 - I insert at bol
 - O open above
 - P paste prev line
 - { previous function
 - } next function
 - | bol / go to column
 - q record macro
 - w next word
 - e end word
 - r replace char
 - t hop char cur buffer
 - y yank
 - u undo
 - i insert mode
 - o open below
 - p paste next line
 - [previous
 -] next
 - \ resume telescope
- Row 3 (Window Management and Editing):**
 - Caps = Esc normal mode
 - A append at eol
 - S delete line
 - D delete to eol
 - F find char backward
 - G eof / goto line
 - H screen top
 - J join lines
 - K help / doc
 - L screen bottom
 - : command line
 - " choose register
 - Enter change word
 - a append
 - s delete char
 - d delete
 - f find char forward
 - g extra cmds
 - h screen top
 - j join lines
 - k help / doc
 - l screen bottom
 - ; hop word full screen
 - ' goto mark bol

Legend: bol = beginning of line, eol = end of line.

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```

:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)

```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- S: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a,z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [m /]m - go to previous / next method start
[M /]M - go to previous / next method end
[t /]t - go to previous / next TODO or NOTE
[e /]e - go to previous / next diagnostic
[g /]g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
m; - toggle mark at current line
m] and m[- go to next/previous mark
dmx and dm<space> - delete mark x / delete all marks
- (7) ci(- change inside brackets; also),[,.,{,}<,>,"',, w,s,p
ca(- change around brackets
di[, da[, yi[, ya[, vi[, va(for delete, yank, select inside/around
ys[motion]{new} - add surrounding {new} to [motion]
cs{old}{new} - change surrounding {old} with {new}
ds{old} - delete surrounding {old}
yss{new} - add surrounding {new} to line
[space]b - change brackets (same as csb)
{new/old} = (,),[,.],{,}<,>,"',, s (any of those)
b (brackets:),[,>), q (quotes: ",',), t (html-tags),
f (function), i (individual start and end)
- (9) duplicate operator to act on current line
(dd = delete line, yy = yank line, >> = indent line)

NeoVim Cheat Sheet - [Space]-Commands

~	!	@	#	\$	%	^	&	*	(change inside (...)	) change inside (...)	_	+	Backsp
change inside ...	1	2	3	4	5	6	7	8	9	0	-	=	
	Q	W	E render prev error	R	T	Y	U	I	O	P	{ change inside (...)	} change inside (...)	nvim mappings
q code action	w	e render next error	r rename	t peek type definition	y	u list uses/refs	i list def, type, refs	o	p format	[change inside [...]	] change inside [...]	\ nvim options	
Caps = Esc	A	S• spectre global	D	F	G	H	J	K	L	:	" change inside "..."	Enter	
		S• spectre local	d peek definition	f• telescope	g• git cmds	h	j	k	l toggle lsp lines	;	' change inside '...'	change inside (...)	

lsp

commands that uses the language server protocol

edit

direct action command, if **red** it enters insert mode

open

open a sidebar or floating window

extra

cargo / rust commands
git commands

f•

commands with a dot need additional inputs

spectre:

[Space]SR - search and replace in working directory (normal or visual mode)
[Space]SW - search current word in working directory (normal mode)
[Space]sr - search and replace in current file (normal or visual mode)
[Space]sr - search current word in current file (normal mode)

git:

[Space]gb - toggle git blame
[Space]gs - toggle git signs (line diff in signcolumn)
[Space]gw - toggle git inline changes (word diff)
[Space]gl - open git log of current file to open vimdiff
[Space]gh / [Space]gH - open git DiffviewFileHistory current file / all
[Space]gd - open git Diffview against current index (close with Ctrl-c)

cargo / rust:

[Space]ct - run test under cursor
[Space]cT - run all tests
[Space]cb - build project
[Space]cr - run project
[Space]cd - open docs in browser
[Space]ce / [Space]cE - explain next / previous error

telescope:

[Space]ff - find files
[Space]ff - find files (incl. hidden/ignored)
[Space]fo - select old / recent files
[Space]fb - select buffers
[Space]fg - live grep in working directory
[Space]fu - fuzzy find in current file
[Space]fp - select from yanks for pasting
[Space]fj - select jumplist
[Space]fm - select marks
[Space]fr - select from register
[Space]f/ - select from search history
[Space]fc - select from command history
[Space]f: - find commands
[Space]fh - find help tags
[Space]fk - find keymaps
[Space]fe - list diagnostics
[Space]fv - list symbols (variable names) of current file
[Space]fV - list symbols (variable names) of workspace
[space]fa - open aerial picker
[Space]fq - select quickfix
[Space]fs - select spell suggestions
[Space]ft - select TODOs and NOTEs
[Space]fzc - select colorscheme
[Space]fzo - find vim-options
[Space]fzh - find highlights
[Space]fza - find autocommands
[Space]fz - find telescope picker

Ctrl-U / Ctrl-D - scroll preview window up/down (normal mode in telescope)
Ctrl-V / Ctrl-T (or v / t in normal mode) - open in new vsplit / tab

NeoVim Cheat Sheet - [Ctrl]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs
Q	W	E	R	T	Y	U	I	O	P	[	]	\	
insert literal key	del next word	scroll line up toggle fn signature	redo paste register	indent line	scroll line down	half-page down delete to bol	[Tab]	previous jump pos ac copilot word	next jump pos ac copilot line	[Esc]			
Esc	A	S	D	F	G	H	J	K	L	;	'	Enter	
	aerial view del to eol	del prev char	half-page up unindent line	page up		prev yank entry	comment ▼	comment ▲	next yank entry			ac copilot all	
Z	X	C	V	B	N	M	,	.	/				
	del next char		block visual paste clipboard	page down del prev word	open nvim-tree	[Enter]			toggle comment				

in nvim-tree:
? or g? - show mappings
Enter - open file

motion

moves the cursor,
or the screen

edit

changes the text

open

open a sidebar
or floating window

mode

changes the nvim mode

Space	
	open auto-complete menu / confirm autocompletion

	normal mode
	insert mode

visual mode:
Ctrl-C/X: copy/cut selection to register + (system clipboard)

additional copilot commands:
Ctrl-Right: request suggestion
Ctrl-Up/Down: next/previous suggestion
Ctrl-Left: dismiss suggestion

autocompletion:
Ctrl-Space / Tab: open autocompletion
in menu:
Ctrl-j / Ctrl-k / Tab / Shift-Tab: move down/up
Enter / Ctrl-Space: confirm suggestion
Ctrl-U / Ctrl-D: scroll docs up/down
Esc - close menu
in function snippet:
Tab / Shift-Tab: next / previous placeholder

in nvim-tree:
? or g? - show mappings
Enter - open file
v / Ctrl-v - open file in vertical split
t / Ctrl-t - open file in new tab
r - rename show full path
Ctrl-R - rename omit base name
Backspace - Close directory
Tab - open preview (stay in nvim-tree)
f / F - start/clear filter
c / p - copy/paste node
d - delete
R - refresh view
K - info about node
Ctrl-] - change root
a - create new file
H / I - toggle hidden/gitignored files
P - go to parent directory
E / W or C - expand/collapse all

NeoVim Cheat Sheet - [Alt]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs						
Q	close all other windows	W	maximize window	E	rotate window left	R	rotate windows right	T	move to new tab	Y	U	I	O	P	[	]	\		
Esc	A	go to previous window	S	equalize all windows	D	go to next window	F	G	H	go to previous window	J	go to window below	K	go to window above	L	go to next window	;	'	Enter
Z	close window	X	open new buffer	C	close tab	V	split window vertically	B	N	go to previous tab	M	go to next tab	,	.	/				