

NeoVim Cheat - Normal Mode

The diagram illustrates Emacs keyboard shortcuts, organized into three rows of colored boxes. Each box contains a key symbol, its function, and a line number (e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 0, -, =, Backsp, Caps = Esc, Enter, Z, X, C, V, B, N, M, <, >, ?, Z., X., C., V., b, n, m., , , ., /).

Row 1: Basic Editing

- ~** toggle case
- !** 1
- @** play macro 2
- #** find (rev) identifier 2
- \$** eol 2
- %** goto match 2
- ^** "soft" bol 2
- &** repeat :s 2
- *** find identifier 2
- (** begin sentence 2
-)** end sentence
- _** "soft" bol down
- previous line
- +** next line
- =** auto format 9
- Backsp** delete left char

Row 2: Text Manipulation

- Q** play last macro
- W** next WORD
- E** end WORD
- R** replace mode
- T** till char backward
- Y** yank to eol
- U** undo line
- I** insert at bol
- O** open above
- P** paste prev line 1
- {** previous function
- }** next function
- |** bol / go to column
- q** record macro
- w** next word
- e** end word
- r** replace char
- t** till char forward
- y** yank 1,7 8,9
- u** undo
- i** insert mode
- o** open below
- p** paste next line 1
- [** previous 3
-]** next 3
- ** resume telescope

Row 3: Navigation

- Caps = Esc** normal mode
- A** append at eol
- S** delete line
- D** delete to eol
- F** find char backward
- G** eof / goto line
- H** screen top
- J** join lines
- K** help / doc
- L** screen bottom
- :** command line
- "** choose register 1
- Enter** change word
- a** append
- s** delete char
- d** delete 1,7 8,9
- f** find char forward
- g** extra cmds 5
- h** ◀
- j** ▼
- k** ▲
- l** ▶
- ;** hop char full screen
- '** goto mark bol
- Z** scroll cmds 4
- X** back-space
- C** delete to eol
- V** visual lines
- B** back WORD
- N** previous (find)
- M** screen middle
- <** un-indent 7,9
- >** indent 7,9
- ?** find (rev)
- Z.** 4
- X.** delete char
- C.** change 1,7 8,9
- V.** visual mode 7
- b** back word
- n** next (find)
- m.** set mark 6
- ,**
- .** repeat cmd
- /** find

Legend:

- bol** = beginning of line
- eol** = end of line,

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```
:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)
```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- S: add surrounding delimiter

ci(- change inside brackets; also),[,]{,}<,>,"',` ,w,s,p
ca(- change around brackets
di[, da[, yi[, ya[, vi[, va(for delete, yank, select inside/around

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a,z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [m /] m - go to previous / next method start
[M /] M - go to previous / next method end
[t /] t - go to previous / next TODO or NOTE
[e /] e - go to previous / next diagnostic
[g /] g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
m; - toggle mark at current line
m) and m[- go to next/previous mark
dmx and dm<space> - delete mark x / delete all marks
- (7) after v, y, c, d, <, > use a (around) or i (inside) followed by
(,), [,], {, }, <., >., ", ', ` , w (word), p (paragraph)
f (function), c (class), s (statement), l (loop)
b (block), m (method call), a (argument), k (comment)
(8) ys(motion){new} - add surrounding {new} to {motion}
cs(old){new} - change surrounding {old} with {new}
ds(old) - delete surrounding {old}
yss{new} - add surrounding {new} to line
[space]b - change brackets (same as csb)
{new/old} = (,), [,], {, }, <., >., ", ', ` , s (any of those)
b (brackets:),], >.), q (quotes: ", ',), t (html-tags),
f (function), i (individual start and end)
- (9) duplicate operator to act on current line
(dd: delete line, cc: change line, yy: yank line, >>: indent line)

NeoVim Cheat Sheet - [Space]-Commands

~ change inside "..."	! 1	@ 2	# 3	\$ 4	% 5	^ 6	& 7	* 8	(change inside (...) 9	) change inside (...) 0	_ -	+ =	Backsp
Q q code action	W w save file	E render prev error e render next error	R r rename	T t peek type definition	Y y	U u list uses/refs	I i list def, type, refs	O o	P p format	{ change inside (...) [change inside [...]	} change inside (...)] change inside [...]	nvim mappings	\ nvim options
Caps = Esc	A a• chatgpt	S• spectre global s• spectre local	D d peek definition	F f• telescope	G g• git cmds	H h	J j	K k	L l toggle lsp lines	: ;	" change inside "..." ' change inside '...'	Enter change inside (...)	

lsp

commands that uses the language server protocol

edit

direct action command, if **red** it enters insert mode

open

open a sidebar or floating window

extra

cargo / rust commands
git commands

f•

commands with a dot need additional inputs

spectre:

[Space]SR - search and replace in working directory (normal or visual mode)
[Space]SW - search current word in working directory (normal mode)
[Space]sr - search and replace in current file (normal or visual mode)
[Space]sr - search current word in current file (normal mode)

git:

[Space]gb - toggle git blame
[Space]gs - toggle git signs (line diff in signcolumn)
[Space]gw - toggle git inline changes (word diff)
[Space]gl - open git log of current file to open vimdiff
[Space]gh / [Space]gH - open git DiffviewFileHistory current file / all
[Space]gd - open git Diffview against current index (close with Ctrl-c)

cargo / rust:

[Space]ct - run test under cursor
[Space]cT - run all tests
[Space]cb - cargo build
[Space]cc - cargo clippy
[Space]cr - cargo run
[Space]cd - open docs in browser
[Space]ce / [Space]cE - explain next / previous error

telescope:

[Space]ff - find files
[Space]ff - find files (incl. hidden/ignored)
[Space]fo - select old / recent files
[Space]fb - select buffers
[Space]fg - live grep in working directory
[Space]fu - fuzzy find in current file
[Space]fp - select from yanks for pasting
[Space]fj - select jumplist
[Space]fm - select marks
[Space]fr - select from register
[Space]f/ - select from search history
[Space]fc - select from command history
[Space]f: - find commands
[Space]fh - find help tags
[Space]fk - find keymaps
[Space]fe - list diagnostics
[Space]fv - list symbols (variable names) of current file
[Space]fV - list symbols (variable names) of workspace
[space]fa - open aerial picker
[Space]fq - select quickfix
[Space]fs - select spell suggestions
[Space]ft - select TODOs and NOTEs
[Space]fzc - select colorscheme
[Space]fzo - find vim-options
[Space]fzh - find highlights
[Space]fza - find autocommands
[Space]fz - find telescope picker

Ctrl-U / Ctrl-D - scroll preview window up/down (normal mode in telescope)
Ctrl-V / Ctrl-T (or v / t in normal mode) - open in new vsplit / tab

chatgpt:

[Space]ac - open chat window
[Space]ae - edit with instruction
[Space]ag - grammar correction
[Space]at - translate
[Space]ak - keywords
[Space]ad - create docstring
[Space]aa - add tests
[Space]ao - optimize code
[Space]as - summarize
[Space]af - fix bug
[Space]ax - explain code
[Space]al - code readability analysis

NeoVim Cheat Sheet - [Ctrl]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs
Q	W	E	R	T	Y	U	I	O	P	[	]	\	
insert literal key	del next word	scroll line up toggle fn signature	redo paste register	indent line	scroll line down	half-page down delete to bol	[Tab]	previous jump pos ac copilot word	next jump pos ac copilot line	[Esc]		open floating terminal	
Esc	A	S	D	F	G	H	J	K	L	;	'	Enter	
	aerial view del to eol	del prev char	half-page up unindent line	page up		prev yank entry	comment ▼	comment ▲	next yank entry			ac copilot all	
Z	X	C	V	B	N	M	,	.	/				
	del next char		block visual paste clipboard	page down del prev word	open nvim-tree	[Enter]			toggle comment				

in nvim-tree:
? or g? - show mappings
Enter - open file

motion	moves the cursor, or the screen
edit	changes the text
open	open a sidebar or floating window
mode	changes the nvim mode

Space	open auto-complete menu / confirm autocompletion
-------	---

normal mode
insert mode

visual mode:
Ctrl-C/X: copy/cut selection to register + (system clipboard)

additional copilot commands:
Ctrl-Right: request suggestion
Ctrl-Up/Down: next/previous suggestion
Ctrl-Left: dismiss suggestion

autocompletion:
Ctrl-Space / Tab: open autocompletion

in menu:
Ctrl-j / Ctrl-k / Tab / Shift-Tab: move down/up
Enter / Ctrl-Space: confirm suggestion
Ctrl-U / Ctrl-D: scroll docs up/down
Esc - close menu

in function snippet:
Tab / Shift-Tab: next / previous placeholder

in nvim-tree:
? or g? - show mappings
Enter - open file
v / Ctrl-v - open file in vertical split
t / Ctrl-t - open file in new tab
r - rename show full path
Ctrl-R - rename omit base name
Backspace - Close directory
Tab - open preview (stay in nvim-tree)
f / F - start/clear filter
c / p - copy/paste node
d - delete
R - refresh view
K - info about node
Ctrl-] - change root
a - create new file
H / I - toggle hidden/gitignored files
P - go to parent directory
E / W or C - expand/collapse all

NeoVim Cheat Sheet - [Alt]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs						
Q	close all other windows	W	maximize window	E	rotate window left	R	rotate windows right	T	move to new tab	Y	U	I	O	P	[	]	\		
Esc	A	go to previous window	S	equalize all windows	D	go to next window	F	G	H	go to previous window	J	go to window below	K	go to window above	L	go to next window	;	'	Enter
Z	close window	X	open new buffer	C	close tab	V	split window vertically	B	N	go to previous tab	M	go to next tab	,	.	/				