

NeoVim Cheat - Normal Mode

The diagram illustrates Emacs keyboard shortcuts, categorized into three rows based on the number of fingers used (indicated by a number in the bottom right corner of each key box).

Row 1: Basic Editing (1-9 fingers)

- 1 finger:** ~ (toggle case), ! (goto mark), @ (play macro), # (find (rev) identifier), \$ (eol), % (goto match), ^ ("soft" bol), & (repeat :s), * (find identifier), ((begin sentence),) (end sentence), _ ("soft" bol down), - (previous line), + (next line), = (auto format), Backsp (delete left char).
- 2 fingers:** . (goto mark), 1, 2, 3, 4, 5, 6, 7, 8, 9, 0 ("hard" bol), - (previous line), + (next line), = (auto format), Backsp (delete left char).

Row 2: Text Manipulation (1-9 fingers)

- 1 finger:** Q (play last macro), W (next WORD), E (end WORD), R (replace mode), T (till char backward), Y (yank to eol), U (undo line), I (insert at bol), O (open above), P (paste prev line), { (prev aerial section), } (next aerial section), | (bol / go to column).
- 2 fingers:** q (record macro), w (next word), e (end word), r (replace char), t (till char forward), y (yank), u (undo), i (insert mode), o (open below), p (paste next line), [(previous),] (next), \ (resume Fzf/Lua).

Row 3: Navigation and Other (1-9 fingers)

- 1 finger:** Caps = Esc (normal mode), A (append at eol), S (del line yank), D (del to eol yank), F (find char backward), G (eof/ goto line), H (screen top), J (join lines), K (help / doc), L (screen bottom), : (command line), " (choose register), Enter (change word).
- 2 fingers:** a (append), S (change surround), d (delete yank), f (find char forward), g (extra cmds), h (screen top), j (join lines), k (help / doc), l (screen bottom), ; (hop char full screen), ' (goto mark bol).
- 3 fingers:** Z (scroll cmds), X (del left no yank), C (del to eol yank), V (visual lines), B (back WORD), N (previous (find)), M (screen middle), < (un-indent), > (indent), ? (find (rev)).
- 4 fingers:** Z (scroll cmds), X (del right no yank), C (delete yank), V (visual mode), b (back word), n (next (find)), m (set mark), , (un-indent), . (repeat cmd), / (find).

Legend: bol = beginning of line, eol = end of line.

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```

:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)

```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- x: delete selection without copying

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a..z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [f /]f - go to previous / next function start
[F /]F - go to previous / next function end
[[/]] - go to previous / next class start
[[/]] - go to previous / next class end
[t /]t - go to previous / next TODO or NOTE
[e /]e - go to previous / next diagnostic
[g /]g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
m; - toggle mark at current line
m] and m[- go to next/previous mark
dmx and dm<space> - delete mark x / delete all marks
- (7) after v, y, c, d, <, > use a (around) or i (inside) followed by
(), [], { }, < > , ' ' , ` ` , w (word), p (paragraph)
f (function), c (class), s (statement), l (loop)
b (block), m (method call), a (argument), k (comment)
- (8) duplicate operator to act on current line
(dd: delete line, cc: change line, yy: yank line, >>: indent line)

change surrounding

sa{motion}{new} - add surrounding {new} around {motion}	{new/
sc{old}{new} - change surrounding {old} with {new}	
sd{old} - delete surrounding {old}	
ss{new} - add surrounding {new} around word	
sA{new} - add surrounding {new} around line	{new}
[space]c{new} - change brackets (same as scb)	{old} =
[space]C{new} - change quotes (same as scq)	
(visual) s{new} - add surrounding {new} around selection	
(visual) S{new} - add surrounding {new} around selection with line breaks	

{new/old} = () [] { } < > " ' `	t: html-tag <tag>inner<\tag>
	f: function my_function(inner),
	g: generic MyType<Inner>
{new} =	i: individual start and end
{old} =	b: any brackets < > { } [] ()
	q: any quotes: ` ' " `
	s: any brackets or quotes

NeoVim Cheat Sheet - [Space]-Commands

~ change inside ...	! 1	@ 2	# 3	\$ 4	% 5	^ 6	& 7	* 8	(change inside (...)	) change inside (...)	_ -	+ =	Backsp
------------------------	--------	--------	--------	---------	--------	--------	--------	--------	-----------------------	-----------------------	-----	-----	--------

Q q write buf & quit win	W w write buf	E render cur error e render next error	R r rename / rust cmds	t list type definitions	Y y	U u list uses/ references	I i	O o	P p format	{ change inside (...) [change inside [...]	} change inside (...)] change inside [...]	nvim mappings \ nvim options
-----------------------------	------------------	---	---------------------------	-------------------------	--------	------------------------------	--------	--------	---------------	--	--	---------------------------------

Caps = Esc	A• copilot chat a code action	S• spectre global s• spectre local	D d peek definition	F f• fzf-lua	G g• git cmds	H h toggle inlay hints	J j	K k	L l toggle lsp lines	: ;	" change inside "..." ' change inside '...'	Enter change inside (...)
------------	----------------------------------	---------------------------------------	------------------------	-----------------	------------------	---------------------------	--------	--------	-------------------------	--------	--	------------------------------

Z z	X x	C change quotes c change brackets	V v	B b• debugging	N n• neotest	M select all visual-mul m search visual-mul	< change inside <,> ,	> change inside >,< .	? keymap overview /. cheat sheets
--------	--------	--------------------------------------	--------	-------------------	-----------------	--	--------------------------	--------------------------	--------------------------------------

cheat sheets:

[Space]/n - normal_mode.pdf
[Space]/s - space.pdf
[Space]/c - ctrl.pdf
[Space]/a - alt.pdf

lsp

commands that uses the language server protocol

edit

direct action command, if **red** it enters insert mode

open

open a sidebar or floating window

extra

cargo / rust commands
git commands

f•

commands with a dot need need additional inputs

spectre:

[Space]SR - search & replace in project (normal/visual)
[Space]SW - search current word in project (normal)
[Space]sr - search and replace in file (normal/visual)
[Space]sr - search current word in file (normal mode)

github copilot chat:

[Space]Aq - quick chat full buffer
[Space]Ac - open chat window
[Space]Ax - explain code
[Space]Ar - review code
[Space]Ao - optimize code
[Space]Af - fix code
[Space]Ae - fix diagnostic
[Space]At - generate tests
[Space]Ad - add documentation
[Space]Ap - format comment (100)
[Space]As - correct spelling
[Space]Aw - improve wording
[Space]Am - summarize
[Space]Ag - git commit message

git:

[Space]gb - toggle git blame
[Space]gs - toggle git signs (line diff in signcolumn)
[Space]gw - toggle git inline changes (word diff)
[Space]gl - open git log of current file to open vimdiff (FzfLua)
[Space]gh / [Space]gH - open git DiffviewFileHistory current file / all
[Space]gd - open git Diffview against current index (close with Ctrl-c)
[Space]ga - stages / unstages git hunk (in visual mode only selected lines)

rename and rust / cargo commands:

[Space]rn - rename symbol (refactoring)
[Space]rt - run test under cursor
[Space]rT - run all tests
[Space]rb - cargo build
[Space]rc - cargo clippy
[Space]rr - cargo run
[Space]rd - open docs in browser
[Space]re / [Space]cE - explain next / current error
[Space]rlb - build test coverage (cargo llvm-cov) and show signs
[Space]rlt - toggle test coverage signs
[Space]rls - show test coverage summary
[Space]rk - move item up / left
[Space]rj - move item down / right

debugging:

[Space]bp - toggle breakpoint
[Space]bs - start new debugging session
[Space]bt - terminate
[Space]bc - continue to next breakpoint
[Space]bn - next step / step over
[Space]bi - step in
[Space]bo - step out
[Space]bu - toggle dap-ui

neotest:

[Space]bt - run test under cursor
[Space]nf - run all tests in file
[Space]na - run all tests in project
[Space]ns - stop running tests
[Space]np - toggle output panel
[Space]nn - toggle summary panel
[Space]nw - toggle watch under cursor
[Space]nc - clear output panel

fzf-lua:

[Space]ff - find files
[Space]fF - find files (incl. hidden/ignored)
[Space]fo - select old / recent files
[Space]fb - select buffers
[Space]fg - live grep (normal & visual)
[Space]fG - live grep (word under cursor)
[Space]fw - find word under cursor
[Space]fu - fuzzy find in current file
[Space]fs - select spell suggestions
[Space]ft - select TODOs (telescope)
[Space]fzc - select colorscheme
[Space]fzo - find vim-options
[Space]fzh - find highlights
[Space]fza - find autocommands
[Space]fzz - find FzfLua picker

F1 - toggle keymapping info
F3 - wrap line in preview window
F4 - toggle preview

[Space]fp - select from yanks for pasting (telescope)
[Space]fj - select jumplist
[Space]fm - select marks
[Space]fr - select from register
[Space]f/ - select from search history
[Space]fc - select from command history
[Space]f: - find commands
[Space]fh - find help tags
[Space]fk - find keymaps

[Space]fe - list errors
[Space]fE - list errors and warnings
[Space]fi - list incoming calls
[Space]fv - list symbols (variable names) of current file
[Space]fV - list symbols (variable names) of workspace
[space]fa - open document structure (aerial like)
[Space]fq - select quickfix

Ctrl-j / Ctrl-k - move up / down
Ctrl-v / Ctrl-t - open in new vsplit / tab
Shift-(Alt)-Up/Down - scroll preview window (fast)

visual-multi (multiple cursors):

Ctrl-Up/Down/Left/Right - toggle cursor at current location and move
[Tab] - switch between cursor and extend mode
Up/Down/Left/Right - move independent of other cursors
Shift-Up/Down/Left/Right - switch to extend mode and select in direction
n/N - go to next/previous match and add a cursor there
q/Q - remove current cursor and go the next/previous match
]/[- go the next/previous cursor
o - switch to other side of selection (in extend mode)
[Space][Space]a - algin at cursors
[Space][Space]C - case conversion menu
[Space][Space]n / [Space][Space]0n - add increasing numbers starting at 1/0

NeoVim Cheat Sheet - [Ctrl]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs
Q	W	E	R	T	Y	U	I	O	P	[	]	\	
insert literal key	del next word	scroll line up toggle fn signature	redo paste register	indent line	scroll line down	half-page down delete to bol	[Tab]	previous jump pos ac copilot word	next jump pos ac copilot line	[Esc]		open floating terminal	
Esc	A	S	D	F	G	H	J	K	L	;	'	Enter	
	del to eol	write buf del prev char	half-page up unindent line	page up		prev yank entry	comment ▼	▲ comment ▲	next yank entry ▶			accept copilot all	
Z	X	C	V	B	N	M	,	.	/				
	del next char	copilot chat	block visual paste clipboard	page down del prev word	open nvim-tree	[Enter]			toggle comment				

motion	moves the cursor, or the screen
edit	changes the text
open	open a sidebar or floating window
mode	changes the nvim mode

Space	
	open auto-complete menu / confirm autocompletion

	normal mode
	insert mode

visual mode:
Ctrl-c/x: copy/cut selection to register + (system clipboard)

additional copilot commands:
Ctrl-Right: request suggestion
Ctrl-Up/Down: next/previous suggestion
Ctrl-Left: dismiss suggestion

autocompletion:
Ctrl-Space / Tab: open autocompletion
in menu:
Ctrl-j / Ctrl-k / Tab / Shift-Tab: move down/up
Enter / Ctrl-Space: confirm suggestion
Ctrl-e: toggle docs
Ctrl-u / Ctrl-d: scroll docs up/down
Esc - close menu
in function snippet:
Tab / Shift-Tab: next / previous placeholder

in nvim-tree:
? or g? - show mappings
Enter - open file
v / Ctrl-v - open file in vertical split
t / Ctrl-t - open file in new tab
r - rename show full path
Ctrl-r - rename omit base name
Backspace - Close directory
Tab - open preview (stay in nvim-tree)
f / F - start/clear filter
c / p - copy/paste node
d - delete
R - refresh view
K - info about node
Ctrl-] - change root
a - create new file
H / I - toggle hidden/gitignored files
P - go to parent directory
E / W or C - expand/collapse all

NeoVim Cheat Sheet - [Alt]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs						
Q	close all other windows	W	maximize window	E	rotate window left	R	rotate windows right	T	move to new tab	Y	U	I	O	P	[	]	\		
Esc	A	go to previous window	S	equalize all windows	D	go to next window	F	G	H	go to previous window	J	go to window below	K	go to window above	L	go to next window	;	'	Enter
Z	close window	X	open new buffer	C	close tab	V	split window vertically	B	N	go to previous tab	M	go to next tab	,	.	/				