

NeoVim Cheat - Normal Mode

~ toggle case	! 1 ²	@· play macro 2 ²	# find (rev) identifier 2 ²	\$ eol 2 ²	% goto match 2 ²	^ "soft" bol 2 ²	& repeat :s 2 ²	* find identifier 2 ²	(begin sentence 2 ²	) end sentence	_ "soft" bol down previous line	+ next line = auto format ⁹	Backsp delete left char
Q play last macro	W next WORD	E end WORD	R replace mode	T· till char backward	Y yank to eol	U undo line	I insert at bol	O open above	P paste prev line ¹	{ previous function	}	 next function	 bol / go to column
q· record macro	w next word	e end word	r· replace char	t· till char forward	y yank ^{1,7} 8,9	u undo	i insert mode	o open below	p paste next line ¹	[· previous ³	]	]· next ³	\ resume telescope
Caps = Esc normal mode	A append at eol a append	S delete line s delete char	D delete to eol d delete ^{1,7} 8,9	F· find char backward f· find char forward	G eof/ goto line g· extra cmds ⁵	H screen top h ◀	J join lines j ▼	K help / doc k ▲	L screen bottom l ▶	: command line ; hop char full screen	"· choose register ¹ '· goto mark bol	Enter change word	
Z scroll cmds ⁴ Z·	X back-space x delete char	C delete to eol c change ^{1,7} 8,9	V visual lines v visual mode ⁷	B back WORD b back word	N previous (find) n next (find)	M screen middle m· set mark ⁶	< un-indent ^{7,9}	> indent ^{7,9}	?· find (rev) / find	bol = beginning of line eol = end of line,			

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```
:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)
```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- S: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a,z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [m /]m - go to previous / next method start
[M /]M - go to previous / next method end
[t /]t - go to previous / next TODO or NOTE
[e /]e - go to previous / next diagnostic
[g /]g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
 m; - toggle mark at current line
 m] and m[- go to next/previous mark
 dmx and dm<space> - delete mark x / delete all marks
- (7) after v, y, c, d, <, > use a (around) or i (inside) followed by
 (.), [.], {., }., <., >. ', ' ', w (word), p (paragraph)
 f (function), c (class), s (statement), l (loop)
 b (block), m (method call), a (argument), k (comment)
- (8) ys[motion]{new} - add surrounding {new} to {motion}
 cs[old]{new} - change surrounding {old} with {new}
 ds[old] - delete surrounding {old}
 yss{new} - add surrounding {new} to line
 [space]b - change brackets (same as csb)
 {new/old} = (.),[.],{.},<.,>.',', s (any of those)
 b (brackets:),],>), q (quotes: ', ' '), t (html-tags),
 f (function), i (individual start and end)
- (9) duplicate operator to act on current line
 (dd: delete line, cc: change line, yy: yank line, >>: indent line)

NeoVim Cheat Sheet - [Space]-Commands

~ change inside ...	! 1	@ 2	# 3	\$ 4	% 5	^ 6	& 7	* 8	(change inside (...) 9	) change inside (...) 0	- -	+ =	Backsp
------------------------	--------	--------	--------	---------	--------	--------	--------	--------	----------------------------	----------------------------	--------	--------	--------

Q q code action	W w save file close win	E render prev error e render next error	R r rename / rust cmds	T t peek type definition	Y y	U u list uses/refs	I i list def, type, refs	O o	P p format	{ change inside (...) [change inside [...]	} change inside (...)] change inside [...]	nvim mappings \ nvim options
--------------------	----------------------------	--	---------------------------	-----------------------------	--------	-----------------------	-----------------------------	--------	---------------	--	--	---------------------------------

Caps = Esc	A a• chatgpt	S• spectre global s• spectre local	D d peek definition	F f• telescope	G g• git cmds	H h	J j	K k	L l toggle lsp lines	:	;" change inside "... ' change inside '...'	Enter change inside (...)
------------	-----------------	---------------------------------------	------------------------	-------------------	------------------	--------	--------	--------	-------------------------	---	--	------------------------------

Z z	X x	C change quotes c change brackets	V v	B b• debugging	N n• neotest	M m	< change inside <..> ,	> change inside <..> .	? keymap overview /. cheat sheets
--------	--------	--------------------------------------	--------	-------------------	-----------------	--------	---------------------------	---------------------------	--------------------------------------

cheat sheets:

[Space]/n - normal_mode.pdf
[Space]/s - space.pdf
[Space]/c - ctrl.pdf
[Space]/a - alt.pdf

lsp

commands that uses the language server protocol

edit

direct action command, if **red** it enters insert mode

open

open a sidebar or floating window

extra

cargo / rust commands git commands

f•

commands with a dot need additional inputs

spectre:

[Space]SR - search & replace in project (normal/visual)
[Space]SW - search current word in project (normal)
[Space]sr - search and replace in file (normal/visual)
[Space]sr - search current word in file (normal mode)

chatgpt:

[Space]ac - open chat window
[Space]ae - edit with instruction
[Space]ag - grammar correction
[Space]at - translate
[Space]ak - keywords
[Space]ad - create docstring
[Space]aa - add tests
[Space]ao - optimize code
[Space]as - summarize
[Space]af - fix bug
[Space]ax - explain code
[Space]al - readability analysis

git:

[Space]gb - toggle git blame
[Space]gs - toggle git signs (line diff in signcolumn)
[Space]gw - toggle git inline changes (word diff)
[Space]gl - open git log of current file to open vimdiff
[Space]gh / [Space]gH - open git DiffviewFileHistory current file / all
[Space]gd - open git Diffview against current index (close with Ctrl-c)

rename and rust / cargo commands:

[Space]rn - rename symbol (refactoring)
[Space]rt - run test under cursor
[Space]rT - run all tests
[Space]rb - cargo build
[Space]rc - cargo clippy
[Space]rr - cargo run
[Space]rd - open docs in browser
[Space]re / [Space]cE - explain next / previous error

neotest:

[Space]bt - run test under cursor
[Space]nft - run all tests in file
[Space]na - run all tests in project
[Space]ns - stop running tests
[Space]np - toggle output panel
[Space]nn - toggle summary panel
[Space]nw - toggle watch under cursor
[Space]nc - clear output panel

telescope:

[Space]ff - find files
[Space]ff - find files (incl. hidden/ignored)
[Space]fo - select old / recent files
[Space]fb - select buffers
[Space]fg - live grep in working directory
[Space]fu - fuzzy find in current file
[Space]fe - list diagnostics
[Space]fv - list symbols (variable names) of current file
[Space]fV - list symbols (variable names) of workspace
[Space]fa - open aerial picker
[Space]fq - select quickfix
[Space]fs - select spell suggestions
[Space]ft - select TODOs and NOTEs
[Space]fzc - select colorscheme
[Space]fzo - find vim-options
[Space]fzh - find highlights
[Space]fza - find autocommands
[Space]fz - find telescope picker
[Space]fp - select from yanks for pasting
[Space]fj - select jumplist
[Space]fm - select marks
[Space]fr - select from register
[Space]f/ - select from search history
[Space]fc - select from command history
[Space]f: - find commands
[Space]fh - find help tags
[Space]fk - find keymaps

Ctrl-U / Ctrl-D - scroll preview window up/down (normal mode in telescope)
Ctrl-V / Ctrl-T (or v / t in normal mode) - open in new vsplit / tab

debugging:

[Space]bp - toggle breakpoint
[Space]bs - start new debugging session
[Space]bt - terminate
[Space]bc - continue to next breakpoint
[Space]bn - next step / step over
[Space]bi - step in
[Space]bo - step out
[Space]bu - toggle dap-ui

NeoVim Cheat Sheet - [Ctrl]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs
Q	W	E	R	T	Y	U	I	O	P	[	]	\	
insert literal key	del next word	scroll line up toggle fn signature	redo paste register	indent line	scroll line down	half-page down delete to bol	[Tab]	previous jump pos ac copilot word	next jump pos ac copilot line	[Esc]		open floating terminal	
Esc	A	S	D	F	G	H	J	K	L	;	'	Enter	
	aerial view del to eol	save file del prev char	half-page up unindent line	page up		prev yank entry	comment ▼	comment ▲	next yank entry			ac copilot all	
Z	X	C	V	B	N	M	,	.	/				
	del next char		block visual paste clipboard	page down del prev word	open nvim-tree	[Enter]			toggle comment				

in nvim-tree:
? or g? - show mappings
Enter - open file

motion

moves the cursor,
or the screen

edit

changes the text

open

open a sidebar
or floating window

mode

changes the nvim mode

Space	
	open auto-complete menu / confirm autocompletion

	normal mode
	insert mode

visual mode:
Ctrl-C/X: copy/cut selection to register + (system clipboard)

additional copilot commands:
Ctrl-Right: request suggestion
Ctrl-Up/Down: next/previous suggestion
Ctrl-Left: dismiss suggestion

autocompletion:
Ctrl-Space / Tab: open autocompletion

in menu:
Ctrl-j / Ctrl-k / Tab / Shift-Tab: move down/up
Enter / Ctrl-Space: confirm suggestion
Ctrl-U / Ctrl-D: scroll docs up/down
Esc - close menu

in function snippet:
Tab / Shift-Tab: next / previous placeholder

in nvim-tree:
? or g? - show mappings
Enter - open file
v / Ctrl-v - open file in vertical split
t / Ctrl-t - open file in new tab
r - rename show full path
Ctrl-R - rename omit base name
Backspace - Close directory
Tab - open preview (stay in nvim-tree)
f / F - start/clear filter
c / p - copy/paste node
d - delete
R - refresh view
K - info about node
Ctrl-] - change root
a - create new file
H / I - toggle hidden/gitignored files
P - go to parent directory
E / W or C - expand/collapse all

NeoVim Cheat Sheet - [Alt]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs						
Q	close all other windows	W	maximize window	E	rotate window left	R	rotate windows right	T	move to new tab	Y	U	I	O	P	[	]	\		
Esc	A	go to previous window	S	equalize all windows	D	go to next window	F	G	H	go to previous window	J	go to window below	K	go to window above	L	go to next window	;	'	Enter
Z	close window	X	open new buffer	C	close tab	V	split window vertically	B	N	go to previous tab	M	go to next tab	,	.	/				