

NeoVim Cheat - Normal Mode

The diagram illustrates Emacs keyboard shortcuts, categorized by function. It is organized into three main horizontal sections: basic editing, text manipulation, and window management. Each section contains a grid of shortcuts, with some shortcuts having multiple variants or modifiers indicated by superscripts.

Basic Editing:

- Toggle case:** ~
- Goto mark:** .
- Play macro:** @
- Find (rev) identifier:** #
- Eol:** \$
- Goto match:** %
- "soft" bol:** ^
- Repeat:** &
- Find identifier:** *
- Begin sentence:** (
- End sentence:**)
- "soft" bol down:** _
- Previous line:** -
- Next line:** +
- Auto format:** =
- Backspace:** Backsp (delete left char)

Text Manipulation:

- Play last macro:** Q
- Record macro:** q
- Next word:** W
- End word:** E
- Replace mode:** R
- Replace char:** r
- Hop char full screen:** T
- Hop char cur buffer:** t
- Yank to eol:** Y
- Yank:** y
- Undo line:** U
- Undo:** u
- Insert at bol:** I
- Insert mode:** i
- Open above:** O
- Open below:** o
- Paste prev line:** P
- Paste next line:** p
- Previous function:** {
- Next function:** }
- Bol / go to column:** |
- Resume telescope:** \

Window Management:

- Caps = Esc:** normal mode
- Append at eol:** A
- Append:** a
- Delete line:** S
- Delete char:** s
- Delete to eol:** D
- Delete:** d
- Find char backward:** F
- Find char forward:** f
- Eof / goto line:** G
- Extra cmds:** g
- Screen top:** H
- Screen bottom:** L
- Join lines:** J
- Join lines:** j
- Help / doc:** K
- Help / doc:** k
- Command line:** :
- Hop word full screen:** ;
- Choose register:** " .
- Goto mark bol:** ' .
- Enter:** change word

Other Shortcuts:

- Scroll cmds:** Z, Z
- Backspace:** X
- Delete char:** x
- Delete to eol:** C
- Change:** c
- Visual lines:** V
- Visual mode:** v
- Back word:** B
- Back word:** b
- Previous (find):** N
- Next (find):** n
- Screen middle:** M
- Set mark:** m
- Un-indent:** <
- Indent:** >
- Find (rev):** ?
- Find:** /

Legend:

- bol:** beginning of line
- eol:** end of line,

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```
:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)
```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- S: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a,z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [m /]m - go to previous / next method start
[M /]M - go to previous / next method end
[t /]t - go to previous / next TODO or NOTE
[e /]e - go to previous / next diagnostic
[g /]g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
m; - toggle mark at current line
m] and m[- go to next/previous mark
dmx and dm<space> - delete mark x / delete all marks
- (7) ci(- change inside brackets; also),[,.,{,}<,>,"',, w,s,p
ca(- change around brackets
di[, da[, yi[, ya[, vi[, va(for delete, yank, select inside/around
ys[motion]{new} - add surrounding {new} to [motion]
cs{old}{new} - change surrounding {old} with {new}
ds{old} - delete surrounding {old}
yss{new} - add surrounding {new} to line
[space]b - change brackets (same as csb)
{new/old} = (,),[,.],{,}<,>,"',, s (any of those)
 b (brackets:),[,>), q (quotes: ",',), t (html-tags),
 f (function), i (individual start and end)
- (9) duplicate operator to act on current line
(dd = delete line, yy = yank line, >> = indent line)