

NeoVim Cheat - Normal Mode

The diagram illustrates Emacs keyboard shortcuts, organized into three rows of colored boxes. Each box contains a key symbol, its function, and a line number (e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9).

Row 1: Basic Editing

- ~** toggle case
- !** goto mark ²
- @** play macro
- #** find (rev) identifier ²
- \$** eol ²
- %** goto match ²
- ^** "soft" bol ²
- &** repeat :s ²
- *** find identifier ²
- (** begin sentence ²
-)** end sentence
- _** "soft" bol down
- previous line
- +** next line
- =** auto format ⁹
- Backsp** delete left char

Row 2: Text Manipulation

- Q** play last macro
- W** next WORD
- E** end WORD
- R** replace mode
- T** till char backward
- Y** yank to eol
- U** undo line
- I** insert at bol
- O** open above
- P** paste prev line ¹
- {** prev aerial section
- }** next aerial section
- |** bol / go to column
- q** record macro
- w** next word
- e** end word
- r** replace char
- t** till char forward
- y** yank ^{1,7} _{8,9}
- u** undo
- i** insert mode
- o** open below
- p** paste next line ¹
- [** previous ³
-]** next ³
- ** resume telescope

Row 3: Navigation and Other

- Caps = Esc** normal mode
- A** append at eol
- S** delete line
- D** delete to eol
- F** find char backward
- G** eof / goto line
- H** screen top
- J** join lines
- K** help / doc
- L** screen bottom
- :** command line
- "** choose register ¹
- a** append
- s** delete char
- d** delete ^{1,7} _{8,9}
- f** find char forward
- g** extra cmds ⁵
- h** ◀
- j** ▼
- k** ▲
- l** ▶
- ;** hop char full screen
- '** goto mark bol
- Enter** change word

Row 4: Navigation and Other (Continued)

- Z** scroll cmds ⁴
- X** back-space
- C** delete to eol
- V** visual lines
- B** back WORD
- N** previous (find)
- M** screen middle
- <** un-indent ^{7,9}
- >** indent ^{7,9}
- ?** find (rev)
- Z** delete char
- X** delete char
- C** change ^{1,7} _{8,9}
- V** visual mode ⁷
- b** back word
- n** next (find)
- m** set mark ⁶
- ,**
- .** repeat cmd
- /** find

Legend:

- bol** = beginning of line
- eol** = end of line,

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```
:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)
```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- S: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a,z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [m /]m - go to previous / next method start
[M /]M - go to previous / next method end
[t /]t - go to previous / next TODO or NOTE
[e /]e - go to previous / next diagnostic
[g /]g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
m; - toggle mark at current line
m] and m[- go to next/previous mark
dmx and dm<space> - delete mark x / delete all marks
- (7) after v, y, c, d, <, > use a (around) or i (inside) followed by
(.), [.], {., }., <., >. ', ' ', w (word), p (paragraph)
f (function), c (class), s (statement), l (loop)
b (block), m (method call), a (argument), k (comment)
- (8) ys[motion]{new} - add surrounding {new} to {motion}
cs[old]{new} - change surrounding {old} with {new}
ds[old] - delete surrounding {old}
yss[new] - add surrounding {new} to line
[space]b - change brackets (same as csb)
{new/old} = (.),[.],{.},<.,>,' ',' ', s (any of those)
b (brackets:),,],>), q (quotes: ', ' '), t (html-tags),
f (function), i (individual start and end)
- (9) duplicate operator to act on current line
(dd: delete line, cc: change line, yy: yank line, >>: indent line)

NeoVim Cheat Sheet - [Space]-Commands

~	!	@	#	\$	%	^	&	*	(change inside (...)	) change inside (...)	_	+	Backsp
change inside ...	1	2	3	4	5	6	7	8	9	0	-	=	
Q	W	E render cur error	R	T	Y	U	I	O	P	{ change inside (...)	} change inside (...)	nvim mappings	
q write buf & quit win	w write buf	e render next error	r rename / rust cmds	t peek type definition	y	u list uses/refs	i list def, type, refs	o	p format	[change inside [...]	] change inside [...]	\ nvim options	
Caps = Esc	A copilot chat	S spectre global	D	F	G	H	J	K	L	:	" change inside "..."	Enter change inside (...)	
	a code action	s spectre local	d peek definition	f telescope	g git cmds	h	j	k	l toggle lsp lines	;	' change inside "...'		
	Z	X	C change quotes	V	B	N	M select all visual-mul	< change inside <,>	> change inside <,>	? keymap overview	cheat sheets: [Space]/n - normal_mode.pdf [Space]/s - space.pdf [Space]/c - ctrl.pdf		
	z	x	c change brackets	v	b debugging	n neotest	m search visual-mul	,	.	/ cheat sheets			

lsp	commands that uses the language server protocol
edit	direct action command, if red it enters insert mode
open	open a sidebar or floating window
extra	cargo / rust commands git commands
f•	commands with a dot need additional inputs

spectre:

[Space]SR - search & replace in project (normal/visual)
 [Space]SW - search current word in project (normal)
 [Space]sr - search and replace in file (normal/visual)
 [Space]sr - search current word in file (normal mode)

github copilot chat:

[Space]Aq - quick chat full buffer
 [Space]Ac - open chat window
 [Space]Ax - explain code
 [Space]Ar - review code
 [Space]Ao - optimize code
 [Space]Af - fix code
 [Space]Ae - fix diagnostic
 [Space]At - generate tests
 [Space]Ad - add documentation
 [Space]Ap - format comment (100)
 [Space]As - correct spelling
 [Space]Aw - improve wording
 [Space]Am - summarize
 [Space]Ag - git commit message

git:

[Space]gb - toggle git blame
 [Space]gs - toggle git signs (line diff in signcolumn)
 [Space]gw - toggle git inline changes (word diff)
 [Space]gl - open git log of current file to open vimdiff
 [Space]gh / [Space]gH - open git DiffviewFileHistory current file / all
 [Space]gd - open git Diffview against current index (close with Ctrl-c)

rename and rust / cargo commands:

[Space]rn - rename symbol (refactoring)
 [Space]rt - run test under cursor
 [Space]rT - run all tests
 [Space]rb - cargo build
 [Space]rc - cargo clippy
 [Space]rr - cargo run
 [Space]rd - open docs in browser
 [Space]re / [Space]cE - explain next / current error
 [Space]rib - build test coverage (cargo llvm-cov) and show signs
 [Space]rit - toggle test coverage signs
 [Space]rls - show test coverage summary

visual-multi (multiple cursors):

Ctrl-Up/Down/Left/Right - toggle cursor at current location and move
 [Tab] - switch between cursor and extend mode
 Up/Down/Left/Right - move independent of other cursors
 Shift-Up/Down/Left/Right - switch to extend mode and select in direction
 n/N - go to next/previous match and add a cursor there
 q/Q - remove current cursor and go the next/previous match
 J/[- go the next/previous cursor
 o - switch to other side of selection (in extend mode)
 [Space][Space]a - algin at cursors
 [Space][Space]C - case conversion menu
 [Space][Space]n / [Space][Space]0n - add increasing numbers starting at 1/0

telescope:

[Space]ff - find files
 [Space]fF - find files (incl. hidden/ignored)
 [Space]fo - select old / recent files
 [Space]fb - select buffers
 [Space]fg - live grep in working directory
 [Space]fu - fuzzy find in current file
 [Space]fp - select from yanks for pasting
 [Space]fj - select jumplist
 [Space]fm - select marks
 [Space]fr - select from register
 [Space]f/ - select from search history
 [Space]fc - select from command history
 [Space]fi - find commands
 [Space]fh - find help tags
 [Space]fk - find keymaps
 [Space]fe - list diagnostics
 [Space]fv - list symbols (variable names) of current file
 [Space]fV - list symbols (variable names) of workspace
 [Space]fa - open aerial picker
 [Space]fq - select quickfix
 [Space]fs - select spell suggestions
 [Space]ft - select TODOs and NOTES
 [Space]fzc - select colorscheme
 [Space]fzo - find vim-options
 [Space]fzh - find highlights
 [Space]fza - find autocommands
 [Space]fz - find telescope picker

Ctrl-U / Ctrl-D - scroll preview window up/down (normal mode in telescope)
 Ctrl-V / Ctrl-T (or v / t in normal mode) - open in new vsplit / tab

debugging:

[Space]bp - toggle breakpoint
 [Space]bs - start new debugging session
 [Space]bt - terminate
 [Space]bc - continue to next breakpoint
 [Space]bn - next step / step over
 [Space]bi - step in
 [Space]bo - step out
 [Space]bu - toggle dap-ui

neotest:

[Space]bt - run test under cursor
 [Space]nf - run all tests in file
 [Space]na - run all tests in project
 [Space]ns - stop running tests
 [Space]np - toggle output panel
 [Space]nn - toggle summary panel
 [Space]nw - toggle watch under cursor
 [Space]nc - clear output panel

NeoVim Cheat Sheet - [Ctrl]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs
Q	W	E	R	T	Y	U	I	O	P	[	]	\	
insert literal key	del next word	scroll line up toggle fn signature	redo paste register	indent line	scroll line down	half-page down delete to bol	[Tab]	previous jump pos ac copilot word	next jump pos ac copilot line	[Esc]		open floating terminal	
Esc	A	S	D	F	G	H	J	K	L	;	'	Enter	
	aerial view del to eol	write buf del prev char	half-page up unindent line	page up		prev yank entry	comment ▼	▲ comment ▲	next yank entry ▶			ac copilot all	
Z	X	C	V	B	N	M	,	.	/				
	del next char	copilot chat	block visual paste clipboard	page down del prev word	open nvim-tree	[Enter]			toggle comment				

in nvim-tree:
? or g? - show mappings
Enter - open file

motion

moves the cursor,
or the screen

edit

changes the text

open

open a sidebar
or floating window

mode

changes the nvim mode

Space	
	open auto-complete menu / confirm autocompletion

	normal mode
	insert mode

visual mode:
Ctrl-C/X: copy/cut selection to register + (system clipboard)

additional copilot commands:
Ctrl-Right: request suggestion
Ctrl-Up/Down: next/previous suggestion
Ctrl-Left: dismiss suggestion

autocompletion:
Ctrl-Space / Tab: open autocompletion
in menu:
Ctrl-j / Ctrl-k / Tab / Shift-Tab: move down/up
Enter / Ctrl-Space: confirm suggestion
Ctrl-U / Ctrl-D: scroll docs up/down
Esc - close menu
in function snippet:
Tab / Shift-Tab: next / previous placeholder

in nvim-tree:
? or g? - show mappings
Enter - open file
v / Ctrl-v - open file in vertical split
t / Ctrl-t - open file in new tab
r - rename show full path
Ctrl-R - rename omit base name
Backspace - Close directory
Tab - open preview (stay in nvim-tree)
f / F - start/clear filter
c / p - copy/paste node
d - delete
R - refresh view
K - info about node
Ctrl-] - change root
a - create new file
H / I - toggle hidden/gitignored files
P - go to parent directory
E / W or C - expand/collapse all

NeoVim Cheat Sheet - [Alt]-Commands

`	1	2	3	4	5	6	7	8	9	0	-	=	Bs						
Q	close all other windows	W	maximize window	E	rotate window left	R	rotate windows right	T	move to new tab	Y	U	I	O	P	[	]	\		
Esc	A	go to previous window	S	equalize all windows	D	go to next window	F	G	H	go to previous window	J	go to window below	K	go to window above	L	go to next window	;	'	Enter
Z	close window	X	open new buffer	C	close tab	V	split window vertically	B	N	go to previous tab	M	go to next tab	,	.	/				