

NeoVim Cheat - Normal Mode

~ toggle case	! 1 ²	@· play macro 2 ²	# find (rev) identifier 2 ²	\$ eol 2 ²	% goto match 2 ²	^ "soft" bol 2 ²	& repeat :s 2 ²	* find identifier 2 ²	(begin sentence 2 ²	) end sentence	_ "soft" bol down previous line	+ next line = auto format ⁹	Backsp delete left char
Q play last macro	W next WORD	E end WORD	R replace mode	T· hop char full screen	Y yank to eol	U undo line	I insert at bol	O open above	P paste before ¹	{ begin paragraph	}	end paragraph	 bol / go to column
q· record macro	w next word	e end word	r· replace char	t· hop char cur buffer	y yank ^{1,8} ₉	u undo	i insert mode	o open below	p paste after ¹	[· previous ³	]	next ³	\ resume telescope
Caps = Esc normal mode	A append at eol a append ⁷	S delete line s delete char	D delete to eol d delete ^{1,7} _{8,9}	F· find char backward f· find char forward	G eof/ goto line g· extra cmds ⁵	H screen top h ◀	J join lines j ▼	K help / doc k ▲	L screen bottom l ▶	: command line ; hop word full screen	"· choose register ¹ '· goto mark bol	Enter change word	
Z scroll cmds ⁴ Z·	X back-space x delete char	C delete to eol c change ^{1,7} _{8,9}	V visual lines v visual mode	B back WORD b back word	N previous (find) n next (find)	M screen middle m· set mark ⁶	< un-indent ⁹ ,	> indent ⁹ .	?· find (rev) / find	bol = beginning of line eol = end of line,			

bol = beginning of line
eol = end of line,

motion	moves the cursor, or defines the range for an operator
command	direct action command, if red it enters insert mode
operator	requires a motion afterwards, operates between cursor & destination
extra	special functions, requires extra input
q.	commands with a dot need a char argument afterwards

main command line commands ('ex'):

```
:w (save), :q (quit) :wq (save&quit), :q! (quit w/o saving)
:e f (open file f), :vsp f (open file in vertical split)
:%s/x/y/gc (replace 'x' by 'y' filewide, but ask),
:%s/\s+$/ / (remove all trailing spaces),
:h (help in neovim), :new (new file in neovim)
:[number] (go to line [number])
:reg (show content of registers)
```

visual mode:

- operator use selection instead of motion
- o: exchange cursor position with start of selection
- J: join all selected lines
- S: add surrounding delimiter

notes:

- (1) use "x before a yank/paste/del command to use that register ('clipboard') (x=a,z,*)
(e.g.: "ay\$ to copy rest of line to register 'a')
- (2) type in a number before any action to repeat it that number of times
(e.g.: 2p, d2w, 5i, d4j)
- (3) [m /]m - go to previous / next method start
[M /]M - go to previous / next method end
[t /]t - go to previous / next TODO or NOTE
[e /]e - go to previous / next diagnostic
[g /]g - go to previous / next git hunk
- (4) zz: scroll cursor to center, zt: top, zb:bottom
- (5) gg: top of file,
gi: go to last insertion and switch to insert mode
gv: reselect last visual selection
gm: middle of screen line, gM: middle of line
ge: previous end of word
gn / gN: go to next/previous find and select
gt / gT: go to next/previous tab

- (6) m, - set next available mark (alphabetical)
m; - toggle mark at current line
m] and m[- go to next/previous mark
dmx and dm<space> - delete mark x / delete all marks
- (7) ci(- change inside brackets; also),[,.,{,<,>,"',, w,s,p
ca(- change around brackets
di[, da[, yi[, ya[, vi[, va(for delete, yank, select inside/around
ys[motion]{new} - add surrounding {new} to [motion]
cs{old}{new} - change surrounding {old} with {new}
ds{old} - delete surrounding {old}
yss{new} - add surrounding {new} to line
[space]b - change brackets (same as csb)
{new/old} = (,),[,.,{,<,>,"',, s (any of those)
 b (brackets:),[,>), q (quotes: ",',), t (html-tags),
 f (function), i (individual start and end)
- (9) duplicate operator to act on current line
(dd = delete line, yy = yank line, >> = indent line)