

SE 3XA3: Module Interface Specification

ScrumBot

Team 304, ScrumBot
Arkin Modi, modia1
Leon So, sol4
Timothy Choy, choyt2

Last Updated: April 6, 2020

Table 1: Revision History

Date	Developer(s)	Change
March 9, 2020	Timothy Choy	Create template, ScrumBot Module
March 10, 2020	Leon So	MeetingList module
March 11, 2020	Leon So	Meeting, MeetingTypes Modules
March 11, 2020	Leon So	Project, ProjectList, Meeting, MeetingTypes, Generic Dict Modules
March 11, 2020	Timothy Choy	Scrumbot Module
March 12, 2020	Leon So	Rename Meeting Module to Generic Meeting Module
March 12, 2020	Timothy Choy	Generic Meeting Module, Fixed Formatting
March 12, 2020	Arkin Modi	Fix Formatting
March 12, 2020	Leon So	Dict, Meeting, Project, Task, TaskList, Sprint Modules
March 12, 2020	Timothy Choy	Project, Meeting Modules
March 12, 2020	Timothy Choy	Completed ScrumBot module
March 13, 2020	Arkin Modi	Updated ScrumBot Module
April 4, 2020	Leon So	Revision 1 changes
April 5, 2020	Leon So	Revision 1 changes

ScrumBot Module

Module

AdminCog, ProjectCog, MeetingCog, MemberCog, Scrumbot, SprintCog, TaskCog

Uses

discord
discord.ext.commands
MeetingTypes
Generic Dictionary
MeetingList
Meeting
TaskList
Task
Sprint
ProjectList
Project

Syntax

Exported Constants

None

Exported Types

None

Exported Access Programs

Routine Name	In	Out	Exceptions
on_ready			

Table 2: ScrumBot Programs

Routine Name	In	Out	Exceptions
load	commands.Cogs	String	MissingRole, Exception
reload	commands.Cogs	String	MissingRole, Exception
unload	commands.Cogs	String	MissingRole, Exception

Table 3: Admin Programs

Routine Name	In	Out	Exceptions
get_roles		discord.embed	
get_roles	String	discord.embed	

Table 4: Member Programs

Routine Name	In	Out	Exceptions
add_meeting	\mathbb{N} , String, Date, Time, MeetingT	String	MissingRole
add_meeting	\mathbb{N} , String, Date, Time, MeetingT, String	String	MissingRole
add_project	String	String	MissingRole
add_project	String, String	String	MissingRole
add_rqe	\mathbb{N} , String	String	MissingRole
add_sprint	\mathbb{N}	String	MissingRole
get_project_desc	\mathbb{N}	discord.embed	
get_rqes	\mathbb{N}	discord.embed	
get_sprints	\mathbb{N}	discord.embed	
list_meetings	\mathbb{N}	discord.embed	
list_projects		discord.embed	
rm_last_sprint	\mathbb{N}	String	MissingRole
rm_meeting	\mathbb{N} , \mathbb{N}	String	MissingRole
rm_project	\mathbb{N}	String	MissingRole
rm_rqe	\mathbb{N}	String	MissingRole
set_project_desc	\mathbb{N} , String	String	MissingRole

Table 5: Project Programs

Routine Name	In	Out	Exceptions
get_meeting_desc	\mathbb{N} , \mathbb{N}	discord.embed	
set_meeting_desc	\mathbb{N} , \mathbb{N} , String	String	MissingRole

Table 6: Meeting Programs

Routine Name	In	Out	Exceptions
add_task	\mathbb{N} , \mathbb{N} , String, Date, Time	String	MissingRole
add_task	\mathbb{N} , \mathbb{N} , String, Date, Time, String	String	MissingRole
list_tasks	\mathbb{N} , \mathbb{N}	discord.embed	
rm_task	\mathbb{N} , \mathbb{N} , \mathbb{N}	String	MissingRole

Table 7: Sprint Programs

Routine Name	In	Out	Exceptions
add_feedback	N, N, N, String	String	MissingRole
get_details	N, N, N	discord.embed	
list_feedback	N, N, N	discord.embed	
rm_feedback	N, N, N, N	String	MissingRole
set_details	N, N, String	String	MissingRole

Table 8: Task Programs

Semantics

Environment Variables

TOKEN: A string constant containing the information linking ScrumBot to Discord's API

State Variables

startup_extensions: A list of command cogs.

State Invariant

None

Assumptions

This module is the interface between the users and the code. The input taken for the export access programs are text-based commands in Discord, and the output is also in text channels as text output. The methods also keep an output in the terminal as a log of commands used.

The exception to this assumption is the access routine on_ready as the output for the method is found in the terminal only. Due to this, there is no output value in the exported access programs table.

Though it is comprised of multiple files with many different purposes, the main purpose for these files are the same. For this reason, they have been grouped together into one module, with the secret being communication between the client from Discord and the system.

It is assumed that author refers to the user that initiated the command.

Access Routine Semantics

ScrumBot Programs

on_ready()

- transition: waits for ScrumBot to connect to Discord’s API servers using the TOKEN, and upon successful connection, will print out the bot’s name and id to the terminal. It is a check for successful connection to the server.

Admin Programs

load(*cog*)

- transition: attempts to load a Cog into ScrumBot through the use of the command `load_extension(cog)`
- output: $out := (exc \Rightarrow \text{“Error: failed to load”} \parallel cog \mid \neg exc \Rightarrow cog \parallel \text{“loaded”})$
- exception:

	$exc :=$
author_role \neq admin	MissingRole
any issue with loading cog	Exception

reload(*cog*)

- transition: attempts to reload the cog in ScrumBot through unloading the cog then loading the cog
- output: $out := (exc \Rightarrow \text{“Error: failed to reload”} \parallel cog \mid \neg exc \Rightarrow cog \parallel \text{“reloaded”})$
- exception:

	$exc :=$
author_role \neq admin	MissingRole
any issue with unloading or loading cog	Exception

unload(*cog*)

- transition: attempts to unload a cog from ScrumBot
- output: $out := (exc \Rightarrow \text{“Error: failed to unload”} \parallel cog \mid \neg exc \Rightarrow cog \parallel \text{“unloaded”})$
- exception:

	$exc :=$
author_role \neq admin	MissingRole
any issue with unloading cog	Exception

Member Programs

get_roles()

- transition: finds all roles that are assigned to the author
- output: $out :=$ a discord.embed such that it contains the chosen author’s name, icon, and a list of their roles

`get_roles(name)`

- transition: takes in the name of a Discord user and finds all roles that are assigned to that user
- output: $out :=$ a discord.embed such that it contains the chosen user's name, icon, and a list of their roles

Project Programs

`add_meeting($n, name, date, time, meeting$)`

- transition: new Meeting($name, date, time, meeting$), add it to project n using add_meeting
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added meeting"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`add_meeting($n, name, date, time, meeting, desc$)`

- transition: new Meeting($name, date, time, meeting, desc$), add it to project n using add_meeting
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added meeting"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`add_project(name)`

- transition: new Project($name$)
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added project"})$
- exception: $exc := \text{author_role} \neq \text{admin} \Rightarrow \text{MissingRole}$

`add_project(name, desc)`

- transition: new Project($name, desc$)
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added project"})$
- exception: $exc := \text{author_role} \neq \text{admin} \Rightarrow \text{MissingRole}$

`add_rqe(n, s)`

- transition: add_rqe(s) in project n

- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added requirements"})$
- exception: $exc := \text{author_role} \neq \text{Business Analyst} \Rightarrow \text{MissingRole}$

`add_sprint(n)`

- transition: new Sprint(), then add the sprint to project n using `add_sprint(sprint)`
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added a sprint"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`get_project_desc(n)`

- output: $out :=$ A discord.embed such that it contains the project name and description of project n

`get_rqes(n)`

- output: $out :=$ A discord.embed such that it contains the project name and list of requirements of project n

`get_sprints(n)`

- output: $out :=$ A discord.embed such that it contains the project name and list of sprints of project n

`list_meetings(n)`

- output: $out :=$ A discord.embed such that it contains the project name and list of meetings of project n , as well as show the times for all the meetings

`list_projects()`

- output: $out :=$ A discord.embed containing all the created projects, identified by their name

`rm_last_sprint(n)`

- transition: removes the last sprint of project n using `rm_sprint()`
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully removed a sprint"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`rm_meeting(n, m)`

- transition: removes a meeting from project n using `rm_meeting(m)`
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully removed a meeting"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`rm_project(n)`

- transition: removes a project by their project id using `remove(n)`
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully removed a project"})$
- exception: $exc := \text{author_role} \neq \text{admin} \Rightarrow \text{MissingRole}$

`rm_rqe(n, m)`

- transition: remove requirement m from project n using `rm_rqe(m)`
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully removed a requirement"})$
- exception: $exc := \text{author_role} \neq \text{Business Analyst} \Rightarrow \text{MissingRole}$

`set_project_desc(n, s)`

- transition: `set_desc(s)` in project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully set description"})$
- exception: $exc := \text{author_role} \neq \text{Business Analyst} \wedge \text{author_role} \neq \text{admin} \Rightarrow \text{MissingRole}$

Meeting Programs

`get_meeting_desc(n, m)`

- output: $out :=$ A discord.embed such that it contains the meeting description of meeting m in project n , showing the meeting name and project name as well

`set_meeting_desc(n, m, s)`

- transition: `set_desc(s)` for meeting m in project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully set description"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

Sprint Programs

`add_task($n, m, name, date, time$)`

- transition: `new Task($name, date, time$)` then `add_task(task)` in sprint m , project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added task"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`add_task($n, m, name, date, time, detail$)`

- transition: `new Task($name, date, time, detail$)` then `add_task(task)` in sprint m , project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added task"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \wedge \text{author_role} \neq \text{Business Analyst} \Rightarrow \text{MissingRole}$

`list_tasks(n, m)`

- output: $out :=$ A discord.embed such that it lists all the tasks of sprint m in project n , as well as their deadlines

`rm_task(n, m, k)`

- transition: `rm_task(k)` in sprint m in project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully removed task"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \wedge \text{author_role} \neq \text{Business Analyst} \Rightarrow \text{MissingRole}$

Task Programs

`add_feedback(n, m, k, s)`

- transition: `add_feedback(s)` in task k , sprint m , project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully added feedback"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`get_details(n, m, k)`

- output: $out :=$ A discord.embed such that it shows the details of task k , in sprint m , in project n , using `get_details()`

`list_feedback(n, m, k)`

- output: $out :=$ A discord.embed such that it lists all the feedback of task k , in sprint m , in project n , using `get_feedback()`

`rm_feedback(n, m, k, x)`

- transition: `rm_feedback(x)` for task k in sprint m in project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully removed feedback"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \Rightarrow \text{MissingRole}$

`set_details(n, m, s)`

- transition: `set_details(s)` for task k in sprint m in project n
- output: $out := (exc \Rightarrow \text{"MissingRole: You have insufficient permissions"} \mid \neg exc \Rightarrow \text{"Successfully set details"})$
- exception: $exc := \text{author_role} \neq \text{Scrum Master} \wedge \text{author_role} \neq \text{Business Analyst} \Rightarrow \text{MissingRole}$

MeetingTypes Module

Module

MeetingTypes

Uses

N/A

Syntax

Exported Constants

N/A

Exported Types

MeetingT = {Grooming, StandUp, Retrospective, SprintPlanning}

Exported Access Programs

None

Semantics

State Variables

None

State Invariant

None

Generic Dictionary Module

Generic Template Module

Dict(T)

Uses

N/A

Syntax

Exported Types

Dict = ?

Exported Constants

None

Exported Access Programs

Routine Name	In	Out	Exceptions
new Dict(T)		Dict(T)	
add	T		
update	\mathbb{N}, T		
remove	\mathbb{N}		KeyError
get_last_id		\mathbb{N}	
to_seq		seq of (\mathbb{N}, T)	

Semantics

State Variables

d: seq of (\mathbb{N}, T)

c: \mathbb{N}

State Invariant

$|d| \geq 0$

$c \geq 0$

Assumptions & Design Decisions

The Dict(T) constructor is called for each object instance before any other access routine is called for that object.

It is assumed that the first term in Dict is referred to as the "key" and the second term is the "value".

Access Routine Semantics

new Dict()

- transition: $d, c := \langle \rangle, 0$
- output: $out := self$

add(e)

- transition: $d := d \parallel \langle c, e \rangle, c := c + 1$

update(id, e)

- transition: $d[id], c := e, id + 1$

remove(id)

- transition: $d := d - \langle id, e \rangle$
- exception: $exc := \langle id, e \rangle \notin d \Rightarrow \text{KeyError}$

get_last_id()

- output: $out := c - 1$

to_seq()

- output: $out := d$ such that $(\forall i \in \mathbb{N} \mid 0 \leq i < |d| \cdot d[i].key() \leq d[i + 1].key())$

MeetingList Module

Template Module

MeetingList is a Dict(Meeting)

Meeting Module

Module

Meeting

Uses

MeetingTypes

Syntax

Exported Constants

None

Exported Types

Meeting = ?

Exported Access Programs

Routine Name	In	Out	Exceptions
new Meeting	String, Date, Time String , MeetingT	Meeting	
new Meeting	String, Date, Time String , MeetingT, String	Meeting	
get_name		String	
get_datetime		String	
get_date		Date	
get_time		Time	
get_type		MeetingT	
get_desc		String	
set_desc	String		

Semantics

State Variables

name: String

date: Date

time: Time

d: Datetime

type: MeetingT

desc: String

State Invariant

None

Assumptions

- The Meeting constructor is called for each object instance before any other access routine is called for that object.

Access Routine Semantics

new Meeting($n, \cancel{d}, \cancel{t}$ *dt*, *type*)

- transition: $name, \cancel{time}, \cancel{date}, \textcolor{red}{d}, type, desc := n, \cancel{d}, \cancel{t} \textcolor{red}{Datetime(dt)}, type, None$
- output: $out := self$

new Meeting($n, \cancel{d}, \cancel{t}$ *dt*, *type*, *desc*)

- transition: $name, \cancel{time}, \cancel{date}, \textcolor{red}{d}, type, desc := n, \cancel{d}, \cancel{t} \textcolor{red}{Datetime(dt)}, type, desc$
- output: $out := self$

~~get_name()~~

- $\cancel{output} : out := name$

~~get_date()~~

- $\cancel{output} : out := date$

~~get_time()~~

- $\cancel{output} : out := time$

get_datetime()

- *output: out := String(d)*

get_type()

- output: $out := type$

get_desc()

- output: $out := \cancel{dese}(\textcolor{red}{desc = None} \Rightarrow \textcolor{red}{\text{"No description"}} \mid \textcolor{red}{desc})$

set_desc(*s*)

- transition: $desc := s$

TaskList Module

Template Module

TaskList is a Dict(Task)

Task Module

Module

Task

Uses

None

Syntax

Exported Constants

None

Exported Types

Task = ?

Exported Access Programs

Routine Name	In	Out	Exceptions
new Task	String, Date, Time String	Task	
new Task	String, Date, Time String , Details	Task	
get_name		String	
get_deadline		(Date, Time) String	
get_details		String	
get_feedback		seq of String	
add_feedback	String		
rm_feedback	N		
set_details	String		

Semantics

State Variables

name: String

deadline: ~~(Date, Time)~~ **Datetime**

details: String

feedback: seq of String

State Invariant

None

Assumptions

- The Task constructor is called for each object instance before any other access routine is called for that object.

Access Routine Semantics

new Task($s, \cancel{d}, \cancel{t} \text{ } dt$)

- transition: $name, deadline, details := s, (\cancel{d}, \cancel{t}) \text{ } Datetime(dt), None$
- output: $out := self$

new Task($s, \cancel{d}, \cancel{t} \text{ } dt, details$)

- transition: $name, deadline, details := s, (\cancel{d}, \cancel{t}) \text{ } Datetime(dt), details$
- output: $out := self$

get_name()

- output: $out := name$

get_deadline()

- output: $out := \cancel{deadline}String(deadline)$

get_details()

- output: $out := (details = None \Rightarrow \text{“No details”} \mid details)$

get_feedback()

- output: $out := feedback$

add_feedback(s)

- transition: $feedback := feedback \parallel s$

$\text{rm_feedback}(s)$

- transition: $\text{feedback} := \text{feedback} - s$

$\text{set_details}(s)$

- transition: $\text{details} := s$

Sprint Module

Module

Sprint

Uses

TaskList, Task

Syntax

Exported Constants

None

Exported Types

Sprint = ?

Exported Access Programs

Routine Name	In	Out	Exceptions
new Sprint		Sprint	
new Sprint	Date	Sprint	
get_date		String	
get_feedback	N	String	KeyError
get_last_task_id		N	
get_tasks		seq of Task	
get_task	N	Task	
add_feedback	N, String		
add_task	Task String, String		
add_task	String, String, String		
add_task_from_file	N, String, String		
add_task_from_file	N, String, String, String		
rm_feedback	N, N		KeyError
rm_task	N		
set_details	N, String		KeyError

Semantics

State Variables

tasks: TaskList

date: Date

State Invariant

None

Assumptions

- The Sprint constructor is called for each object instance before any other access routine is called for that object.

Access Routine Semantics

new Sprint(n)

- transition: $tasks, date := TaskList(), Datetime.today()$
- output: $out := self$

new Sprint(n, d)

- transition: $tasks, date := TaskList(), Datetime(d)$
- output: $out := self$

get_date()

- output: $out := String(date)$

get_tasks($\#$)

- output: $out := tasks.to_seq()$

get_task(n)

- output: $out := get_tasks()[n]$

get_feedback(n)

- output: $out := get_task(n).get_feedback()$
- exception: $exc := get_task(n) == None \Rightarrow \text{KeyError}$

get_last_task_id()

- output: $out := tasks.get_last_id()$

add_feedback(n, s)

- transition: $:= get_tasks(n).add_feedback(s)$
- exception: $exc := get_task(n) == None \Rightarrow \text{KeyError}$

`add_task(taskname, deadline)`

- transition: *tasks* := *tasks.add*(~~task~~*new Task(name, deadline)*)

`add_task(name, deadline, details)`

- transition: *tasks* := *tasks.add*(*new Task(name, deadline, details)*)

`add_task_from_file(n, name, deadline)`

- transition: *tasks* := *tasks.update*(*n, new Task(name, deadline)*)

`add_task_from_file(n, name, deadline, details)`

- transition: *tasks* := *tasks.update*(*n, new Task(name, deadline, details)*)

`rm_feedback(task_id, feedback_id)`

- transition: *tasks* := *get_task(task_id).rm_feedback(feedback_id)*
- exception: *exc* := *get_task(task_id)* == None \Rightarrow KeyError

`rm_task(n)`

- transition: *tasks* := *tasks.remove*(*n*)

`set_details(n, s)`

- transition: *tasks* := *get_task(n).set_details(s)*
- exception: *exc* := *get_task(n)* == None \Rightarrow KeyError

ProjectList Module

Template Module

ProjectList is a Dict(Project)

Project Module

Module

Project

Uses

Sprint, Tasklist, Task

Syntax

Exported Constants

None

Exported Types

Project = ?

Exported Access Programs

Routine Name	In	Out	Exceptions
new Project	String	Project	
new Project	String, String	Project	
get_desc		String	
get_feedback	N, N	String	IndexError
get_last_meeting_id		N	
get_meetings		seq of Meeting	
get_meeting_desc	N	String	KeyError
get_meeting_name	N	String	KeyError
get_name		String	
get_rqs		seq of String	
get_sprints		seq of Sprint	
get_task	N, N	Task	IndexError
get_tasks	N	seq of Task	IndexError
set_desc	String		
add_feedback	N, String		IndexError
add_meeting	Meeting String, String, MeetingT		
add_meeting	String, String, MeetingT, String		
add_rqe	String		
add_sprint	Sprint		
add_sprint_from_file	Date		
add_task	String, String		IndexError
add_task	String, String, String		IndexError
add_task_from_file	N, String, String		IndexError
add_task_from_file	N, String, String, String		IndexError
rm_feedback	N, N		IndexError
rm_meeting	N		KeyError
rm_rqe	N		IndexError
rm_sprint			IndexError
rm_task	N		IndexError
set_details	N, String		IndexError
set_meeting_desc	N		KeyError
set_meeting_desc	N, String		KeyError
update_meeting	N, String, String, MeetingT		
update_meeting	N, String, String, MeetingT, String		

Semantics

State Variables

name: String
desc: String
meetings: MeetingList
rques: seq of String
sprints: seq of Sprint
c: \mathbb{N}

State Invariant

$c = |sprints| \wedge c \geq 0$

Assumptions

- The Project constructor is called for each object instance before any other access routine is called for that object.

Access Routine Semantics

new Project(*n*)

- transition: $name, desc, rques, sprints := n, \text{None}, [], []$
- output: $out := \text{self}$

new Project(*n*, *d*)

- transition: $name, desc, rques, sprints := n, d, [], []$
- output: $out := \text{self}$

get_desc()

- output: $out := (desc = \text{None} \Rightarrow \text{“No description”} \mid desc)$

get_feedback(*sprint_index*, *task_index*)

- output: $out := sprints[sprint_index].get_feedback(task_index)$
- exception: $exc := sprint_index > |sprints| - 1 \Rightarrow \text{IndexError}$

get_last_task_id()

- output: $out := sprints[-1].get_last_task_id()$

get_meetings()

- output: $out := meetings.to_seq()$

$get_meeting_desc(n)$

- output: $out := meetings[n].get_desc()$
- exception: $exc := meetings[n] == None \Rightarrow \text{KeyError}$

$get_meeting_name(n)$

- output: $out := meetings[n].get_name()$
- exception: $exc := meetings[n] == None \Rightarrow \text{KeyError}$

$get_name()$

- output: $out := name$

$get_rqes()$

- output: $out := rqes$

$get_sprints()$

- output: $out := sprints$

$get_task(sprint_index, task_index)$

- output: $out := sprints[sprint_index].get_task(task_index)$
- exception: $exc := sprint_index > |sprints| - 1 \Rightarrow \text{IndexError}$

$get_tasks(n)$

- output: $out := sprints[n].get_tasks()$
- exception: $exc := n > |sprints| - 1 \Rightarrow \text{IndexError}$

$set_desc(s)$

- transition: $desc := s$

$add_feedback(n, s)$

- transition: $sprints := sprints[-1].add_feedback(n, s)$
- exception: $exc := |sprints| == 0 \Rightarrow \text{IndexError}$

$add_meeting(\text{meeting}name, dt, m_type)$

- transition: $meetings := meetings.add(\text{meeting}new Meeting(name, dt, m_type))$

add_meeting(name, dt, m_type, desc)

- transition: *meetings := meetings.add(new Meeting(name, dt, m_type, desc))*

add_rqe(s)

- transition: *rques := rques || s*

add_sprint(~~sprint~~)

- transition: *sprints, c := sprints || ~~sprint~~new Sprint() , c + 1*

add_sprint_from_file(d)

- transition: *sprints := sprints || new Sprint(date)*

add_task(name, deadline)

- transition: *sprints := sprints[-1].add_task(name, deadline)*
- exception: *exc := |sprints| == 0 ⇒ IndexError*

add_task(name, deadline, details)

- transition: *sprints := sprints[-1].add_task(name, deadline, details)*
- exception: *exc := |sprints| == 0 ⇒ IndexError*

add_task_from_file(n, name, deadline)

- transition: *sprints := sprints[-1].add_task_from_file(n, name, deadline)*
- exception: *exc := |sprints| == 0 ⇒ IndexError*

add_task_from_file(n, name, deadline, details)

- transition: *sprints := sprints[-1].add_task_from_file(n, name, deadline, details)*
- exception: *exc := |sprints| == 0 ⇒ IndexError*

rm_feedback(task_index, feedback_index)

- transition: *sprints := sprints[-1].rm_feedback(task_index, feedback_index)*
- exception: *exc := |sprints| == 0 ⇒ IndexError*

rm_meeting(n)

- transition: *meetings := meetings.remove(n)*
- exception: *exc := meetings[n] == None ⇒ KeyError*

`rm_rqe(n)`

- transition: $rqs := rqs - rqs[n]$

`rm_sprint()`

- transition: $sprints, c := sprints[0 : |sprints| - 2], c - 1$
- exception: $exc := c = 0 \Rightarrow \text{IndexError}$

`rm_task(n)`

- transition: $sprints := sprints[-1].rm_task(n)$
- exception: $exc := |sprints| == 0 \Rightarrow \text{IndexError}$

`set_details(n, s)`

- transition: $sprints := sprints[-1].set_details(n, s)$
- exception: $exc := |sprints| == 0 \Rightarrow \text{IndexError}$

`set_meeting_desc(n)`

- transition: $meetings := meetings[n].set_desc(\text{None})$
- exception: $exc := meetings[n] == \text{None} \Rightarrow \text{KeyError}$

`set_meeting_desc(n, s)`

- transition: $meetings := meetings[n].set_desc(s)$
- exception: $exc := meetings[n] == \text{None} \Rightarrow \text{KeyError}$

`update_meeting(id, name, dt, m_type)`

- transition: $meetings := meetings.update(id, \text{New Meeting}(id, name, dt, m_type))$

`update_meeting(id, name, dt, m_type, desc)`

- transition: $meetings := meetings.update(id, \text{New Meeting}(id, name, dt, m_type, desc))$