Enhancing Real-Time Point-Cloud Streaming through In-Network Computing

Master's Degree in Engineering in Computer Science

Leonardo Chiarparin (2016363)


Academic Year 2025 / 2026




SAPIENZA
UNIVERSITÀ DI ROMA

From XR to Point Cloud Streaming


1 Introduction



Polygonal mesh



Voxel grid



Point Cloud

Context and Motivation


- **Extended Reality**: virtual, augmented, mixed
- One timing budget, sensing to display [4, 14]
- **Six degrees of freedom**, chosen after capture

The 8iVFB Dataset

- **Loot**, from the **8i Voxelized Full Bodies** [2]
- 300 frames of about 794 thousand samples
- Quantised on a lattice of 1.820 mm [15]

Architecture and Interfaces

1 Introduction



Four coarse application blocks are joined by a transport that carries bytes and inspects none of them [8]. Projection, coding and both reverse loops sit inside the **Encoder**, which therefore sets the pace of the chain [5, 12].



Limits of Real-Time Volumetric Workflows

1 Introduction

Throughput

- 3 Gbit / s of raw samples at nominal cadence
- Coding is a precondition, not a refinement

Delay

- A new input every 33.333 ms
- Each queue crossed increases elapsed time

Granularity

- A cloud spans ten thousand datagrams
- Stages wait for the last of them

Resource Coupling

- Unrelated duties share one boundary
- Individual tasks cannot be relieved alone



Research Questions and Contributions

1 Introduction

RQ1

Which operations admit a progressive evaluation **in transit**, and which of them yield a value that a later component can consume without recomputing it?

RQ2

What does moving the geometric frontier do to the **load** it withdraws, to the **headroom** it returns, and to the end-to-end latency a viewer perceives?

RQ3


Does the graph sustain 30 fps, and does saturation appear as quantified **backpressure** instead of silent loss?

RQ4


Does the decoded stream keep its **fidelity** once the same arithmetic is resolved elsewhere?

Computation Bound to Packet Traversal

2 Background



Everything is paid at the **destination**



Part of it is settled **on the way**

Origins and Definition


- Chosen because the traffic already crosses it [7]
- Each placement answers for itself [9, 11]

The Data Plane Development Kit

- Kernel bypassed, one isolated core [3]
- Payload resident in **user space** needs no copy

Anatomy of the Redistributed Graph


3 Methodology



Service paths and the state they carry follow the chaining architecture [6, 10], while the implementation sources, build recipe and platform specification needed to reproduce the system are publicly available [1].

Geometry Resolved While Forwarding

3 Methodology



Packet-progressive reductions

$$S_N = \sum_{p \in P_N} p$$

$$p_N^{\min} = \min_{p \in P_N} p, \quad p_N^{\max} = \max_{p \in P_N} p$$


Frame-completing quantities

$$C = \frac{S_N}{N}, \quad r_{\max} = \max_{p \in P} \|p - C\|_2$$

$$f = \frac{0.2\,D}{r_{\max}}, \quad g = (1+\delta)\max\left(\frac{E'_x}{W}, \frac{E'_y}{H}, \frac{E'_z}{W}\right)$$

Regulation Driven by Measured Load

3 Methodology



$$T_{\text{base}} = \frac{1000}{f_{\text{t}}}, \qquad E_n = \alpha\, T_n + (1-\alpha) E_{n-1}, \qquad \rho_n = \frac{E_n}{s\, T_{\text{base}}}$$

α: Smoothing weight, f_{t}: Nominal rate, ρ_n: **Workload ratio**, s: Active factor, T_n: Service interval




The Conditions Evaluated

4 Performance Evaluation

Family	Runs	Purpose
Baseline	`B0-R1..R3`, with nothing changed	How much the nominal configuration varies on its own, setting the threshold for subsequent comparisons
Ablation	`O-OFF-R1..R2`, both offload switches are disabled	What relocating the geometric frontier costs in practice once everything around it is deliberately held fixed
Packet pressure	`P40`, `P40-NO-T`, `P84`, `M1000`, datagram capacity and grouping	How the pipeline responds as packet pressure rises, with the regulator enabled and then withdrawn

The Repeated Baseline


5 Results



The reduction is **35.99 per cent**. Transport, decomposition, control arrangement and deployment all differ besides the site of the frontier, so it belongs to **the redesign as a whole** under these conditions.

Where the Computation Is Paid


5 Results



	Camera	Ingress	Hub R0	Encoder	Hub R1	Decoder	Hub R2	Egress	Terminal
○	18.326	11.724	6.205	17.577	0.009	37.525	0.616	1.336	3.586
□	15.055	1.935	4.226	46.821	0.010	38.326	0.714	1.267	3.939
△	16.871	2.471	6.636	25.601	0.008	37.558	0.631	1.044	2.632

Pressure Imposed Through the Datagram Rate

5 Results



Halving the points per packet is the only condition that brings the regulator out of its idle state. The cadence settles at **26.074 fps**, so saturation becomes a deliberate adaptation of the source.

What the Redistribution Achieved

6 Conclusions

The redistribution relocates the work without materially changing what reaches the **User**: valid point counts match across all 300 frames, and every loss is attributed to the hop where it occurs.

7	35.99 %	8 / 9
Units following the criterion	Less end-to-end delay	Trials at nominal cadence

Where the Evidence Stops

- Single host, one sequence, fixed compression
- Core assignment is specific to this topology
- Service representation mirrors the header only

What Should Be Attempted Next

- Dynamic workload model beyond static fractions
- Cross the frame barrier with slice segments [13]
- Repeat across other platforms and datasets



Enhancing Real-Time Point-Cloud Streaming through In-Network Computing

Thank you for listening!

Any questions?



References

References

[1] Leonardo Chiarparin. *Enhancing Real-Time Point-Cloud Streaming through In-Network Computing — Implementation Sources and Platform Specification*. Software repository. 2026. URL: `https://github.com/Leonardo-Chiarparin/Thesis`.

[2] Eugene d'Eon, Bob Harrison, Taos Myers, and Philip A. Chou. *8i Voxelized Full Bodies — A Voxelized Point Cloud Dataset*. Tech. rep. WG11M40059/WG1M74006. ISO/IEC JTC1/SC29 Joint WG11/WG1 (MPEG/JPEG), 2017.

[3] DPDK Project. *Data Plane Development Kit — Programmer's Guide and API Documentation, Release 22.11.4 LTS*. URL: `https://doc.dpdk.org/guides-22.11/`.

[4] Mohammed S. Elbamby, Cristina Perfecto, Mehdi Bennis, and Klaus Doppler. "Toward Low-Latency and Ultra-Reliable Virtual Reality". In: *IEEE Network* 32.2 (2018), pp. 78–84.

[5] Danillo Graziosi, Ohji Nakagami, Satoru Kuma, et al. "An Overview of Ongoing Point Cloud Compression Standardization Activities: Video-Based (V-PCC) and Geometry-Based (G-PCC)". In: *APSIPA Transactions on Signal and Information Processing* 9 (2020), e13.

[6] Joel Halpern and Carlos Pignataro. *Service Function Chaining (SFC) Architecture*. RFC 7665. Internet Engineering Task Force, 2015.

[7] Ike Kunze, Klaus Wehrle, Dirk Trossen, et al. *Use Cases for In-Network Computing*. RFC 9817. Computing in the Network Research Group. Internet Research Task Force, 2025.

[8] Maria Giovanna Lacaria. "Point Cloud Coding for Extended Reality Services". Master's Degree in Communications Engineering. MA thesis. Sapienza University of Rome, Faculty of Information Engineering, Informatics and Statistics, 2026.

[9] Dan R. K. Ports and Jacob Nelson. "When Should the Network Be the Computer?" In: *Proceedings of the Workshop on Hot Topics in Operating Systems (HotOS)*. ACM, 2019, pp. 209–215.

[10] Paul Quinn, Uri Elzur, and Carlos Pignataro. *Network Service Header (NSH)*. RFC 8300. Internet Engineering Task Force, 2018.

[11] Amedeo Sapio, Marco Canini, Chen-Yu Ho, et al. "Scaling Distributed Machine Learning with In-Network Aggregation". In: *18th USENIX Symposium on Networked Systems Design and Implementation (NSDI)*. USENIX Association, 2021, pp. 785–808.

References

References

[12] Sebastian Schwarz, Marius Preda, Vittorio Baroncini, et al. “Emerging MPEG Standards for Point Cloud Compression”. In: *IEEE Journal on Emerging and Selected Topics in Circuits and Systems* 9.1 (2019), pp. 133–148.

[13] Gary J. Sullivan, Jens-Rainer Ohm, Woo-Jin Han, and Thomas Wiegand. “Overview of the High Efficiency Video Coding (HEVC) Standard”. In: *IEEE Transactions on Circuits and Systems for Video Technology* 22.12 (2012), pp. 1649–1668.

[14] Yaping Sun, Zhiyong Chen, Meixia Tao, and Hui Liu. “Communications, Caching, and Computing for Mobile Virtual Reality: Modeling and Tradeoff”. In: *IEEE Transactions on Communications* 67.11 (2019), pp. 7573–7586.

[15] Yusheng Xu, Xiaohua Tong, and Uwe Stilla. “Voxel-Based Representation of 3D Point Clouds: Methods, Applications, and Its Potential Use in the Construction Industry”. In: *Automation in Construction* 126 (2021), p. 103675.