

[VBForums](#) > [General](#) > [Application Deployment](#)[\[RESOLVED\] Deploying / Installing MySQL ODBC Connector with app](#)

Aug 13th, 2008, 09:43 AM

✓ [RESOLVED] Deploying / Installing MySQL ODBC Connector with app

I am hoping someone can help me to get an inno script together that will install the MySQL odbc drivers with my app. I found the script below but it doesn't appear to be working. Does anyone know how this can be accomplished?

```
Code:
; start odbc files
Source: c:\windows\system32\myodbc3.dll; DestDir: {sys}; flags: onlyifdoesntexist
Source: c:\windows\system32\myodbc3d.dll; DestDir: {sys}; flags: onlyifdoesntexist
Source: c:\windows\system32\myodbc3.lib; DestDir: {sys}; flags: onlyifdoesntexist
Source: c:\windows\system32\my3dsn.hlp; DestDir: {sys}; flags: onlyifdoesntexist

; NOTE: Don't use "Flags: ignoreversion" on any shared system files

[Registry]
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: dword; ValueName: UsageCount; ValueData: $00000001
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\ODBC Drivers; ValueType: string; ValueName: MySQL; ValueData: Installed
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: Driver; ValueData: {sys}\myodbc3.dll
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: Setup; ValueData: {sys}\myodbc3.dll
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: APILevel; ValueData: 2
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: ConnectFunctions; ValueData: YYN
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: DriverODBCVer; ValueData: 02.50
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: FileUsage; ValueData: 0
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: FileExtns; ValueData: *.txt
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: SQLLevel; ValueData: 1
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\ODBC Data Sources; ValueType: string; ValueName: auctions; ValueData: MySQL
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Driver; ValueData: {sys}\myodbc3.dll
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Description; ValueData:
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Database; ValueData: auction
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Server; ValueData: localhost
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: User; ValueData: auction
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Password; ValueData: password
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Port; ValueData:
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Option; ValueData: 0
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Stmt; ValueData:
```

Last edited by kxcntry99; Aug 19th, 2008 at 08:23 AM.

Aug 15th, 2008, 08:55 AM

Re: Installing MySQL ODBC Connector with app

I changed the script to the following but when I try and call the driver I get the following error:

[Microsoft][ODBC Driver Manager] Data source name not found and no default driver specified.

anyone know what I am missing or how to handle this ?

[Files]

```
; start odbc files
```

```
Source: C:\Documents and Settings\browkevi\Desktop\myodbc3.dll; DestDir: {sys}; flags: onlyifdoesntexist
Source: C:\Documents and Settings\browkevi\Desktop\myodbc3s.lib; DestDir: {sys}; flags: onlyifdoesntexist
Source: C:\Documents and Settings\browkevi\Desktop\myodbc3s.dll; DestDir: {sys}; flags: onlyifdoesntexist
Source: C:\Documents and Settings\browkevi\Desktop\myodbc3.lib; DestDir: {sys}; flags: onlyifdoesntexist
Source: C:\Documents and Settings\browkevi\Desktop\myodbc3.hlp; DestDir: {sys}; flags: onlyifdoesntexist
```

```
; NOTE: Don't use "Flags: ignoreversion" on any shared system files
```

[Registry]

```
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: dword; ValueName: UsageCount; ValueData: $00000001
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\ODBC Drivers; ValueType: string; ValueName: MySQL; ValueData: Installed
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: Driver; ValueData: {sys}\myodbc3.dl
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: Setup; ValueData: {sys}\myodbc3.dll
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: APILevel; ValueData: 2
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: ConnectFunctions; ValueData: YYN
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: DriverODBCVer; ValueData: 02.50
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: FileUsage; ValueData: 0
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: FileExtns; ValueData: *.txt
Root: HKLM; SubKey: Software\ODBC\ODBCINST.INI\MySQL; ValueType: string; ValueName: SQLLevel; ValueData: 1
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\ODBC Data Sources; ValueType: string; ValueName: auctions; ValueData: MySQL
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Driver; ValueData: {sys}\myodbc3.dll
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Description; ValueData:
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Database; ValueData: auction
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Server; ValueData: localhost
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: User; ValueData: auction
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Password; ValueData: password
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Port; ValueData:
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Option; ValueData: 0
Root: HKLM; SubKey: Software\ODBC\ODBC.INI\auctions; ValueType: string; ValueName: Stmt; ValueData:
```



Aug 19th, 2008, 08:22 AM

#3

Re: Installing MySQL ODBC Connector with app

Ok I came up with a script that will install the files needed for the driver and run the ODBC registration process. This script seems to work with any build of the MySQL 3.51 connector. I.e. I wrote it for the 3.51.26 version and have tested it with the 2.51.12 and 3.51.16 version.

Hopefully this will help those that come after me looking to do the same thing.

Code:

[Files]

```
; start odbc files
```

```
Source: H:\Install_Support\mysql_connector_3.51.16\lib\myodbc3.dll; DestDir: {sys}; flags: onlyifdoesntexist
Source: H:\Install_Support\mysql_connector_3.51.16\lib\myodbc3s.lib; DestDir: {sys}; flags: onlyifdoesntexist
Source: H:\Install_Support\mysql_connector_3.51.16\lib\myodbc3s.dll; DestDir: {sys}; flags: onlyifdoesntexist
Source: H:\Install_Support\mysql_connector_3.51.16\lib\myodbc3.lib; DestDir: {sys}; flags: onlyifdoesntexist
```

```
Source: H:\Install_Support\mysql_connector_3.51.16\bin\myodbc3i.exe; DestDir: {sys}; flags: onlyifdoesntexist
Source: H:\Install_Support\mysql_connector_3.51.16\bin\myodbc3m.exe; DestDir: {sys}; flags: onlyifdoesntexist
Source: H:\Install_Support\mysql_connector_3.51.16\bin\myodbc3c.exe; DestDir: {sys}; flags: onlyifdoesntexist
```

```
; NOTE: Don't use "Flags: ignoreversion" on any shared system files
```

[Run]

```
; run the registration process to add the connector to the ODBC manager
```

```
Filename: "{sys}\myodbc3i"; Parameters:"-a -d -t""MySQL ODBC 3.51 Driver;DRIVER=myodbc3.dll;SETUP=myodbc3s.dll""";
```

