A_

// AUDITNET · NETWORK CONFIGURATION AUDITING

User guide

System administrator

Step-by-step guide to the network configuration auditing console.

Version 1.0 · October 2026
English

Contents

Your profile: system administrator

Signing in to AuditNet

- Sign in
- Recover your password

The console

- Side menu
- Top bar
- User menu
- User guide
- Session

My account

- Your details
- Change your password
- Language, theme and email notices

Dashboard and client status

- Dashboard
- Client status

Organizations and sites

- Register an organization
- Edit, disable or enable
- Sites
- Change the plan
- Review deadlines

Users and profiles

- Register a user
- Actions on a user
- Profiles and permissions

Plans and requests

- Resolve a request
- Catalog and prices

Devices

- Register a device
- Edit, deactivate or reactivate
- Device types

Baselines and rules

- Baselines
- Rules

Audits

- Import a configuration
- Run an audit
- Read the result

Audit history

- Search
- Details and trend

Findings

- Search
- Details and tracking

Critical alerts

- Assign or return an alert

Audit reports

- Generate a report
- View and download

Logs

Administration panel

Email notices

Troubleshooting

Your profile: system administrator

AuditNet is a web platform for auditing the configuration of network devices (Cisco IOS/IOS-XE routers and switches). Each organization registers its devices, defines how each device type must be configured (baselines and rules), imports the actual configurations and audits them. The result is findings with evidence, alerts for the most serious ones and reports for management.

As **system administrator** you have the widest scope: you see and operate every organization.

YOU CAN	WHERE
Register client organizations, assign them a plan and manage their sites	Organizations and sites
Create users of any profile, change them, disable them, reset passwords and unlock accounts	Users
Approve or reject plan change requests and adjust reference prices	Plans and requests
Register device types and manage the inventory of any organization	Devices
Define baselines and rules, import configurations and run audits	Baselines, Rules, Audits
Work on findings and alerts and generate reports	Findings, Critical alerts, Reports
Review the logs and platform health, run the periodic review and create backups	Logs, Administration panel

> **Important:** the five profiles are fixed and their permissions are enforced by the server. Even if someone knows the address of a screen, the operation is rejected when their profile is not allowed to do it.

Signing in to AuditNet

› Sign in

1. Open the AuditNet address your organization gave you in an up-to-date browser (Chrome, Edge or Firefox).
2. Enter your **username or email** and your **password**.
3. Click **Sign in**.




Figure 1. Sign-in screen with the theme and language selectors at the top right

At the top right you can choose, before signing in, the **theme** (Light or Dark) and the **language** (ES, EN, PT). If your account already has a saved theme and language, those are used once you sign in.

> **Lockout:** after 5 wrong passwords in a row the account is locked for 15 minutes. Wait, or ask an administrator to unlock it.

› Recover your password

1. On the sign-in screen click **Forgot your password?**
2. Enter your username or email and click **Send link**.
3. Check your email: you receive a link that is valid for **30 minutes** and can be used only once.
4. Open it, choose the new password, repeat it and click **Save password**.




Figure 2. Requesting the link to create a new password

The email arrives in the language of the screen you requested it from. Saving the new password closes any open sessions and removes the lockout caused by failed attempts.

The password must be **10 to 72 characters long**, **combine letters and numbers** and **not contain your username**. The screen ticks each condition as you type.

The console




Figure 3. Dashboard after signing in: side menu, top bar and access to the guide

› Side menu

On the left is the menu with the screens your profile can use. Each icon has a short code; hover over it to see the full name.

CODE	SCREEN	CODE	SCREEN
`~/`	Dashboard	`BL`	Baselines
`CLI`	Client status	`RUL`	Rules
`ORG`	Organizations and sites	`RUN`	Audits
`USR`	Users	`HIS`	Audit history
`PLN`	My plan / Plans and requests	`LOG`	Findings
`BIT`	Logs	`ALR`	Critical alerts
`ADM`	Administration panel	`REP`	Reports
`DEV`	Devices		

Only the screens of your profile are shown.

› Top bar

- **Location:** on the left, where you are (for example `AuditNet / findings`).
- **Go to module:** in the center, type the name of a screen and press Enter to go straight there. For example `findings`, `alerts`, `reports` or `account`.
- **Connection status:** `online` means the services are responding.
- **User menu:** on the right, with your username.

› User menu




Figure 4. User menu: language, theme, My account, guide and sign out

Here you change the **language** (ES, EN, PT) and the **theme** (Light or Dark); both are saved in your account and used in any browser. You also have **My account**, the PDF **guide** for each profile you have and **Sign out**.

› User guide

At the top of the dashboard there is a **User guide** card with a download button for each profile of your account. The PDF is downloaded in the console language. **Hide** removes the card in that browser; the guide is still available in the user menu.

› Session

The session lasts a limited time (My account shows when it expires) and it also ends if an administrator changes your profile, your organization or your password. In that case AuditNet takes you to the sign-in screen with a notice.

My account

Open it from the user menu → **My account**.




Figure 5. My account: your details and the password change

› Your details

The **Identity** panel shows your username, email, organization, profile and when the session expires. To change your name, email, organization or profile, ask an administrator.

› Change your password

1. Enter your **current password**.
2. Enter the **new password** and repeat it. The conditions are ticked as you type.
3. Click **Change password**.

Changing it closes your other open sessions; the current one stays open.

› Language, theme and email notices




Figure 6. Language, theme and email notices

- **Language:** applies to the console, the guides and the emails AuditNet sends you.
- **Theme:** Light or Dark. It is saved in your account.
- **Email notices:** tick the ones you want to receive and click **Save notices**. Only the ones that apply to your profile are shown (see the *Email notices* chapter).

Dashboard and client status

› Dashboard

It is the first screen after signing in. It summarizes the status of your organization (the system administrator chooses the organization at the top right or sees all of them together).

- **Overall risk level:** high, medium or low, with the reason.
- **High:** there are pending critical findings or current alerts on devices of high or critical criticality.
- **Medium:** there are pending high-severity findings on devices of medium or low criticality.
- **Low:** only medium or low severity findings remain pending, or none.
- **Indicators:** audited devices, current compliance, pending findings, critical and high, current alerts, audits in the last 30 days, overdue findings and outdated configurations. **Each indicator opens the detail** (for example, *overdue findings* opens Findings filtered by overdue).
- **Pending findings by severity** and **Deviations per week** (detected and closed in the last 8 weeks). Hover over a bar to see the numbers, or open *show table*.
- **Current alerts**, **Recent audits** and **Highest-risk devices**, with links to each one.

› Client status

From **Status by site →** or the `CLI` menu. It shows the risk of each site, pending findings by severity, recent audits, devices sorted by risk level and the organization's available reports.




Figure 7. Client status: overall risk and the organization's indicators

Current compliance is the percentage of rules met in the last audit of each device. An **overdue finding** is a pending one that exceeded the deadline for its severity (by default: critical 7 days, high 15, medium 30 and low 60; each organization can adjust them).

Organizations and sites

`ORG` menu. Client organizations are on the left; when you choose one, its sites appear on the right and its plan and review deadlines below.




Figure 8. Registered organizations and sites of the chosen organization

› Register an organization

1. Click **+ organization**.
2. Fill in the **identifier** (short code, saved in uppercase) and the **legal name**. Both are unique on the platform.
3. Choose the **initial plan**: - **Piloto** (pilot): enter the trial days (60 to 90). - **Empresa** (enterprise): enter the agreed devices and users. - **Inicial** and **Profesional** use the catalog limits.
4. Click **Register organization**.




Figure 9. New organization with its initial plan

› Edit, disable or enable

With the organization selected, **Edit** changes the identifier or the legal name. **Disable** prevents its users from signing in (open sessions are closed immediately); its sites, devices, audits and reports are kept. **Enable** activates it again.

› Sites

- **+ site:** name (unique within the organization) and location.
- **Edit** changes that data.
- **Disable** on a site prevents assigning new devices to it; the devices it already has keep their history.

› Change the plan

In the **Plan and usage** panel click **Change plan**, choose the new plan and click **Apply plan**. It applies immediately. If the organization uses more devices or users than the new plan allows, the change is rejected. If there is a pending request, the panel shows it with a link to resolve it.

› Review deadlines

Each organization defines within how many days a finding must be fixed according to its severity, how often a device is audited again and after how many days its configuration counts as outdated. It is explained in the chapter about your organization and works the same for any organization you choose.

Users and profiles

USR menu. It lists all platform users with their organization, profile, status and last access.




Figure 10. Users, access profiles and permission matrix

› Register a user

1. Click **+ user**.
2. Fill in **full name**, **email**, **username** (letters without accents, numbers, dot, hyphen or underscore; it cannot be changed later), **organization** and an **initial password** that meets the policy.
3. Check one or more **profiles**. A user can have several, for example organization administrator and analyst.
4. Click **Register user**.

The user receives a welcome email with their username (without the password): share the initial password through a secure channel.

› Actions on a user

ACTION	WHAT IT DOES
Edit	Changes name, email, organization and profiles. If you change the profile or the organization, their open sessions are closed.
Password	Assigns a new password, removes any lock and closes their sessions.

ACTION	WHAT IT DOES
Unlock	Appears when the account was locked after failed attempts.
Disable / Enable	Logical deletion: they cannot sign in and their sessions are closed, but their history is kept.

> Nobody can disable themselves or remove their own administrator profile, and there must always be at least one active system administrator. Your own password is changed from My account.

› Profiles and permissions

The five profiles are fixed and their permissions are enforced by the services. In **Access profiles** only the description of each one can be edited. The **Permission matrix** shows what each profile (ADM, ORG, ANL, AUD, RSP) can do in each module.

Plans and requests

`PLN` menu. Organizations request plan changes from *My plan*; you resolve them here. You also maintain the catalog reference prices.




Figure 11. Requests to resolve and plan catalog

› Resolve a request

In **Requests to resolve** each request shows the organization, the current and requested plan, the billing (monthly or yearly), who requested it and their comment.

- **Approve:** you can write a reply to the client. The plan applies immediately; if the organization uses more than the new plan allows, the approval is rejected.
- **Reject:** the reason is required and the client sees it in My plan.

In both cases the person who requested the change receives an email. Resolved requests remain in **History**.

› Catalog and prices

PLAN	LIMITS
Piloto	Up to 10 devices and 5 users, trial of 60 to 90 days
Inicial	Up to 50 devices and 15 users
Profesional	Up to 150 devices and 40 users

PLAN	LIMITS
Empresa	Custom limits and price

Edit price changes the monthly reference price (empty = *on request* or *free of charge*) and the terms. Limits cannot be edited. The platform does not charge: prices are for reference and the change is recorded in the transaction log.

> To assign a plan without a prior request, use **Change plan** in *Organizations and sites*.

Devices

`DEV` menu. It is the inventory of network devices that can be audited. At the top are the search (identifier, name or vendor) and the criticality and status filters; when you choose a device, its details appear on the right.




Figure 12. Device inventory with the details of the chosen device

› Register a device

1. Click **+ register asset**.
2. Fill in: - **identifier:** unique code within the organization, for example `ROS-RTR-01`; - descriptive **name**; - **device type** (the vendor is filled in from the type); - **organization** (the system administrator chooses it; the organization administrator registers in their own); - **site** (optional); - **criticality:** low, medium, high or critical. It weighs on the risk level and on alerts.
3. Click **Register device**. It is created with active status.




Figure 13. New device

The new device counts toward the active device limit of the organization's plan.

› Edit, deactivate or reactivate

In the device details: **Edit** changes its data (the organization cannot be changed). **Deactivate** makes it inactive: it keeps its history, but does not accept new configurations or audits. **Reactivate** enables it again. Both actions ask for confirmation and every change is recorded in the transaction log with the previous and new values.

› Device types

Types (for example *Router ISR 4331 · Cisco · IOS-XE*) are a catalog shared by all organizations, and baselines are defined per type. Only the system administrator registers them, with **+ type**: name, vendor and family or operating system.

Baselines and rules

A **baseline** is the expected configuration for a device type in an organization. Its **rules** are the controls the engine checks in every audit. There can be only **one active baseline per device type and organization**: it is the one used when auditing.

› Baselines

`BL` menu. When you choose a baseline you see its organization, type, version, number of rules and audits, and its previous versions.




Figure 14. Baselines with the details of the current version

Create a baseline

1. Click **+ new baseline**.
2. Fill in **name**, **description**, **device type** and **organization**.
3. Click **Create baseline**. It is created as version 1, active.

Changes to a baseline

ACTION	WHAT IT DOES
Edit	Changes the description. It does not change the criteria, so no new version is created.
New version	Copies the active rules into a new version, which becomes active; the previous one becomes inactive and keeps its audits.

ACTION	WHAT IT DOES
Deactivate / Activate	If you deactivate the only active baseline of a type, new audits of that type have no applicable baseline.

> **Frozen rules:** once a version has been used in audits, its rules are not changed, to preserve the evidence. To change them, create a new version.

› Rules

`RUL` menu. It lists the controls with their baseline, condition, severity and status. When you choose one you see its pattern, impact and recommendation.




Figure 15. Control rules with the details of a rule

Create a rule

1. Click **+ new rule**.
2. Choose the **baseline** and fill in **code** (letters, numbers, hyphens, dots or underscores, for example `SEC-SSH-01`), **name** and **severity** (low, medium, high or critical).
3. Choose the **condition**:

CONDITION	PASSES WHEN	EXAMPLE
must contain	the pattern appears in the configuration	`service password-encryption`
must not contain	the pattern does not appear	`transport input telnet`

CONDITION	PASSES WHEN	EXAMPLE
expected value	a line starting with the parameter has exactly that value	parameter `ip ssh version`, value `2`

4. Fill in **description**, **impact** (what risk it implies) and **recommendation** (how to fix it).
5. Click **Create rule**.




Figure 16. New rule

The comparison is case-insensitive and repeated spaces count as one. A baseline cannot have two active rules that check the same thing, nor one that requires the opposite of another.

Edit changes everything except the code and the baseline. **Deactivate** removes the rule from new audits; previous audits keep their result.

Audits

`RUN` menu. The imported **configurations** are at the top and the **audits run** below. On the right, the context of whatever you choose.

› Import a configuration

1. Click **+ load configuration**.
2. Choose the **device**.
3. Paste the **running-config** or upload a `.txt` or `.cfg` file (the content appears in the box).
4. Click **Import configuration**.




Figure 17. Loading a configuration

Each import is a **new version** of the device (v1, v2, …). The original is kept exactly as received and a normalized copy is created for comparison. The original file stays in the file repository with its SHA-256 hash: it can be downloaded from the configuration context and AuditNet verifies that it has not changed.

› Run an audit

1. Choose the configuration in the list. The context shows the **applicable baseline** and how many active rules it has.
2. Click **run audit**.

If no applicable baseline appears, there is no active baseline for that device type in the organization.

› Read the result




Figure 18. Result of an audit with the evaluation of each rule

- **rules evaluated / rules met**, **findings** and **highest severity**.
- **Rule evaluation:** each rule with PASSED or FINDING and its evidence (the line found or what is missing).
- **See findings →** opens the findings of this audit; **See in history (trend) →** compares it with the previous one.

What else happens when auditing:

- Each rule that is not met generates a **finding**.
- Findings of **high or critical** severity generate a **critical alert** (only one per device and rule) and an email to those who have that notice turned on.
- Pending findings from previous audits of the same device whose rule is now met change to **resolved** on their own and their alert is closed.

Audit history

`HIS` menu. All audits, with the evaluated configuration, the baseline and the rules used. It is read-only.




Figure 19. History with the details and trend of an audit

› Search

Filter by device, baseline, highest severity, result (compliant or with findings), who ran it and date range, and click **Search**. Audits run by the periodic review appear as **automatic**.

› Details and trend

When you choose an audit you see the configuration (version and who imported it), the baseline with its version, the rules applied and the findings generated with their current status. The **trend** compares it with the previous audit of the same device:

CATEGORY	MEANING
new deviations	rules that passed before and now do not
fixed	rules that failed and now pass
persisting	rules that keep failing
new rules / removed rules	changes in the baseline between one audit and the other

See only the history of this device filters the list by that device and **See findings of this audit** opens its findings.

Findings

`LOG` menu. A **finding** is a rule that was not met in an audit, with its evidence. The list is **prioritized**: pending findings first, from highest to lowest severity, taking the device criticality into account.




Figure 20. Prioritized findings with the deadline of each one

› Search

At the top there are filters by status (including *overdue*), severity, device, baseline and detection date, and a search by rule, device or evidence. The indicators show pending, critical and high, in review and closed findings. The status column shows the **deadline**: *N days left*, *due today* or *overdue by N days*.

› Details and tracking

When you choose a finding you see the rule, the condition, the device, the baseline, the audit that detected it, the deadline, the pattern searched, the **evidence** and the **tracking** (each status change with user, date and comment).




Figure 21. Details of a finding with the tracking form

Change the status

1. Choose the **new status**.
2. Write a **comment**: it is required except when moving to *in review*.
3. Click **Update status**.

STATUS	WHEN TO USE IT	CAN MOVE TO
open	just detected or reopened	in review, resolved, risk accepted
in review	someone is working on the fix	open, resolved, risk accepted
resolved	it was fixed on the device	open (reopen)
risk accepted	it is decided not to fix it, with a justification (exception or false positive)	open (reopen)

> The usual path is to fix the device, import the new configuration and audit: if the rule is now met, the finding changes to **resolved** on its own with the SISTEMA user and a comment that names the audit. Closing a finding (resolved or risk accepted) closes its alert; reopening it makes the alert current again.

Critical alerts

`ALR` menu. Each finding of **high or critical** severity generates an alert (at most one current alert per device and rule). Their purpose is to get someone to take charge quickly.




Figure 22. Prioritized alerts with the chosen alert

Filter by status (current ones by default), severity, device criticality, device and site. The indicators show the current, unattended, assigned and critical alerts.

STATUS	MEANING
active	nobody has taken it yet
in progress	it was assigned to a technical profile
closed	its finding was resolved or the risk was accepted

› Assign or return an alert




Figure 23. Details of the alert with the finding that triggered it

1. Choose the alert: you see the finding that triggered it, the device and its evidence.
2. In **action** choose: - **assign to Network analyst** or **assign to Technical auditor**: it changes to *in progress*; the comment is optional (what needs to be checked); - **return to active (unassigned):** the reason is required.
3. Click **Update alert**.

An alert is not closed by hand: it closes on its own when its finding is resolved or the risk is accepted. To reactivate it, reopen the finding.

Audit reports

`REP` menu. A report gathers audits with their executive summary, findings, severity, impact and evidence. It is saved as a **snapshot**: it reflects the status of the findings at the time it was issued and does not change even if the data changes later.




Figure 24. Criteria for a new report and generated reports

› Generate a report

1. In **Criteria** enter the date range (**from** and **to**) or the numbers of **specific audits** separated by commas (for example `12, 15`; in that case the dates are optional).
2. Optionally, narrow it down by **device**, finding **severity** and **status**. Unchecked = all.
3. Click **Generate report**.

The system administrator also chooses the organization (or all of them). A report includes up to 500 audits: if the criteria cover more, narrow the dates. The title is built in the language of the person who generates it.

› View and download




Figure 25. Document view of the report

When you choose a report, the document is shown: general data, executive summary with compliance, scope and criteria, distribution of findings, included audits, details of each finding and notes.

- **Download PDF:** prints the document on A4 with page numbers. It comes out in the console language.
- **Download CSV:** for Excel, with one row per finding. In Spanish and Portuguese it uses `;` as separator and in English `,`.

Logs

`BIT` menu. Three read-only records, each in its own tab:

LOG	WHAT IT RECORDS	WHERE IT IS STORED
System audit	access and security: sign-ins, rejections, locks, account changes	PostgreSQL
Transactions	business operations with the previous and new values (creations, changes, audits, plans)	PostgreSQL
Exceptions	unexpected service errors, with their trace	MongoDB




Figure 26. System audit log

Filter by event, result, user, entity or service and by dates, and click **Search**. When you choose a record you see all its fields. The **tracking code** identifies the same operation in the three logs: from the details, *Filter by this code in the 3 logs* shows everything that happened in that operation.

Administration panel

`ADM` menu. Platform status, email, periodic review, files, backups and account security.




Figure 27. Administration panel

PANEL	WHAT IT SHOWS OR ALLOWS
Platform status	whether the services respond, their version, memory and components (PostgreSQL, MongoDB, storage). **Refresh** checks again.
Plans	how many plan change requests are waiting to be resolved, with a link to *Plans and requests*.
Email	the outbox: pending, sent and failed. Notices are sent automatically and failed ones are retried; **Send pending** forces the sending.
Periodic review	the last run (re-audits, overdue findings, outdated configurations, emails). It runs on its own every day at 6:00; **Run review now** starts it immediately.
File repository	imported configurations and reports with their SHA-256 hash. **Upload pending** uploads those that do not have their file yet.
Backups	**Create backup** creates a ZIP with the data of all tables and the restore script. It contains personal data: download it only to a safe place.
Security	active users, locked accounts, sign-ins and rejections in the last 24 hours, with a link to the system log.

Email notices

AuditNet sends emails in each recipient's language.

Always (they cannot be turned off):

- **New user:** when your account is created, with your username.
- **Password recovery:** the link you requested.
- **Plans:** to the system administrator when an organization requests a plan change, and to the requester when it is resolved.

Audit notices (chosen in My account → Email notices):

NOTICE	WHAT IT INCLUDES	RECEIVED BY
New critical alerts	one email per audit with its critical or high severity alerts	network analyst, IT management lead, organization administrator
Deadlines and outdated configurations	daily review: findings past their deadline and devices without a new configuration	network analyst, IT management lead, organization administrator
Monthly summary	in the first days of each month, the organization's activity for the previous month	IT management lead, organization administrator

They are turned on by default. The technical auditor and the system administrator do not receive audit notices.

Troubleshooting

SITUATION	WHAT TO DO
Incorrect username or password	Check upper and lower case and that Caps Lock is off. If you do not remember it, use **Forgot your password?**
The account is locked	After 5 failed attempts it is locked for 15 minutes. Wait, recover the password or ask an administrator to unlock it.
Your session ended	It expired or an administrator changed your profile, your organization or your password. Sign in again.
I cannot see a screen or a button	Your profile does not have that permission. The permission matrix is in *Users* (for administrators) and the first chapter of this guide summarizes what your profile does.
There is no active baseline for the selected device type	The organization has no active baseline for that device type. The technical auditor creates or activates it.
I cannot add devices or users	The plan limit was reached or the Piloto plan trial expired. The organization administrator requests a change in *My plan*.
Emails do not arrive	Check *My account* → *Email notices* and the spam folder. Audit notices depend on the profile.
The screen shows another language or theme	Change them in the user menu; they are saved in your account.
The guide does not download	Try from the user menu → *Guide*. If it still fails, tell the system administrator.