FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

30 Series Row-Crop Tractors - 4030, 4230, 4430, 4630

ENGINE
OIL FILTER
(4030) T19044
(4230, Diesel) AR43634
(4230, Gas) AR26350
(4430, 4630) AR43634
Replace every 200 hours.
(Click here for **capacity**)

ENGINE
FUEL FILTER (DIESEL)
AR50041
(4030, 4230)
(4430, 4630) - Qty. 2
Check every 10 hours or daily.
Replace as required.

CAB
RECIRCULATIONAIRFILTER
(STANDARD) RE12793
(HEAVY-DUTY) RE67830
Check every 200 hours.
Replace annually and
as required.

ENGINE
SECONDARY AIR FILTER
(4030, 4230) AR79942
(4430) AR79680
(4630) AR81313
Clean as required. Replace annually.

CAB
FRESH AIR FILTER
R60846
(If tractor has replacement SGB) R65450
Check every 200 hours.
Replace annually and as required.

ENGINE
PRIMARY AIR FILTER
(4030, 4230) AR79941
(4430) AR79679
(4630) AR82915
Clean as required. Replace annually.

HYDRAULICS
FILTER ELEMENT
R27173
Clean filter every 1200 hours. See your John Deere dealer for service.

ENGINE
FUEL FILTER (Gas)
(4030, 4230) AR50141
Check every 10 hours or daily.
Replace as required.

TRANSMISSION/HYDRAULIC
OIL FILTER
(2WD) AR75603
(With PFWD) (4230 TSN -026769) (4430 TSN -045434) (4630 TSN -017284) AR75603
(With PFWD) (4230 TSN 026770-) (4430 TSN 045435-) (4630 TSN 017285-) AR98098
For SRT or QRT - Qty. 1
For PST - Qty. 2
SEALING WASHER
R34733
Replace every 200 hours (QRT and SRT only) or every 600 hours (PST only).
(Click here for **capacity**)

JOHN DEERE
Genuine Parts and Service

April 2015. Subject to change without notice.

http://www.deere.com/en_US/parts/servicessupport/filteroverviews

CAPACITIES
30 Series Row-Crop Tractors - 4030, 4230, 4430, 4630

CAPACITIES (Approximate):

Fuel Tank:

4030 ..... 132.5 L (35 gal)
4230 (Diesel and Gasoline) ..... 140 L (37 gal)
4430 ..... 174 L (46 gal)
4630 ..... 246 L (65 gal)

Cooling System:
Cool-Gard™ II

4030 (With cab) ..... 22.7 L (6 gal)
4030 (Without cab) ..... 20.8 L (5.5 gal)
4230 (With cab) ..... 24.6 L (6.5 gal)
4230 (Without cab) ..... 22.7 L (6 gal)
4430 (With cab) ..... 29.9 L (8 gal)
4430 (Without cab) ..... 28.4 L (7.5 gal)
4630 (With cab) ..... 36 L (9.5 gal)
4630 (Without cab) ..... 34 L (9 gal)

Crankcase with Filter:
Torq-Gard™

4030 ..... 16 L (4.3 gal)
4230 (Diesel) ..... 16 L (4.3 gal)
4230 (Gas) ..... 11.4 L (3 gal)
4430 ..... 15.1 L (4 gal)
4630 ..... 16 L (4.3 gal)

Transmission (PST):
Hy-Gard™

4030 ..... 49.2 L (13 gal)
4230 ..... 37.9 L (10 gal)*
4430 ..... 37.9 L (10 gal)*
4640 ..... 45.4 L (12 gal)*

Transmission (QRT):
Hy-Gard™

4230 ..... 41.6 L (11 gal)*
4430 ..... 41.6 L (11 gal)*
4630 ..... 80 L (21 gal)*

Transmission (SRT):
Hy-Gard™

4030 ..... 49.2 L (13 gal)*
4230 ..... 41.6 L (11 gal)*
4430 ..... 41.6 L (11 gal)*
4630 ..... 79.5 L (21 gal)*

* Add 17 L (4.5 gal) if equipped with PFWD.

Return to Filter Overview

JOHN DEERE
Genuine Parts and Service

April 2015. Subject to change without notice.