

Miele Hood Fan Slim

30" Wide



DAS4720

BASIC DIMENSIONS	
Canopy Height	3.6 cm., 1½ in.
Canopy Width	75.8 cm., 29⅞ in.
Canopy Depth	27.3 cm., 10¾ in.

USER CONVENIENCE	
Electronic Controls	•
Run-on time 5/15 min	•
Easy-to-clean CleanCover hood liner	•
Miele@home Networking	•
EasySwitch	•
Automatic Function	Con@ctivity 3.0
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
Operation	EasySwitch
Booster Levels	1
Normal operating mode Con@ctivity	•

SAFETY	
Safety shut-off	

ACCESSORIES SUPPLIED	
Non-return flap	

LIGHTING AND FAN	
Number x W	1 x 3 W
Light intensity	330 Lx
Colour Temperature	3500 Kelvin
Dimmer Function	•
Fan	Dual-action fan

OPERATING MODES	
Type of air guide	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151, DUU 150
Active charcoal filter (order separately)	DKFS 31-R

VENTED SYSTEM	
Air throughput and sound emissions	Values upon request
Maximum air throughput in cfm according to HVI	427
Air throughput with Booster level 1 (m³/h) according to EN 61591	497.35 (845) ft³/min (m³/h)

FILTER SYSTEM	
Number of dishwasher-safe stainless steel grease filters (10-ply)	1

DESIGN	
Colour	Stainless Steel