




A web app to compute CO_2eq for different modes of transportation worldwide.
<https://lowtrip.fr>



Authors:

Chiara PELLAS
CentraleSupélec engineer
Co-founder of Mollow

Clara NI
CentraleSupélec engineer
Open-source software engineer at SNCF

Paola GRES
CentraleSupélec engineer
Full-stack developer at Ithaque

Xavier BONNEMAIZON
CentraleSupélec engineer, Master in climate sciences
PhD Student at Laboratory for Sciences of Climate and Environment, IPSL

March, 2024

1 Introduction

The work presented here is independent and not-for-profit. This work has been carried out on a voluntary basis and presents no conflict of interest with the authors' work structures or the authors themselves. This work is open-source and all the materials can be found on GitHub(1).

The aim of this web app is to present precise carbon inventories per passenger for each mode of transport and each journey. These results enable users to make informed choices in the context of reducing their greenhouse gas emissions to mitigate climate change. As a reminder, average net yearly per-capita emissions should not exceed 2 tons CO_2eq in 2050 to limit global warming below $2^\circ C(2)(3)$.

To the best of our knowledge, this is the first open source software that provides this kind of multimodal travel-based information on emissions with such features. Notably, the user is able to create multi-step routes, and country-specific emission factors are used for rail transport as for electric cars.




Figure 1: Illustration of yearly carbon emissions per capita and per country by Visual Capitalist(4)

2 Methods

The general method to estimate greenhouse gas emissions for one passenger consists of the estimation of an emission factor for a given mean of transport (in $CO_2eq/p.km$) that multiplies the traveled distance.

$$CO_2eq_{travel,vehicle} = length_{travel} \times EF_{vehicle}$$

In the following, we describe the methods and hypotheses made in order to compute carbon inventories for each mode of transport. Emission factors are mainly retrieved or updated from the Base Empreinte(5) dataset of ADEME. They include upstream and combustion of the traction energy used as well as vehicle construction.

To validate these numbers, a cross validation with other sources and methods is also proposed when possible. We also investigate the contributions from the building of infrastructures and maintenance.

2.1 Train

The geometry of the railway for a given trip is provided by the Railway Routing(6) platform that relies on OpenStreetMap (OSM) data(7). The dataset for railways from OSM can be easily observed on OpenRailwayMap(8). This geometry is mapped with geospatial data of countries' borders in order to split the geometry in each crossed country. Then, the carbon inventory is computed as:

$$CO_2 = \sum_{i \in countries} length_i \times EF_i$$

- $length_i$ the calculated length of the rail journey in country i such as $\sum_{i \in countries} length_i = length_{total}$
- EF_i the emission factor (in $CO_2/p.km$) of rail transport for the country i .

Country dependent emission factors for Europe are given by ADEME Base Carbone(5). Current values are based on the publication « INFRAS-IWW » of International Union of Railways (2004)(9) and reached their end of validity in December 2017. We used the same methodology on the latest report of similar work we were able to find (2011)(10) to compute these emission factors. Their methodology aggregates data from electric and fossil fuel powered train, the electricity mix of the country, and filling rates.

For other countries (China, Japan, USA, India & Russia), values were retrieved using the Railway Handbook(11) produced by the International and Environmental Agency and the Union of Railways in 2017. For all other countries, an emission factor of $100gCO_2/p.km$ is used (order of magnitude corresponding to the highest emission factor proposed by the International Energy Agency(12) for rail transport).

Such emission factors include upstream and combustion of the traction energy used only. To add the vehicle's construction contribution, we add the value given by SNCF in its latest report on sustainability(13): $0.6gCO_2eq/p.km$. The results are depicted in Figure 2.




Figure 2: Emission factors for rail transport (Construction & Usage)

Note that these emissions factors are averaged over a country. On specific railways, and mainly due to the nature of the used traction energy (see Figure 5 for instance) and filling rates, these emission factors may vary. Other GES than CO_2 were not taken into account as they are too few emitted to significantly change the value of CO_2eq .

Cross validation

The emission factor given by UCI for France is $5.4CO_2eq/p.km$, which is higher than the $4gCO_2eq/p.km$ suggested in the SNCF latest report but still comparable.

2.2 Plane

Plane route was hypothesized to be as the great-circle distance (shortest path between two points on Earth) plus detour and holding phases near the airport. To estimate the coefficient of detour we use a global average(14) of 7.6% of the total distance.

Holding patterns are taken into account given the order of magnitude given by ATMOSFAIR(15). Their methodology suggests that it accounts for 1kg of fuel (or 3.81kg of CO_2 (16)) per passenger. We decided to add this amount of CO_2 to the final emissions. We found it an appropriate approach given the low significance on the final emissions.

We used emission factors from ADEME(5) which used data from TARMAAC (Traitements et Analyses des Rejets éMis dans l'Atmosphère par l'Aviation Civile) calculator and the DGAC (Direction Générale de l'Aviation Civile). Different emission factors are used for CO_2 emissions, depending on the trip length:

Distance (km)	Item	Emissions ($gCO_2/p.km$)	Associated consumption ($L/p.100km$)
<1000	Construction	0.38	-
	Fuel (upstream)	24.2	-
	Fuel (combustion)	117	4.64
1000 - 3500	Construction	0.36	-
	Fuel (upstream)	17.6	-
	Fuel (combustion)	84.8	3.37
>3500	Construction	0.26	-
	Fuel (upstream)	14.3	-
	Fuel (combustion)	68.7	2.73

Table 1: Flight emission factors from ADEME and associated consumption

Cross-validation

Given that the emission factor for kerosene(16) is $2.52kgCO_2/L$, one could retrieve the associated average consumption per passenger during the flight using the emission factors derived from the burning of fuel. Wikipedia(17) gives an average fuel consumption per passenger in 2018 of $3.5L/p.100km$, and notes that this number depends greatly on distance traveled. The associated consumption retrieved from ADEME’s values (Table 4) are of the same order of magnitude.

non- CO_2 effects

To take into account non- CO_2 radiative effects that are short-lived components (contrails, NOx emissions and its reactions with O3 and CH4, other components...), we apply a multiplication factor to the CO_2 emission factor (from fuel combustion only) to get a CO_2 -equivalent emission factor value. ADEME uses a factor 2(5) for conservative purposes as this coefficient was evaluated from the 1999 IPCC report and came with very high uncertainties ($\approx 300\%$)(18)(19) .

Recent scientific studies (Lee et al., 2021)(18) suggests to re-evaluate upwards this number to 3 using an adapted Global Warming Potential (GWP*) metric over 100 years. GWP* addresses the challenges related to comparing short-lived and long-lived forcing components. It is computed using ‘flow-based’ methods that have been introduced representing both short-lived and long-lived climate forcers explicitly as ‘warming-equivalent’ emissions that have approximately the same impact on the global average surface temperature over multi-decade to century timescales. It also takes into account the current exponential growth of air traffic.

These studies also reduced the amount of uncertainty in the non- CO_2 terms to $\pm 70\%$. This is partly due to the development of process-based approaches simulating contrail cirrus in recent years. We propose here to apply a coefficient of 3 using GWP* (latest best estimate) with margin errors corresponding to $\pm 70\%$ (18). ATMOSFAIR(15) compared different metrics and similar literature and decided to use the same value.

Please note that applying this coefficient on the flight level might be inaccurate in the sense that all flights do not produce the same amount of contrails cirrus (see for instance the Contrails Map(20)): the method we employ here is an average used to account for a global phenomenon.

2.3 Car & Bus

The road shortest route is computed via the Open Street Map Routing(21) (OSRM) API. The total length of the journey is then computed and multiplied by an emission factor.

Emission factors for private car and bus coaches were retrieved from ADEME(5) which used the Handbook of Emission factors for Road Transport (HBEFA) data. It was originally developed on behalf of the environmental protection agencies of Germany, Switzerland and Austria. In the meantime, other countries (Sweden, Norway, France) and the JRC (European Research Centre of the European Commission) are supporting the process.

The energy demand of an electric personal car is on average $0.187kWh/km$ according to the EV

Database(22). The emissions related to the use of an electric car thus depend on the carbon intensity of the electricity used to fill the vehicle’s batteries (eCI). We retrieve electricity generation carbon footprints from Our World in Data(23) (see Figure 3) to compute country specific emission factors for electric cars. Then, we employ a similar approach as the one used for Trains. Note that we are therefore making the underlying assumption that the batteries are charged using local electricity.

Vehicle	Item	Emissions ($gCO_2/p.km$)
Thermal car	Construction	25.6
	Fuel (upstream & combustion)	192
Electric car	Construction	83.6
	Fuel (upstream electricity)	$0.187(kWh/km) \times eCI(gCO_2/kWh)$
Bus	Construction	4.42
	Fuel (upstream & combustion)	25

Table 2: Emission factors for car and bus from ADEME and EV Database(22)




Figure 3: Carbon intensity of electricity generation - eCI (gCO_2/kWh) 2022

For private cars, we compute emissions associated with different filling rates (1 to 5 passengers) to account for carpooling, and add 4% of fuel consumption by additional passengers to take into account the additional weight(24) (person and luggage).

Cross Validation

Emission factors were also computed with the COPERT(25) methodology for the mode “Highway” and a speed of 120km/h. We average values from diesel and petrol cars from 3 different segments with Euro 6 a/b/c standard. Other GES than CO_2 were not taken into account as they are too few emitted to significantly change the value of CO_2eq . These values do not take into account the construction of the vehicles.

Fuel	Segment	Emissions ($gCO_2/p.km$)
Petrol	Small	165.5491
	Medium	191.5759
	Large-SUV-Executive	226.5866
Diesel	Small	165.9873
	Medium	165.9873
	Large-SUV-Executive	236.5592
Average		192.0409

Table 3: Emission factors for thermal car at 120 km/h and Highway mode from COPERT.

The same approach was applied for standard coaches (<18t) at 90km/h: $EF_{bus} = 599.0042gCO_2eq/km$. Taking into account a share of 60%(26) and a maximum number of passengers equals to 50 we get the following emission factor: $EF_{bus} \approx 19.7gCO_2eq/p.km$. These values are consistent with the ones retrieved from ADEME (Table 2).

2.4 Ferry

In order to compute the route for the ferry, we have to create a network of possible paths the ferry might use. We create a mesh on the surrounding areas of the departure and arrival locations, removing the land. We also add the coastlines and the direct path between the two locations (removing the land as well). We add lines linking the supplied locations to its closest coastline to include departure and arrival in the graph (Figure 4).

Then, the shortest path between the two locations is calculated using the Dijkstra algorithm. Such a methodology may not depict the actual ferry route or shortest path, but is still representative. The density of the mesh depends on the supplied location (the more they are far away, the less dense it is) to avoid excessive computational time.




Figure 4: Calculated Ferry route between Edimbourg and Helsinki. Blue lines represent possible path and red dots connection between them. The retained route is highlighted in green.

For the emission factor, we use this analysis made by Maël Thomas-Quillévéré in Future.eco(27). The example of the Mega Express Four(28) was used and the carbon footprint is attributed based on the usable volume taken by each purchased services.

Service	Volume (m^3)	Emission Factor ($kgCO_2/p.km$)
Entire boat	110092.5	311.27
Cabin	38.94	0.110
Seat	2.9	0.008
Customer services	28.03	0.08
Car presence	40.15	0.114

Table 4: Detail of a Ferry personal carbon footprint

Therefore, in lowtrip, we systematically take into account the basic services offered to customers, and add the other emission factors according to the user’s choice between a normal seat or a cabin, as well as whether or not a car is present.

2.5 Sailboat

The same technique as for the ferry is used to compute the path of a sailboat.

Regarding the emission factor of a sailboat, we use 2023 data from the company Sailcoop that performed hundreds of sail crossing between St-Raphaël and Calvi. Based on their yearly fuel consumption, the average emission factor for a passenger was $69gCO_2/p.km$.

For both Ferry and Sailing, the life cycle analysis of the boat depends on the use time as these vehicles do not age with distance but with time. Therefore, we do not account for the production of these vehicles as the use time for a single cross is very short compared to the lifetime of these vehicles. These emissions must be attributed to the owner of the vehicle.

2.6 Bicycle

While classic bicycles don’t need fuel, they need to be produced as well. Through an average life cycle analysis, the construction of a bicycle account for $5gCO_2/km$ driven(29). Here, we do not take into account the emissions from the calories needed to cycle as it would be highly dependent on individual’s diet and should account in the related emission field. The geometry of the journey was retrieved using the OpenRouteService(30) API.

2.7 Infrastructure

Accounting the emissions from infrastructure for road and flight transport does not modify greatly the overall emissions factor. Indeed, the building of highways and airports normalized by passenger.km are estimated to be respectively $0.7gCO_2/p.km$ and $0.3gCO_2/p.km$ (31).

Regarding the carbon footprint of the railway infrastructure, we employ the value of $6.5gCO_2/p.km$ (32) which is recommended for corridors that have a share of tunnels and bridges below 30%.

We do not account yet for the infrastructure of bicycle lanes and ferry transport.

3 Results

Construction and infrastructure are not significant for air transport. Similarly, infrastructure for road transport and vehicle construction for rail transport do not play a major role in the final inventory. The contributions of maintenance for a given transport mean, estimated by Carbone4 for SNCF(13), also appear to be negligible compared to the other sources of emissions. Consequently, these terms are neglected to improve visualization and understanding.

Our platform allows emissions comparison between a personal trip (potentially using different steps and means of transport) and direct travels between start and end points. A second form can be filled

to compare another personal trip with the first one. Results are displayed in bar charts with total emissions displayed for each option and details accessible through a mouse-over.

4 Future development ideas

All mean of transport

- Add estimated travel time
- Add estimated price depending on time & day of departure

Train

- Distinguish emission factors between electrified railways and non-electrified railways (Figure 5)
- Distinguish high speed railways and regional railways
- Distinguish different filling rates scenarios

Plane

- Create or use an API to compute only flight routes that exist
- Account for taxiing emissions
- Distinguish between flights that produce contrails and others

Car & Bus

- Distinguish different average vehicle fleets for different countries (currently France)
- Distinguish different emission factors for speed limits depending on the road
- Distinguish different vehicle sizes (small, medium, SUV, light truck...)
- Distinguish different filling rates scenarios for bus

Ferry

- Create or use an API to use existing ferry routes
- Create user-supplied options (ex: presence of a car or not) to compute a more detailed emission factor




Figure 5: Electrified and non electrified main railways in Europe from OSM data.

References

- [1] Bonnemaizon, X., Gres, P., Ni, C. & Pellas, C. lowtrip. URL <https://github.com/XavB64/lowtrip/>.
- [2] Intergovernmental Panel on Climate Change. Figure SPM.5: AR6 synthesis report. URL <https://www.ipcc.ch/report/ar6/syr/figures/summary-for-policymakers/figure-spm-5/>.
- [3] United Nations. Population. URL <https://www.un.org/en/global-issues/population>. Publisher: United Nations.
- [4] Deshmukh, A. Visualizing global per capita CO2 emissions. URL <https://www.visualcapitalist.com/visualizing-global-per-capita-co2-emissions/>.
- [5] ADEME. Base empreinte | documentation. URL <https://base-empreinte.ademe.fr/documentation/base-carbone>.
- [6] Beyssac, P. Railway routing. URL <https://signal.eu.org/osm/>.
- [7] OpenStreetMap. URL <https://www.openstreetmap.org/>.
- [8] OpenRailwayMap. URL <https://www.openrailwaymap.org/>.
- [9] UIC Environment. External costs of transport. URL https://uic.org/cdrom/2005/external_costs_env/pages/introduction.html.
- [10] CE Delft. External costs of transport in europe. URL <https://cedelft.eu/publications/external-costs-of-transport-in-europe/>.
- [11] IEA & UIC. Railway handbook - energy consumption and CO2 emissions. URL https://uic.org/IMG/pdf/handbook_iea-uic_2017_web3.pdf.
- [12] Well-to-wheel (wake/wing) GHG intensity of motorised passenger transport modes – charts – data & statistics. URL <https://www.iea.org/data-and-statistics/charts/well-to-wheel-wake-wing-ghg-intensity-of-motorised-passenger-transport-modes-2>.
- [13] SNCF. INFORMATION SUR LA QUANTITE DE GAZ a EFFET DE SERRE EMISE a l'OCCASION d'UNE PRESTATION DE TRANSPORT. URL <https://medias.sncf.com/sncfcom/rse/methodologie-generale-infoges.pdf>.
- [14] Dobruszkes, F. & Peeters, D. The magnitude of detours faced by commercial flights: A global assessment. *Journal of Transport Geography* **79**, 102465 (2019). URL <https://www.sciencedirect.com/science/article/pii/S0966692318305544>.
- [15] ATMOSFAIR. Emissions calculator. URL <https://www.atmosfair.de/wp-content/uploads/flight-emissionscalculator-documentation-calculationmethodology.pdf>.
- [16] Kérosène. URL https://fr.wikipedia.org/w/index.php?title=K%C3%A9ros%C3%A8ne&oldid=210168197#Effet_de_serre. Page Version ID: 210168197.
- [17] Fuel economy in aircraft. URL https://en.wikipedia.org/w/index.php?title=Fuel_economy_in_aircraft&oldid=1205088742. Page Version ID: 1205088742.
- [18] Lee, D. S. *et al.* The contribution of global aviation to anthropogenic climate forcing for 2000 to 2018 **244**, 117834. URL <https://www.sciencedirect.com/science/article/pii/S1352231020305689>.
- [19] IPCC. Radiative forcing estimates for persistent line-shaped contrails - AR4 WGI chapter 2 section 2.6.2: Changes in atmospheric constituents and in radiative forcing. URL https://archive.ipcc.ch/publications_and_data/ar4/wg1/en/ch2s2-6-2.html.
- [20] Breakthrough Energy and Transport & Environment Laboratory at Imperial College. Contrails map. URL <https://map.contrails.org/>.

- [21] Project OSRM. URL <https://project-osrm.org/>.
- [22] EV database. URL <https://ev-database.org/cheatsheet/energy-consumption-electric-car>.
- [23] Ritchie, H., Rosado, P. & Roser, M. Electricity mix URL <https://ourworldindata.org/electricity-mix>.
- [24] Ressources naturelles du Canada. Le poids du véhicule a une incidence sur la consommation de carburant URL https://natural-resources.canada.ca/sites/www.nrcan.gc.ca/files/oeef/pdf/transportation/fuel-efficient-technologies/autosmart_factsheet_16_f.pdf.
- [25] EMISIA. COPERT | the industry standard emissions calculator. URL <https://www.emisia.com/utilities/copert/>.
- [26] ARAFER. Bilan 1er trimestre 2019 | marché librement organisé des services interurbains par autocar. URL https://www.autorite-transport.fr/wp-content/uploads/2019/07/arafere_bilan-marche-autocars-2019-t1.pdf.
- [27] Thomas-Quillévéré, M. Empreinte ferry. URL <https://futur.eco/documentation/transport/ferry/empreinte-par-km-volume>.
- [28] *Mega Express Four*. URL https://fr.wikipedia.org/w/index.php?title=Mega_Express_Four&oldid=210167623. Page Version ID: 210167623.
- [29] Federation. How much CO2 does cycling really save? URL <https://ecf.com/news-and-events/news/how-much-co2-does-cycling-really-save>.
- [30] Openrouteservice. URL <https://openrouteservice.org/>.
- [31] UIC. Carbon footprint of high-speed rail.pdf. URL https://railroads.dot.gov/sites/fra.dot.gov/files/fra_net/15009/Carbon%20Footprint%20of%20High-Speed%20Rail%20UIC%202011.pdf.
- [32] UIC. Carbon footprint of railway infrastructure URL https://uic.org/IMG/pdf/carbon_footprint_of_railway_infrastructure.pdf.