

User Guide to `lunix`, Comprehensive Unix API Module for Lua

William Ahern

October 20, 2016

Contents

Contents	i
1 About	1
2 Dependencies	2
2.1 Operating Systems	2
2.2 Libraries	2
2.2.1 Lua 5.1, 5.2, 5.3	2
2.3 GNU Make	2
3 Installation	3
3.1 Building	3
3.1.1 Targets	3
3.2 Installing	3
3.2.1 Targets	4
4 Usage	5
4.1 Modules	5
4.1.1 unix	5
environ[]	5
arc4random	5
arc4random_buf	5
arc4random_stir	6
arc4random_uniform	6
chdir	6
chmod	6
chown	6
chroot	6
clock_gettime	6
closedir	6
dup	7
dup2	7
execve	7
execl	7
execvp	7
execvp	7
_exit	8
exit	8
fcntl	8
fdatasync	8
fdopen	8
fdopendir	8
fdup	8
fileno	8
flockfile	8
fstat	8
fsync	9
ftrylockfile	9
funlockfile	9
fopen	9
fpipe	9

fork	9	raise	16
gai_strerror	9	read	16
getaddrinfo	9	readdir	16
getegid	10	recvfrom	17
getenv	10	rename	17
geteuid	10	rewinddir	17
getgroups	11	rmdir	17
getmode	11	S_ISBLK	17
getgid	11	S_ISCHR	17
getgrnam	11	S_ISDIR	17
getgroups	11	S_ISFIFO	17
gethostname	12	S_ISREG	18
getifaddrs	12	S_ISLNK	18
getpgid	12	S_ISSOCK	18
getpgrp	12	sendto	18
getpid	13	setegid	18
getppid	13	seteuid	18
getprogname	13	setenv	18
getpwnam	13	setgid	18
getrlimit	13	setgroups	19
getrusage	14	setlocale	19
gettimeofday	14	setpgid	19
getuid	14	setrlimit	19
grantpt	14	setsid	19
ioctl	14	setuid	19
isatty	14	sigaction	19
issetugid	14	sigfillset	20
kill	14	sigemptyset	20
lchown	14	sigaddset	20
link	14	sigdelset	20
lockf	14	sigismember	20
lseek	15	sigprocmask	20
lstat	15	sigtimedwait	21
mkdir	15	sigwait	21
mkpath	15	sleep	21
open	15	stat	21
opendir	15	strerror	22
pipe	15	strsignal	23
posix_fadvise	15	symlink	23
posix_fallocate	15	tcgetpgrp	23
posix_openpt	16	tcsetpgrp	23
posix_fopenpt	16	timegm	23
pread	16	truncate	23
ptsname	16	tzset	23
pwrite	16	umask	23

uname	23	wait	24
unlink	24	waitpid	24
unlockpt	24	write	24
unsetenv	24		
4.1.2 unix.dir	25		
dir:files	25	dir:rewind	25
dir:read	25	dir:close	25

1 About

`lunix` is a bindings library module to common Unix system APIs. The module is regularly tested with Linux/glibc, Linux/musl, OS X, FreeBSD, NetBSD, OpenBSD, Solaris, and AIX. The best way to describe it is in contradistinction to `luaposix`, the most popular bindings module for Unix APIs in Lua.

Thread-safety Unlike `luaposix`, it strives to be as thread-safe as possible on the host platform. Interfaces like `strerror_r` and `O_CLOEXEC` are used throughout. The module even includes a novel solution for the inherently non-thread-safe `umask` system call, where calling `umask` from one thread might result in another thread creating a file with unsafe or unexpected permissions.

POSIX Extensions Unlike `luaposix`, the library does not restrict itself to POSIX, and emulates an interface when not available natively on a supported platform. For example, the library provides `arc4random` (absent on Linux and Solaris), `clock_gettime` (absent on OS X), and a thread-safe `timegm` (absent on Solaris).

Leak-safety Unlike `luaposix`, the library prefers dealing with `FILE` handles rather than raw integer descriptors. This helps to mitigate and prevent leaks or double-close bugs—a common source of problems in, e.g., asynchronous applications. Routines like `chdir`, `stat`, and `opendir` transparently accept string paths, `FILE` handles, `DIR` handles, and raw integer descriptors.

2 Dependencies

2.1 Operating Systems

`lunix` targets modern POSIX-conformant and POSIX-aspiring systems. But unlike `luaposix` it branches out to implement common GNU and BSD extensions. All interfaces are available on all supported platforms, regardless of whether the platform provides a native interface.

I try to regularly compile and test the module against recent versions of OS X, Linux/glibc, Linux/musl, FreeBSD, NetBSD, OpenBSD, Solaris, and AIX.

2.2 Libraries

2.2.1 Lua 5.1, 5.2, 5.3

`lunix` targets Lua 5.1 and above.

2.3 GNU Make

The Makefile requires GNU Make, usually installed as `gmake` on platforms other than Linux or OS X. The actual `Makefile` proxies to `GNUmakefile`. As long as `gmake` is installed on non-GNU systems you can invoke your system's `make`.

3 Installation

The module is composed of a single C source file to simplify compilation across environments. Because there several extant versions of Lua often used in parallel on the same system, there are individual targets to build and install the module for each supported Lua version. The targets `all` and `install` will attempt to build and install both Lua 5.1 and 5.2 modules.

Note that building and installation and can accomplished in a single step by simply invoking one of the install targets with all the necessary variables defined.

3.1 Building

There is no separate `./configure` step required.¹ System introspection and feature detection occurs during compile-time. The “`configure`” make target can be used to cache the build environment so one needn’t continually use a long command-line invocation.

All the common GNU-style compiler variables are supported, including `CC`, `CPPFLAGS`, `CFLAGS`, `LDFLAGS`, and `SOFLAGS`. Note that you can specify the path to Lua 5.1, Lua 5.2, and Lua 5.3 include headers at the same time in `CPPFLAGS`; the build system will work things out to ensure the correct headers are loaded when compiling each version of the module.

3.1.1 Targets

- `all`
Build modules for Lua 5.1 and 5.2.
- `all5.1`
Build Lua 5.1 module.
- `all5.2`
Build Lua 5.2 module.
- `all5.3`
Build Lua 5.3 module.

3.2 Installing

All the common GNU-style installation path variables are supported, including `prefix`, `bindir`, `libdir`, `datadir`, `includedir`, and `DESTDIR`. These additional path variables are also allowed:

- `lua51path`
Install path for Lua 5.1 modules, e.g. `$(prefix)/share/lua/5.1`

¹Optional autoconf configuration is currently being tested. Run `./bootstrap` to build the `./configure` script

`lua51cpath`

Install path for Lua 5.1 C modules, e.g. `$(prefix)/lib/lua/5.1`

`lua52path`

Install path for Lua 5.2 modules, e.g. `$(prefix)/share/lua/5.2`

`lua52cpath`

Install path for Lua 5.2 C modules, e.g. `$(prefix)/lib/lua/5.2`

`lua53path`

Install path for Lua 5.3 modules, e.g. `$(prefix)/share/lua/5.3`

`lua53cpath`

Install path for Lua 5.3 C modules, e.g. `$(prefix)/lib/lua/5.3`

3.2.1 Targets

`install`

Install modules for Lua 5.1 and 5.2.

`install5.1`

Install Lua 5.1 module.

`install5.2`

Install Lua 5.2 module.

`install5.3`

Install Lua 5.3 module.

4 Usage

4.1 Modules

4.1.1 `unix`

At present `unix` provides a single module of routines.

`environ[]`

Binding to the process-global `environ` array using metamethods.

`__index`

Utilizes the internal `getenv` binding.

`__newindex`

Utilizes the internal `setenv` binding.

`__pairs`

Takes a snapshot of the `environ` table to be used by the returned iterator for key–value loops. *Other than Solaris¹, no system supports thread-safe access of the `environ` global.*

`__ipairs`

Similar to `__pairs`, but the iterator returns an index integer as the key followed by the environment variable as a single string—“FOO=BAR”.

`__call`

Identical to the `__pairs` metamethod, to be used to create an iterator directly as Lua 5.1 doesn’t support `__pairs`.

`arc4random()`

Returns a cryptographically strong uniformly random 32-bit integer as a Lua number. On Linux the `RANDOM_UUID sysctl` feature is used to seed the generator if available.² This avoids fiddling with file descriptors, and also works in a chroot jail. On other platforms without a native `arc4random` interface, such as Solaris, the implementation must resort to `/dev/urandom` for seeding.

Note that unlike the original implementation on OpenBSD, `arc4random` on OS X and FreeBSD (prior to 10.0) seeds itself from `/dev/urandom`. This could cause problems in chroot jails.

`arc4random_buf(n)`

Returns a string of length *n* containing cryptographically strong random octets using the same CSPRNG underlying `arc4random`.

¹See https://blogs.oracle.com/pgdh/entry/caring_for_the_environment_making

²Some Linux distributions, such as Red Hat, disable `sysctl`.

`arc4random_stir()`

Stir the arc4random entropy pool using the best available resources. This normally should be unnecessary.

`arc4random_uniform([n])`

Returns a cryptographically strong uniform random integer in the interval $[0, n - 1]$ where $n \leq 2^{32}$. If n is omitted the interval is $[0, 2^{32} - 1]$ and effectively behaves like `arc4random`.

`chdir(dir)`

If *dir* is a string, attempts to change the current working directory using `chdir`. Otherwise, if *dir* is a FILE handle referencing a directory, or an integer file descriptor referencing a directory, attempts to change the current working directory using `fchdir`.

Returns **true** on success, otherwise returns **false**, an error string, and an integer system error.

`chmod(file, mode)`

file may either be a string path for use with `chmod`, or a FILE handle or integer file descriptor for use with `fchmod`. *mode* may be an integer value or symbolic string.

Returns **true** on success, otherwise returns **false**, an error string, and an integer system error.

`chown(file[, uid][, gid])`

file may either be a string path for use with `chown`, or a FILE handle or integer file descriptor for use with `fchown`. *uid* and *gid* may be integer values or symbolic string names.

Returns **true** on success, otherwise returns **false**, an error string, and an integer system error.

`chroot(path)`

Attempt to `chroot` to the specified string *path*.

Returns **true** on success, otherwise returns **false**, an error string, and an integer system error.

`clock_gettime(id)`

id should be the string “realtime” or “monotonic”, or the integer constant `CLOCK_REALTIME` or `CLOCK_MONOTONIC`.

Returns a time value as a Lua floating point number, otherwise returns **nil**, an error string, and an integer system error.

`closedir(dir)`

Closes the DIR handle, releasing the underlying file descriptor.

`dup(file[, flags])`

file may either a FILE handle or integer file descriptor. *flags* is an optional integer value.

Returns an integer descriptor on success, otherwise returns `nil`, an error string, and an integer system error.

`dup2(file, file, [, flags])`

file may either a FILE handle or integer file descriptor. *flags* is an optional integer value.

Returns an integer descriptor on success, otherwise returns `nil`, an error string, and an integer system error.

`execve(path[, argv][, env])`

Executes *path*, replacing the existing process image. *path* should be an absolute pathname as the `$PATH` environment variable is not used. *argv* is a table or `ipairs`-iterable object specifying the argument vector to pass to the new process image. Traditionally the first such argument should be the basename of *path*, but this is not enforced. If absent or empty the new process image will be passed an empty argument vector. *env* is a table or `ipairs`-iterable object specifying the new environment. If absent or empty the new process image will contain an empty environment.

On success never returns. On failure returns `false`, an error string, and an integer system error.

`execl(path, ...)`

Executes *path*, replacing the existing process image. The `$PATH` environment variable is not used. Any subsequent arguments are passed to the new process image. The new process image inherits the current environment table.

On success never returns. On failure returns `false`, an error string, and an integer system error.

`execlp(file, ...)`

Executes *file*, replacing the existing process image. The `$PATH` environment variable is used to search for *file*. Any subsequent arguments are passed to the new process image. The new process image inherits the current environment table.

On success never returns. On failure returns `false`, an error string, and an integer system error.

`execvp(file[, argv])`

Executes *file*, replacing the existing process image. The `$PATH` environment variable is used to search for *file*. Any subsequent arguments are passed to the new process image. The new process image inherits the current environment table.

On success never returns. On failure returns `false`, an error string, and an integer system error.

`_exit([status])`

Exits the process immediately without first flushing and closing open streams, or calling `atexit` handlers. If *status* is boolean `true` or `false`, exits with `EXIT_SUCCESS` or `EXIT_FAILURE`, respectively. Otherwise, *status* is an optional integer status value which defaults to 0 (`EXIT_SUCCESS`).

`exit([status])`

Like `_exit`, but first flushes and closes open streams, and calls `atexit` handlers.

`fcntl(file|dir|fd, ...)`

FIXME

`fdatasync(file|dir|fd)`

FIXME

`fdopen(file|dir|fd[, mode])`

FIXME

`fdopendir(file|dir|fd)`

FIXME

`fdup(file[, flags])`

file may either be a FILE handle or integer file descriptor. *flags* is an optional integer or symbolic mode.

Returns a FILE handle on success, otherwise returns `nil`, an error string, and an integer system error.

`fileno(file|dir|fd)`

Resolves the specified FILE handle or DIR handle to an integer file descriptor. An integer descriptor is returned as-is.

`flockfile(fh)`

Locks the FILE handle *fh*, blocking the current thread if already locked. Returns `true`.

This function only works on FILE handles and not DIR handles or integer descriptors.

`fstat(path|file|dir|fd[, field ...])`

See `stat`.

`fsync(file|dir|fd)`

FIXME

`ftrylockfile(fh)`

Attempts to lock the FILE handle *fh*. Returns **true** on success or **false** if *fh* was locked by another thread.

`funlockfile(fh)`

Unlocks the FILE handle *fh*. Returns **true**.

`fopen(path|file|dir|fd,[mode][,perm])`

FIXME.

`fpipe([mode])`

FIXME.

`fork()`

Forks a new process. On success returns the PID of the new process in the parent and the integer 0 in the child. Otherwise returns **false**, an error string, and an integer system error.

`gai_strerror(error)`

Returns an error string corresponding to the specified EAI integer *error*.

`getaddrinfo(host, [port], [hints][, field ...])`

Returns an iterator over the addresses resolved for *host* and *port*. If a resolution error occurred, returns **nil**, an error string, an EAI error integer, and a system error integer (if EAI error is EAI_SYSTEM).

host should be a string host name. *port* is an optional port number which defaults to 0.

hints is an optional table controlling the manner and scope of resolution. For example, if a family is not specified the resolver will return a unique result for each address-family combination supported by the system. The following fields are supported:

.flags

Bitwise or of one of more of AI_PASSIVE, AI_CANONNAME, AI_NUMERICHOST, AI_NUMERICSERV, AI_ADDRCONFIG, AI_V4MAPPED (if supported), and AI_ALL (if supported).

.family

AF_UNSPEC, AF_INET, or AF_INET6.

.socktype

SOCK_DGRAM, SOCK_STREAM, or SOCK_SEQPACKET (if supported).

.protocol

IPPROTO_IP, IPPROTO_IPV6, IPPROTO_TCP, IPPROTO_UDP, IPPROTO_ICMP, or IPPROTO_RAW (if supported).

If no fields are specified, the iterator returns a table with the following fields:

.family

See description of family for hints table.

.socktype

See description of socktype for hints table.

.protocol

See description of protocol for hints table.

.addr

IP address as human-readable string.

.canonical

Canonical hostname of IP address (if AI_CANONNAME flag was specified in hints table).

.port

Integer port.

If fields are specified, the iterator returns a list of fields in the order specified.

getegid()

Returns the effective process GID as a Lua number.

getenv(*name*)

Returns the value of the environment variable *name* as a string, or **nil** if it does not exist.

*Not thread-safe on any system other than Solaris³ and NetBSD⁴. Linux/glibc **getenv** is thread-tolerant as pointers returned from **getenv** will remain valid throughout the lifetime of the process, but Linux/glibc will write over existing values on update so concurrent use with **setenv** could lead to inconsistent views.*

geteuid()

Returns the effective process UID as a Lua number.

³See https://blogs.oracle.com/pgdh/entry/caring_for_the_environment_making

⁴NetBSD provides **getenv_r(3)**

`getgroups()`

Queries supplement group list. On success returns an array of supplement GIDs. Otherwise returns `nil`, an error string, and an integer system error.

`getmode(mode[, omode])`

The `getmode` interface derives from the routine so-named in almost every `chmod(1)` utility implementation and which exposes the parser for symbolic file permissions.

mode should be a symbolic mode value with a valid syntax as described by POSIX within the `chmod(1)` utility man page. If specified, *omode* should be an integer or a string in decimal, hexadecimal, or octal notation, and represents the original mode value used by the symbolic syntax for inheritance.

`getgid()`

Returns the real process GID as a Lua number.

`getgrnam(grp[, ...])`

grp is an integer GID or string symbolic group name suitable for use by either `getgrgid(3)` or `getgrnam(3)`, respectively.

If no other arguments are specified, on success returns a table with the following fields

.name

Symbolic group name as a string, or `nil` if absent.

.passwd

Password information as a string, or `nil` if absent.

.gid

GID as integer.

.mem

Array of supplementary group names, or `nil` if absent.

If additional arguments are given, on success each field specified (as named above) is returned as part of the return value list. “members” may be used as an alternative to “mem”. Note that the return value may be `nil` if the field was absent.

If no group was found, returns `nil` followed by the error string “no such group”.

If a system error occurred, returns `nil`, an error string, and an integer system error.

`getgroups()`

Returns table of supplementary GIDs on success, otherwise `nil`, an error string, and an integer system error.

`gethostname()`

Returns system hostname as string on success, otherwise `nil`, an error string, and an integer system error.

`getifaddrs([...])`

Returns an iterator over the current system network interfaces on success. If a system error occurred, returns `nil`, an error string, and an integer system error.

If no arguments are specified, each invocation of the iterator returns a table with the following fields

.name

Interface symbolic name as a string.

.flags

Interface flags as an integer bit field.

.family

Interface address family as an integer.

.addr

Interface address as a string, or `nil` if of an unknown address family.

.netmask

Interface address netmask as a string, or `nil` if absent or of an unknown address family.

.prefixlen

Interface address prefixlen as an integer, or `nil` if absent or of an unknown address family.

.dstaddr

Interface destination address if point-to-point, or `nil` if absent or of an unknown address family.

.broadaddr

Interface broadcast address, or `nil` if absent or of an unknown address family.

If arguments are given, each field specified (as named above) is returned as part of the return value list on every invocation of the iterator.

`getpgid()`

FIXME.

`getpgrp()`

FIXME.

`getpid()`

Returns the process ID as a Lua number.

`getppid()`

Returns the parent process ID as a Lua number.

`getprogname()`

Returns the program name as a string, otherwise `nil`, an error string, and an integer system error.

`getpwnam(usr[, ...])`

usr is an integer UID or string symbolic user name suitable for use by either `getpwuid(3)` or `getpwnam(3)`, respectively.

If no other arguments are specified, on success returns a table with the following fields

.name

Symbolic user name as a string, or `nil` if absent.

.passwd

Password information as a string, or `nil` if absent.

.uid

UID as integer.

.gid

Primary GID as integer.

.dir

Home directory path, or `nil` if absent.

.shell

Login shell path, or `nil` if absent.

.gecos

Additional user information, or `nil` if absent.

If additional arguments are given, on success each field specified (as named above) is returned as part of the return value list. Note that the return value may be `nil` if the value was empty in the database.

If no user was found, returns `nil` followed by the error string “no such user”.

If a system error occurred, returns `nil`, an error string, and an integer system error.

`getrlimit([what])`

FIXME.

`getrusage([who])`

FIXME.

`gettimeofday([ints])`

Returns the current time as a Lua floating point number or, if *ints* is **true**, as two integers representing seconds and microseconds.

On failure returns **nil**, an error string, and an integer system error.

`getuid()`

Returns the real process UID as a Lua number.

`grantpt(file)`

FIXME.

`ioctl(file, ...)`

FIXME.

`isatty(file)`

FIXME.

`issetugid()`

Returns **true** if the process environment is considered unsafe because of `setuid`, `setgid`, or similar operations, otherwise **false**.

`kill(pid, signo)`

Sends signal *signo* to process or process group *pid*. Returns **true** on success, otherwise **false**, an error string, and an integer system error.

`lchown(path1[, uid][, gid])`

FIXME.

`link(path1, path2)`

Creates a new directory entry at *path2* as a hard link to *path1*.

Returns **true** on success, otherwise **false**, an error string, and an integer system error.

`lockf(file, cmd[, size])`

FIXME.

`lseek(file, offset, whence)`

FIXME.

`lstat(path[, field ...])`

Identical to `stat`, except only accepts string paths and uses the `lstat` system call.

`mkdir(path[, mode])`

Create a new directory at *path*. *mode*, if specified, should be a symbolic mode string following the POSIX syntax as described by the `chmod(1)` utility man page. Otherwise, *mode* defaults to 0777. In either case, *mode* is masked by the process umask.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

`mkpath(path[, mode][, imode])`

Like `mkdir`, but also creates intermediate directories if missing. *imode* is the mode for intermediate directories. Like *mode* it is restricted by the process umask, but unlike *mode* the user write bit is unconditionally set to ensure the full path can be created.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

`open(path|file[, mode][, perm])`

FIXME.

`opendir(path|file|dir|fd)`

Creates a DIR handle for reading directory entries. Caller may specify a path string, a Lua FILE handle, another DIR handle, or an integer descriptor. In the latter three cases, the underlying descriptor is duplicated using `dup3` (if available) or `dup2` because there's no safe way to steal the descriptor from existing FILE or DIR handles. But it's not a good idea to mix reads between the two original and duplicated descriptors as they will normally share the same open file entry in the kernel, including the same position cursor.⁵

Returns a DIR handle on success, otherwise `nil`, an error string, and an integer system error.

`pipe(mode)`

FIXME.

`posix_fadvise(file, offset, len, advice)`

FIXME.

`posix_fallocate(file, offset, len)`

FIXME.

⁵In the future may add ability to open `/proc/self/fd` or `/dev/fd` entries, which should create a new open file entry.

`posix_openpt([flags])`

FIXME.

`posix_fopenpt([flags])`

FIXME.

`pread(file, size, offset)`

FIXME.

`ptsname(file)`

FIXME.

`pwrite(file, data, offset)`

FIXME.

`raise(signo)`

Sends signal *signo* to calling thread. Returns **true** on success, otherwise **false**, an error string, and an integer system error.

`read(file, size)`

FIXME.

`readdir(dir[, field ...])`

Reads the next directory entry. If no field arguments are specified, on success returns a table with the following fields

.name

Name of file.

.ino

Inode of file.

.type

A numeric value describing the file type, similar to the “mode” field returned by `stat`, except without any permission bits present. You can pass this value to `S_ISREG`, `S_ISDIR`, `S_ISFIFO`, etc.

Available on Linux and BSD derivatives, but, e.g., will be `nil` on Solaris.

If additional arguments are given, on success each field specified (as named above) is returned as part of the return value list. Note that the return value may be `nil` if the value was unavailable.

If the end of directory entries has been reached, returns `nil`.

If a system error occurred, returns `nil`, an error string, and an integer system error.

`recvfrom(file, size[, flags])`

FIXME.

`rename(path1, path2)`

Renames the file *path1* to *path2*. The paths must reside on the same device.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

`rewinddir(dir)`

Rewinds the DIR handle so the directory entries may be read again.

`rmdir(path)`

Remove the directory at *path*.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

`S_ISBLK(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a block device.

Returns `true` or `false`.

`S_ISCHR(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a character device.

Returns `true` or `false`.

`S_ISDIR(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a directory.

Returns `true` or `false`.

`S_ISFIFO(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a FIFO or pipe.

Returns `true` or `false`.

`S_ISREG(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a regular file.

Returns `true` or `false`.

`S_ISLNK(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a symbolic link.

Returns `true` or `false`.

`S_ISSOCK(mode)`

Tests whether the specified *mode* value—as returned by, e.g., `stat` or `readdir`—represents a socket.

Returns `true` or `false`.

`sendto(file, data[, flags][, addr])`

FIXME.

`setegid(gid)`

Set the effective process GID to *gid*. *gid* must be an integer or symbolic group name.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

`seteuid(uid)`

Set the effective process UID to *uid*. *uid* must be an integer or symbolic user name.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

`setenv(name, value[, overwrite])`

Sets the environment variable *name* to *value*. If the variable already exists then it is not changed unless *overwrite* is `true`. *overwrite* defaults to `true`.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

This function is thread-safe on Solaris and NetBSD. For Linux/glibc see note at `getenv`. FreeBSD, OpenBSD, and Linux/musl are confirmed to be not thread-safe. The status of AIX and OS X is unknown. In general `setenv` should be avoided in multi-threaded environments.

`setgid(gid)`

Set the real process GID to *gid*. *gid* must be an integer or symbolic group name.

Returns `true` on success, otherwise `false`, an error string, and an integer system error.

setgroups{ ...}

Sets the supplement group list. Takes an array of GIDs. On success returns **true**. Otherwise returns **false**, an error string, and an integer system error.

As an extension, group names may be specified instead of integer GIDs. However, an unresolvable group name currently causes an error to be thrown rather than returned. Until this is fixed, use **getgrnam** to explicitly resolve names to GIDs.

setlocale(*category* [, *locale*])

Set or query the program locale. *category* is an integer constant which specifies the category of localization, and should be one of **LC_ALL**, **LC_COLLATE**, **LC_CTYPE**, **LC_MONETARY**, **LC_NUMERIC**, or **LC_TIME**.

locale can be either a string identifier for the locale, or **nil** to query the specified category. An empty locale string selects the system's native locale.

Returns a locale string identifier on success, otherwise **nil** if the specified *category* and *locale* could not be honored.

setpgid(*pid*, *pgid*)

FIXME.

setrlimit(*what* [, *soft*] [, *hard*])

FIXME.

setsid()

Create a new session and process group.

Returns the new process group ID on success, otherwise **nil**, an error string, and an integer system error.

setuid(*uid*)

Set the real process UID to *uid*. *uid* must be an integer or symbolic user name.

Returns **true** on success, otherwise **false**, an error string, and an integer system error.

sigaction(*signo*, [*action*], [*oaction*])

Sets or queries the signal disposition for the signal *signo*.

If specified, *action* is a table used to update the signal disposition.

.handler

Currently handler may only be **SIG_DFL**, **SIG_ERR**, or **SIG_IGN**. Lua functions are not currently supported, but may in the future. In the meantime, applications can use **sigtimedwait** to atomically dequeue signals in a thread-safe manner.

.mask

A sigset_t userdata object, or the string "*" (see sigfillset).

.flags

Bitwise or of one or more of SA_NOCLDSTOP, SA_ONSTACK, SA_RESETHAND, SA_RESTART, SA_SIGINFO, SA_NOCLDWAIT, and SA_NODEFER.

Returns **true** on success if *oaction* is **nil** or **false**.

Returns a table on success if *oaction* is **true**. The table describes the signal disposition at the time **sigaction** was initially called.

Otherwise returns **nil**, an error string, and an integer system error.

sigfillset(*[set]*)

Returns a sigset_t userdata object with all bits filled. If *set* is specified should be an existing sigset_t userdata object to reuse.

sigemptyset(*[set]*)

Returns a sigset_t userdata object with all bits cleared. If *set* is specified should be an existing sigset_t userdata object to reuse.

sigaddset(*set[, signo ...]*)

Returns a sigset_t userdata object with the specified signals set. If *set* is not a sigset_t object, a new, empty sigset_t is instantiated and initialized according to whether *set* is **nil**, an integer signal number, an array of integer signal numbers, or the string "*" (filled) or "" (empty). If specified, *signo* and additional arguments should be integer signal numbers to be added to the sigset_t object.

sigdelset(*set[, signo ...]*)

Like **sigaddset**, but *signo* and subsequent integer signal numbers are cleared from the sigset_t object.

sigismember(*set, signo*)

Returns **true** if *signo* is a member of sigset_t *set*, otherwise false.

sigprocmask(*[how, set[, oset]]*)

If *how* and *set* are defined, sets the signal mask of the current process or thread. *how* should be one of SIG_BLOCK, SIG_UNBLOCK, or SIG_SETMASK. *set* should be a sigset_t userdata object, or a number, string, or array suitable for initializing a sigset_t object as discussed in **sigaddset**.

Returns the old mask as a sigset_t userdata object on success, otherwise **nil**, an error string, and an integer system error. *oset* is an optional sigset_t userdata object to be reused as the return value, and is first cleared before passing to the system call.

Whether the process or thread mask is set is implementation defined, and varies across platforms. Threaded applications should use `pthread_sigmask`, which is guaranteed to set the mask of the current thread.⁶ Unfortunately, there is no interface which is guaranteed to only set the process mask. New threads inherit the mask of the creating thread, so standard practice is typically to block everything in the main thread while creating new threads.

`sigtimedwait(set[, timeout])`

Atomically clears any pending signal specified in *set* from the pending set of the process *and* thread. If none are pending, waits for *timeout* seconds, or indefinitely if *timeout* is not specified. Fractional seconds are supported.

On success returns an integer signal number cleared from the pending set and an array representing the members of the `siginfo_t` structure (without the “si_” prefix).⁷ On error returns `nil`, an error string, and an integer system error. If *timeout* is specified and no signal was cleared before the timeout, the system error will be `ETIMEDOUT`.

OS X and OpenBSD lack a native `sigtimedwait` implementation. On OS X `linux` uses `sigpending` and `sigwait` to emulate the behavior. However, in a multi-threaded application if another thread clears a signal between `sigpending` and `sigwait` then `sigwait` could block indefinitely. There’s no way to solve this race condition.⁸ On OpenBSD `sigwait` is only available through `libpthread`, but on OpenBSD `libpthread` must be loaded at process load-time and cannot be brought in as a `dlopen` run-time dependency. Therefore an alternative emulation is used which clears the pending signal by installing a noop signal handler. This is not thread-safe if another thread is also installing a signal handler simultaneously. Threaded applications on these platforms should be mindful of these limitations. The `cqueues` project supports thread-safe signal listening with `kqueue` on both OpenBSD and Mac OS X.

`sigwait(set)`

FIXME.

`sleep(n)`

FIXME.

`stat(path|file|dir|fd[, field ...])`

Stats the specified file. Caller may specify a path string, a Lua FILE handle, a DIR handle (see `opendir`), or an integer descriptor.

If no field arguments are specified, on success returns a table with the following fields

⁶Use of `pthread_sigmask` requires linking with `-lpthread` on some platforms and for this reason is presently not supported by `linux`.

⁷Currently only the `.si_signo` member is copied from `siginfo_t`.

⁸One possible solution is to explicitly `raise` the signal before calling `sigpending`, but this solutions relies on untested assumptions about signal handling on these platforms.

.dev
Device identifier as integer of device containing file.

.ino
Inode identifier as integer.

.mode
Mode—type, permissions, etc—as integer.

.nlink
Link count as integer.

.uid
Owner UID as integer.

.gid
Owner GID as integer.

.rdev
Device identifier as integer if character or block special file.

.size
File size as integer.

.atime
Last data access timestamp as floating-point number with sub-second fractional component⁹.

.mtime
Last data modification timestamp as floating-point number with sub-second fractional component.

.ctime
Last file status change timestamp as floating-point number with sub-second fractional component.

.blksize
File-system-specified preferred I/O block size as integer.

.blocks
Number of blocks allocated for this object as integer.

If field arguments are given, on success each field specified (as named above) is returned as part of the return value list. Note that the return value may be `nil` if the value was unavailable.

On error returns `nil`, an error string, and an integer system error.

strerror(*error*)

Returns an error string corresponding to the specified system *error* integer.

⁹All platforms currently support timestamps with sub-second precision. However, the underlying filesystem may not record a timestamp with sub-second precision.

`strsignal(signo)`

Returns a string describing the specified signal number.

`symlink(path1, path2)`

Creates a new directory entry at *path2* as a symbolic link to *path1*.

Returns **true** on success, otherwise **false**, an error string, and an integer system error.

`tcgetpgrp(file)`

FIXME.

`tcsetpgrp(file, pgid)`

FIXME.

`timegm(tm)`

tm is a table of the form returned by the Lua routine `os.date("*t")`. This allows converting a datetime in GMT directly to a POSIX timestamp without having to change the process timezone, which is inherently non-thread-safe.

Returns a POSIX timestamp as a Lua number.

`truncate(file[, size])`

Truncate *file* to *size* bytes (defaults to 0). *file* should be a string path, or **FILE** handle or integer file descriptor.

Returns **true** on success, otherwise **false**, an error string, and an integer system error.

`tzset()`

Initializes datetime conversion information according to the TZ environment variable, if available.

Return **true**.

`umask([cmask])`

If *cmask* is specified, sets the process file creation mask and returns the previous mask as a Lua number.

If *cmask* is not specified, queries the process umask in a thread-safe manner and returns the mask as a Lua number.

`uname([...])`

If no arguments are given, on success returns a table with the following fields

.sysname

Name of the current system as a string.

.nodename

Name of this node within an implementation-defined communications network as a string.

.release

Release name of the operating system as a string.

.version

Version of the operating system as a string.

.machine

Hardware description of the system as a string.

If additional arguments are given, on success each field specified (as named above) is returned as part of the return value list.

On failure returns **nil**, an error string, and an integer system error.

unlink(*path*)

Deletes the file entry at *path*.

Returns **true** on success, otherwise **false**, an error string, and an integer system error.

unlockpt(*file*)

FIXME.

unsetenv(*name*)

Deletes the environment variable *name* from the environment table.

Returns **true** on success, otherwise **false**, an error string, and an integer system error.

*This function is thread-safe on Solaris, NetBSD, and Linux/glibc. But see note at **getenv**. Also see note at **setenv**. In general **unsetenv** should be avoided in multi-threaded environments.*

wait(*[pid]* [, *options*])

FIXME.

waitpid(*[pid]* [, *options*])

FIXME.

write(*file*, *data*)

FIXME.

4.1.2 `unix.dir`

The `unix.dir` module implements the prototype for DIR handles, as returned by `unix.opendir`.

`dir:files([field ...])`

Returns an iterator over `unix.readdir(...)`.

`dir:read([field ...])`

Identical to `unix.readdir`.

`dir:rewind()`

Identical to `unix.rewinddir`.

`dir:close()`

Identical to `unix.closedir`.